# Agricultural Equipment and Supplies 2021/2022





### Dear customer,

Tras Following the conclusion of several highly successful years in partnership with the Kerbl Group, we are delighted to present another joint agricultural requirements catalogue to you this year.

Due to this cooperation with the Kerbl Group, we will now be able to offer you an even larger range of products: choose from over 10,000 additional items from our product range and continue to profit from products of the highest quality, distributed by the Kerbl Group as an experienced and reliable partner with excellent service.

GEA Farm Technologies, based in Bönen, provides farmers with integrated product and application solutions for milk production and animal husbandry, which range from the design and planning of stable and operating concepts to daily herd and operational management. With its combined technical expertise in the areas of milk production, manure technology, stable facilities, automatic feeding systems as well as up-to-date services, including hygiene services, the product range covers all herd sizes all over the world, as well as all customer requirements based on the various types of operations involved.

The parent company, GEA Group Aktiengesellschaft, is one of the largest system suppliers for the food processing industry as well as a wide range of other process industries. As an international technology group, it focusses on process technology and components for sophisticated production processes in various end markets.

See for yourself our extensive range of high-quality products with a balanced price-performance ratio in the new edition of our Agricultural Supplies catalogue.

CCCA approved quality

GEA Farm Technologies GmbH & Kerbl Group

# **Table of contents**

7

7

G <del>E/</del> \	GEA Exclusive Programme	04 - 17	Stable and Yard Essentials	167 - 192	Veterinary Equipment	202	G <del>E/</del>
<b>M</b>	Calf Rearing Camera Surveillance Veterinary Obstetrics Dietary Supplements	18 - 65	Scales and Measuring De Shovels and Forks Moisture Level Readers Stable and Yard Lighting Lashing and Lifting	vices	Sheep Breeding and Farming Lamb Rearing Hoof Care	203 - 209	
	Dairy Farming	67 - 93	Pest Control Electric Insect Control	193 - 200	Clippers		<b>.</b>
	Udder Care and Milking Hygi Milk Filters Milking Accessories		Chemical Insect Control Rat and Mouse Control		Safety in the workplace Protective Clothing Boots	210 - 230	
	and Cattle Farming Dehorning Weaning Supplies Bandages and Bindings	94 - 166	Pig Breeding and Pig Farming	201	Gloves		A
	Hoof and Claw Care Grooming Marking Troughs and Hay Racks Drinking Bowls and Frost Pro	otection					Ť
							-

# Explanation of our packaging and sales units.

OU	Items/pack unit	€
1 blister pack	Pack of 6	Price per pack
1 pouch	Pouch of 10	Price per pouch
12 items	Pouch of 12	Price per item
1 pack	Pack of 30	Price per pack
40 items	Pack of 40	Price per item
1 box	Box of 5	Price per box
8 items	Box of 8	Price per item
1 display	Display of 10	Price per display
6 items	Display of 6	Price per item
•	<b>A</b>	<b>A</b>

### **0U**

Order unit for retail Always order a multiple of the number stated (e.g. OU = 12items, order in lots of 12).

### Items/pack unit No. of items per order unit/pack unit



### Price/€ Price per OU If the OU column is empty or missing, the price is per item. All prices provided are the manufacturer's recommended retail prices and are inclusive of VAT.



### Pack units

Possible pack units for 1 OU.



**B**B

### Pallet

No. of order units (OU) per pallet.



### All items marked with this icon must be shipped by freight carrier due to their scale/size or weight. This means that additional, separate freight costs are required! Optimise freight costs by ordering entire pallet units.

# Service

Professional product advice

# Do you require specific advice on our products?

wice depart

Tolonho

E-mail

Our specially trained product experts are available for your questions and can provide detailed information at any time via phone or e-mail for the following product areas.

For more information about these product areas, please go to our website.

Service department	Telephone	E-mail
IP Camera		
Germany:	+49 8086 933-545	support_ipcam@kerbl.com
Austria:	+43 4224 81555-645	kamera@kerbl-austria.at
International:	+49 8086 933-545	support_ipcam@kerbl.com
LED Lighting		
Germany:	+49 8086 933-551	led@kerbl.com
Austria:	+43 4224 81555-646	led@kerbl-austria.at
International:	+49 8086 933-551	led@kerbl.com
Drinking Technology		
Germany:	+49 8086 933-520	traenketechnik@kerbl.com
Austria:	+43 4224 81555-647	traenketechnik@kerbl-austria.at
International:	+49 8086 933-520	drinkingbowls@kerbl.com
Clippers		
Germany:	+49 8086 933-552	schermaschinen@kerbl.com
Austria:	+43 4224 81555-648	schermaschinen@kerbl-austria.at
International:	+49 8086 933-552	clippers@kerbl.com
Pest Control		
Germany:	+49 8086 933-554	schaedlingsbekaempfung@kerbl.com
Austria:	+43 4224 81555-649	schaedlingsbekaempfung@kerbl-austria.at
International:	+49 8086 933-554	pestcontrol@kerbl.com
Fencing		
Germany:	+49 8086 933-577	weidezaun@kerbl.com
Austria:	+43 4224 81555-651	weidezaun@kerbl-austria.at
International:	+49 8086 933-577	fencing@kerbl.com
Hoof Care		
Germany:	+49 8086 933-541	klauenpflege@kerbl.com
Austria:	+43 4224 81555-653	klauenpflege@kerbl-austria.at
International:	+49 8086 933-541	clawcare@kerbl.com
Feed		
Germany:	+49 8086 933-321	futter@kerbl.com
Austria:	+43 4224 81555-652	futter@kerbl-austria.at
International:	+49 8086 933-321	supplementfeed@kerbl.com
Hobby Farming		
Germany:	+49 8086 933-323	hobbyfarming@kerbl.com
Austria:	+43 4224 81555-655	hobbyfarming@kerbl-austria.at
International:	+49 8086 933-323	hobbyfarming@kerbl.com
Smartfarming		
Germany:	+49 8086 993-301	smartfarming@kerbl.com
Austria:	+43 4224 81555-654	smartfarming@kerbl-austria.at
International:	+49 8086 993-301	smartfarming@kerbl.com



# Website content

### Discover our range of online services.

Just as we are constantly striving to improve our existing products and develop new ones, we are mindful too of our services that accompany our product portfolio.

With our free newsletter and news on our website, we pick out exclusive products and topics of seasonal interest for you and provide you with information on very special offers. We also endeavour to make your product experience more extensive and informative with videos, brochures and other information.

We'd like to give you a closer look at a few of our highlights here.

### Browsing catalogue and service pages

If you don't have one of our catalogues to hand, or simply want to browse through our collection with the 'true' catalogue feeling, then our online browsing catalogue is exactly what you need. It combines the advantages of a catalogue and online browsing: a search function makes finding items easier and takes you direct from every page back to the website, which contains more detailed information.

The services pages on our website also contain generally useful forms such as repair requests, pick-up requests for dry batteries and return slips.

### Better product presentation with videos, 360° photo player and downloads

### **Product videos**

You can now find out even more about our products in appealing, informative and attractive product videos.

All features and functions are shown live in action. We also present areas of use that some people may previously have been unaware of. Explanatory and installation videos facilitate operation and clarify features. In this way, we are trying to answer questions on products in advance and also provide you with real added value.

### **Product** images

While we can only show you basic illustrations of a product in our catalogue, we can also provide you with digital copies of further photos showing detailed views and usage, for example.



### **Downloads**

Just on the right, next to the picture of the product, is the download box in which you can find further information such as brochures or operating instructions.



We are also offering complete 360° views of selected products in addition to our high-resolution professional product photos.



4 33 VOD 87

GE#

Ŧ

This gives you the option of viewing the product in advance from all sides and in extreme close-up, in high resolution and in sharp focus. Although you still cannot touch it, you can get a much better, more realistic feel for the product.

Neue	Proc	lukte	
Haleh	and	ummon	Duo

müheloses Anbringen und Entfernen durch zweiteiliges Design
 optimale Erkenhörkeit durch prädischen Farbode, beidseitige
Beschrittung und großes Formati (54 x 59 mm)
 opeignet für Halsmariterungsbänder mit einer Breite bis zu 40 mm
 zum Pätein angemeldet
 Große Arbeitserleichterung

Größe Arbeitserleichterung: Die Halsbandnummern Duo blefen v.a. bei Veränderungen im Tierbestand eine größe Arbeitserleichterung. Konventionelle Halsbandnummern müssen vom Halsband geschol werden, was gledoch aufgrund von Verschmutzungen schon nach ku Anwendungszeit gar nicht mehr oder nur unter größten Nühen mögi

er Umständen ist sogar ein komplettes Zerlegen des Halsbands Equipment, wie Transponder, Sensor oder Gewicht nötig, obwoh eine einzelne Nummer getauscht werden muss.



### Kerbl goes Social Media

You too can find us on social media, on Facebook, Instagram and YouTube. This way, you won't miss out on Kerbl's latest news about our company, products and activities.

You can find an overview of all social media channels at: https://www.kerbl.de/socialmedia



# **New GEA Products 2020**

### **GEA Supplies Set Economy**

Set consisting of: 1 x GEA Spray Oil WL-75, 500 ml, 1 x Original GEA Glide Silicone Spray, 400 ml, 1 x GEA Udder Paper ProfilacDermacel, 350 sheets/roll, 1 x Stainless Steel Wall Mount for Disposable Gloves, with Spring, 1 x IPCam 2.0 HD, 1 x black Disposable Nitrile Gloves, size XL, 100 pcs/pack



### **GEA Supplies Set Premium**

Set consisting of: 1 x GEA Cattle Clippers, 1 Battery, GT503/GT504, 1 x Udder Hair Remover with Curved Lance, 1.5 m Hose with Gas Cartridge Connector, 1 x Gas Cartridge for Udder Hair Remover, 340 g (600 ml), 1 x Electronic Fly Killer EcoKill Inox, 2 x 20 W, IPX4, 1 x Ultrasound Device Felix 400



### **GEA Spray Oil WL-75**

Versatile universal oil for various applications in agriculture.

Ref. no.	GEA no.	Contents	Ø		€
151850-GEA	7315-4974-800	500 ml / Spray Can	1/12	840	

Made in Germany

Made in Germany

151827-GEA

Made in Germany

GEA

Made in Germany

ginal Ör

5L

151826-GEA

VL-75

GE

GEA

Ŧ

### **GEA Vacuum Pump Oil VCL 22**

The original Vacuum Pump Oil VCL 22 is specially designed for lubricating GEA vacuum pumps. The reliability of your vacuum pump has been confirmed through extensive testing with VCL 22.

• for vacuum pump lubrication • made from ultra-pure base oils • contains anti-corrosion additive, ensuring your vacuum pump is resistant to ageing

• certified according to DIN 51 502 Class VCL

Ø Ref. no. GEA no. Contents MOQ Pieces / unit € 151823-GEA 151823-GEA 7315-0809-000 1 L / Bottle 6 pieces 6 / box 1/6 264 151824-GEA 7315-0810-000 5 L / Canister 2 pieces 2 / box 1/2 96 151825-GEA 7315-0811-000 10 L / Canister 1 20 151826-GEA 7315-0812-000 200 L / Barrel 1 2 151827-GEA 7315-0813-000 30 L / Canister 1 16

151825-GEA

### **GEA Vacuum Pump Oil for Miele**

• tested for vacuum pumps from Miele

Ref. no.	GEA no.	Contents	Ø		€
151822-GEA	7315-0808-000	5 L / Canister	1/4	96	

### **GEA Glide**

### Silicone and Rubber Care Spray

• reduced assembly time and effort • maintains and protects long-term • prevents premature ageing in the long term and increases longevity • prevents seals freezing solid • colour-refreshing effect, improves the aesthetics • approved for silicone liners, silicone hoses and all rubber parts for milking machines

Ref. no.	GEA no.	Contents	MOQ	Pieces / unit	Ø		€
291207-GEA	7315-2394-000	400 ml / Spray Can	6 pieces	6 / box	1/6	870	



GEA

### **GEA Milk Filter Sock**

- for vacuum systems
- gentle passage during filtration high-quality, food-safe material

# GEA Milk Filter Sock 70 g/m<sup>2</sup>

Our proven standard filter for everyday use

• 70 g/m<sup>2</sup> • food safe • sewn





Ref. no.	GEA no.	Width	Length	Suitable for	MOQ	Pieces / unit	Ø	€
46278-GEA	7319-0001-000	57 mm / 60 mm	250 mm	GEA / Lister / Meltec / Lemmer Fullwood	4 pack	370 / box	1/4	
46192-GEA	7315-4976-000	57 mm / 60 mm	320 mm	DeLaval / Hand / Flaco / Utina / Gascoigne-Melotte	1 pack	370 / box	1/4	
46280-GEA	7319-0002-000	57 mm / 60 mm	455 mm	GEA / Meltec / Gascoigne-Melotte	4 pack	370 / box	1/4	
46283-GEA	7319-0004-000	57 mm / 60 mm	530 mm	Lemmer Fullwood / GEA (Mlone)	4 pack	370 / box	1/4	
46286-GEA	7319-0006-000	75 mm / 78 mm	605 mm	GEA / Boumatic / S.A.C.	8 pack	200 / box	1/8	
46197-GEA	7315-4976-100	57 mm / 60 mm	620 mm	DeLaval / Hand / Flaco / DEC / Gascoigne-Melotte	1 pack	370 / box	1/4	
46290-GEA	7319-0007-000	75 mm / 78 mm	800 mm	GEA / Impulsa / Meltec	1 pack	200 / box	1/10	
46534-GEA	7315-5062-100	124 mm	914 mm	AR Performer	1 pack	200 / box	1/4	
46535-GEA	7315-5062-200	124 mm	851 mm	Meltec / Westfalia Systemat	1 pack	200 / box	1/4	
46536-GEA	7315-5062-300	51 mm	610 mm	Meltec	1 pack	200 / box	1/10	

# GEA Milk Filter Sock 100 g/m<sup>2</sup>

• 100 g/m<sup>2</sup> • food safe • sewn





Ref. no.	GEA no.	Width	Length	MOQ	Pieces / unit	Ð	€
46289-GEA	7315-4936-000		790 mm	1 pack	200 / pack	1/4	
46293-GEA	7315-4934-000		850 mm	1 pack	50 / pack	1/9	

# GEA Milk Filter Sock 120 g/m<sup>2</sup>

The sturdy one for continuous use and high wear recommended especially for milking robots

• 120 g/m<sup>2</sup> • food safe • sewn



Ref. no.	GEA no.	Width	Length	Suitable for	MOQ	Pieces / unit	Ø	€
46284-GEA	7319-0005-000	57 mm / 60 mm	530 mm	Lemmer Fullwood / GEA (Mlone) / GEA Monobox	1 pack	100 / pack	1/10	
46285-GEA	7315-4933-000	75 mm / 78 mm	605 mm	GEA / Boumatic / S.A.C. / Lely (Robotic Milker)	1 pack	100 / pack	1/8	
46281-GEA	7315-4931-000	57 mm / 60 mm	455 mm	GEA / Meltec / Gascoigne-Melotte	1 pack	100 / pack	1/10	
46287-GEA	7315-4932-000	57 mm / 60 mm	620 mm	DeLaval / Hand / Flaco / DEC / Gascoigne-Melotte	1 pack	100 / pack	1/10	
46291-GEA	7319-0008-000	75 mm / 78 mm	800 mm	GEA / Impulsa / Meltec	1 pack	100 / pack	1/10	
46292-GEA	7315-4935-000	125 mm	860 mm	Miscellaneous	1 pack	100 / pack	1/4	

# GEA Milk Filter Sock 140 g/m<sup>2</sup>

The all-rounder for the highest requirements

• 140 g/m<sup>2</sup> • food safe • sewn



Ref. no.	GEA no.	Width	Length	MOQ	Pieces / unit	Ð	€
46520-GEA	7315-4918-000	57 mm / 60 mm	455 mm	1 pack	100 / pack	1/10	
46521-GEA	7315-4919-000	57 mm / 60 mm	530 mm	1 pack	100 / pack	1/10	
46522-GEA	7315-4920-000	57 mm / 60 mm	620 mm	1 pack	100 / pack	1/10	
46523-GEA	7315-4921-000	75 mm / 78 mm	605 mm	1 pack	100 / pack	1/8	
46524-GEA	7315-4922-000	75 mm / 78 mm	800 mm	1 pack	100 / pack	1/10	

# GEA Milk Filter Sock 55 g/m<sup>2</sup>

The slim one for use in milking machines for sheep and goats

• 55 g/m<sup>2</sup> • food safe • sewn



Ref. no.	GEA no.	Width	Length	Suitable for	MOQ	Pieces / unit	Ø	€
46282-GEA	7319-0003-000	57 mm / 60 mm	455 mm	GEA / Meltec / Gascoigne-Melotte	1 pack	250 / pack	1/4	

# **GEA Filter Disc**

• suitable for GEA Pulsators

Ref. no.	GEA no.	Width	Length	Surface weight	Suitable for	MOQ	Pieces / unit	Ø	€
46274-GEA	7315-4106-000	50 mm	110 mm	38 g/m²	Constand Pulsator (before 1987)	1 pack	12 / pack	1	
46275-GEA	7315-4107-000	50 mm	116 mm	38 g/m²	Constand Pulsator (from 1987)	1 pack	12 / pack	1/1.000	
46276-GEA	7315-4108-000	46,5 mm	70 mm	80 g/m <sup>2</sup>	Reversing valves, solenoid valves	1 pack	12 / pack	1	

**!!** 

GEA

I mark

潦

7

### **GEA Milk Tube Cleaning Sponge**

• for removing residue in milk tubes in vacuum systems • can be used multiple times, simply rinse out with warm water • reliable • compressed front surface • Material: polyurethane

white sponge: after milking grey sponge: after rinsing



Made in Germany

Ref. no.	GEA no.	Description	MOQ	Pieces / unit	Ø	€
46271-GEA	7315-4103-000	for Plexiglas lines diam. 40 mm	1 pack	12 / pack	1/10	
46272-GEA	7315-4104-000	for 40 mm diam. stainless steel pipes	1 pack	12 / pack	1/7	
46273-GEA	7315-4105-000	for Plexiglas and stainless steel lines diameter 50 mm	1 pack	12 / pack	1/6	

### **GEA Udder Paper Sowotaan 200**

• high-quality single-use udder paper • extra strong wet strength • well-suited for moist udder cleaning with water or an udder cleaning solution



Instructions	for	use:
monuctions	101	usc.

Cleaning udders with udder paper should take place after pre-milking so that any germs in the pre-milk do not remain on the udder. Please use a clean udder cloth for each animal.

Ref. no.	GEA no.	Colour	Contents	MOQ	Pieces / unit	Ð		€
15831-GEA	7315-0742-000	white	200 sheet / Roll	1 pack	10 / pack	1	63	

### **GEA Udder Paper Sowotaan Jumbo**

GEA no.


7315-0744-000

Colour

white

Contents

• high-quality single-use udder paper • extra strong wet strength • well-suited for moist udder cleaning with water or an udder cleaning solution • can also be used when dry



Ref. no.

15833-GEA



### **GEA Udder Paper ProfilacDermacel**

• highly absorbent and stable udder paper in Airlaid quality • well-suited for dry udder cleaning • roughened surface removes dirt from the udder • teat-stimulating · recommended for cleaning your robot's camera



Ŧ

T

Recommended for GEA CameraCleanse AMS & GEA CameraCleanse descaler AMS

Ref. no.	GEA no.	Colour	Contents	MOQ	Pieces / unit	Ē	Ħ	€
15832-GEA	7315-0743-000	white	350 sheet / Roll	1 pack	6 / pack	1	36	

### **GEA Udder Paper Sowotaan Wet**


• wet single-use udder paper for wet-cleaning of udders • as a starter kit, we recommend ordering the Udder Paper (15837-GEA) and the bucket with lid (15786-GEA) together

Soaked in Original GEA Udder Cleaner!

Ref. no.	GEA no.	Colour	Contents	MOQ	Pieces / I	unit		€
15837-GEA	7315-4950-000	white	900 sheet / Roll	2 pack	2 / piec	es 1/2	120	
Ref. no.	GEA no.	Description		Colour	Material	Ø	€	
15823		Hol	der for udder cloth buck	ket		stainless steel	1/10	
15834-GEA	7315-4975-400	Bucket empty no lid			white		1	
15786-GEA	7315-4974-400	Bucket empty with lid		white		1		

### **GEA Udder Cloth ProfilacDermatex**

• reusable fleece udder cloth • washable up to 300 x • best cleaning results thanks to surface with excellent grip • Material: Non-woven fabric





GEA

### **GEA Dip Cup NonReturn**

• a return flow protection prevents used dip material from flowing back into the bottle • clean dip material, full effect on the cow teats • specially developed splash guard with draining to an overflow chamber: less overflow, less waste • soft plastic bottle for low-fatigue working even for a large animal population • practical belt hook

_							
	Ref. no.	GEA no.	Colour	Capac	ity 🗍		€
1	15643-GEA	7315-4975-000	green	300 r	nl 1/132	792	
	Ref. no.	GEA no.	Description		Colour	Ø	€
	15646-GEA	7315-5066-300	Replacem	ent Bottle	white transparent	t 1/200	



The ORIGINAL

for viscous media



GE/

### GEA Dip Cup NonReturn Twin

• excellent for light applications of film-forming or "barrier dips" with high viscosity • double hose accepts the same amount of dip medium, but only requires half the power for pressing • a return flow protection prevents used dip material from flowing back into the bottle • clean dip material, full effect on the cow teats • specially developed splash guard with draining to an overflow chamber: less overflow, less waste • soft plastic bottle for low-fatigue working even for a large animal population • practical belt hook

Ref. no.	GEA no.	Colour	Capacit	y 🗊		€
15647-GEA	7315-4975-100	green	300 m	l 1/132	792	
Ref. no.	GEA no.	Descrip	otion	Colour	Ø	€
15646-GEA	7315-5066-300	Replaceme	nt Bottle	white transparent	1/200	

### **GEA Dip Cup NonReturn Cross**

• cross dip cup with return flow protection • suitable for cows, goats and sheep • dip loss is avoided due to the unique dip medium container with a drip guard edge • with a double hose so that viscous, film-forming media can be used • soft plastic bottle for low-fatigue working even for a large animal population • practical belt hook

Ref. no.	GEA no.	Colour	Capacity	Ø	€
15649-GEA	7315-4975-300	green	300 ml	1/150	
Ref. no.	GEA no.	Description	Colour	Ø	€
15646-GEA	7315-5066-300	Replacement Bottle	white transparent	1/200	



### GEA Dip Cup FoamExpert+

• patented foaming system • suitable for various dip materials, several valve inserts are available • can be used with different foaming dip materials • quick, uniform foaming via just compression • extremely fine and uniform foaming • less dip consumption due to very effective wetting of the teats • hygienic, as side air inlet has a cover • easy to disassemble for cleaning • for pre-milking and post-milking disinfection

Ref. no.	GEA no.	Colour	Ø	€
15669-GEA	7315-5074-500	green	1/132	
Ref. no.	GEA no.	Descr	iption	Colo
15646-GEA	7315-5066-300	Replacem	ent Bottle	white tran



# GEA Dip Cup FoamExpert

• with special foaming sleeve insert in the container • practical belt hook

Ref. no.	GEA no.	Colour	Capacity	Ø		€
15648-GEA	7315-4975-200	green	300 ml	1/132	528	
Ref. no.	GEA no.	Description		Colour	Ø	€
15646-GEA	7315-5066-300	Replacement Bo	ottle wh	ite transparent	1/200	

### **GEA Dip Sprayer PortaSpray**

• high-quality spray head with metal nozzle • specially angled spray nozzle for optimum teat cleaning and spot-accurate dipping • only use sprayable dipping agents

Ref. no.	GEA no.	Colour	Capacity	Ø		€
15642-GEA	7315-4974-900	green	600 ml	1/100	400	

### **GEA Teat Spraying System ProStream**

teat spraying system with adjustable nozzle. Can be used as a mastitis prophylaxis with dip media or as a spraying system for interim disinfection of the milking cup. A self-regulating pressure valve always ensures an optimum spray mist. The supply of up to 50 spray guns is possible so that this system can grow as your business grows. No electrical connection required.

• with a tried and true spraying mechanism • with a vacuum-operated spray pump, supply hose, 3 flexible spiral hoses and 3 spray guns



### Adjustable pressure

GE

 Achieves the best spray results using any agents of your choice

### Self-regulating pressure

foaming

• Ensures stable flow for up to 5 simultaneously active spray pistols

### Relief valve

• De-pressurises the system via a valve when the vacuum is switched off and triggers a backwash of the filter in the dipping agent feed

### Expandable up to 50 spray pistols

Adjustable to the requirements of the largest herds

Ref. no.	Description	Length	Ð	€
151845	Spray Gun ProStream with handle	30 cm	1/200	
151844	Spray Tube ProStream without handle	16 cm	1	
151843	Spiral Hose ProStream for teat spraying system		1/40	
151841	Extension Set ProStream with 1 m lance		1/40	
151840	Spare Parts Set ProStream		1	

GEA

Ŧ

GEA

### **GEA Disposable glove Nitril**

• textured, therefore providing excellent grip • especially suitable as a milking glove: white flakes in the milk, a sign of mastitis, can be detected more easily on the black background • ambidextrous • non-sterile • complies with: EN 455 • tested according to: EN 374-1 • free from allergy inducing nitrosamines, thiurames, thiazoles and latex proteins, latex-free, Free of powder • 1.5 AQL (quality standard) • food safe

r • 1.5 AQL	•	CER Y	
GEA		State	
Mitraihanduchuluk Maraie Glover 240 mm -0.13 mm 14.5 mi		EN ISO 374-5:2016	EN ISO 374 Type

Ref. no.	GEA no.	Colour	Size	Length	Material thickness	MOQ	Pieces / unit	Ē		€
15315-GEA	7315-5151-200	black	6.5-7 / S	24 cm	5,5 mil = 0,13 mm	1 pack	100 / pack	1/10	360	
15316-GEA	7315-5151-300	black	7.5-8 / M	24 cm	5,5 mil = 0,13 mm	1 pack	100 / pack	1/10	360	
15317-GEA	7315-5151-400	black	8.5-9 / L	24 cm	5,5 mil = 0,13 mm	1 pack	100 / pack	1/10	360	
15318-GEA	7315-5151-500	black	9.5-10 / XL	24 cm	5,5 mil = 0,13 mm	1 pack	100 / pack	1/10	360	
15319-GEA	7315-5151-600	black	10.5-11 / XXL	24 cm	5,5 mil = 0,13 mm	1 pack	100 / pack	1/10	360	

### GEA Wall bracket for disposable gloves

• made from stainless steel: heavy-duty and rust-free, even in wet conditions (e.g. in the milking station) • screw-on fastening • can be affixed vertically and horizontally • stable position and suitable for all sizes thanks to spring that pushes the dispenser box to the front

Ref. no.	GEA no.	Material	Ø		€
15339-GEA	7315-5151-700	stainless steel	1/8	192	

### **GEA Hygiene Apron**

This food-grade apron is made from particularly lightweight material, for low-fatigue working. Contaminants hardly stick to the aprons, as they are manufactured without seams or eyelets and feature a pore-free surface. The aprons are ideally suited for use in hygienic areas, as they are detectable. This ensures that no product particles remain in foods.

made from high-quality, thermoplastic polyurethane (TPU) • Food safe as per (EU) No. 1935/2004 • detectable
 extremely tear- and abrasion-resistant with very high elasticity • especially pleasant wearing comfort for low-fatigue working • material resistant to cleaning agents • can be sterilised and disinfected • Temperature resistance: -20 °C
 food safe • machine washable at 95 °C

Ref. no.	GEA no.	Colour	Length	Width	Ø	€
15606-GEA	7315-5067-500	green	155 cm	90 cm	1/20	



1.2016



### **GEA Milker Apron**

• extra-durable Pro Milker Apron for working at the milking station and dairy room • extremely tear and kink-proof • washable and made from a durable, flexible material • limited acid resistance • Temperature resistance: -30 - 50  $^{\circ}$ C

Composition							
Textile		100 % Polye	ster				
Coating		100 % PVC					
Ref. no.	GEA no.	Colour	Size	Length	Width	Ø	€
15613-GEA	7315-0677-000	green	М	115 cm	100 cm	1/20	
15614-GEA	7315-0678-000	green	L	125 cm	118 cm	1/20	
15615-GEA	7315-0679-000	green	XL	140 cm	124 cm	1/20	

# GA GA

GE/

Ŧ

### **GEA Milker Apron**

### with pockets

 extra-durable Pro Milker Apron for working at the milking station and dairy room • with pockets for milking utensils • with shoulder straps and an additional strap for closing at the front and back • each pocket has 2 water drains • extremely tear and kink-proof • limited acid resistance • washable and made from a durable, flexible material • Temperature resistance: -30 - 50 °C

Composition							
Textile		100 % Polye	ster				
Coating		100 % PVC					
Ref. no.	GEA no.	Colour	Size	Length	Width	Ø	€
15616-GEA	7315-0680-000	green	S	110 cm	118 cm	1/40	
15617-GEA	7315-0681-000	green	L	125 cm	118 cm	1/20	



### **GEA Protective Sleeve**

• adjustable on the upper strap • well-suited for working in side-by-side milking stations

• waterproof milking sleeves • elasticated strap at both ends • in pairs

Composition					
Textile		100 % PVC			
Ref. no.	GEA no.	Colour	Length	Pieces / unit	
15398-GEA	7315-5075-000	green	50 cm	2 / pieces	1/100



# **GEA Case for Dangerous Goods**

Complies with GGVS and ADR guidelines

Personal protective equipment for use when transporting dangerous goods and in agriculture and industry when handling chemicals and cleaning products.

set includes: 1 x tightly fitting pair of goggles as per EN 166, 1 pair of nitrile gloves size 10 / XL as per EN 374, 1 x 250 ml eye wash bottle with 4.9 % phosphate buffer solution as per EN 15154-4, in a practical, dust-proof case  $24 \times 21 \times 7.5$  cm

Ref. no.	GEA no.	Ø	€
34508-GEA	7315-5314-300	1/16	



### **GEA Milking Pail**

• for daily use • can be used to check each individual cow's milk yield • also for mobile milking machines • suitable for GEA milking machines • suitable for GEA stainless steel covers • for colostrum or abnormal milk • Material: Polycarbonate • with metal carry handle • with double fill scale (kg; lb) • food safe





Ref. no.	Colour	Capacity	Frame height	Ø		€		
151052-GEA	green	30 L	14 cm	1	24			
Ref. no.		Description			Material	Ø	Ð	€
151058	Milking	Pail Lid Supports ID	13 mm x AD 17 mm	F	Polycarbonate	205 mm	1/20	
151059	Milking	Pail Lid Supports ID	16 mm x AD 20 mm	F	Polycarbonate	205 mm	1/20	
151060	Rubber Seal for milking pail covers						1/26	

### **GEA Udder Care Products SalvoCare Mint**

• with peppermint oil • cares for stressed teats and udders • its nurturing ingredients keep the udder tissue supple • SalvoCare Mint also has a cooling effect that is pleasant for the animal • ensures a healthy udder and high-quality milk when used regularly • no waiting time



Ref. no.	GEA no.	Contents	Ħ		€
15260-GEA	7315-0611-000	500 ml / Hanging Bottle	1/6	522	
15264-GEA	7315-0615-000	2500 ml / Dispenser bottle	1/3	144	
15310-GEA	7315-5074-000	1000 ml / Hanging Bottle	1/6	192	
Ref. no.		Description		Ð	€
15568	Dispens	er for 2500 ml dispenser bottle		1/72	



# **GEA Cordless Clipper Cow**

The GEA cordless clippers by Aesculap, fitted with lithium-ion batteries and a sleek and ergonomic design. The GEA clippers are also a perfect fit for women's hands and boast low weight, low noise and long battery life. The device is also fitted with an intelligent lithium-ion battery system. On the one hand, the battery technology protects the device from overheating and switches it off until it has cooled when the battery temperature reaches >50 °C. On the other hand, the charger provides information on the battery status with two LED displays.

 extremely light, just 900 g incl. batter and shaving blade • just 40 mm diameter and 12.5 cm in circumference in the grip area, therefore also great for small hands
 very comfortable noise level • very short and handy at 295 mm in length • very well balanced • Powerful and long-lasting • lithium technology so no memory effect • battery from tool professionals • electronic push button recessed in the housing means no more accidental switching the machine on or off when handling
 Aesculap Clipper Blades Made in Germany

Included in delivery: 1 x cordless clippers, Li-ion Battery, 1 x charger, 1 x clipper blade set, 1 x small oil bottle, 1 x Durable plastic case

Technical data	
Voltage	10,8 V
Clipper head system	Shearing Blade Set
Drive	DC motor
Stroke rate	approx. 2.500 strokes/min
Battery technology	Li-Ion
Battery capacity	2.000 mAh
Battery run time	80 min
Battery charge time	55 min
Sound pressure level	65 dB (A)
Dimensions	29,5 x 7,5 x 7,8 cm
Weight	900 g incl. battery and clipping head
Ref. no.	GEA no.

7315-5151-800

GT644-OG-GEA

7,8 cm		Green LED Charge level mulcator.
ttery and cli	pping head	Flashing = battery charging / constant
		Red LED battery indicator: Constant li
Æ	£	as temperature too high (above E0 °C)

Ref. no.	Description	Weight	Ø	€
GT641	Spare Battery for Clippers	190 g	1/14	

1/8



### Green LED charge level indicator: Flashing = battery charging / constant = battery full

Red LED battery indicator: Constant light = battery not being charged as temperature too high (above 50 °C) / flashing = battery defective or foreign object between the charging contacts

- Calf blankets support the immune system during the first few days and prevent diarrhoea and other illnesses
- The risk of illness increases at temperatures below 10 °C
- Protection against sudden changes in the weather
- Avoids cold stress in new-born calves
- The calves generally wear the calf blankets for 3 to 4 weeks, and longer if necessary
- Calf blankets are not suitable for group housing

### **GEA Calf blanket**

A high-quality calf blanket for optimum young animal protection. Great attention has been paid to the fit, the processing quality and material properties in order to meet the highest standards.

durable and tearproof polyester 210D ripstop outer material • thermo-insulating foam filling for maximum temperature control at a low weight • technical material properties of the outer material: waterproof (5000 mm water column) and breathable (2000 g/m<sup>2</sup>) • breathable and moisture-wicking fleece lining prevents excessive sweating and channels moisture away from the body • tested and optimised fit • flexible resizing by length-adjustable and elastic straps with snap fasteners on belly flap and leg straps, plus hook-and-loop fastener to the chest flap • easy to clean • breathable to 2000 g/m<sup>2</sup>/24 h
 machine washable at 30 °C



# GEA Calf Bucket with hygienic valve

### ... the one with the flap!

14229-GEA

7315-5073-200

The newly developed hygienic valve with flap mechanism reduces germs and provides healthy growth for calves. The hygienic valve with flap was developed together with practitioners and uses a flap instead of a ball check valve, making it easy to clean with any kind of round brush. The removable intake manifold means no more inaccessible corners. The teat comes away from the valve in one movement. The bayonet fitting means the teat comes off and goes on again in no time. The drying aid is positioned on the side of the feeder handles, offering space to store the cleaned teat and bayonet ring. The bucket is transparent, allowing you to check the fill level from a distance.

• Easy to clean • food safe • with metal carry handle • acid-proof • with printed fill scale on the back, with additional embossed scale on the inside



Ref. no.	GEA no.	Description	Colour	Material	Length	MOQ	Pieces / unit	Ð	€
1441		Cover for Feeding Bucket simply	grey					1/50	
1410		Mounting Bracket simply		metal galvanised		10 pieces	10 / pack	1/10/150	
1454		Calf Teat Latex	beige		100 mm	50 pieces	50 / pack	1/50/500	
1454/3		Calf Teat Latex	beige		100 mm	1 blister pack	3 / blister pack	1/120	
14230-G	7315-5305-800	Hygienic Valve						1/100	
14224/5-G	7315-5152-000	Butterfly Valve for hygienic valve				1 pouch	5 / pouch	1	

8 L

green transparent

1/5

180

Ŧ

GEA

-----

# **Camera surveillance**

IPCams – incredibly simple installation thanks to 'plug & view': Connect the camera to the network and enable on your smartphone, tablet or PC. Now several users can access the live image on their smartphone, PC or tablet. Suitable for use in networks or the internet. Internet access via cable or wireless is essential! This means you can enjoy live images in under a minute.

### IPCam 360 FHD

### with 4x optical zoom

the new hinge can pivot 90 ° and be fixed in place at any point: Ideal positioning on walls, slopes and ceilings for true all-round visibility • quick swivelling outdoor IP camera with huge field of view (Pan / Tilt / Zoom): swivels horizontally by 355° and vertically by 90° • excellent image quality with 2 megapixels • weatherproof aluminium housing • bright 4x zoom optics • 30 metre night vision via 6 infrared LEDs • WDR support (wide dynamic range) for a balanced image of both brighter as well as darker image areas
remote control and access worldwide via app or browser, immediate connection using the app via a QR code • WiFi-compatible and ONVIF compliant: compatibility according to an international standard • free app (eyecloud) for iOS and Android, available in the AppStore and from Google Play • Motion detection: automatically starts recording on SD(HC/XC) card, notification via email • includes operating instructions





supports ONVIF

Included in delivery: 1 x IPCam 360 FHD, 1 x power pack, 1 x Wi-Fi antenna, 1 x patch cable

Technical da	ita		10809				
Zoom			4x optical zoom				
Image Senso	r		2,7 CMOS				
Video resolu	tion supported		Full HD 1080 (1920 x 1080) / HD 720 (1280 720) / VGA (640 x 480) / QVGA (320 x 240)				
Frame rate			15 fps (HD) / 25 fps (VGA)				
Panel f/1,6							
horizontal visible range			355 °				
Vertical visible range			90 °				
Viewing ang	le		40 - 120 °				
Number of L	EDs		6				
Night vision	range		30 m				
Transfer type	1		LAN / WLAN				
Weight			1,9 kg				
Voltage			12 V				
Power			10 W				
Protection class			IP66				
D (		102 141					
Ref. no.	Length	Width	Height ∰ €				
10809	33 cm	25 cm	14 cm 1/8				





# **Camera surveillance**

NEW

New product

GE#

### IPCam 360 FHD mini

• quick swivelling outdoor IP camera • excellent image quality with 2 megapixels • extensive viewing area (pan / tilt / zoom): swivels around 355° horizontally and 90° vertically, adjustable speed • remote control and access worldwide via app or browser, immediate connection using the app via a QR code • WiFi-compatible and ONVIF compliant: compatibility according to an international standard • free app (eyecloud) for iOS and Android, available in the AppStore and from Google Play • Motion detection: automatically starts recording on SD(HC/XC) card, notification via email • Recording to microSD(HC/XC) card up to 128 GB • weatherproof aluminium housing • includes operating instructions

Included in delivery: 1 x IPCam 360 FHD mini, 1 x 230 Volt power pack, 1 x patch cable, 1 x Wi-Fi antenna

Technical data	10825							
Image Sensor	2,7 CMOS							
Video resolution supported		Full HD 1080	(1920 x 108	30)				
Frame rate	Frame rate			15 fps (HD) / 25 fps (VGA)				
Night vision range	30 m							
Weight		1 kg						
Voltage		12 V	12 V					
Power		10 W						
Protection class		IP66						
Ref. no. Length	Width	Height	Ø	€				
10825 21 cm	21 cm	12,5 cm	1/10		-			

### IPCam 2.0 HD

### The internet camera for everyone!

remote control and access worldwide via app or browser, immediate connection using the app via a QR code
 WiFi-compatible and ONVIF compliant: compatibility according to an international standard
 free app (eyecloud) for iOS and Android, available in the AppStore and from Google Play
 motion detection: recording starts automatically, alarm via e-mail, image upload to FTP server
 recording to microSD(HC/XC) card up to 16 GB

### supports ONVIF

Included in delivery: 1 x IPCam 2.0 HD, 1 x power pack, 1 x Wi-Fi antenna, 1 x patch cable

Technical data	10810
Zoom	Digital zoom
Image Sensor	1/4" CMOS
Video resolution supported	HD 720 (1280 x 720) / VGA (640 x 480) / QVGA (320 x 240)
Frame rate	15 fps (HD) / 25 fps (VGA)
Viewing angle	60 °
Number of LEDs	30
Night vision range	15 m
Antenna reach	50 m
Weight	620 g
Voltage	12 V
Power	10 W
Protection class	IP65
Ref. no. 🛱 € 🤇	









Ŧ

# **Moocall Calving Alarm**

### The hour before/of birth!

Don't miss another birth! The tried and tested calving alarm by Moocall reliably informs you of an impending birth. You'll have enough time to make all the necessary provisions and notify the vet if required. The newborn calf will be well cared for and receive the vital colostrum dose right after birth. Give help in time and save both cow and calf! • Attach 3 days before the calculated birthdate • Alerts approx. one hour before birth via SMS, email or app • sends to two phone numbers and three e-mail addresses (adjustable) • free "Breed Manager by Moocall" app for iOS and Android • Device can be used successively on all animals • suitable for all cattle breeds (Limousin, Angus, Fleckvieh, Holstein Friesian, Jersey, etc.) thanks to flexibly adjustable ratchet closure • 30 days battery time • easy charging via USB interface • built-in SIM – ready to use • Data plans etc. included in the service fee – included in the first year after activation • works worldwide via GSM, even with weak network coverage, and with any mobile phone/smartphone • Plastic



#### with USB charging cable



#### Step by step:

- 1. Register the device online or by phone
- 2. Charge the device
- 3. Switch on and send a test message
- 4. Open the ratchet fastener
- 5. Adjust the rubber pad
- 6. Attach at crotch height
- 7. Finished!



Ref. no.	Colour	Length	Ø		€
10500	green / red	19 cm	1/10	220	

### Moocall sends the following messages:

- Sensor has come off the cow's tail
- High activity in the last hour (advance warning)
- High activity in the two hours (birth alarm)
- After 4 days, remove the sensor for 4 hours
- Low battery (20 %)
- Test message

# **HK Calf Pullers**

GE/

1.0

Ŧ

# Rheintechnik



Cows and heifers usually give birth without help. But if complications occur during the second stage, mechanical calf pullers are a life-saving aid. Alongside care and expertise, the use of a suitable calf puller is especially important. Otherwise, serious injury or stillbirth could result. An HK calf puller is the right tool to choose. Since Hermann Kaspar developed the HK calf puller more than 50 years ago, more than 1.5 million have been sold.





### What makes HK calf pullers unique?

### Tie rod

- Stable, thick-walled steel tube, length 180 cm
- A unique, patented groove design gives the mechanism a secure hold
- The tie rod's geometry means the locking plates are applied all over the surface, rather than only at certain points. This improves force transfer and reduces wear
- The rounded edges of the grooves further minimise wear and tear
- · The unique machining process lends the tube greater wall thickness and therefore greater stability
- The tube can be disassembled into three parts, for easy storage: HK Rheintechnik calf pullers are ideal for transporting in cars (e.g. for vets)

### HK Plastic Attachment Support - The classic one

sturdy plastic heads with lateral angled clamps

 $\bullet$  small, easy to handle, lightweight  $\bullet$  ideal for recumbent births where larger heads can often not be positioned under the recumbent cow  $\bullet$  3-year guarantee

### HK Plastic Attachment Support with adjustable side clamp

The steel frame is adjusted to the shape of the pelvis, which prevents the ischium and the long ischium muscles from slipping.

• Triple adjustment option means it can be adjusted to each individual animal, i.e. the frame is suitable for both dairy breed with a narrow pelvis and for beef breeds with a wide pelvis • wide, sturdy head for an even more non-slip fit • 3-year guarantee

### **HK Flexi Frames**

The best protection against slipping. The frame surrounds the mother's pelvis and reliably prevents slipping down and to the side.

• tiltable, pulling motion possible both towards the tail and towards the udder • Frame made from galvanised steel tube with a smooth surface, making it both hygienic and easy to clean • 3-year guarantee

Ref. no.	Bowl width	Pipe diameter	Suitable for	Ø		€
106820	52 cm	26 mm	Dairy Breeds	1	20	
106821	58 cm	30 mm	Beef Breeds, Cows with wide pelvises	1	20	

### **Accessories for HK Calf Pullers**

Ref. no.	Description	Length	suitable for	Ð	€
106908	Extension for HK calf puller	30 cm		1	
106907	Threaded Piece for attaching the extension		106908	1	




# **HK Calf Pullers**

### HK Calf Pullers with Mechanism 2020

Benefits of the Mechanism 2020

• low weight, as made entirely out of aluminium • with 3 hooks for the calving ropes enabling both alternate and equal tension • super easy to use quick release, even under load • the mechanism can be moved 360° around the tube in all models, providing unlimited flexibility • 3-year guarantee





### **HK Calf Pullers with Mechanism 2060**

The tension limiter prevents pulling the calf with too much force. Without regulation, tensile forces of up to 600 kg can be achieved, representing a substantial risk of injury to the cow and calf. For normal births, forces of up to 160 kg are entirely sufficient. The HK Rheintechnik Mechanism 2060 is fitted with a freely adjustable tension control. The lever locks when the pre-set force is attained. The tension control can also be released in an emergency.

with HK Flexi Frames



1

16

• low weight, as made entirely out of aluminium • with 2 hooks for the calving ropes (equal tension) • super easy to use quick release, even under load • the mechanism can be moved 360° around the tube in all models, providing unlimited flexibility • 3-year guarantee

Adjustable tension limiter

58 cm



10140,10141

Ref. no.	Description	Bowl width	Ð		€
102060	with large plastic head and steel clamps	49 - 63 cm	1	30	
10140	with HK Flexi Frames	52 cm	1	48	
10141	with HK Flexi Frames	58 cm	1	16	

GE#

ا يور

Ŧ

### Spare Cord for HK calf puller

• does not absorb blood and does not become rigid • Material: PPMF • 3-strand • twisted • in pairs

PPMF only absorbs a maximum of 0.1 % moisture instead of 10 %, unlike the polyamide previously used. This means it doesn't shrink when drying, becomes rigid less rapidly and is longer lasting. The rope also absorbs hardly any blood and stays hygienic white.

Ref. no.	Colour	Length	Ø	€
103	white	80 cm	1/100	
103/1	white	80 cm	1	

### Vink SECURPART Calf Puller

• Downwards, upwards and rearwards tensile force possible • sturdy and durable design • the tension can be eased immediately in case of complications • Traction type: Equal Traction • stainless steel

Ref. no.	Length	Ð	€
1045	160 cm	1	
1046	180 cm	1	

Ref. no.	Description	packaged	suitable for	Ø	€
10451	Calving Cord for calf puller in pairs	in pairs	1045, 1046	1/200	

### Vink SECURPART Calf Puller Modell A 800 Bayern

This birth aid can allow a single person to carry out difficult births, even if the foetus is the wrong way round. The strap goes around the hind quarters of the animal and prevents slipping off - suitable for all breeds. Tensile forces can be applied to all sides (bottom, top, back) and the tensile force can be released immediately in the event of complications. If required, the user can have both hands free.

• suitable for prone and standing births • with lever action for alternating tension • wear-resistant and made from non-rusting steel • Traction type: Alternate traction



Ref. no.	Length	Suitable for	Ē		€
1047	180 cm	Beef Breeds	1	13	

Ref. no.	Description	packaged	suitable for	Ø	€
10488	Calving Cord for calf puller in pairs	in pairs	1047	1/200	

# **Calving Cord**

• 2 eyelets • Material: PPMF • flat braided

Colour

white

white

white

• per piece

Ref. no.

1036

1036/1

1025

PMF • flat braided	The second se	1036	ALL SAF	میں میں اور			
					Contraction of the second seco		
Length	MOQ	Pieces / unit	$\blacksquare$	€	Comment		
125 cm			1/10/420				
125 cm	1 blister pack	1 / blister pack	1				
190 cm			1/100				
					_	and a start of the	1222

### **Calving Cord**

• 2 eyelets • flat braided for gentle birth • soft quality • per piece

Ref. no.	Colour	Length	Ø	€
10259	yellow / red	130 cm	1/25/350	



### Pregnancy Tester for cows

avoid unpleasant surprises such as false pregnancy or missed abortions thanks to fast, simple and reliable pregnancy detection from 90 days after insemination using sonar • no previous expertise or training required
in most cases, the test takes less than 30 seconds • no unpleasant transrectal examination required for the animal and no risk at all • the device is comfortably worn on the belt, leaving both hands free for measurement
Supplied in a solid plastic case



### **Estrus Detection for cattle**

• for determining the optimum mating or insemination time • the device monitors changes in the characteristics of vaginal discharge during the ovulation cycle by measuring its electrical resistance. The breeder is then able to determine the exact time of ovulation. • it can also be used to confirm an early pregnancy from the 19th to the 23rd day after insemination. • insemination or impregnation at the optimum time during estrus saves precious semen. • reduction of the period of time between giving birth and the next pregnancy • operated with: 1 x 9 V - Block PP3 Alkaline

Ref. no.	Ø	€
10250	1/10	

We recommend taking a reading once or twice a day over a period of a few consecutive days.

The first few minutes are decisive! The calf comes hind legs first or stays in the birth canal for too long. Breathing does not start, birth mucus closes the airways. Now is the time to act quickly! The calf is often pulled up by its hind legs or hung over the closest fence to enable the mucus to flow out of the airways. But the opposite actually happens: The calf has even more trouble breathing as its internal organs press against its lungs and bronchi. Using a resuscitator, colloquially known as a 'calf saver', is much easier on the farmer's back and also far more effective.

### HK Calf Resuscitator according to Dr. Bron

The HK Rheintechnik calf resuscitator looks like a large air pump. The suction cup is placed over the calf's nose and mouth. 1. Mucus is removed from the respiratory tract in one powerful stroke. 2. The mucus is expelled from the pump, then air is pumped into the airways. The lung's lobes and alveoli can unfold. This process can be repeated several times until the calf starts breathing by itself.



### Advantages:

- Especially sturdy: The metal cylinder is shock-resistant, the hard plastic suction cup with rubber lip is also practically indestructible. This makes the Dr Bron calf resuscitator perfect for quick use in emergency situations.
   Easy handling
- Can also be used by a single person

Ref. no.	Ð	€
1032	1	



**Top Seller** 

**Top Quality** 

GE#

Ŧ

### Lubricating Gel VetGel

 $\bullet$  lubricating gel to make hands and arms slippery and an excellent skin protection during rectal and vaginal examinations  $\bullet$  sperm-friendly

Recommended by veterinarians!									
Ref. no.	Contents	Ø		€					
1027	1000 ml / Bottle	1/6	378						
10272	5000 ml / Canister	1	84		-				

### **HK Lubricating Gel**

 $\bullet$  covers the skin with an optimal lubricating layer  $\bullet$  for all types of veterinary medical examinations  $\bullet$  ideally suited for hands, arms, gloves and instruments  $\bullet$  optimal pH value to maintain sperm quality

Ref. no.	Contents	Ē		€
10266	1000 ml / Bottle	1/10	600	
10267	5000 ml / Canister	1/4	192	

# Veterinary disposable gloves VETtop with shoulder protection

ideal for veterinaries
self-adhesive
very sensitive
for single-use only
food safe



Ref. no.	Colour	Size	Length	Material thickness	MOQ	Pieces / unit	Ø		€
15376	green transparent	unisize	120 cm	25 micron = 0,025 mm	1 pack	50 / pack	1/10	360	

### Veterinary disposable gloves VETtop

- ideal for veterinaries tearproof very sensitive
- for single-use only food safe

5		oniy • 1000 sale					10 POT			
	Ref. no.	Colour	Size	Length	Material thickness	MOQ	Pieces / unit	Ø		€
	1536	transparent	unisize	90 cm	28 micron = 0,028 mm	1 pack	100 / pack	1/15	360	

# Veterinary disposable gloves VETbasic

- multi-purpose: for farmers, veterinarians but also suitable for use as
- a refuelling glove for single-use only food safe

الا					a Ju p		
Ref. no.	Colour	Size	Length	Material thickness	MOQ	Pieces / unit 🗐 🚍 €	
15364	orange	unisize	90 cm	25 micron = 0,025 mm	1 pack	100 / pack 1/15 360	

### **Cattle Hobble with padding**

- particularly animal-friendly padding swivel to prevent chain tangling prevents injuries
- helps cows get up after giving birth Material: Polyester



Ref. no.	Leg distance	Ð	€
10284	40 cm	1/10/30	

### Cattle Hobble Top-Qualität

• increased tensile and tear resistance through special braiding method • extra-thick strap material for maximum load • helps cows get up after giving birth



### recommended by professional associations in Germany!

Ref. no.	Leg distance	Ø	€
10291	40 cm	1/10	
10292	22 - 42 cm	1/10	

### **Cattle Hobble Standard**

• helps cows get up after giving birth • prevents injuries • Material: Nylon

recommended by professional associations in Germany!

Ref. no.	Leg distance	Ø	€
10281	40 cm	1/10	
10282	20 - 42 cm	1/10	

### **Prolapse Bandage**

• prevents a prolapse from escalating and becoming chronic • Material: Nylon







### Cow Blanket for mature cattle

• warm, well-fitting blanket for ill and downer cows • can also be used for protection during exhibitions • outer materials made from tear-resistant 600 denier ribstop polyester • with soft, flexible, adjustable leg straps to the front and back • extremely water-resistant up to a 3000 mm water column • 3000 g/m<sup>2</sup>/24 h (air permeability) • machine washable at 30 °C

Ref. no.	Colour	Width	Total length	Ð	€
1545	grey	140 cm	145 cm	1/6	
1546	grey	140 cm	155 cm	1/6	
1548	grey	140 cm	175 cm	1/6	



### Cow Lifting Frame Profi for cows

• very robust and stable design - has been proving itself for decades • an indispensable tool for cows that can not stand on their own (e.g. difficult birth) • a sensible investment that quickly pays for itself and should be a must for every dairy farmer • the rubberised grip clamps can be adjusted to the size of the cow • any animal can be raised with the help of a pulley or other device • Material: metal

The best professional device!

Ref. no.	Colour	Suitable for	permissible animal weight	Ø		€
1067	green	small to medium breeds of cattle	900 kg	1	24	
1068	green	large cattle breeds, Beef Cattle	1.500 kg	1	8	

### **Cow Lifting Frame Standard for cows**

• inexpensive lifting device for cows in the standard version • for standing up downer cows • clamps are infinitely adjustable to the specific bowl width • any animal can be raised with the help of a pulley or other device • Material: metal

Ref. no.	Colour	Suitable for	permissible animal weight	Ø		€
1057	green	small to medium breeds of cattle	800 kg	1	42	

### **Cow Lifting Device**

developed for short to medium term support of weak cows • helps the cow regain full mobility • promotes blood circulation • the bib increases the load surface and supports the animal when lifting • significantly fewer pressure points thanks to the wide surface area • robust tearproof PVC material
padding to the belts in the udder area prevents chafing wounds • robust belts with adjustable ratchets enable the belt length to be adjusted even under load • all metal parts are galvanised • can be adjusted to different sizes • comes as a complete set in a carrying case







**Calving Supplies** 

1057

1067

GE#

Ŧ

Ref. no.	Colour	permissible animal weight	Ē		€
1066	green	1.000 kg	1/2	42	

# **Colostrum management**

# ColostroStart

### Colostrum management

The feeding of calves during the first days of life or even immediately after birth is crucial for their further development. First milk, also known as colostrum, has a higher percentage of immunoglobulins and nutrients than normal cow's milk. Consequently, the new-born calf needs to take in higher quantities of the high-quality colostrum straight away. It is recommended that a colostrum store be created with frozen colostrum. This means that there is always a stock of high-quality first milk available. If the quality of the colostrum after birth is poor (e.g. in heifers) or the amount produced is too low, frozen colostrum can be used instead. The products in our ColostroStart Colostrum Management System are the best way to help you to provide your new-born calves with colostrum. The aluminium pouches (4 litre) are easy to fill and can be pasteurised (optional), frozen and reheated without any problems. To administer the colostrum, simply screw on the drinking teat or drencher probe.

### We have put together retail sets geared towards your needs:

- 14640: ColostroStartSET 10
- 10 colostrum bags 1 teat 1 drencher probe


### 14641: ColostroStartSET 50

• 50 colostrum bags • 3 teats • 3 drencher probes


To make filling the pouches even easier, we offer the ColostroFILLER filling tool. The optional ColostroCASE drinks trough bag keeps the first milk warm for longer, making feeding easier.



### How it works:



# **Colostrum management**



### **Calf Feeding Bucket**

• complete with Super-Teat and screw valve • Easy to clean • if necessary mounting bracket item no. 1410 • Material: Plastic • food safe • with metal carry handle • acid-proof • with embossed measuring scale

Available in customer-specific composition. Note the instructions at the end of the catalogue.

Ref. no.	Colour	Capacity	MOQ	Pieces / unit	Ø		€	
144	grey	8 L	5 pieces	5 / pack	1/5	240		

### Calf Bucket with FixClip New Generation valve

The FixClip valve breaks completely new ground with the patented clamp closure, making removal and installation, as well as the cleaning of the valve and teat, easier and quicker than ever before.
Easy to clean • food safe • with metal carry handle • acid-proof • with printed fill scale on the back, with additional embossed scale on the inside

**New generation** –The completely modified shape guarantees a secure fit for the clip and valve body. The additional extension on the back of the clip, in particular, makes it easier to use, because it fastens the clip to the bucket and ensures a secure fitting while calves drink.

The advantages are obvious:

• minimal bacterial contamination and therefore healthier calves

New product NEW

٠	minimal time required for changing and cleaning the valve	

Ref. no.	Description	Colour	Capacity	MOQ	Pieces / unit	Ø		€
14235	with natural rubber teat	white transparent	8 L	5 pieces	5 / pack	1/5	180	

### Valve FixClip New Generation

The hygienic feeding bucket valve with the patented clip fastener!

**New generation** –The completely modified shape guarantees a secure fit for the clip and valve body. The additional extension on the back of the clip, in particular, makes it easier to use, because it fastens the clip to the bucket and ensures a secure fitting while calves drink.

It is assembled and dismantled in seconds, and the feeding bucket valve can be thoroughly cleaned with a brush. This ensures a high level of hygiene during feeding.

The FixClip valve has only three parts:

- · Valve body (a) with straight intake supports, making it easier to access for cleaning
- Removable valve flap (b)
- Clip (c) for fixing the teat and valve body to the feeding bucket

The FixClip valve is suitable for all conventional feeding buckets with a hole opening of 36 - 38 mm, but is only usable with the specially developed Vital Teats (item no. 14248/5), Super Teats (14249/5) and natural rubber teats (14251/5).

Ref. no.	Description	Colour	MOQ	Pieces / unit	Ø	€
14236	single	blue	5 pieces	5 / pouch	1	
14237	with natural rubber teat	blue			1/25	
14237/2	with natural rubber teat		1 blister pack	2 / blister pack	1	
14238/2	with Super Teat		1 blister pack	2 / blister pack	1	
14239/2	with Vital Teat		1 blister pack	2 / blister pack	1	
Ref. no.	Description		MOQ	Pieces / unit	Ø	€
142363/5	Butterfly Valve for FixClip Valve		1 pouch	5 / pouch	1	

### Teat for FixClip Valve

### Vital Teat:

• promotes natural suckling behaviour • the desire to suckle is better satisfied through slow and relatively difficult suckling • increases saliva production and therefore promotes digestion

### Super Teat:

• the proven standard teat

### Natural rubber teat:

· especially suitable for young calves

Ref. no.	Description	Colour	MOQ	Pieces / unit	Ø	€
14248/5	Vital Teat	black	1 pack	5 / pack	1/10/100	
14249/5	Super-Teat	red	1 pack	5 / pack	1/10/100	
14251/5	Natural rubber teat	beige	1 pack	5 / pack	1/10/100	



14249/5

New product

С

а

b

NEW

14211

14273

### **Screw Valve**

Ref. no.	Description	Colour	can be used for	MOQ	Pieces / unit	Ø	€
14276	149 and Super Teat 147	grey	for all Kerbl feeding buckets			1/50	
1490/2	149 and Super Teat 147	grey	for all Kerbl feeding buckets	1 blister pack	2 / blister pack	1/50	
14277	149 and Latex Teat 1454	grey	for all Kerbl feeding buckets			1/50	
149	complete	grey	for all Kerbl feeding buckets	10 pieces	10 / pack	1/10	
149/2	complete	grey	for all Kerbl feeding buckets	1 blister pack	2 / blister pack	1/100	

### sealing ring for feeding buckets

Ref. no.	Description	Colour	Thickness	can be used for	MOQ	Pieces / unit	Ø	€
148	Standard	red	3 mm	Screw valve 149	50 pieces	50 / pouch	1/50/5.000	
148/5	Standard	red	3 mm	Screw valve 149	1 blister pack	5 / blister pack	1/100	
1480	Standard	blue	4 mm	Galvanised feeding bucket	50 pieces	50 / pouch	1/50/2.500	
1480/5	Standard	blue	4 mm	Galvanised feeding bucket	1 blister pack	5 / blister pack	1	
1489	НІКО	red	2,5 mm	Screw valve 149	50 pieces	50 / pouch	1/50	
1489/5	HIKO	red	2,5 mm	Screw valve 149	1 blister pack	5 / blister pack	1	

### **Cover for Feeding Bucket**

Cover for 13 L bucket: Dirt, rain water and flies can not get into the bucket. The feeding bucket and cover are easy to hang on the mounting brackets.

Cover, single: Keeps dirt out of the bucket interior. A feeding bucket with an attached cover can be mounted to calf house fences and retrofitted mounting brackets. Available in several colours.

Cover MilkGuard: Flies, dirt and rainwater cannot get into the bucket interior thanks to the completely closed cover, ensuring a high standard of hygiene. Feeding buckets with an attached cover can be easily attached to mounting brackets.

Ref. no.	Description	Colour	can be used for	Ð	€	
1441	simply	grey	for all Kerbl feeding buckets	1/50		
14211	simply	green	for all Kerbl feeding buckets	1/50		
14272	MilkGuard	white transparent	for all Kerbl feeding buckets	1/50		
14273	13	white transparent	14284 Feeding Bucket 13 L	1/76		NEW

# **Mounting Bracket**

• suitable for all feeding buckets

1408: Thanks to the bucket safety catch, the feeding bucket stays in position when being drunk from and cannot be pushed back.

Also suitable for mounting on calf house fences.

Ref. no.	Description	Material	MOQ	Pieces / unit	Ø		€	L
1408	with bucket safety catch	metal galvanised			1/50	900		L
1410	simply	metal galvanised	10 pieces	10 / pack	1/10/150	6.000		r
1410/2	simply	metal galvanised	1 blister pack	2 / blister pack	1	1.800		

### Catch Bucket Guard

The catch ensures that the animal cannot toss the feeding bucket out of the bucket holder. Also suitable for mounting on calf house fences. • suitable for all feeding buckets

1406: Can be retrofitted to existing mounting brackets (item nos. 1408, 1410). 1407: the feeding bucket can be hung directly in it

Ref. no.	Description	Material	MOQ	Pieces / unit	Ø		€	
1406	retrofittable	Plastic	1 pack	3 / pack	1/3/60	1.800		
1407	with bucket holder	Plastic	1 pack	3 / pack	1/3/60	1.800		NEW



1407

1406





1441

L
l

1408

•••

Ŧ

# Calf Feeder Tray Multi Feeder

### No portioning

• for the simultaneous provision of drinks to up to 5 calves • makes animal surveillance easier during milk feeding • without portioning and with rounded corners, thus very easy to clean • for hanging on barn walls, feed barriers, fences, etc. (pipes up to max. Ø 61 mm (2") • with an easy to use rotary snap closure for attaching and securing to the tray • ideally suited to the large-area Calf House (item nos. 14440, 14520, 14540) • stackable • easy to transport • not suitable for sanitary valves (ref. 14220/2, Art. 14230) and FixClip Valves • food safe • chemical-resistant



Ref. no.DescriptionColourCapacityLengthWidthHeight $\bigcirc$ $\bigcirc$ $\leftarrow$ 14218with 5 valves (149) and 5 Super Teats (147)green30 L70 cm35,4 cm27,8 cm15714201with 5 valves (149) and 5 latex teats (1454)green30 L70 cm35,4 cm27,8 cm15714202with 5 Big Softy Teats (14141)green30 L70 cm35,4 cm27,8 cm15714215single, with large openings for Super and Latex Teatsgreen30 L70 cm35,4 cm27,8 cm15714203single, with small openings for Big Softy Teatsgreen30 L70 cm35,4 cm27,8 cm15714203single, with small openings for Big Softy Teatsgreen30 L70 cm35,4 cm27,8 cm15714203single, with small openings for Big Softy Teatsgreen30 L70 cm35,4 cm27,8 cm15714203single, with small openings for Big Softy Teatsgreen30 L70 cm35,4 cm27,8 cm15714203Screw Valve 149 and Super Teat 147 14910/5grey1 pack5 / pack111411/5Teat Big Softyblack100 mm1 blister pack5 / pack114141/5Teat Big Softy and Little Softy teats with valve orange1 pack5 / pack1114142Corner for Big Softy and Little Softy teats with valve <br< th=""><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></br<>										
14201       with 5 valves (149) and 5 latex teats (1454)       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14202       with 5 Big Softy Teats (14141)       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14215       single, with large openings for Super and Latex Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14203       single, with small openings for Big Softy Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14203       single, with small openings for Big Softy Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14203       Single, with small openings for Big Softy Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14910/5       Screw Valve 149 and Super Teat 147       grey       1 pack       5 / pack       1       1         14915/5       Screw Valve 149 and Latex Teat 1454       grey       1 pack       5 / pack       1         14890/5       sealing ring       white       1 pack       5 / pack       1         148890/5       sealin	Ref. no.	Description	Colour	Capacity	Length	Width	Height			€
14202       with 5 Big Softy Teats (14141)       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14215       single, with large openings for Super and Latex Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14203       single, with small openings for Big Softy Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         Ref. no.       Description       Colour       Length       MOQ       Pieces / unit       Image: Colour       Image: Colour       1       57         14910/5       Screw Valve 149 and Super Teat 147       grey       1 pack       5 / pack       1       5         14910/5       Screw Valve 149 and Latex Teat 1454       grey       1 pouch       5 / pack       1         14910/5       Screw Valve 149 and Latex Teat 1454       grey       1 pouch       5 / pack       1         14910/5       Screw Valve 149 and Latex Teat 1454       grey       1 pouch       5 / pack       1         14141/5       Teat Big Softy       black       100 mm       1 blister pack       5 / blister pack       1         14890/5       sealing ring       white       1 pack       10 / pack	14218	with 5 valves (149) and 5 Super Teats (147)	green	30 L	70 cm	35,4 cm	27,8 cm	1	57	
14215       single, with large openings for Super and Latex Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14203       single, with small openings for Big Softy Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         Ref. no.         Description       Colour       Length       MOQ       Pieces / unit       Image: Colour       €         14910/5       Screw Valve 149 and Super Teat 147       grey       1 pack       5 / pack       1       1         14141/5       Teat Big Softy       black       100 mm       1 blister pack       5 / pack       1         14890/5       sealing ring       white       1 pack       5 / pack       1         14142       Corner for Big Softy and Little Softy teats with valve       orange       1 pack       10 / pack       1         14144       Corner for Big Softy and Little Softy teats without valve       white       1 pack       10 / pack       1	14201	with 5 valves (149) and 5 latex teats (1454)	green	30 L	70 cm	35,4 cm	27,8 cm	1	57	
14215       Super and Latex Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         14203       single, with small openings for Big Softy Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         Ref. no.       Description       Colour       Length       MOQ       Pieces / unit       Image: Colour       Image: Colour       1 pack       5 / pack       1       1         14910/5       Screw Valve 149 and Super Teat 147       grey       1 pack       5 / pack       1       1       1         14915/5       Screw Valve 149 and Latex Teat 1454       grey       1 pouch       5 / pouch       1       1         14141/5       Teat Big Softy       black       100 mm       1 blister pack       5 / blister pack       1         14890/5       sealing ring       white       1 pack       5 / pack       1         14142       Corner for Big Softy and Little Softy teats with valve       orange       1 pack       10 / pack       1         14144       Corner for Big Softy and Little Softy teats without valve       white       1 pack       10 / pack       1	14202	with 5 Big Softy Teats (14141)	green	30 L	70 cm	35,4 cm	27,8 cm	1	57	
I4203       Big Softy Teats       green       30 L       70 cm       35,4 cm       27,8 cm       1       57         Ref. no.       Description       Colour       Length       MOQ       Pieces / unit       Image: Colour       Image: Colour       1       Image: Colour	14215	5 5 1 5	green	30 L	70 cm	35,4 cm	27,8 cm	1	57	
14910/5Screw Valve 149 and Super Teat 147grey1 pack5 / pack114915/5Screw Valve 149 and Latex Teat 1454grey1 pouch5 / pouch114141/5Teat Big Softyblack100 mm1 blister pack5 / blister pack114890/5sealing ringwhite1 pack5 / pack114142Corner for Big Softy and Little Softy teats with valveorange1 pack10 / pack114144Corner for Big Softy and Little Softy teats without valvewhite1 pack10 / pack1	14203		green	30 L	70 cm	35,4 cm	27,8 cm	1	57	
14915/5Screw Valve 149 and Latex Teat 1454grey1 pouch5 / pouch114141/5Teat Big Softyblack100 mm1 blister pack5 / blister pack114890/5sealing ringwhite1 pack5 / pack114142Corner for Big Softy and Little Softy teats with valveorange1 pack10 / pack114144Corner for Big Softy and Little Softy teats without valvewhite1 pack10 / pack1	Ref. no.	Description		Colour	Length	n MOQ	Pieces	s / unit	Ē	€
14141/5Teat Big Softyblack100 mm1 blister pack5 / blister pack114890/5sealing ringwhite1 pack5 / pack114142Corner for Big Softy and Little Softy teats with valveorange1 pack10 / pack114144Corner for Big Softy and Little Softy teats without valvewhite1 pack10 / pack1	14910/5	Screw Valve 149 and Super Teat	147	grey		1 pack	5/	pack	1	
14890/5sealing ringwhite1 pack5 / pack114142Corner for Big Softy and Little Softy teats with valveorange1 pack10 / pack114144Corner for Big Softy and Little Softy teats without valvewhite1 pack10 / pack1	14915/5	Screw Valve 149 and Latex Teat 1	454	grey		1 pouch	n 5/p	ouch	1	
14142     Corner for Big Softy and Little Softy teats with valve     orange     1 pack     10 / pack     1       14144     Corner for Big Softy and Little Softy teats without valve     white     1 pack     10 / pack     1	14141/5	Teat Big Softy		black	100 mr	n 1 blister p	ack 5 / blist	ter pack	1	
14144         Corner for Big Softy and Little Softy teats without valve         white         1 pack         10 / pack         1	14890/5	sealing ring		white		1 pack	5/	pack	1	
	14142	Corner for Big Softy and Little Softy teats	s with valve	orange		1 pack	10 /	pack	1	
14214 Cover for Multi Feeder black 1/100	14144	Corner for Big Softy and Little Softy teats	without valve	white		1 pack	10 /	pack	1	
	14214	Cover for Multi Feeder		black					1/100	


# **Drinking Trough Multi Feeder**

### with portioning

with 5 portion compartments for the simultaneous provision of drinks to up to 5 calves • makes animal surveillance easier during milk feeding • Volume per portion compartment: 3 litres • with rounded corners, thus very easy to clean
for hanging on barn walls, feed barriers, fences, etc. • easy mounting and securing of the trough thanks to elastic straps • stackable • easy to transport
acid-proof • only suitable for Big Softy Teats • ideally suited to the large-area Calf House (item nos. 14440, 14520, 14540) • food safe



Ref. no.	Description	Colour	Capacity	Length	Width	Height			€
14204	with Big Softy Teats	green	30 L	81 cm	43 cm	38 cm	1	48	
14205	without teat	green	30 L	81 cm	43 cm	38 cm	1	48	
Ref. no.	Description		Colour	Length	MOQ	Pieces / unit	Ē	9	€
14141/5	Teat Big Softy		black	100 mm	1 blister pack	5 / blister pack	1		
14142	Corner for Big Softy and Little Softy	teats with valve	orange		1 pack	10 / pack	1		
14144	Corner for Big Softy and Little Softy te	ats without valve	white		1 pack	10 / pack	1		
14214	Cover for Multi Feede	r	black				1/10	)0	



### Teat

• for automatic drinkers • with round holes




### round holes

Ref. no.	Description	Colour	Length	MOQ	Pieces / unit	Ø	€
1472	Standard	white	100 mm	50 pieces	50 / pack	1/50/500	
1472/3	Standard	white	100 mm	1 blister pack	3 / blister pack	1/120	
1474	Super	red	100 mm	50 pieces	50 / pack	1/50/500	
1474/3	Super	red	100 mm	1 blister pack	3 / blister pack	1	
1478	Rubber	honey	100 mm			1/50/500	

# **Teat Big Softy**

• replacement teat for Calf Drinking Tray Multi Feeder, Double Calf Drinking Trough MILK TRAIN and Calf Drinking Trough MILK BAR



### Calf Teat MilkyTeat

- with integrated flap valve for easy drinking - Spare teat for application with calf bottles - suitable for SpeedyFeeder and MilkyFeeder

Ref. no.	Colour	MOQ	Pieces / unit	Ø	€
14672	grey	1 pouch	10 / pouch	1/30	

NEW

New product


Ŧ

### Aluminium calf feeder valve with teat

• extremely quick opening using a bayonet joint makes the item very hygienic and easy to clean



Ref. no.	MOQ	Pieces / unit	Ø	€				
1415			1/20					
1415/2	1 blister pack	2 / blister pack	1/50					
							Æ	
Ref. no.		Descript	ion		MOQ	Pieces / unit	±1	€
1419	Tea	t for Aluminium c	alf drink	er valve	20 pieces	20 / pack	1/20/200	
1419/3	Tea	t for Aluminium c	alf drink	er valve	1 blister pack	3 / blister pack	1/50	



### Calf Bottle MilkyFeeder

with 3-stage valve for adjustment of the drinking speed
easy-to-clean due to the large bottle opening
teat with integrated flap valve for easy drinking
with screw fastener
14677: Teat with cover, also suitable for 1422 and 1487
with measuring scale (in I, qt.)

with 3-stage valve of the drinking sp				9
Ref. no.	Capacity	Ē	Ħ	€
14676	4 L	1/12	144	
			Æ	
Ref. no.	Description		Ħ	€
14677	Teat with lid		1/250	

#### **Milk Bottle**

• suitable for single animal breeding and for drug administration

• complete with teat • with measuring scale



Ref. no.	Description	Capacity	Ø	Ħ	€
1425	round	1 L	1/20	320	
1426	angular	2 L	1/20	160	
1461	square, with handle	3 L	1/40	320	

### **Milk Bottle**

• with milk teat 1432 • can also be used with the drench probe (item no. 14682, 14683) • for milk portions as well as liquid therapy and electrolyte treatment of calves • large filler hole with screw cap outparts of an arrivate read arrivat

• external grip without cavities making it easy to clean and prevent nucleating deposits • Material: Plastic

• food safe • with measuring scale

Ref. no.	Capacity	Ø		€
14255	2,5 L	1/10	260	
14257	4 L	1/10	160	

Ref. no.	Description	suitable for	Ø	€
1432	Milk Teat for milk bottle		1/25/300	
14256	Metal Holder	14255	1/10	
14258	Metal Holder	14257	1/10	



14257

GE/


Ŧ

1461

	70 mm) diameter • Screw Imp" teat • large base en		andle • Bottle tle opening		187	1422	() [ a	ipeedy Feed blue), Speed Drencher (re und Big Drei green).	ły d)
Ref. no.	Capacity		€	100			1423		
1422	2,5 L	1/20 240							
1487	4 L	1/12 144							
								_	
Ref. no.	Description	Æ	€					SHO	OF
1423	Teat with lid	1/25						ANTERNALI	ONAL LTD
						14674	-		
<ul> <li>with 3-stage valv</li> <li>speed</li> <li>easy-to-cle</li> <li>with moveable particular</li> </ul>	her MilkyDren re for adjustment of the d robe attachment • with so th cover, also suitable for uring scale (in I, qt.)	rinking e opening crew fastener	for ac	3-stage valve ljustment of the ing speed	14675	P			?
Ref. no.	Capacity		Probe length	n 🛱		€			
14674	4 L		52 cm	1/12	96				
Ref. no.	Descrip	otion		Probe length	Ē	€			
Ref. no. 14675	Descrip Probe fixed			Probe length 52 cm	1/80	€			
				-		€			
14675 <b>Calf Drenc</b> • for liquid therapy • with measuring s with 3-stage value for adjustment of	Probe fixed to the fixed of the	with cover		-	1/80	€ 14695	14692		14699
14675 Calf Drenc • for liquid therapy • with measuring s with 3-stage value	Probe fixed to the fixed of the	with cover		-	1/80	2			14699
14675 <b>Calf Drenc</b> • for liquid therapy • with measuring s with 3-stage value for adjustment of the drinking spece	Probe fixed we he	with cover	crew fastener	52 cm	1/80	14695		C	
14675 <b>Calf Drenc</b> • for liquid therapy • with measuring s with 3-stage value for adjustment of the drinking spect	Probe fixed we fixed	with cover t of calves • with so on	crew fastener	52 cm	1/80	14695 I 4695 I 4695 I 4695			14699 €
14675 <b>Calf Drenc</b> • for liquid therapy • with measuring s with 3-stage value for adjustment of the drinking spec- Ref. no. 14692	Probe fixed we he	with cover t of calves • with so on probe	crew fastener	52 cm	1/80	14695 I 4695 I 4695 I I 4695 I	1/10	☐	
14675 <b>Calf Drenc</b> • for liquid therapy • with measuring s with 3-stage value for adjustment of the drinking spect Ref. no. 14692 14693	Probe fixed ve her Profi and electrolyte treatmen icale ve of ed Descripti with flexible with fixed p	with cover t of calves • with so t of calves	crew fastener	52 cm	1/80	14695 I 4695 I 4695 I I 4695 I 4695	1/10 1/10	120 120	
14675 <b>Calf Drenc</b> • for liquid therapy • with measuring s with 3-stage value for adjustment of the drinking spec- Ref. no. 14692	Probe fixed we he	with cover t of calves • with so t of calves	crew fastener	52 cm	1/80	14695 I 4695 I 4695 I I 4695 I	1/10	☐	
14675 Calf Drenc • for liquid therapy • with measuring s with 3-stage value for adjustment of the drinking spectrum Ref. no. 14692 14693 14695	Probe fixed ve her Profi and electrolyte treatmen icale ve of ed Descripti with flexible with fixed p	with cover t of calves • with set t of calves • with	crew fastener	52 cm	1/80	14695 I 4695 I I 4695 I I I I I I I I I I I I I I I I I I I	1/10 1/10 1/10	120 120 120 120	Ę
14675 Calf Drenc • for liquid therapy • with measuring s with 3-stage value for adjustment of the drinking spect Ref. no. 14692 14693 14695 Ref. no.	Probe fixed ve her Profi and electrolyte treatmen icale ve of ed Descripti with flexible with fixed p	with cover t of calves • with set on probe probe Descript	crew fastener	52 cm	1/80	14695 I 4695 I 4	1/10 1/10 1/10	120 120 120	
14675 Calf Drenc • for liquid therapy • with measuring s with 3-stage value for adjustment of the drinking spectrum Ref. no. 14692 14693 14695	Probe fixed ve her Profi and electrolyte treatmen icale ve of ed Descripti with flexible with fixed p	with cover t of calves • with set t of calves • with	crew fastener	52 cm	1/80	14695 I 4695 I I 4695 I I I I I I I I I I I I I I I I I I I	1/10 1/10 1/10 n	120 120 120 120	Ę

#### **Speedy Drencher**

 $\cdot$  drinking bottle with 3-way valve  $\cdot$  ergonomic bi-directional handle  $\cdot$  Screw cap with large bottle opening  $\cdot$  large base ensures high stability



Ø

1/30


300

152 cm

#### **Drench Bag**

14678

• transparent feed pouch for liquid therapy and electrolyte treatment of calves • with zip closure for easy filling and cleaning • with flexible probe incl. tube • with tube clamp to regulate drinking speed and to close the tube • with embossed measuring scale



2,5 L



GE7

Ŧ

1-1

### Syringe Drencher

• manual design • light and unbreakable • easy to take apart and clean • Dosage settings: steplessly adjustable using the setting wheel

Ref. no.	Capacity	Ð	€
23610	70 ml	1/50	
23612	200 ml	1/20	
2366	300 ml	1/20	
2380	500 ml	1/10	

Ref. no.	Description	suitable for	Ð	€
23616	sealing ring for drencher	23610	1/5	
23618	sealing ring for drencher	23612	1/5	
23615	sealing ring for drencher	2366	1/5	
23619	sealing ring for drencher	2380	1	

### Drencher

- the ideal filler bottle for livestock - wide opening (70 mm) for easy filling with dry or liquid foodstruff - 12 cm long feeder unit



1437

2380



236

23612

2361

All covers fit all Speedy Feeders (blue), Speedy Drencher (red) and Big Drencher (green).



Ref. no.	Description	Capacity	Probe length	Ø		€
1424	Easy Drencher	1,2 L	12 cm	1/30	540	
1484	Big Drencher	2,5 L	12 cm	1/20	240	
Ref. no.	I	Description	Probe length		Ø	€
14102	Probe	for Big Drencher	12 cm		1	

### **Dry Food Bottle**

• complete with teat and plastic holder • developed for calf rearing feed, which can be given from the 2nd day for approx. 3 months and greatly promotes the development of the rumen • the future output (milk production) of the animal is thus increased, and the utilisation of feed is significantly improved

						1428
Capacity	Ø		€			
4 L	1/20	180			0	
				<u> </u>		
I	Description			Ð	€	
Teat fo	or dry food bott	le		1/25/300		
Milk Te	eat for milk bott	:le		1/25/300		
N	letal Holder			1/6		
	4 L Teat fo Milk Te	4 L 1/20 Description Teat for dry food bott	4 L 1/20 180 Description Teat for dry food bottle Milk Teat for milk bottle	4 L 1/20 180 Description Teat for dry food bottle Milk Teat for milk bottle	4 L     1/20     180       Description       Teat for dry food bottle     1/25/300       Milk Teat for milk bottle     1/25/300	4 L     1/20     180       Description     Image: Constraint of the state of the

1432

1429

#### Milk warmer MilkPot 50

Specialist literature and studies indicate that the feeding of young calves has a marked effect on animal health, development and therefore the later performance of the animal. To achieve positive results, an in-depth knowledge on the part of the farmer and technical equipment are usually required. Our milk warmer provides the ideal support for calf rearing, especially for medium-sized operations. It closes the gap between immersion heaters and mobile milk tanks with elaborate equipment. Quickly and without much effort, up to 50 litres of milk or milk substitute mixture can be heated up. The milk is heated using a water bath gently and without causing it to scorch. The milk warmer is also ideal for pasteurising milk.

#### Stirrer optionally available!

The powerful optional stirrer ensures clump-free stirring of milk substitute. By briefly switching the mixer on while fresh milk is heating, the heating time can be shortened. The cover with integrated mixer can easily be placed on the MilkPot 50 (Art. 141450) and screwed into position.

- 1,000 rpm
- 370 W

Ref. no.

141450

Ref. no.

141461

141462

ready to connect



Technical data	141450
Capacity	50 L
Voltage	230 V AC
Mains frequency	50 Hz
Temperature control range up to	0 - 100 °C
Weight	32 kg
Connecting Cable	

Description

Cover with agitator

Supporting feet

Height

63 cm

Ø

45,5 cm

Colour

blue

Heating output

2.500 W

# Milk heater for calf feeding

GE#

Ŧ

- made from food-grade stainless steel
- · easy cleaning thanks to the lid which can be fully opened
- with volume scale inside the tank
- · water bath: separate inlet and outlet, viewing window to check fill levels
- stepless thermostat
- pasteurisation possible
- 1" outlet with slider valve from the food industry
- with rod thermometer (food-safe)
- incl. lid



# Milk Heater FastHeat

#### FastHeat and FastHeat Digital

The latest generation calf milk heater.

Calf milk heaters from the FastHeat range combine functional design with clear time and energy savings.

#### **Energy saving**

At just 1700 W, the new FastHeat calf milk heaters use much less energy than conventional products. The patented design and reduced height of the cast aluminium radiator enable even low fill levels to be heated to the desired temperature quickly, without unnecessary energy loss.

#### Quick and uniform heating

FastHeat calf milk heaters make use of the milk's heat convection in a pretty smart way: The heated milk rises to the surface while the cold milk drops to the bottom of the bucket where the heater heats it up again. Because the heater is typically located in the coolest part of the milk due to its reduced build height (bottom of the bucket), it can transfer its heating energy to the milk at full capacity, and thus quite efficiently. This ensures efficient and uniform heating of the milk.

From 18 °C to 42 °C in around 11 minutes (bucket holding 8 litres of water).



### Milk heater for calf feeding FastHeat Digital

• digital control with steplessly-selectable temperatures (from 10 °C to max. 90 °C) • stores the last target temperature set • illuminated display • visual and audible signal output, e.g. when the set target temperature is reached • safety cut-out in the event of dry operation • connecting cable holder so that the connecting plug always stays dry • with practical and reliable handle • extremely lightweight - only 2.7 kg (around 25 % lighter than standard products) • easy to clean thanks to PTFE-coated heater element • with thermal fuse • 3 m connecting cable

Optimised for feeding buckets with volumes up to 10 litres



Very easy to clean thanks to its patented shape and PTFE coating!

Technical data	14160
Voltage	230 V
Mains frequency	50 Hz
Diameter of the heating element	16,5 cm
Dip depth	8 - 69 cm
Temperature control range up to	10 - 90 °C
Weight	2,7 kg
Connecting Cable	3 m





# Milk heater for calf feeding

GE/

Ŧ

### Milk heater for calf feeding FastHeat

with tried and tested temperature regulation making it easy to operate with the usual comfort
visual signal output, e.g. when the set target temperature is reached
with practical handle

• extremely lightweight - only 2.7 kg (around 25 % lighter than standard products) • easy to

clean thanks to PTFE-coated heater element • with thermal fuse • 3 m connecting cable

iical data	14150		Very easy to clean thanks to its	
oltage	230 V		patented shape	1
ains frequency	50 Hz		and PTFE coating!	
Diameter of the heating element	16,5 cm			
Dip depth	8 - 69 cm			
Temperature control range up to	90 °C			
Weight	2,7 kg			
Connecting Cable	3 m			
Ref. no. Colour H	Heating output	Height	Plug type	

14150	white	1.700 W	81,5 cm	with safety plug	1	25

### Milk heater for calf feeding EasyHeat

with handle section for one-handed operation • adjustable thermostat
 easy to clean thanks to a polished heater made from cast aluminium • very stable • powerful heating output • can be used for fill heights starting at approx. 13 cm • with mounting for connection cable • 3 m connecting cable



#### Technical data

230 V
50 Hz
16 cm
13 - 75 cm
0 - 80 °C
4,7 kg
3 m



Ref. no.	Colour	Heating output	Height	Plug type	Ø		€
14170	green	2.300 W	86 cm	with safety plug	1	20	
14170-CH	green	2.300 W	86 cm	with Swiss plug	1	24	
14172	green	3.000 W	86 cm	with safety plug	1	20	

# Milk heater for calf feeding

#### Milk heater for calf feeding with PTFE coating and bar handle

• with practical handle for one or two-handed operation • adjustable thermostat • very stable • powerful heating output • can be used for fill heights starting at approx. 15 cm • with thermal fuse • 3 m connecting cable

#### Benefits of the PTFE (polytetrafluoroethylene) coating:

- very easy to clean thanks to the dirt-repellent nature of the PTFE coating
- · absolutely acid resistant
- coating has a high temperature resistance, so the heating ring does not burn

from 18 °C to 42 °C in around 16 minutes (bucket holding 8 litres of water).

Technical dat	ta	1420				
Voltage		230 V				18
Mains freque	ncy	50 Hz				
Diameter of t	he heating elemen	nt 16 cm			-	2
Dip depth		15 - 69 cm				
Temperature	control range up to	o 80 °C				
Weight		4,7 kg				
Connecting C	able	3 m				
Ref. no.	Colour	Heating output	Height	Plug type	Ē	
1420	white	2.300 W	81,5 cm	with safety plug	1	25

#### Milk heater for calf feeding with handle

• with practical handle for one or two-handed operation • adjustable thermostat • very stable • powerful heating output • can be used for fill heights starting at approx. 15 cm • with thermal fuse • 3 m connecting cable



from 18 °C to 42 °C in around 16 minutes (bucket holding 8 litres of water).

Technical data	1418
Voltage	230 V
Mains frequency	50 Hz
Diameter of the heating element	16 cm
Dip depth	15 - 69 cm
Temperature control range up to	80 °C
Weight	4,7 kg
Connecting Cable	3 m





Ref. no.	Colour	Heating output	Height	Plug type	Ø		€
1418	white	2.300 W	81,5 cm	with safety plug	1	25	

1.0

渝

7



### Calf box

The calf box ensures that the calf enjoys plenty of fresh air, but is not exposed to any draughts. It is also protected from harmful pathogenic bacteria. The animal does not lie directly on the floor in the calf box, but rather on the raised grille. This keeps the calf warmer and dryer. The calf box is available in two sizes.

- stable,hot dip-galvanised metal frame
- GRP base grille (two-part) offering excellent grip and anti-slip properties
- easy-to-clean side walls made from PVC panels with smooth surface
- the open gap in the upper area of the side walls allows the calf to have visual contact with its neighbours
- revolving door which opens in both directions
- includes a watering bucket mounting bracket and two foldable bucket • brackets
- Bucket not included
- · Comes disassembled







Feeding places can be individually blocked



roof optionally available



The folding handle on the front make moving it exceptionally easy



Can be transported with pallet forks

transport device optionally available

#### Suitable in accordance with animal welfare regulations:

Our calf houses and boxes comply with animal welfare regulations and have the optimum design for the requirements of calf rearing. Find out more online at www.kerbl.de

#### Local animal protection regulations must be observed! Please note separate freight costs.

Technical data	14610	14611								
External hut dimension	ns 173 x 93 x 131 cm	201 x 107 x 131 cm		Outer dimensions incl. bucket holder						
House inner dimension	ns 130 x 85 x 106 cm	160 x 10	0 x 106 cm							
House weight	121 kg	160 kg								
Ref. no.	Description	Ē	<i>≣</i> €						窟	窟
14610	Calf box small	1	5	<b>B</b>			1			ante
14611	Calf box large	1	5				6	$\mathbf{q}$	$\mathbf{H}$	Ŧ
Ref. no.	Description		Length	Width	Height	Weight	Ø		€	
14612	Roof for calf box small		153 cm	98 cm	3,5 cm	22 kg	1	24		<b>. .</b>
14613	Roof for calf box large		180 cm	120 cm	3,5 cm	25 kg	1	25		<b>B</b>
14609	Transport Device for calf box						1	50		
14610-1	GRP Base Grille for calf box small (two part)		130 cm	85 cm	2,5 cm	15,6 kg	1			<b>•</b> ••
14611-1	GRP Base Grille for calf box large (two part)		160 cm	100 cm	2,5 cm	22 kg	1			<b>B</b>
14611-2	PVC panel Calf box for side wall		165 cm	3 cm	25 cm		1			
14611-3	PVC panel Calf box for rear wall		97 cm	3 cm	25 cm		1			

Ŧ




### CalfHouse PE UV+

#### The especially robust one!

High stability and durability are ensured because it is made from high-guality, impact-resistant HDPE plastic with integrated UV stabilisers. The hut entrance threshold, reinforced with steel tubes, ensures a high level of stability. Optimal climate control of the Calf House is achieved via the adjustable ventilation flap that can be fixed at all levels. This also makes it easy to fill the Hay Rack. The especially smooth interior surfaces make cleaning child's play and thus improves hygiene.

- increasing roof slope with ventilation openings ensure optimum air circulation so that humid air can • heat escape at the top
- pure white surfaces prevent overheating of the interior space
- additional UV stabilisers prevent the calf house heating excessively and reduce the natural degeneration of the material
- Bucket, feed box and hay rack not included •



#### Multifunctional revolving doors:

- Flex rail (a) with drinking bucket and bucket safety catch (b), 2 feed openings (c), with hinged bucket holders for feed buckets
- The high position of the feed bucket promotes the natural stretching of the neck, so that the milk can pass directly into the abomasum.
- The bucket's inclined position ensures it is fully emptied •
- Flex rail for variable mounting of the bucket holder and the optional dry feed bottle holder



#### Lightweight fencing:


The reduced weight of the lightweight fencing (approx. 30 kg) makes it easier to lift and to reposition the house integrated in the fence, while also offering a high degree of stability.



#### Heavyweight fencing:

The heavyweight version (approx. 45 kg) is extremely robust and its increased weight ensures even greater stability.





#### Practical and convenient



Barrier near the base of the fence allows unimpeded access



Tip the hut into the fence for easy cleaning or repositioning



To clean the forecourt, fold the fence over the hut



Handle for easy lifting



Threshold at the hut entrance stops bedding getting out



The revolving door can optionally also be placed in the house entrance to lock the calf in



Side guards stop calves from slipping through and lend stability



Large solid rubber tyres with needle bearing enable easy moving

#### Suitable in accordance with animal welfare regulations:

Our calf houses and boxes comply with animal welfare regulations and have the optimum design for the requirements of calf rearing. Find out more online at www.kerbl.de

Local animal protection regulations must be observed! Please note separate freight costs.


Technical d	ata 14	1565	1	4566		14570				
House mate	erial po	olyethylene	р	olyethylene		polyeth	iylene			
External hut	t dimensions 20	)5 x 115 x 135 cm	2	05 x 115 x 13	5 cm	205 x 1	15 x 135 c	m		
House weig	ht 37	7,5 kg	3	7,5 kg		37,5 kg	]			
Fencing dim	nensions		1	50 x 110 x 96	cm	150 x 1	10 x 96 cm	ı		
Fencing wei	ight		а	pprox. 30 kg		approx	. 45 kg			
Ref. no.		Descri	ption				Æ	Ħ	€	
14565		CalfHouse PE UV+	without fer	ncing			1	17		<b>.</b> B
14566		CalfHouse PE UV+	with light fe	encing			1	4		<b>•</b> ••
14570		CalfHouse PE UV+ v	with heavy f	encing			1	4		<b>. .</b>
Ref. no.	Description	Material	Length	Width	Height	Weight	Ø		€	
145620	Fence Easy	metal galvanised	150 cm	110 cm	96 cm	30 kg	1	24		<b>P</b>
14572	Fence heavy	metal galvanised	150 cm	110 cm	96 cm	45 kg	1	22		<b>~</b>
14568	Door and Tyre Set for CalfHo PE UV+	use				13 kg	1	34		
14567	threshold Retrofit Kit	metal	98 cm	2,5 cm	17 cm	2,2 kg	1	200		
3230	Hay Rack small model	metal galvanised	56 cm	29,5 cm	23 cm		1	78		




### **CalfHouse Premium Plus**

#### More space! More stability!

This Calf House, increased in both length and height, offers the calf improved protection from the weather and gives farmers more space when handling the calf. The CalfHouse Premium Plus is built using special fibreglass material with a very high surface mass. This gives it excellent resistance against tears and impacts. The wall construction is also additionally reinforced in all edge areas and in the corners of the calf house. The easy-to-clean plastic barrier improves hygiene. This Calf House also has an optimal ventilation system that regulates the climate in the house without any draughts. Bucket not included





#### Multifunctional revolving doors:

- Flex rail (a) with drinking bucket and bucket safety catch (b), 2 feed openings (c), with hinged bucket holders for feed buckets
- The high position of the feed bucket promotes the natural stretching of the neck, so that the milk can pass directly into the abomasum.
- The bucket's inclined position ensures it is fully emptied
- Flex rail for variable mounting of the bucket holder and the optional dry feed bottle holder





#### Lightweight fencing:

The reduced weight of the lightweight fencing (approx. 30 kg) makes it easier to lift and to reposition the house integrated in the fence, while also offering a high degree of stability.

#### Heavyweight fencing:

The heavyweight version (approx. 45 kg) is extremely robust and its increased weight ensures even greater stability.

Ŧ

#### Practical and convenient



Barrier near the base of the fence allows unimpeded access



Tip the hut into the fence for easy cleaning or repositioning



To clean the forecourt, fold the fence over the hut



Handle for easy lifting



Threshold at the hut entrance stops bedding getting out



The revolving door can optionally also be placed in the house entrance to lock the calf in



Side guards stop calves from slipping through and lend stability



Large solid rubber tyres with needle bearing enable easy moving

#### Suitable in accordance with animal welfare regulations:

Our calf houses and boxes comply with animal welfare regulations and have the optimum design for the requirements of calf rearing. Find out more online at www.kerbl.de

#### Local animal protection regulations must be observed! Please note separate freight costs.


Technical data	14581	14580		14	585					
House material	GFK	GFK		GF	K					
External hut dimensions	210 x 115 x 145,5 cr	m 210 x 11	15 x 145,5 ci	m 21	0 x 115 x 14	5,5 cm				
House weight	37 kg	37 kg		37	kg					
Fencing dimensions		150 x 11	10 x 96 cm	15	0 x 110 x 96	cm				
Fencing weight		approx.	30 kg	ар	prox. 45 kg		_			
Ref. no.		Description					Æ	Ħ	€	
14581	CalfHouse Pr	emium Plus with	out fencing				1	10		<b>.</b> •
14580	CalfHouse Pre	emium Plus with	light fencing				1	4		<b>•</b> •
14585	CalfHouse Pre	mium Plus with h	eavy fencin	g			1	4		<b>•</b> ••
Ref. no.	Description	Material	Length	Width	Height	Weight	Ø		€	
144720	Fence Easy	metal galvanised	150 cm	110 cm	96 cm	30 kg	1	24		<b>P</b>
144322	Fence heavy	metal galvanised	150 cm	110 cm	96 cm	45 kg	1	22		
14304	threshold	Plastic	100 cm	2,3 cm	14,5 cm	4 kg	1	168		




### **CalfHouse Master Plus**

The CalfHouse Master Plus, which has proven itself over 10,000 times, profits from our skill and many years of experience in the design of high quality Calf Houses, and unifies all the proven features of the CalfHouse series regarding stability, comfort and animal well-being – at an excellent price/performance ratio. With its generous dimensions, the CalfHouse Master Plus, made from glass fibre reinforced plastic offers the calf protection from the weather and free space for handling by the farmer. This Calf House also has an optimal ventilation system that regulates the climate in the house without any draughts.

• Bucket and feed box not included





#### Multifunctional revolving doors:

- Flex rail (a) with drinking bucket and bucket safety catch (b), 2 feed openings (c), with hinged bucket holders for feed buckets
- The high position of the feed bucket promotes the natural stretching of the neck, so that the milk can pass directly into the abomasum.
- The bucket's inclined position ensures it is fully emptied
- Flex rail for variable mounting of the bucket holder and the optional dry feed bottle holder





#### Lightweight fencing:

The reduced weight of the lightweight fencing (approx. 30 kg) makes it easier to lift and to reposition the house integrated in the fence, while also offering a high degree of stability.

#### Heavyweight fencing:

The heavyweight version (approx. 45 kg) is extremely robust and its increased weight ensures even greater stability.

Ŧ

(-----

#### Practical and convenient



Barrier near the base of the fence allows unimpeded access



Tip the hut into the fence for easy cleaning or repositioning



To clean the forecourt, fold the fence over the hut



Handle for easy lifting



Threshold at the hut entrance stops bedding getting out



The revolving door can optionally also be placed in the house entrance to lock the calf in



Side guards stop calves from slipping through and lend stability



Large solid rubber tyres with needle bearing enable easy moving

A

B

168 1

1,8 g

#### Suitable in accordance with animal welfare regulations:

threshold

Our calf houses and boxes comply with animal welfare regulations and have the optimum design for the requirements of calf rearing. Find out more online at www.kerbl.de

#### Local animal protection regulations must be observed! Please note separate freight costs.

Technical data	14301	14470		14	485					
House material	GFK	GFK		GF	K					
External hut dimensions	200 x 115 x 135 cm	200 x 11	5 x 135 cm	20	0 x 115 x 13	5 cm				
House weight	27 kg	27 kg		27	kg					
Fencing dimensions		150 x 11	0 x 96 cm	15	0 x 110 x 96	cm				
Fencing weight		approx.	30 kg	ар	prox. 45 kg					
							Æ			
Ref. no.		Description					$\blacksquare$		€	
14301	CalfHouse N	laster Plus witho	ut fencing				1	12		
14470	CalfHouse Ma	aster Plus with li	ght fencing				1	4		
14485	CalfHouse Ma	ister Plus with he	eavy fencing				1	4		
Ref. no.	Description	Material	Length	Width	Height	Weight	Ø		€	
144720	Fence Easy	metal galvanised	150 cm	110 cm	96 cm	30 kg	1	24		
144322	Fence heavy	metal galvanised	150 cm	110 cm	96 cm	45 kg	1	22		Į
14304	threshold	Plastic	100 cm	2,3 cm	14,5 cm	4 kg	1	168		

Larch

100 cm

2,3 cm

14,5 cm

14302



### **CalfHouse Premium XL**

The multi-animal Calf House made from glass fibre reinforced plastic offers space for up to 5 calves (local animal protection regulations must be observed). A sliding window is placed at the back to make animal control and filling the optional hay rack, among other things, easier. The additional reinforcing frame around the Calf House ensures the highest stability. The Calf House with fence provides optimum oversight and makes animal control easier.

- Feeding places can be individually blocked
- Side grilles can easily be swung back against the cabin walls
- easy access via large entrance door, even a calf transporter fits through the door
- pre-drilled holes on runners for straw catching and floor securing
- House and fencing easy to transport with a tractor
- Feeding bucket and long feeder troughs not included

14520: Included: Hut incl. reinforcing frames and fencing, eyebolts, wooden sleeper, drinking bucket holder and two trough holders for long feed troughs (item no. 3268).

#### Versatile and robust



Catch grille:

- With 5 or 7 feeding places
- With catch system: Individual and complete locking possible
- Lockable, fold-up drinking bucket holder, also length and height-adjustable
- Adjustable feeding place width
- Incl. trough holder
- Catch grille width information: with drinking bucket holder, max. length



Side and catch grilles can be arranged as required



The reinforcing frame gives the house additional stability



Catch grille can be hung back on the house



a tractor



Optional feeding space separation



The optional canopy provides protection against weather and sun

# CalfHouse Premium XL with catch grille (item no. 14539)

- Suitable for 2 3 calves (local animal protection regulations must be observed)
- Catch grille can be opened and swung up on both sides
- To prevent calves from stepping in the gap between the house and the catch grille while drinking, the optional kit plate set item no. 14529 can be retrofitted.

# Twin set, CalfHouse Premium XL with fence (item no. 14530)

- Also available as a twin set for up to 10 calves
- Tip: With an additional fence component, the twin set can quickly and easily be divided into two bays.

#### Suitable in accordance with animal welfare regulations:

Our calf houses and boxes comply with animal welfare regulations and have the optimum design for the requirements of calf rearing. Find out more online at www.kerbl.de

Local animal protection regulations must be observed! Please note separate freight costs.

Technical	data 145	520	14518			14539			14530			
House ma		· ·	GFK			GFK			GFK			
		x 223 x 189 cm		223 x 189	) cm	238 x 22	2 v 100 c		238 x 2	72 v 10	0.cm	
		0 X ZZ 3 X 109 CIII	104 kc		) CIII	230 X 22	5 X 109 C		230 X Z	23 X 10	9 (111	
House we	5	224 420	104 Kg						200 4	17 12		
Fencing d	limensions 209	) x 221 x 120 cm							209 x 4	47 x 12	U cm	
Ref. no.		De	scription					F	ŦØ 륟	3	€	
14520		CalfHouse Pren	nium XL w	vith fencir	ng				1			B
14518		CalfHouse P	remium X	L single	5				1 4	ļ		<b>B</b>
14539		CalfHouse Premi	um XL wit	h catch g	rille				1			<b>P</b> P
14530		CalfHouse Premium >	L with fer	ncing; 2-p	oiece set				1			B
Ref. no.	Description	Material	Length	Width	Height	suitable for	MOQ	Pieces / uni	t 🗐		€	
14466	Canopy	Polyester PVC- coated	300 cm	270 cm					1			•
14524	Reinforcing Frame	metal galvanised							1			<b>.</b> .
14526	Trough Holder for long feed troug	gh metal galvanised	82 cm	13,5 cm	18 cm	3268			1	100		
14527	Holder for 5 concentrated feed buckets	metal galvanised	184 cm	42 cm	20 cm				1	36		<b>~</b>
14529	Tread Protection Set								1			
14528	Feeding place separator	metal galvanised	37,5 cm	14 cm	55,2 cm		1 pack	2 / pack	1	50		
14458	threshold	Larch	203 cm	3,5 cm	19 cm				1	52		
14454	Hay Rack	metal galvanised	113 cm	41 cm	38 cm				1	50		<b>•</b> ••
14522	Fence for CalfHouse Premium XL	metal galvanised							1			P.

New product







### **CalfHouse Premium XXL**

The large-area Calf House made from glass fibre reinforced plastic offers space for up to 7 calves (local animal protection regulations must be observed). The additional reinforcing frame around the Calf House ensures the highest stability for even large animals. The swivelling ventilation slots control the air circulation in the back area of the Calf House. A sling bar is attached at the house roof ridge to enable easy lifting and transporting. The Calf House with fence provides optimum oversight and makes animal control easier.

- Feeding places can be individually blocked
- Side grilles can easily be swung back against the cabin walls
- easy access via large entrance door, even a calf transporter fits through the door
- pre-drilled holes on runners for straw catching and floor securing
- · House and fencing easy to transport with a tractor
- · Feeding bucket and long feeder troughs not included

14540: Included: Hut incl. reinforcing frames and fencing, sling bars, wooden sleeper, drinking bucket holder and four trough holders for long feed troughs (item no. 3268).

#### Versatile and robust



#### Catch grille:

- With 5 or 7 feeding places
- With catch system: Individual and complete locking possible
- Lockable, fold-up drinking bucket holder, also length and height-adjustable
- Adjustable feeding place width
- Incl. trough holder
- Catch grille width information: with drinking bucket holder, max. length



Side and catch grilles can be arranged as required



The reinforcing frame gives the house additional stability



Catch grille can be hung back on the house

New product

÷







House and fencing easy to transport with a tractor

Optional feeding space separation

#### Suitable in accordance with animal welfare regulations:

Our calf houses and boxes comply with animal welfare regulations and have the optimum design for the requirements of calf rearing. Find out more online at www.kerbl.de

Technical data	14540	14519	Local animal protection regulations must be observed! Please note separate freight costs.
House material	GFK	GFK	A front-loader with forklift will be required for unloading!
External hut dimensions	340 x 296 x 204 cm	340 x 296 x 204 cm	
Fencing dimensions	280 x 299 x 120 cm		

Ref. no.		Descriptio	n							€		
14540	Ca	alfHouse Premium XX	L with fe	ncing					1			<b>P</b>
14519		CalfHouse Premium	XXL sing	le					1			<b>P</b>
Ref. no.	Description	Material	Length	Width	Height	suitable for	MOQ	Pieces / unit	₿		€	
14546	Fence for CalfHouse Premium XXL	metal galvanised								1		<b>P</b>
14526	Trough Holder for long feed trough	metal galvanised	82 cm	13,5 cm	18 cm	3268			1	100		
14549	Tread Protection Set								1			
14528	Feeding place separator	metal galvanised	37,5 cm	14 cm	55,2 cm		1 pack	2 / pack	1	50		

#### **Modular fence stabling**

For keeping calves in a barn or roofed area, the fencing can simply be attached to the wall using a wall bracket. Or it can be anchored to the floor. The fencing can also be put together to suit individual requirements. Choose between a catch grille, a fence part with door and feeding places and a fence part with grille. All fencing types are available in two lengths.

• pre-drilled holes on runners for straw catching and floor securing • Bucket and long feeder trays not included.

Catch grille:

• Individual and complete locking possible • Lockable, fold-up drinking bucket holder, also length and height-adjustable • Adjustable feeding place width • incl. trough holder • Catch grille width information: with drinking bucket holder, max. length



14498, 14496, 14497: Available from March 2020

Ref. no.	Description		N	laterial		Length	Width	Height	Ø		€	
14495	Wall bracket		metal	galvanis	ed				1	400		
14493	Catch grille, 5 places		metal	galvanis	ed 2	213 cm	52 cm	120 cm	-	1	-	<b>.</b> B
14498	Catch grille, 7 places		metal	galvanis	ed 2	285 cm	52 cm	120 cm	-	1		<b>. .</b>
14491	Fence part with door and feeding	places, short	metal	galvanis	ed 2	215 cm	3 cm	120 cm	-	1		<b>. .</b>
14496	Fence part with door and feeding	places, long	metal	galvanis	ed 2	285 cm	3 cm	120 cm	-	1		<b>. .</b>
14492	Fence part grille, shor	t	metal	galvanis	ed 2	215 cm	3 cm	120 cm	-	1		<b>- -</b>
14497	Fence part grille, long	]	metal	galvanis	ed 2	285 cm	3 cm	120 cm	-	1		<b>•</b> ••
Ref. no.	Description	Material	Length	Width	Height	suitable	for MO	Q Pieces unit	/	Ŧ	€	
14526	Trough Holder for long feed trough	metal galvanised	82 cm	13,5 cm	18 cm	3268				1		
14527	Holder for 5 concentrated feed buckets	metal galvanised	184 cm	42 cm	20 cm					1		• •
14528	Feeding place separator	metal galvanised	37,5 cm	14 cm	55,2 cm		1 pag	k 2/pac	k	1		

### **Combo Feed Box small**

With galvanised rack inlay for the combined feeding of concentrated feed and hay. Ideal for calves switching from wet to dry feed.

• suitable for all individual calf houses • can be hung on the inside of the fence • can easily be filled from the outside • cover protects contents from the rain • sturdy plastic container

# **Calf cabin accessories**



GE/

Ŧ

Ref. no.	Colour	Width	Depth	Height	Capacity	Ø		€
144352	green	330 mm	512 mm	270 mm	11,5 L	1	40	

### **Concentrated Feed Box small**

With panel insert for the feeding of concentrated feed.

• suitable for all individual calf houses • can be hung on the inside of the fence • can easily be filled from the outside • cover protects contents from the rain • sturdy plastic container





Ref. no.	Colour	Width	Depth	Height	Capacity	Ø		€
144353	green	330 mm	512 mm	270 mm	13 L	1	40	

### **Combo Feed Box**

For combined feeding of roughage and concentrates

• easy filling possible • Protects feed from rain • Drainage in feed bowl for easy cleaning • is mounted externally to the feed opening • suitable for individual calf houses and calf boxes • includes hanging bracket • Rack capacity: 20 L • Feed bowl capacity: 5.5 L







# Calf cabin accessories

### Feed Trough Long

#### for hanging

Ref. no.

 especially stable with glass fibre reinforced plastic • extra-strong loops • fits plug trays and nearly every device of up to 50 mm size
 Dimensions: Depth 35 cm (28 cm without mounting bracket) • for hanging

Colour

Width



3268     green     100 cm     35 cm     24 cm     42 L     1     120       Ref. no.     Description     Material     Length     Width     Height     suitable for										
	3268	green	100 cm	35 cm	24 cm	42	L	1	120	
14526 Trough Holder for long feed trough metal galvanised 82 cm 13.5 cm 18 cm 3268 1	Ref. no.	Descrip	otion	Material	Length	Width	Height	suitable for	Ð	€
	14526	Trough Holder for l	ong feed trough	metal galvanised	82 cm	13,5 cm	18 cm	3268	1	

nperature-re can be prin Available in	wl for food • impact- a esistant plastic • bowl ited on request • food s customer-specific con	and safe nposition.					
Note the ins	structions at the end o	of the catalogue.					
							Made in the EU
Ref. no.	Colour	Ø	Capacity	Ø	€		Made in the EU
Ref. no. 324811	Colour grey	Ø 31,5 cm	Capacity 6 L	<b>∰</b> 1/5	€		Made in the EU
					€		
324811	grey	31,5 cm	6 L	1/5	€		Made in the EU
324811 324812	grey green	31,5 cm 31,5 cm	6 L 6 L	1/5 1/5	€		
324811 324812 324815	grey green aquamarine	31,5 cm 31,5 cm 31,5 cm	6 L 6 L 6 L	1/5 1/5 1/5	€	V	
324811 324812 324815 324816	grey green aquamarine rosé	31,5 cm 31,5 cm 31,5 cm 31,5 cm	6 L 6 L 6 L 6 L 6 L	1/5 1/5 1/5 1/5 1/5		V€	

### Feeding Bowl stainless steel

 $\bullet$  universal bowl for food  $\bullet$  especially sturdy and hygienic  $\bullet$  ideal for use in stables  $\bullet$  Material: stainless steel stainless

Ref. no.	Ø	Capacity	Ø	€
324828	30 cm	5,5 L	1/50	

### All-Purpose Bucket

• very sturdy design • Material: Plastic

Available in customer-specific composition. Note the instructions at the end of the catalogue.

Top Seller
Made in the EU

NEW

New product

Ref. no.	Description	Colour	Ø	Capacity	Ø		€
29881		olive green	33 cm	12 L	1	350	
298800	food safe	blue transparent	33 cm	12 L	1	350	
298801	food safe	transparent pink	33 cm	12 L	1	350	
Ref. no.		Description			Colour	Ħ	€
29935	Cover fo	or stable and construction bucket			black	1/30	

# Calf cabin accessories

340

New product

Ŧ

NEW

1

### **Bucket Mount**

• robust • for hanging buckets and food bowls

<ul> <li>clip-on</li> <li>321216:</li> <li>Bucket ring ca</li> <li>for wall moun</li> </ul>	an be folded away when not in use	321216	1444					GEA
Ref. no.	Description	Material	Ø	Ħ		€		
1444	Standard	metal galvanised	29,5 cm	1	310		NEW	
321216	foldable, for wall mounting	metal galvanised	28 cm	1/10	480		_	

metal galvanised

28 cm

### Holder for 5 concentrated feed buckets

• suitable for e.g. stable and construction buckets (29881) and feed bowls (324811-324816) • for CalfHouse Premium XL (14520) • also suitable for wall mounting

Dutch model

Ref. no.	Material	Length	Width	Height	Ø		€	
14527	metal galvanised	184 cm	42 cm	20 cm	1	36		<b>.</b> •

### Hay Rack

1445

• suitable for CalfHouse Premium 4/5, FLIXBOX group igloo, CalfHouse Premium XL and CalfHouse Premium XXL • Material: metal galvanised • screw-on fastening

Ref. no.	Length	Width	Height	Rod distance	Bar thickness	Ð		€
14454	113 cm	41 cm	38 cm	75 mm	10 mm	1	50	<b>•</b> ••

### Feed Trough Long with float valve

Simple water supply for your animals without any installation work. Connect the hose - and that's it!

• float valve can be used on both sides of the trough • pipe piece and cover made from stainless steel • inc. click coupling for garden hose • for hanging • Material: Plastic

Technical da	ta	223111	1	9	
Dimensions (	W x D x H)	100 x 35 x 24 cm	223113	223113	
Ref. no.	Colour	Water connection	Capacity	Ø	€
223111	green	1/2"	42 L	1	
Ref. no.		Description	€ €	E	
223113		Floating valve	1/10	NEW	



### Mounting Set for drinking trough

• for mounting on calf house fencing • suitable for all water bowls

Ref. no.	Description	Ð	€
221972	Mounting Set for drinking trough	1	



# **Calf occupation**

lew product

NEW

### **Occupational items for calves**

The purpose of occupational items is to calm their unmet desire to suckle and provide an outlet for their energy. They also help to prevent misbehaviour (e.g. mutual suckling). Calves' acceptance and interest in these items is very high and also long-lasting. The calves like playing and busying themselves with the various toys.

32678

'Toys for young animals' immediately create a positive and friendly impression in the calf shed.

### Scratch Mat


• made from natural rubber material • mobile and soft nubs provide optimum coat care without risk of skin irritation • rectangular shape with many mounting holes for stable mounting • multi-functional applications such as flat on the wall or around pillars, posts or corners


Ref. no.	Colour	Length	Width	Ð	€	
32678	black	40 cm	30 cm	1/12		
32689	black	60 cm	40 cm	1/6		-
						-

32689

### Scratch Brush

ensures ideal fur cleaning and care • head and throat in particular can be cleaned • suitable for cattle and calves, horses, goats etc.
various mounting options (walls, corners, stables, posts) • Bristle material: Polyamide • Bristle length: 5 cm





### Feed Ball Toy HeuBoy

• the ball is especially suitable for use in stables, pastures or paddocks

• 19 feed openings per 70 mm • durable UV-resistant plastic • for up to 3 kg of hay • Filled via 116 mm filling opening with screw cap

can also be hung on a cable or chain

- · Calves enjoy playing with the swinging ball or eat hay from it
- Suitable for group housing

Ref. no.	Colour	Ø	Ø thread	Ð	€
3210385	blue	40 cm	60 mm	1	
3210386	red	40 cm	60 mm	1	
Ref. no.		Description		Ø	€
3210385-1	Cov	er for Heuboy	ооу 1/8		



# **Calf occupation**

### HayBag

The HayBag brings together many benefits in one product.

• up to 15 % less feed wastage • smooth, soft material surface prevents injuries • easy to fill and clean • ideal for species-appropriate feeding of hay • universally usable and easy to mount in stables or pasture • Material: Plastic

326102: 12 side holes with 20 cm spacing 326103: 15 side holes with 20 cm spacing

- Calves have to work for their food and engage in a playful way
- Suitable for group housing





GE/

Ŧ

323506

NEW

Ref. no.	Description	Colour	Capacity	Capacity	Ð	€	
326102	Small	black	8 kg	85 L	1/10		
326103	Big	black	16 kg	195 L	1/10		
Ref. no.	Description		Material	suitable for	Ð	€	I
323506	Wall Mount		metal galvanised	323500, 326102, 326103, 323509	1/10		
326104	Floor bracket		metal galvanised	323520, 326102, 326103	1		

### **Teat Activity Set**

· Calves can fulfil their unmet need to suckle · for easy wall mounting

· suitable for individual and group housing

Ref. no.	Description	Ħ	€	
14129	Teat Activity Set	1		_
Ref. no.	Description	Colour	Ħ	€
14128	Calf Teat without holes	blue	1/50	





- made from organic natural materials (100 % cotton)
- on a coil woven

22608

· Calves are attracted to this and enjoy gnawing at it

Hanging Chain with ring

· Suitable for individual and group housing

Ref. no.	Length	Thickness	Ē	€
22681	250 m	8 mm	1/2	

New product



### **Teething Ring Nature**

• made from food-grade, naturally renewable raw materials • made from polylactic acid derived from sugar cane, reinforced with wood fibres • organic, changeable, healthy and harmless material to keep animals occupied • GM-free • biodegradable • long service life • biocompatible • carefully selected, HACCP-compliant hardwood from sustainable forest management

Ref. no.	Description	Colour	Ø	Ð	€
22638	without hanging chain	nature	18 cm	1/50	
22639	with hanging chain 75 cm	nature	18 cm	1/50	
Ref. no.	Description	Material		Length	Link thickness
22607	Hanging Chain with ring	metal galvanis	sed	75 cm	4 mm

metal galvanised



€

Ħ

1/25/100

1/25

6 mm

75 cm

# **Calf Blankets**

- · Calf blankets support the immune system during the first few days and prevent diarrhoea and other illnesses
- The risk of illness increases at temperatures below 10 °C
- Protection against sudden changes in the weather
- Avoids cold stress in new-born calves
- The calves generally wear the calf blankets for 3 to 4 weeks, and longer if necessary
- Calf blankets are not suitable for group housing

#### Calf blanket EasyWear

• super lightweight and functional calf blanket for all year round • special padding regulates the temperature and ensures excellent thermal insulation • wind- and water-resistant due to welded stitching • no protruding belt, thus low risk of injury for the calf • stable plastic fasteners • machine washable at 30 °C







# **Calf Blankets**

GE7

35

Ŧ

### Calf blanket ThermoPlus

• outer materials made from tear-resistant 600 denier ribstop polyester • with anatomical chest and belly fastener • stable closures with additional hook and loop security • water-resistant up to 3,000 mm water column • 200 g polyfleece filling for optimum protection even in extreme outdoor temperatures • breathable properties prevent excessive sweating • machine washable at 30 °C





Ref. no.	Colour	Total length	Ø	€
14148	dark blue	70 cm	1/15	
14149	dark blue	80 cm	1/15	

### Calf blanket Ripstopp

• outer materials made from tear-resistant 600 denier ribstop polyester • with Nylon strap and plastic clip fasteners • water-resistant material with up to a 3000 mm water column • breathable properties prevent excessive sweating • machine washable at 30 °C





Ref. no.	Colour	Total length	Ē	€
14155	grey	70 cm	1/25	
14156	grey	80 cm	1/25	

#### Mark of quality for feed from the Bavarian Farmers' Association

Farms taking part in the 'Offene Stalltür' (Open Barn Door) programme commit themselves to using only feed bearing this stamp. This guarantees general animal feed safety at these farms. Agrochemica quality products are also GMP+ and QS certified.

**Bolus Phosphogol** 

#### Phosphorus bolus for dairy cows

Cows with optimum phosphorus supply have a better start to lactation, are healthier and produce more milk. Phosphorus deficiency occurs ever more frequently in calving cows. The Phosphogol bolus enables the targeted supply of phosphorus around calving time.

• very high content of rapidly available phosphorus (37 g) per bolus! • additional supply of calcium (15 g) • easy application and economical – one bolus per dose is enough • the administration in combination with the Calzogol bolus ensures an adequate supply of calcium and phosphorus at the same time

#### Feeding recommendation:

Administer one bolus with the applicator as per the instructions when calving. If required, administer a second bolus approx. 12 hours after birth.

							New product
Re	. no.	Single weight	MOQ	Pieces / unit	Ø	€	
15	987	185 g	1 pack	4 / pack	1/8		Feed supplemen

### **Bolus Calzogol**

#### Calcium bolus (milk fever)

Cows with optimum calcium supply have a better start to lactation, are healthier and produce more milk.
 very high levels of fast and slow availability calcium (45 g) and vitamin D3 (40,000 I.E.) per bolus!
 calcium sources with varying release rates supply the cow evenly with calcium
 very well tolerated by membranes – no irritation of the mouth, esophagus and rumen
 no caustic calcium chloride
 easy application and economical – one bolus per dose is enough



Quality for feed

Dietary mineral feed for milk cows to lower the risk of milk fever. High calcium content in the form of readily available calcium salts.

supplement for dairy cows

#### Feeding recommendation:

Administer one bolus with the applicator as per the instructions when calving. If required, administer a second bolus approx. 12 hours after birth.

Ref. no.	Single weight	MOQ	Pieces / unit	Ø	€
15980	175 g	1 pack	4 / pack	1/8	

#### **Bolus Ket-o-Vital®**

#### **Energy Bolus (Ketosis)**

• Healthy cows become pregnant quicker and provide more milk. • Bolus that works on various physiological levels – liver - rumen - immune system • the glucoplastic substances support the energy metabolism. The risk of ketosis / acetonaemia decreases. Very high milk yield, birth problems, stress, heat and obesity at the time of birth are classical risk factors for ketosis • safe dosage and application. The animals have more appetite, are fitter and recover faster

#### Feeding recommendation:

Administer two boluses shortly after calving using a bolus applicator as per the instructions. If required, administer another bolus 12 hours after calving.

Ref. no.	Single weight	MOQ	Pieces / unit	Ø	€
15982	135 g	1 pack	4 / pack	1/8	



Dietary supplementary feed for milk cows to lower the risk of milk ketosis. Glucose-supplying raw materials.

# **Dietary supplement**

Quality for feed



### **Bolus Fertilgol**

#### Beta Carotene Bolus (fertility)

• A quick pregnancy shortens the calving interval and improves economic success. • for male and female breeding animals just before and during the covering or insemination period • supports a successful embryo transfer (recipient and donor animals) • the high beta carotene content aids the corpus luteum formation, colostrum quality, the oestrus cycle and sperm quality • a well-developed corpus luteum has a positive influence on the embryonic survival rate • easy and safe application through the even release of beta carotene, vitamins and trace elements over a period of min. 20 days • the release rate has been scientifically confirmed

#### Feeding recommendation:

Female cows: Administer the first bolus 30 days before insemination. Administer the second bolus shortly before or after insemination

Stud bulls: Administer one bolus every 20 - 30 days during breeding season. The bolus dissolves in 20 days in the rumen

Ref. no.	Single weight	MOQ	Pieces / unit	Ø	€
15983	95 g	1 pack	8 / pack	1/8	

#### **Bolus Vitagol**



Well-nourished animals have the best conditions for good growth, vitality and fertility • for male and female cattle • the long-term bolus releases vitamins and trace elements safely and evenly over a period of at least 90 days. The release rate has been scientifically confirmed • a constant supply of essential vitamins and trace elements cannot be safely guaranteed with conventional feed, especially in pastures / hill farms / mountain farms. The solution is the Vitagol long-term bolus. • individual animals in a herd can be targeted for a boost of vitamins and trace elements

#### Feeding recommendation:

Young cattle < 300 kg live weight: one bolus every 3 months, administer using a bolus applicator as per the instructions.

Cattle > 300 kg: two boluses every 3 months, administer using a bolus applicator as per the instructions.

Ref. no.	Single weight	MOQ	Pieces / unit	Ð	€
15981	110 g	1 pack	8 / pack	1/8	



#### **Buffer and Electrolyte Bolus**

For digestive problems, low appetite and reluctance to drink

• Sodium bicarbonate is a very effective buffer. The use of buffers helps to resist excess acidity. Excess acidity is often the reason why calves are weak and dull and have no desire to drink • Lost electrolytes are effectively replaced. This stabilises water levels during e.g. transport and heat • stress-free and safe administration. Administration can also be done without an applicator. Simply place the bolus lengthways on the base of the tongue using your hand. The calf will swallow the bolus with no problems • applicator not included

#### Feeding recommendation:

Immediately administer one bolus as per the instructions at the first signs of digestive problems.. Then administer one bolus after each liquid meal for 2 - 3 days.

Ref. no.	Single weight	MOQ	Pieces / unit	Ø	€
15984	13 g	1 pack	15 / pack	1/12	
Ref. no.	De	scription		Ð	€
15985	Introducer f	or Bolus Buf	ferlyt	1/12	



Dietary mineral feed (for ruminants with fully developed rumen) for the long-term supply of trace elements and/or vitamins to grazing animals.

High content of trace elements and vitamins.



Mineral feed (for calves) for additional supply of buffers and electrolytes.

Quality for feed



**Dietary supplement** 

Quality for feed

Dietary mineral feed (for cattle with fully developed rumen) to

support preparation for oestrus and reproduction.

High content of vitamin A

GE/

Ŧ

# **Dietary supplement**

#### for bolus and ruminal magnet • for single-handed operation • rounded edges • Introducer sleeve: internal diameter 36 mm, length 11 cm, with retaining springs • suitable for Calzogol bolus (item no. 15980), Ket-o-Vital bolus (item no. 15982), Fertilgol bolus (item no. 15983), Vitagol bolus (item no. 15981) Phosphogol bolus (item no. 15987) and cage magnets Ħ Ref. no. Colour Material Length € 2129 1/30 green stainless steel 53 cm 2139 stainless steel 70 cm 1/30 green

### **Head Support for Cattle**

Introducer

simple and safe fixing of the head • facilitates treatments and the administration of drugs or feed
Fastening on feed grate • suitable for pipes with a diameter of up to max. 7.5 cm • Reduces stress and risk of injury to animals and keepers



Ref. no.	$\blacksquare$	€
2164	1	


### Diarrhoea Test for calves

#### Fast test for cattle and calves

When you want to know for sure whether or not your calf is suffering from E. coli, rotaviruses, corona viruses or cryptosporidia, then the test provides the answer. Often times, multiple infections from different pathogens occur along with the individual infections.

#### How to use:

• take a diarrhoea sample and mix it with the supplied reagent fluid • next, place the mixture on the test cassette • rapid identification of the pathogen is possible after approx. 10 minutes, so that swift initial measures can be taken, e.g. intensive disinfection



# **Dietary supplement**

GE/

Ŧ

NEW

New product

Dia Stop

New product

15

Calf Paste

15995

calf Paste

Dietary supplement for calves



Immunoglobulins are natural proteins whose clear objective is to protect vertebrates against carcinogens. Numerous university and field tests have shown that natural immunoglobulins (IgY) from eggs can act as a potent supplementary feed for protecting the as-yet immature immune system of young animals. IgY plays a key role in 'filling in the immunity gap', because it binds diarrhoea-inducing pathogens in the gut.

### **Globigen Colostrum**

High-quality colostrum supplement for the additional supply of natural immunoglobulins in the first days of life

• Use in the case of insufficient colostrum quality or amount • Supply of natural egg immunoglobulins • supports the immune system • supports intestinal health • can reduce the frequency of diarrhoea • improves weight gain • quick and easy to use • can be stirred directly into the colostrum

#### Feeding recommendation: Add to the colostrum (first milk) New product NEW Calves: 50 – 100 g per animal per day 15994 Lambs and kids: 5 - 10 g per animal per day Period of use: 3 - 4 days Stir the powder into warm (approx. 39 °C) colostrum and administer during the first 6 hours of life. To ensure the powder dissolves easily, add max. 100 g of powder per litre of milk, 15993 or max. 10 g of powder per 100 ml of milk. Feed when no colostrum is available Calves: Dissolve 200 g in 2 litres of normal milk, milk substitute or water Lambs and kids: Dissolve 20 g in 0.2 litres of normal milk, milk substitute or water Colostrum Period of use: 3 - 4 days Colostrum Ref. no. Contents A € Feed supplement for calves, 15993 1 kg / Can lambs and kids 15994 2,5 kg / Bucket 1 Globigen Dia Stop

Stabilises the water and electrolyte balance to support physiological digestion

- supports the calf during diarrhoea Supply of natural egg immunoglobulins can reduce the use of antibiotics
- supports intestinal health improves weight gain can be used preventively

#### Feeding recommendation:

During, after or to prevent digestive problems (diarrhoea), mix 1 slightly heaped scoop (25 g) into 1 litre of warm (39 °C) water, milk substitute or milk twice a day. In the event of severe diarrhoea, mix 50 g of Dia Stop into 2 litres of warm water twice a day.

Ref. no.	Contents	Ø	€
15995	2 kg	1	
15996	7,5 kg	1	

Dietary supplement for calves	

### Globigen Calf Paste

#### Paste for calves to stabilise their physiological digestion

• for a successful start in life • Supply of natural egg immunoglobulins • supports the immune system • supports intestinal health • healthy intestines increases the motivation of the animals • can be used preventively • Paste for easy administration

#### Feeding recommendation:

Early days help from days 1 to 3 after birth: 10 ml per animal per day In acute scenarios (e.g. increased exposure to bacteria): 10 ml per animal per day for 3 days

Ref. no.	Contents	MOQ	Pieces / unit	Ø	€
15992	30 ml / injector	1 pack	6 / pack	1/10	

NEW

# **Udder Cleaning**

### Udder Paper UdderoClean

• highly suitable for wet and dry cleaning • high moisture absorption for optimal wet cleaning • high-wet-strength and lint-free • stimulating effect via the crepe structure • 100 % virgin pulp • food safe • 100 % biodegradable

1579: with cardboard core 15787: no cardboard core 15800: no cardboard core 15895: no cardboard core



Ref. no.	Colour	Contents	Sheet dimensions (L x W)	MOQ	Pieces / unit	Ø		€
1579	white	2 x 200 sheet / Roll	24 x 23 cm	5 pieces	5 / pack	1/5	315	
15787	white	800 sheet / Roll	23 x 22 cm	1 pack	2 / pack	1	108	
15800	white	800 sheet / Roll	23 x 22 cm	1 pack	6 / pack	1	36	
15895	white	1000 sheet / Roll	21 x 21 cm	1 pack	6 / pack	1	40	

### Udder Paper StimuClean

massages and stimulates, preferably dry • can also be used damp (not wet) • prevents transmission of germs
especially absorbent (start with max. 3 litres of cleaning solution) • with cardboard core



Ref. no.	Colour	Contents	Sheet dimensions (L x W)	Ð		€
15798	grey	2 x 780 sheet / Pack	24 x 20 cm	1	66	

# **Udder Cleaning**

15861

GE/

Ŧ

### **UdderoClean Bag**

 practical solution for the storage of cut udder paper • easy and fast removal of individual sheets • no unnecessary back and forth at the milking station • with a collection bag for used udder paper • ideal for large livestock • Belt length easily adjustable • water-resistant material
 incl. two straps for fastening dip cups • suitable for wet and dry paper

• suitable for Kerbl udder paper cut 15851 • with click-closure

Ref. no.	Description	Colour	Length	Width	Height	Ð	€	
15860	Belt bag with Collection Bag	black	26 cm	12 cm	16 cm	1/50		-
15861	Collection Bag	black	12 cm	20 cm	28 cm	1/50		

15860

#### Udder Paper UdderoClean


• cut • ready for use straight away and thus time-saving • easy and fast removal of individual sheets • high-wet-strength and lint-free • stimulating effect via the crepe structure • suitable for Kerbl belt bag 15860 • 100 % virgin pulp • moist • 100 % biodegradable

Ref. no.	Colour	Contents	Sheet dimensions (L x W)	MOQ	Pieces / unit	Ø		€
15851	white	3 x 250 sheet / Pack	26 x 21 cm	3 pack	3 / box	1/3	162	

#### **Udder Paper moist**

 stimulating effect via the crepe structure • ready for use straight away and thus time-saving • strong cleaning effect via selected raw materials • 100 % virgin pulp
 food safe • QAC-free





Ref. no.	Colour	Contents	Sheet dimensions (L x W)	MOQ	Pieces / unit	Ø		€
15817	white	800 sheet / Bucket	20 x 20 cm			1	72	
15818	white	800 sheet / Refill Pack	20 x 20 cm	2 pieces	2 / box	1/2	168	

### **Udder Cloth moist**

• for external use only • Udder Cleaning • Stimulation of milk production • Milking time reduction • Milker's hand cleaning • Material: Non-woven fabric • QAC-free



recommended	by farmers!

Ref. no.	Colour	Contents	Sheet dimensions (L x W)	MOQ	Pieces / unit	Ð	Ħ	€
15815	white	1000 sheet / Bucket	20 x 20 cm	2 pieces	2 / box	1/2	48	
15816	white	1000 sheet / Refill Pack	20 x 20 cm	2 pieces	2 / box	1/2	60	

# **Udder Cleaning**

### Udder Cloth UdderoClean Super

reusable cloth for cleaning udders and reducing bacteria levels
machine washable and can be boiled to 95 °C • Material: Non-woven fabric



washable a	and boil-proof					
Ref. no.	Colour	Contents	Sheet dimensions (L x W)	Ø		€
15666	white	50 sheet / Pack	37 x 34 cm	1/6	72	
15667	white	50 sheet / Pack	29 x 27 cm	1/8	128	

### Dispenser for udder paper

• for (udder) paper rolls with centre pull • cover made from sturdy plastic housing (ABS)

• with transparent and lockable cover • with integrated tear-off edge • easy wall mounting

• fits Kerbl UdderoClean udder paper (800 and 1000 sheets) and UdderoClean Air Premium

(350 sheets) • supplied without paper



Ref. no.	Colour	Width	Depth	Height	Weight	Ø		€
15790	black	250 mm	358 mm	255 mm	1.200 g	1/4	32	

### Holder for udder cloth bucket

- for flexible attachment of the dispenser bucket at the milking station
- suitable for bucket 15817 (cleaning paper, moist) and 15815





Ref. no.	Material	Ø		€
15823	stainless steel	1/10	80	

### Wall Roll Holder



# **Milking Test**

12 kg

GE/

Ŧ

#### **Udder Wood Wool**

Pure natural product made from untreated wood! Only the best spruce and pine from Germany is used for udder wood wool. This makes our product very fine quality and gentle on the udder!

- guaranteed to be free from wood preservatives single-use, economical and hygienic low-cost
- simple, fast and very gentle udder cleaning massage effect for good stimulation before milking
- suitable for all livestock farming colour and structural variations are possible as wood is a natural materials, this is not a quality defect! 100 % natural

100 % natural	
Ref. no. 🗐 🚍 €	KERBL
15821 1 16	and the second sec


#### **Indicator Paper**

• is used to quickly identify secretion disorders that are often a sign of the onset of udder diseases • the paper has been prepared with a special indicator substance on four spots, marked according to the udder quarters • the corresponding indicator points must be moistened with milk of the first jets of each teat canal.

Ref. no.	Contents	Ø	€
1535	25 sheet / Pack	1/500	


### **SHOOF Mastitis Tester Original**

• the X-Spurt tester makes mastitis testing a quick and efficient matter • a short press on the X-Spurt handle, which also serves as a reservoir for the test fluid, sends an equal measure of test fluid into all four test areas at the same time, the samples then mix with the test fluid thanks to the tester's circular movements • 300 ml test fluid in the holder is enough to test around 15 cows



### Schalm test disk

• for California mastitis testing • one milk sample (approx. 2 ml) is added to each well, each from one udder quarter



### Pre-milk Cup

• for checking the first milk streams from each teat • with black plate

Ref. no.	Colour	Ø	€	
1529	green	1/100		

### Pre-milk Cup Ambic

• with a sieve insert • for checking the first milk streams from each teat • made of robust plastic • anti-spray insert



# **Udder Care**

### **Teat Pens Silicon**

• soft teat tips made of bio-compatible silicon • simple and hygienic insertion into the teat thanks to the handle section

Material

Silicon

nple and e section			Constant of the second se
Contents	Ð	€	
20 pieces / Can	1/10/250		
			-



#### **Teat tips**

Ref. no.

15659

flexible & sterile

• for immobilising injured teats • the new teat insert is similar to the naturally occurring sebum and therefore, according to scientific tests which have been carried out, does not damage the teat canal • does not contain drugs and there is no waiting time • the wax-like consistency adapts to the teat canal

• bonding or scarring of the teat canal is prevented • malleable at body temperature (does not dissolve)

can be milked out of the teat canal if necessary

Colour

green

					No waiti	ing time.			
Ref. no.	Colour	MOQ Pie	eces / unit	Æ	€				
1566	white	1 blister pack 6 / k	olister pack	1					
			·					6	-

...

### Wool Teat Plug Uddero Dil

• with pearl • with Vaseline as a lubricant • for insertion into the teat canal in the case of milk duct strictures, damaged teats and after surgery

Ref. no.	Colour	Material	Contents	MOQ	Pieces / unit	Ē	€
1554	white	Cotton	20 pieces / Can	10 pieces	10 / box	1/10/300	

### Wool Teat Plug with ointment

• with Vaseline as a lubricant • for insertion into the teat canal in the case of milk duct strictures, damaged teats and after surgery

Ref. no.	Colour	Material	Contents	Ø	€
1523	white	Cotton	20 pieces / Can	1/10/300	



### **Dilation Plug**

• teat plugs with reinforced woollen thread • Length: approx. 5.5 cm • in split chamber vessel with Vaseline® each 20 in number • has a dilatory and suction effect • for insertion in the milk duct • after injury or operations to prevent teat duct constriction

Ref. no.	Colour	Contents	Ē	€	KERB
1565	red / white	20 pieces / Can	1/6/504		A COLUMN OF THE OWNER

### Teat cannula

• Teat cannulas keep the teat canal open • for injuries to teats or teat tips, surgical widening of the milk duct

Ref. no.	Material	Contents	Ð	€
1537	Plastic	10 pieces / Can	1/12/1.008	





#### **Udder Disinfection Dip Cup Standard** · splash guard with outflow into an overflow chamber prevents spilling and GE# wastage of the dip • also suitable for viscous dips thanks to wide suction hose • reservoir with measuring scale • with practical belt hook Ref. no. Æ Colour Capacity € 15656 300 ml 1/20 640 green reat Dip Cup **Dip Cup Non-Return** A backstop in the interior of the attachment prevent used dip running back into the reservoir - hygienic, practical, safe! The dip is discarded after use and the dip cup can be refilled with new dip by pressing the reservoir. • splash guard with outflow into an overflow chamber prevents spilling and wastage of the dip • also suitable for viscous dips thanks to wide suction hose • reservoir with measuring scale • with practical belt hook Ħ Ref. no. Colour Attachment capacity Capacity € Teat Dip Cup 15652 green 300 ml 30 ml 1/20 640 Non-Return Dip Sprayer Uddero Sprayer • high-quality spray head with metal nozzle • specially angled spray nozzle for optimum teat cleaning and spot-accurate dipping • with dual valve technology without pressure drop after a pause in spraying • only use sprayable dipping agents • chemical-resistant Top Quality Ŧ Ħ Ref. no. Colour Capacity € KERBL 15256 blue 500 ml 1/25 400 Uddero Dipsprayer Dip Sprayer Angular • targeted teat cleaning and precise dipping thanks to specially angled nozzle • Nozzle can be freely adjusted between spray jet to direct jet • only use sprayable dipping agents • chemical-resistant Ħ Ref. no. Colour Capacity € 15250 500 ml 1/25 400 green *KERBL* Dipsprayer Angular Dip Sprayer with teat cup • targeted teat cleaning and precise dipping thanks to specially angled nozzle with upwardly angled teat cup • Nozzle can be freely adjusted between spray jet to direct jet • only use sprayable dipping agents *KERBL* Dipsprayer Ref. no. Colour Capacity Ĥ € 15252 green 500 ml 1/20 320

## **Udder Care**

## **Udder Care Products CareMINT**

contains peppermint oil with cooling effect for improved blood circulation
 unique formulation thanks to the addition of high-quality tea tree and
 calendula oils • the synergistic effect of the ingredients yields maximum care
 results for teats and udders exposed to daily stresses • daily use can improve the
 resilience of skin and tissue in a completely natural way • when used regularly,
 can have a positive influence on maintaining the health of udders and the
 production of high-quality milk • simultaneously cleans the udder and provides
 care to support therapy

Ref. no.	Contents	Ð		€
15311	1000 ml / Hanging Bottle	1/6	192	

#### Udder Gel

• washable care balm with a gel-like consistency • vegetable oils give the udder tissue effective protection and care • promotes milk generation and ensures a fast milk flow • prevents dry, chapped skin and keeps muscles and tendons soft and supple





with high-quality essential oils

Ref. no.	Contents			€
1520	500 g / Can	1/12	600	
1521	1000 g / Can	1/6	396	
15215	2500 g / Bucket	1/4	168	

#### **EUTRA Milking Fat**

• for better milk quality and profitability in dairy farming

• for the natural care of teats and udders

The genuine Swiss milking grease!

Ref. no.	Contents	Ð		€
1516	250 ml / Can	1/6	1.344	
1517	500 ml / Can	1/6	720	
1518	1000 ml / Can	1/6	720	
1519	2000 ml / Bucket	1/4	216	
15211	5000 ml / Bucket	1/2	70	
15212	10 L / Bucket	1	55	



## **Udder Protection**

## Wound care spray

#### to support self-healing

• ready-to-use spray • promotes fast self-healing with superficial injuries and skin lesions • Wounds dry faster therefore heal faster • scabbed skin lesions are kept silky smooth and any itching that develops during the healing process is kept at bay • the resulting protective film prevents the wound from re-opening allowing it to heal completely • approved for all animals kept for food production • not subject to regulations on residue levels • spray on the affected areas 1-2 times a day for up to 1 week • suitable for all working animals

#### Please note the use and safety instructions.

with mint oil and allantoin				
Ref. no.	Contents	Ø	Ħ	€
15239	500 ml / Spray bottle	1/12	480	

#### Teat Bandage UdderoSoft

 $\mbox{ \bullet}$  does not stick to the skin or wound  $\mbox{ \bullet}$  self-adhesive, soft and elastic

					- C	K
double sid	led protective	film for better h	ygiene			
Ref. no.	Colour	Length	Width	Æ	€	Ľ.

Ref. no.	Colour	Length	Width	Ē	€
15660	beige	5 m	6 cm	1/50	

This product was specially developed to treat large animals and is only for use in veterinary medicine/hoof and claw care.

#### **Teat Protector**

 proven design • for protection against teat injuries in the pasture and in narrow stalls • this net is also a valuable aid in mastitis treatment • all you have to do when milking is open the hook

Size	$\blacksquare$		€
М	1/10	100	
L	1/10	100	
XL	1/10	100	
		M 1/10 L 1/10	M         1/10         100           L         1/10         100



#### Teat Protector with neck strap

• chest and neck strap for additional support and proper fit on the cow • this teat protector limits teat injuries that can happen quickly in too narrow a stable or on the pasture • also ideal for the prevention of impact injuries

Ref. no.	Size	Ø	€
1567	М	1/10	
1568	L	1/10	
1569	XL	1/10	



T	U	
	/	

Ŧ

GE#

## Hand Care

## Hand Cleaner with Cleansing Beads

Liquid hand cleaner for moderate to severe soiling caused by oil, grease and lubricant in industry, workshops and agriculture: • contains skin-friendly, mild cleaning and care substances with high-quality moisturising agents • with skin-friendly cornmeal scrubbers • without microplastic • does not clog drains • pH value adapted for human skin • silicone-free, solvent-free, soap-free • dermatologically tested




Ref. no. Contents 🖽 🚍	€
151193 500 ml / Bottle 1/10 900	
151194 2500 ml / Bottle 1/6 216	
151195         2500 ml / Bottle with Metering Pump         1/6         216	
Ref. no. Description	<b>H</b> •
151187 Wall Mount for 2500 ml bottle	1/6/24
151188 Dispensing Pump for 2500 ml bottle	1/96




#### Hand-wash Paste

 with special wood flour (no sand) • lightly fragranced • high and particularly mild cleaning power • with skin-friendly, environmentally neutral natural friction agents • pH value adapted for human skin
 extremely economical to use • does not clog drains • Applications: for moderate to severe soiling caused by all kinds of dirt, such as oil, grease, lye, lubricants, etc. • silicone-free, solvent-free, soap-free







## Hand Wash Brush

- the perfect hand-washing brush for heavy soiling robust plastic back
- with a row of strong polyester bristles Bristle length: 1 cm



Ref. no.	Colour	Length	Width	Height	Ħ	€
29183	green / yellow	10,5 cm	4,5 cm	3 cm	1/30	

GE/

Ŧ

151810

## Soft Soap Edelweiß

The alternative to products that harm the environment and very expensive specialist cleaning products. Protects the environment from phosphates, silicates, carbonates, sulphates, bleaching agents, enzymes and much more as a result. Contains only easily degradable raw washing products.

- Universal application for rinsing, washing and cleaning for the gentle cleaning
- of textiles, tiles, stone and PVC flooring, paintwork, glass, enamel and much more
- $\bullet$  can also be used as a washing detergent up to 60 °C  $\bullet$  environmentally compatible
- phosphate-free, formaldehyde-free

Ref. no.	Contents	Ø		€
151175	1000 ml / Can	1/16	480	
151176	5000 ml / Bucket	1	90	

## **Paper Towel Roll**

- extremely absorbent glued also suitable for udder cleaning
- food safe

Ref. no.	Description	Colour	Contents	Sheet dimensions (L x W)	MOQ	Pieces / unit	Ø		€
29560	2-ply	blue	1000 sheet / Roll	36 x 22 cm	1 pack	2 / pack	1	60	
29562	3-ply	blue	500 sheet / Roll	36 x 36 cm	1 pack	2 / pack	1	36	

## Wall Roll Holder

• for cleaning rolls and udder paper up to 40 cm width • Supplied without plaster rolls • folding • for wall mounting

Ref. no.	Colour	Material	Ø		€
29563	blue	metal painted	1	90	

## **Dispensing Pump**

• for 1-litre bottles and canisters with approx. delivery volume of approx. 4 ml

• suitable for Domo-Ultra and Domo-Mild from GEA • Material: Plastic

Ref. no.	Flow volume	suitable for Ø opening	Ø	€
151810	4 ml	25 mm	1/250	


## **Dispensing Pump**

• made from a special, oil-resistant plastic • enables exact and safe emptying and refilling of chemicals and commercially available lubricating oils • incl. adapter for 5, 10 and 30 litres • for DIN42, DIN51, and DIN61 threads

Ref. no.	Flow volume	Ð	€
151811	30 ml	1/40	




## **Pumps and Accessories**



#### **Milking Hygiene Rinser Anka** 151874 • with hose connection • Variable adjustable spray or concentrated jet • high water flow • Material: Nylon GE# fibre-glass reinforced • use before max .: 7 bar 151874: Water flow 25 l/min 151873: Water flow 90 - 115 l/min 151873 Ħ Ref. no. Connection Colour € 3/4" 1/100 151874 green / black 2.000 151876 151875 1/80 2.000 151873 1″ green / black Ref. no. Description Colour Material Ħ € Hose Connector 3/4" black Plastic 1/10/500 151876 151875 Hose Connector 1" black Plastic 1/10/320 **Rinser Super Jet** • with hose connector • Variable adjustable spray or concentrated jet • flow rate regulated separately • suitable for water temperatures up to 35 °C • Material: Plastic with anti-slip coating • Water flow rate: 50 L/min • use before max.: 4 - 6 bar Ref. no. Æ Colour € Ŧ 151871 black / red 1/12 360 **Rinser Twist Jet** • with hose connector • Variable adjustable spray or concentrated jet • suitable for water temperatures up to 35 °C • Material: Plastic with anti-slip coating • Water flow rate: 38 - 47 L/min • use before max.: 4 bar Ref. no. Colour 俑 Ħ € 1/25 750 151872 yellow / black Cleaning shower with crash bars • brass interior • crash bars made from sturdy plastic • Variable adjustable spray or concentrated jet • suitable for water temperatures up to 50 °C • 1/2" internal thread, rotatable • Material: Plastic • Water flow rate: 50 L/min • use before max.: 12 bar

Ref. no.	Colour	Ð	€
151870	blue	1/10	





## Spray Shower orig. Gilmour

• suitable for hot and cold water • Housing made from cast metal

• with insulated handle • Lever fixing for continuous spraying • Stainless Steel Spring • self-adjusting anti-drip seal • incl. hose

coupling (15732)



Plastic



Ref. no.

1573

1574

Ref. no.

15731

15732

## Spray Guns with accessories

• original Gilmour shower (with brass insert) • incl. accessories (3-metre, 1/2" water hose, hose jacket, hose clamp)

**Hose Coupling** 

Ref. no.	Colour	Ø		€
151808	red	1/10	160	



1/10/500

## **Spray Rinser Komfort**

Со

• high quality metal spray shower • non-slip and abrasion-resistant surface for comfortable and fatigue-free working • steplessy adjustable nozzle from full jet to fine mist • incl. 3-step hose connection and standardised hose coupling (1.2")

nnection	Ð		€	
1/2"	1/24	792		
				15731



Ref. no.	Description	Colour	Material	Ð	€
15731	Hose Connector 3-tier	black	Plastic	1/10/500	
15732	Hose Coupling	black	Plastic	1/10/500	

111

15732

black

Ref. no.

resistance • 5 defined dosing position	lly from stainless steel • high chemical		
Ref. no. ∰ € 151798 1/10	The 1-litre bottle (art. 151807) for disinfectants is available as an option!		
Accessories for foam	151800 151801	151803	151807

#### Acces lance

lance					
Ref. no.	Description	Material	can be used for	Ø	€
151807	Bottle for Foam Lance, 1 litre	Plastic		1/20	
151800	Manual screw attachment, 1/4" OT x 28 mm		Kärcher and Kränzle Professional High-Pressure cleaners	1/20	
151801	Rotary screw attachment ST-146, M 22 IT x 1/4" OT		Kärcher Professional High-pressure Cleaner	1/20	
151803	Plug nipple, 1/4" OT	stainless steel	Nilfisk / Alto, Ehrle and Kränzle high-pressure cleaners	1/20	
151802	Counter-nipple, M22 OT x 1/4" OT	brass	for all common high-pressure cleaners	1/20	

Milking and washing apron • premium quality • ideal for all work related to agriculture, house and garden • high quality plastic • waterproof • extremely tear and kink-proof • Temperature resistance: -25 - 70 °C



**Milking Hygiene** 

GE/

7

T

Ref. no.	Colour	Length	Width		€
15147	blue	120 cm	80 cm	1/20	
15151	blue	125 cm	100 cm	1/20	
15153	blue	125 cm	125 cm	1/20	
15148	white	120 cm	80 cm	1/20	
15150	white	125 cm	100 cm	1/20	
15149	green	120 cm	80 cm	1/20	
15152	green	125 cm	100 cm	1/20	

## Milking and washing apron PU

ultra-lightweight and durable work apron made from polyurethane
 ideal for working in the stable, garden or home • easy to adjust the required length with a plastic click fastener • ultra-tear-resistant and shape stable • temperature-resistant • waterproof

Composition	1				
Textile		100 % Poly	ester		
Coating		100 % poly	urethane		
Ref. no.	Colour	Length	Width	Ħ	€
15286	blue	120 cm	80 cm	1/80	
15288	blue	125 cm	100 cm	1/80	

## Milking and washing apron MaxiMove

• high freedom of movement thanks to a separated and overlapping leg area • ideal for all work related to agriculture, house and garden • easy to adjust the required length with a plastic click fastener • temperature-resistant • waterproof

Composition	n				
Coating		100 % PVC			
Ref. no.	Colour	Length	Width	Ø	€
15620	blue	120 cm	80 cm	1/20	
15621	blue	125 cm	100 cm	1/20	

## **Milking Hygiene**



-

GE/

Ŧ

## **Hygiene Sleeve Protector**

The tight-fitting wrist cuff makes sure that no water, etc. can get into the sleeve protector. Scissors can be used, if necessary, to quickly shorten the cuff to customise the fit.

• extremely tear- and abrasion-resistant • material resistant to cleaning agents • waterproof (> 3000 mm water column) • flexible in the cold, at down to -20 °C • can be sterilised and disinfected • detectable • with elastic • Temperature resistance: -20 - 95 °C • food safe • in pairs • machine washable at 95 °C


	100 % Polyuret	hane (TPU)		$\nabla$
Colour	Size	Length	Ø	€
light grey	S / M	50 cm	1/20	
light grey	L / XL	50 cm	1/20	
	light grey	Colour Size light grey S / M	light grey S / M 50 cm	Colour Size Length light grey S / M 50 cm 1/20

Size S/M is ideal for wrists greater than 14 cm in diameter. Size L/XL is ideal for wrists greater than 18 cm in diameter. You can cut to fit with scissors.

## **Disposable Protective Sleeve**

- elasticated strap at both ends tear-resistant 0,03 mm
- Material: polyethylene

Ref. no.	Colour	Length	MOQ	Pieces / unit	Ð	€
15397	blue	45 cm	1 pouch	100 / pouch	1/10	



**Protective Sleeve Softshell** 

• Oversleeves made from elastic softshell material • practical with thumb holes to prevent slipping • one size with drawstring to the upper arm for flexible fixing • extremely water-resistant up to a 3000 mm water column • breathable to 1000 g/m<sup>2</sup>/24 h • in pairs

Compositio	n			
Textile		100 % Polyes	ter	
Ref. no.	Colour	Length	Ē	€
15388	dark blue	54 cm	1/80	

## **Protective Sleeve Oxford**

• high-quality oversleeves made from the finest Oxford polyester • waterproof and breathable thanks to their special coating • elasticated strap at both ends • in pairs

Composition				
Textile		100 % Polyest	er	
			<u> </u>	
Ref. no.	Colour	Length	Ø	€
15387	blue	40 cm	1/80	

## **Protective Sleeve**

• 100 % watertight • with elastic waist • Temperature resistance: -25 - 70 °C • in pairs

Composition	i			
Textile		100 % PVC		
Ref. no.	Colour	Length	Ħ	€
15385	blue	40 cm	1/20	








## **Disposable glove Nitrile Premium**

• especially suitable as milking gloves • 30 cm long for comfortable protection • for the toughest conditions • ambidextrous • non-sterile • tested according to: EN 374/1 (protection from chemicals and micro-organisms) • free from allergy inducing thiurames, thiazoles and latex proteins, latex-free, Free of powder • 1.5 AQL (quality standard) • Weight size M: 12 - 13 g/piece • food safe







EN ISO 374-1:2016 Туре В

R				, Nitile Premium					Ū	JKT
Ref. no.	Colour	Size	Length	Material thickness	MOQ	Pieces / unit	Ð		€	
15325	light blue	6.5-7 / S	30 cm	8 mil = 0,2 mm	1 pack	50 / pack	1/20	300		
15326	light blue	7.5-8 / M	30 cm	8 mil = 0,2 mm	1 pack	50 / pack	1/20	300		
15327	light blue	8.5-9 / L	30 cm	8 mil = 0,2 mm	1 pack	50 / pack	1/20	300		
15328	light blue	9.5-10 / XL	30 cm	8 mil = 0,2 mm	1 pack	50 / pack	1/20	300		
15329	light blue	10.5-11 / XXL	30 cm	8 mil = 0,2 mm	1 pack	50 / pack	1/20	300		

## **Disposable glove Nitrile Profi**

• 30 cm long for comfortable protection • for the toughest conditions • ambidextrous

- non-sterile tested according to: EN 374/1 (protection from chemicals and micro-organisms)
- latex-free, Free of powder, free from allergy inducing thiurames, thiazoles and latex proteins
- 1.5 AQL (quality standard) Weight size M: 11 12 g food safe



## ۶Ĩ

Ref. no.	Colour	Size	Length	Material thickness	MOQ	Pieces / unit		€
15380	blue	6.5-7 / S	30 cm	8 mil = 0,19 mm	1 pack	50 / pack	1/20 360	
15381	blue	7.5-8 / M	30 cm	8 mil = 0,19 mm	1 pack	50 / pack	1/20 360	
15382	blue	8.5-9 / L	30 cm	8 mil = 0,19 mm	1 pack	50 / pack	1/20 360	
15383	blue	9.5-10 / XL	30 cm	8 mil = 0,19 mm	1 pack	50 / pack	1/20 360	
15384	blue	10.5-11 / XXL	30 cm	8 mil = 0,19 mm	1 pack	50 / pack	1/20 360	

## **Disposable glove Nitrile Long Black**

• 30 cm long for comfortable protection • fully textured, therefore providing excellent grip • especially suitable as a milking glove: white flakes in the milk, a sign of mastitis, can be detected more easily on the black background • ambidextrous • non-sterile • tested according to: EN 374/1 (protection from chemicals and micro-organisms) • free from allergy inducing thiurames, thiazoles and latex proteins, latex-free, Free of powder • 1.5 AQL (quality standard) • Weight size M: 7,7 - 8 g • food safe





Ref. no.	Colour	Size	Length	Material thickness	MOQ	Pieces / unit	Ø		€
15320	black	6.5-7 / S	30 cm	5,5 mil = 0,14 mm	1 pack	50 / pack	1/20	360	
15321	black	7.5-8 / M	30 cm	5,5 mil = 0,14 mm	1 pack	50 / pack	1/20	360	
15322	black	8.5-9 / L	30 cm	5,5 mil = 0,14 mm	1 pack	50 / pack	1/20	360	
15323	black	9.5-10 / XL	30 cm	5,5 mil = 0,14 mm	1 pack	50 / pack	1/20	360	
15324	black	10.5-11 / XXL	30 cm	5,5 mil = 0,14 mm	1 pack	50 / pack	1/20	360	

GE/

統

Ŧ

## GEA Wall bracket for disposable gloves

• made from stainless steel: heavy-duty and rust-free, even in wet conditions (e.g. in the milking station) • screw-on fastening • can be affixed vertically and horizontally • stable position and suitable for all sizes thanks to spring that pushes the dispenser box to the front

Ref. no.	Customer no.	Material	Ø		€
15339-GEA	7315-5151-700	stainless steel	1/8	192	

## **Disposable glove Nitrile Classic**

ambidextrous
non-sterile
free from allergy inducing nitrosamines, thiurames, thiazoles and latex proteins, latex-free, Free of powder
1.5 AQL (quality standard)
Weight size M: 5,6 - 5,8 g
food safe



Ref. no.	Colour	Size	Length	Material thickness	MOQ	Pieces / unit	Ø		€	EN ISO 374-1:2016 
15370	light blue	6.5-7 / S	24 cm	4 mil = 0,1 mm	1 pack	100 / pack	1/10	360		
15372	light blue	7.5-8 / M	24 cm	4 mil = 0,1 mm	1 pack	100 / pack	1/10	360		
15373	light blue	8.5-9 / L	24 cm	4 mil = 0,1 mm	1 pack	100 / pack	1/10	360		
15374	light blue	9.5-10 / XL	24 cm	4 mil = 0,1 mm	1 pack	100 / pack	1/10	360		JKPT

NITRILE C

## **Disposable glove Nitrile Basic**

• ambidextrous • non-sterile • latex-free, Free of powder, free from allergy inducing nitrosamines, thiurames and thiazoles • 1.5 AQL (quality standard) • Weight size M: 3,3 - 3,5 g • food safe





Ref. no.	Colour	Size	Length	Material thickness	MOQ	Pieces / unit	Ð		€
15330	blue	6.5-7 / S	24 cm	0,07 mm	1 pack	100 / pack	1/10	360	
15331	blue	7.5-8 / M	24 cm	0,07 mm	1 pack	100 / pack	1/10	360	
15332	blue	8.5-9 / L	24 cm	0,07 mm	1 pack	100 / pack	1/10	360	
15333	blue	9.5-10 / XL	24 cm	0,07 mm	1 pack	100 / pack	1/10	360	

## **Round-headed brush**

- suitable for hygienic areas (HACCP) heat-resistant up to: 140 °C Bristle material: Polyester
- Material: Plastic

Ref. no.	Colour	Ø	Ð	€
151783	white	120 mm	1/5	

## Can Brush

• with wide-set bristles • ideal for cleaning hard to reach places • Bristle material: Polyester • Material: Plastic

Ref. no.	Colour	Length	Ø	€
29177	white / blue	22 cm	1/10	

## Washing brush

- suitable for hygienic areas (HACCP) - heat-resistant up to: 140 °C - Bristle material: Polyester - Material: Plastic

Ref. no.	Colour	Length	Ø	€
151784	white	20,5 cm	1/5	

## Handle Brush

• with ergonomic plastic handle • suitable for hygienic areas (HACCP) • heat-resistant up to: 140 °C • Bristle material: Polyester • Material: Plastic

bristles heat-re	esistant to 140 °C					
Ref. no.	Description	Colour	Length	Ð	€	
29174	with long handle	white / blue	40 cm	1/5		
151780	with short handle	white	14 cm	1/5		

## Universal and boiler brush

6

• Polypropylene bristles, medium hardness • Bristle thickness: 0,3 mm

29182

up to 80 °C heat-resistant

up to 100 °C heat-resistant


Ref. no.	Description	Colour	Length	Width	Ø	€
29172	without handle	blue	200 mm	125 mm	1/10	
Ref. no.	Description	Length	€			
29173	Fibreglass Handle	100 cm 1	1/20			
29182	Fibreglass Handle	145 cm 1	1/20			

29173

## Large scrubber

- bristles heat-resistant to 140 °C - suitable for hygienic areas (HACCP) - plug-in system with union nut - with PST bristles - with handle thread - matching handle: 29182

Ref. no.	Colour	Width	Ø		€	C	
151781	white	40 cm	1/5	330		AL N. J.	WWWWWWWWW
Ref. no.	Desc	ription		Length	Ø	€	A A A A A A A A A A A A A A A A A A A
29182	Fibregla	ss Handle		145 cm	1/20		



151780

29174



						Milking Hygiene	
Flexo Bi	cleaning brush • E	Bristle material: F	olypropylene		44	the superside the particular the second	
• Material: Pla	astic					Sector States	GE
Ref. no.	Colour	Length	Ħ	€	up to 80 °C heat-resistant	A Contraction	
29176	white	19 cm	1/10/100		up to ov cheat resistant	authos	1
Claanin	g and Scru	ubbing B	ruch				
Scrubbing I	-		asn		19 Mart	Called States	
<ul> <li>wet-proof pl</li> </ul>	astic back • Bristl	e material: Polyp	ropylene		1111	A LA PARA ANY ANY	
					120	Martin Contraction	
						Minimum Contractor	
Ref. no.	Colour	Length	Ø	€	up to 60 °C heat-resistant	ALL	
29178	beige	22 cm	1/30				
Nachin	a bruch						
Washin	<b>y Drusn</b> rial: Polyamide • I	Material: Plastic					
							5
						- Att States	
Ref. no.	Colour	Length	Ē	€		- Alter and the	
2916	white	19 cm	1/50	t	up to 60 °C heat-resistant		1
<b>Double</b> • with plastic	<b>Brush</b> handle for optima	l hygiene		1			ť
			Æ.		A. C. C. C. C.		
Ref. no. 151830	Length 40 cm	Ø 13 mm	€				
151050	40 Cm	15 11111	1/200				
Pipe Bru	ısh					\$5555555555555555555555555555555555555	1
	handle for optima	I hygiene				******************************	
			ci-	arres 1	and leave all		
				Antheinet	Second Contraction		
Ref. no.	Length	Ø	€				
151831	62 cm	~ 70 mm	1/100				
Hose W	iper						
	•			والمروار والمروار والمروار والمروار			
			and	un	and a contraction of the	111/20000000000000000000000000000000000	
-	meeseend			5-6-6-0-			
0	13333353U	220023	999999	0000	99999999999999999999999999999999999999	はいいいしきもいいいいいいいい	
Ref. no.	longth	€					
2914	155 cm	1/50					

## **Teat Cup Brush**

- 3-level bristle spiral staggered bristle length to 59 mm diameter Plastic Handle
- acid-proof heat-resistant up to: 100 °C Material: Plastic

Ref. no.	Length	Ø	€
151785	50 cm	1/50	

#### **Teat Cup Brush**

• with wooden handle	• extremely hard-wearing				29149
Ref. no.	Description	Length	Ø	€	
2913	Bristle spiral 3-tier	50 cm	1/30		

40 cm

1/30

#### **Basin**

29149

• made from high-quality, pure polyethylene • extremely high cold impact strength • impact and shock-resistant • extremely acid-resistant • with smooth surfaces for easy cleaning • complete drainage through chamfered trough base • the outlet is fitted with a sieve and a drain connection piece • Wall bracket or table frame not included. • Material: polyethylene • shatter-proof • food safe • with outlet

Bristle spiral 2-tier

29414: up to max. 95 kg load capacity (mounted on wall brackets) 29415: up to max. 150 kg load capacity (mounted on wall brackets)



# 29419

temperature resistant from - 65 °C to + 85 °C

Ref. no.	Length	Width	Height	Capacity	Ø		€	
29414	74 cm	62 cm	25 cm	5 cm 65 L		100		
29415	100 cm	62 cm	28 cm	100 L	1	50		<b>•</b> ••
Ref. no.		Description		Material	suitab	ole for	Ø	€
29402		Wall Bracket		metal galvanised	294	414	1	
29404		Wall Bracket		metal galvanised	294	415	1	
29419		Table Frame		metal galvanised	294	414	1	
29420		Table Frame		metal galvanised	294	415	1	


GE/

#### **Udder Hair Remover PREVENTA**

• the Preventa removes udder hair quickly and painlessly using a "cold" flame (about 200 ° C) • the bent torch allows ergonomic working in an upright position • the well thought-out design of the device with its standby-lever guarantees a quick and safe use. • eliminates pathogens like bacteria and viruses completely • Mastitis and Johne's disease can be prevented • shortens preparation time before milking • hairless udders are easier to clean • improves the general udder hygiene

#### 15676: Gas cartridge not included

• the contents are enough for approx. 2-3 operating hours (depending on consumption) • the supplied belt clip makes using the gas cartridge easy and time-saving



## TailWell2<sup>®</sup> Power Tail Trimmer II

Ħ

1/10

€

Ref. no.

18250

#### The logical further development of the successful model from New Zealand!

• makes the arduous work involved with cutting hair on the tails of dairy cows easier • twice annual removal of cow tail hair that is contaminated with faeces and urine allows for optimal hygiene of livestock, milk and milker. • pre-cutting the hair is not necessary even in the case of heavy soiling or crusting. • works quietly and creates a smooth haircut in a maximum of 4 seconds per tail • Principle: It works on the principle of an outer blade rotating around an inner one, therefore there is no risk of injury to the animal or the operator • with a powerful battery, up to 200 tail shears with just one charge • the in-house developed grinding paste supplied allows for easy and simple grinding of the blades even by inexperienced users (necessary after 1000 to 2000 shears). • fits virtually all battery-powered screwdrivers operating at min. 14 Volt, 1,250 rpm (battery screwdriver not included) • supplied in a handy plastic case for safe storage • includes DVD and handbook





Ref. no.	Description	Contents	Ø	€
18251	Blade for Tail Trimmer II		1	
18252	Grinding Paste for Tail Trimmer		1	
1850488	Clipper Oil	100 ml	1/50/200	
18241	Blade for Tail Trimmer I (previous model		1	

## **Filters and Milk Hoses**

## Sana Milk Filters Premium 120 g

 high-quality, food-safe nonwoven fabric • finest filtration • very high wet strength • especially suitable for large amounts of milk and the highest standards
 recommended for robotic milters • 120 g/m<sup>2</sup> • food safe • sewn



recommended	for	robotic	milters
recommended	101	TODOLIC	miniters

Ref. no.	Width	Length	Suitable for	MOQ	Pieces / unit	Ð	€
46783	44 mm	570 mm	DeLaval	1 pack	100 / pack	1/10	
46784	44 mm	1.044 mm	DeLaval	1 pack	100 / pack	1/8	
46786	78 mm	620 mm	Lely (Robotic Milker) / GEA / Boumatic / S.A.C.	1 pack	100 / pack	1/8	
46787	78 mm	1.125 mm	Lely (Robotic Milker)	1 pack	100 / pack	1/5	

#### Sana Disc Filters

• high-quality, food-safe nonwoven fabric • Suitable for: Milk Sieves

Ref. no.	Ø	MOQ	Pieces / unit	Ø	€	
46752	115 mm	1 pack	200 / pack	1/60		バ
46753	120 mm	1 pack	200 / pack	1/60		
46754	125 mm	1 pack	200 / pack	1/60		
46755	140 mm	1 pack	200 / pack	1/60		
46756	160 mm	1 pack	200 / pack	1/35		
46757	170 mm	1 pack	200 / pack	1/35		
46758	180 mm	1 pack	200 / pack	1/30		
46759	190 mm	1 pack	200 / pack	1/30		
46760	200 mm	1 pack	200 / pack	1/30		
46761	220 mm	1 pack	200 / pack	1/30		
46762	240 mm	1 pack	200 / pack	1/10		
46763	270 mm	1 pack	200 / pack	1/10		

## Sana Disc Filters with hole

• high-quality, food-safe nonwoven fabric • Suitable for: Milk Sieves

Ref. no.	Ø	MOQ	Pieces / unit	Ø	€	
46770	220 mm	1 pack	100 / pack	1/30		ス
46771	300 mm	1 pack	100 / pack	1/10		_

## Milk Sieve stainless steel

• for use in cooling tanks and milk cans • suitable for Ø 170 mm cotton discs • all parts 100 % stainless steel • hygienic, hassle-free cleaning

#### stainless steel

Included in delivery: 1 x milk sieve, 1 x coarse mesh, 1 x fine mesh, 1 x perforated panel, 1 x clamping ring

Ref. no.	Capacity	Ð	€
15182	10 I	1/5	

Ref. no.	Description	Material	Ø	Ð	€
151631	Sieve Insert Net	stainless steel	170 mm	1	
15183	Sieve Insert Perforated Disc	stainless steel	170 mm	1	
15184	Clamping Ring for milk strainer	stainless steel	170 mm	1	







15184



## **Milking Sealing Plug conical**

 $\bullet$  for use with animals with three teats  $\bullet$  conical shape with three-finger grip for easy insertion and removal  $\bullet$  suitable for all teat cups

Ref. no.	Colour	Material	MOQ	Pieces / unit	Ø	€
151040	blue	Plastic	10 pieces	10 / pouch	1/10/200	

## **Milking Sealing Plug**

 $\cdot$  ideal for the milking machine, with animals with three teats  $\cdot$  quickly solves the problem and adds cleanliness to milking  $\cdot$  suitable for all teat cups

Ref. r	o. Colour	Material	MOQ	Pieces / unit	Ø	€
291	1 black	Plastic	10 pieces	10 / pack	1/10/150	
2911	/1 black	Plastic	1 blister pack	c 1 / blister pack	1	

## **Universal Cleaning Sponge**

• for cleaning pipelines in the food industry (milk, wine, delicatessen) • food safe

Ref. no.	Colour	Height	Ø	MOQ	Pieces / unit	Ø	€
4670	white	70 mm	40 mm	1 pack	10 / pack	1/100	
4671	white	70 mm	50 mm	1 pack	10 / pack	1/100	
4672	white	70 mm	60 mm	1 pack	10 / pack	1/80	
4676	white	80 mm	70 mm	1 pack	10 / pack	1/60	


## Milk dummy cap

• for covering the teat cup • for safe and hygienic milking of three-teat cows


Ref. no.	Colour	Interior diameter	Ð	€
151804	yellow	57 mm	1/350	
151806	yellow	60,3 mm	1/350	
151805	yellow	63,5 mm	1/300	

## **Milking Stool**

• with steel leg, coil spring and wooden seat • with adjustable polyamide straps for putting on • Seat height: 34 cm



## **Milking Accessories**



## **Milking Accessories**

## Which lid fits which bucket?

Here you will find an overview to help you find the right product. You will find additional product information for the listed products on the following pages.



## **Milking Pail Stainless Steel**

• without accessories • Material: stainless steel stainless • with metal carry handle

Ref. no.	Description	Capacity	Frame height	Ð		€
151001	short	25 L	117 mm	1	24	
151002	Standard	25 L	143 mm	1	24	

## **Milking Pail Plastic**

• for daily use • can be used to check each individual cow's milk yield • also for mobile milking machines • suitable for systems made by popular brands (e.g. Westfalia) • Material: Polycarbonate • with metal carry handle • with double fill scale (kg; lb) • food safe

Ref. no.	Description	Colour	Capacity	Frame height	Ø		€
151050	Standard	red	30 L	143 mm	1	24	
151051	Standard	blue	30 L	143 mm	1	24	
151052	Standard	green	30 L	143 mm	1	24	
151055	short	blue	30 L	117 mm	1	24	
151056	short	green	30 L	117 mm	1	24	

## **Milking Accessories**

Ŧ

## **Milking Pail Lid**

- transparent polycarbonate extremely durable and easy to clean flat design
- for Plastic and Stainless Steel Milking Pail 25/30 Litres



new flat shape as per QM milk standard

Ref. no.	Description	Material	Ø		€
151058	Supports ID 13 mm x AD 17 mm	Polycarbonate	205 mm	1/20	
151059	Supports ID 16 mm x AD 20 mm	Polycarbonate	205 mm	1/20	
Ref. no.	Description				€
151060	Rubber Seal for milking pail covers			1/26	

## Stainless Steel Lid for milking pails

Stainless Steel Lid for Milking Pail 25/30 I with Mount for Pulsator Adapter (ADM 14 mm)

• connecting pieces 13 x 16 mm • Rubber ring for stainless steel lid

151007: suitable for 151001, 151055, 151056 151009: suitable for 151002, 151050, 151051, 151052



Ref. no.	Description			Material	Ø	€
151007	suitable for pail with handle height 117 mm			stainless steel	1/10	
151009	suitable for pail with handle height 143 mm			stainless steel	1/10	
Ref. no.	Description	Ē	€			
151006	Rubber Ring	1/100		_		

## **Milking Machine Oil Viscano**

• Viscano stands out for its extraordinary viscosity at different outside temperatures • this ensures that all brands of milking machines can be operated easily at both high and low ambient temperatures • Viscano is characterised by high resistance to ageing as well as very good corrosion protection and anti-wear properties • Viscosity at 40 °C: 68 mm<sup>2</sup>/s

Not suitable or approved for GEA systems!

#### ATTENTION: the relevant manufacturer's requirements must be met!

Ref. no.	Contents	Ð		€
1549	1 L / Bottle	1/12	480	
1570	5 L / Canister	1/3	90	
1555	10 L / Canister	1	40	



#### **Rod thermometer**

• with fastening thread • Probe length 38 cm • Measuring range 0 - 100 °C or 37 - 210 °F • food safe

		Contraction of the second seco	A B B B B	
Ref. no.	Material	Ø	€	
141453	stainless steel	1/10		

#### **Milk and Cheese Thermometer**

• with hanging tab • Measuring range -10 °C - 110 °C • can be boiled



Ref. no.	Material	Ð	€	
29144	Plastic	1/100		_

Contains no mercury!

## Measuring cup

- with handle and drain spout stackable Material: Polypropylene
  chemical-resistant, oil resistant with measuring scale food safe



Ref. no.	Colour	Capacity	Ø		€
291194	transparent	500 ml	1/200	1.600	
291195	transparent	1000 ml	1/120	960	
291196	transparent	2000 ml	1/60	480	

## **Milking Accessories**

## Waikato Milk measuring device

• 30 kg - Original Waikato • Milk meters are an important aid for agriculture • farmers can recognise high and low-performance animals early on with regular use of milk meters • the milk meter stores a small percentage of the total yield in a calibrated container; the total amount can then be read from this • also ideal for fat analysis • ICAR-certified • holder (157116) not included in supply • with printed measurement scale

AIKATO

Ref. no.	Colour		€			-
15700	blue	1/6				157116
Ref. no.			Ð	€		
157116		Но	older for milk	c meter	1/70	
15705		Mounting Bracket transportable			1/10	



## Quarter milker

milk with an increased cell count or milk from an udder quarter contaminated with foreign substances can be milked separately
extremely robust • Easy to clean • for milking machines up to 57 kPa • with carrying handle

A

Ref. no.	Colour	Capacity	Ð	€	
15902	white / blue	8 L	1/12		
15903	white / blue	12 L	1/12		NEW

## **SHOOF Quarter Milker**

milk with an increased cell count or milk from an udder quarter contaminated with foreign substances can be milked separately with this product
unbreakable
Easy to clean
with carrying handle

Ref. no.	Colour	Capacity	Ø	€
15701	white / blue	8 L	1/12	



Ŧ

GE/



HOO

Made in Germany

## **Battery-operated Horn Remover buddex**

#### Proven Buddex technology in a new, ergonomic design!

• humane dehorning: The unique focal ring reliably prevents horn growth in animal-friendly way • Temperature at the burner tip: The high temperature of 700 °C at the burner ring means that de-horning is carried out on the calf withi ole of se conds Jv hegir • the heat-up pha ag ris ор ca wi

against the ho risk for the us operation mea cable clutter • with the other	orn bud. There is er • the Buddex ans maximum fre single-handed	no shaft that is f heats up to 700° eedom of movem operation means 0/12 Volt power	e only begins once press fully heated, and so no H C in just 7 seconds! • b ent during de-horning - that the calf can be kep pack • Battery built-in	burn attery no		budder budder budder
Technical da	ta	17	/90			Top Seller
max. heat-up	time	ap	prox. 4 sec			
max. burning	tip temperature	e ap	prox. 700 °C	360°		Made in Germany
Weight		80	00 g incl. battery	360°		
Ref. no.	Colour	Length	Ø burning tip	Ð	€	
1790	green	19,5 cm	18 mm	1/10		

#### Dehorner with transformer

• with 24 Volt safety transformer • incl. stainless steel burner tip • very high heat output and considerable reserve power of dehorning tip (heating cartridge is located inside the dehorning tip) • easy handling due to light weight • with ergonomic handle • with stainless steel tray • Material: stainless steel

stainless steel

Technical data	17460
Voltage	24 V
Power	250 W
max. heat-up time	~ 11 min
max. burning tip temperature	620 °C
Length of burning rod	15,5 cm
Weight	630 g incl. cable
Cable length	4 m

Ref. no.	Colour	Length	Ø burning tip	Ð
17460	black	30 cm	18 mm	1

17451 17452	

€

black	30 cm	18 mm	1				
	Description		Material	Ø	Ø	€	
Burn	ing rod single 24 V /	250 W			1/30		
	Burning tip		stainless steel	18 mm	1/100		
	Burning tin		stainless steel	15 mm	1/100		

Ref. no. 17455 17451 17452

## Dehorner GasBuddex

The professional tool for humane dehorning of calves. Fast heating up time and high maximum temperature of 650 °C make the GasBuddex a tool of the highest quality. Stainless steel finish guarantees durability and meets the highest expectations!

 pain-free to the greatest possible extent for a calf through a dehorning process of maximum 10 seconds long • operating temperature of about 650 °C is reached within max. 3 minutes • practical design through non-slip handle and balanced centre of gravity • dependable, automatic Piezo ignition • Material: stainless steel • Gas included.
 includes operating instructions • 2-year warranty



approx. 650  $^{\circ}\text{C}$  operating temperature

Technical dat	a		•					
max. burning	tip temperature	approx.	650 °C					
max. heat-up	time	approx.	3 min	Included in de	alivary: 1 v dat	orner, 2 x gas		
Duration of w	ork	120 - 18	0 min		56), 1 x spare t			
Weight		765 g		case, Tools	, i x spure (	ip, i x inclui		
Ref. no.	Colour	Length	Ø burning tip	Ħ	€			
1730	green	31 cm	20 mm	1/6				
1731	green	31 cm	15 mm	1/6				
								1738
Ref. no.		Description		Ø	Contents		€	
1738	Bu	rning tip for GasBud	dex	25 mm		1/10		
1732	Bu	rning tip for GasBud	dex	20 mm		1/10		e
1733	Bu	rning tip for GasBud	dex	15 mm		1/10		
1734	Ga	s Nozzle for GasBud	dex			1/10		e
1756		Gas Cartridge			110 ml	1/12/72		

## Soldering iron Direct connection

• incl. stainless steel burner tip • very high heat output and considerable reserve power of dehorning tip (heating cartridge is located inside the dehorning tip) • easy handling due to light weight • with ergonomic handle • with stainless steel tray • Material: stainless steel

stainless ste	eel						1			
Technical da	ta	17	450							
Voltage		23	0 V							
Mains freque	ncy	50	Hz							
Power		21	0 W					Made in Ge	rman	у
max. heat-up	time		prox. 11 min							
	tip temperature	e 62	0 °C							
Length of bu	rning rod		,5 cm							
Weight		63	0 g incl. cable							
Cable length		3 r	N							
Ref. no.	Colour	Length	Ø burning tip	Æ	€			CI I	D	A
17450	black	30 cm	18 mm	1/30					Ν.	
						-				
Ref. no.	Descr	iption	Material	Ø	ĺ	Ð	€			
17451	Burni	ng tip	stainless steel	18 mm	1	/100				
17452	Burni	ng tip	stainless steel	15 mm	1	/100		1745	1	17

Ŧ

1753

KERB

## **Gas Dehorner Portasol 3**

• for fast and effective calf dehorning • gas-operated with fillable gas tank • robust stainless steel housing • easy to maintain thanks to the new dehorner assembly • newly developed, more robust burner head made of stainless steel • new ignition system with "click-ignition" for easy reliable gas mixture ignition; Portasol 3 is manually ignited • supplied in sturdy plastic boxes • Gas not included. • includes operating instructions

approx. 600	) °C operating t	emperature						
Technical da	ta	1752		-	0		0	
max. burning	g tip temperature	e appro	к. 600 °С			9		
max. heat-up		approz	k. 5 min					
Duration of v	vork	45 mi	l					
Weight		320 g						
Ref. no.	Length	Ø burning tip	Ø	€				
1752	23,8 cm	18,5 mm	1/15					
Ref. no.		Description			Ø	Contents	Ø	€
17520		Burning tip			15 mm		1/100	
17521		Burning tip		1	8,5 mm		1/100	
1753		Gas Cartridge				200 ml	1/12	

## Gas Dehorner D-Horn

• with 3-metre hose for connection to standard gas cylinders • robust design and light weight for long-term use • with brass dehorning tip • a pressure regulator (not included) is required for use • Gas not included.

Technical da	ata	1721							
max. burnin	g tip temperature	appro	x. 610 °C						
max. heat-u	p time	appro	x. 4 min						
Weight		500 g							
Ref. no.	Length	Ø burning tip	Ø	€					
1721	33 cm	18 mm	1/30		-				15687
Ref. no.		Descrip	otion			Ø	Ø	€	
1796		Burnin	g tip			15 mm	1/25		
1797		Burnin	g tip			18 mm	1/20		_
15687	Pi	ressure Reducer for g	as bottle con	nection			1/20		_



GE/

Ŧ

## Hornstick

#### Pen for external application to calves

 $\bullet$  for calves aged 1 to 4 weeks  $\bullet$  several calves (approx. 4-5 depending on use) can be dehorned with one stick  $\bullet$  incl. instructions

FOR EXPORT ONLY!

					Please note the use and
Ref. no.	MOQ	Pieces / unit	Ø	€	safety instructions.
1713	5 pieces	5 / pack	1/5/500		Not approved for Germany and Austria!

#### Wire Saw according to Liess

 $\bullet$  exclusively for dehorning  $\bullet$  lightweight and easy to handle  $\bullet$  Order wire saw handles separately  $\bullet$  in plastic jar

Ref. no.	Description	Length	Ē	€
1714	in plastic jar	3,6 m	1/100	
17141	in plastic jar	12 m	1/100	
Ref. no.	Description		Ð	€
1715	Wire Saw Handle in pairs		1/100	

#### **Aesculap Wire Saw**

- extra strong wire saw for birth assistance and dehorning
- professional quality from Aesculap in plastic jar

Ref. no.	Length	Ē	€
VF676	10 m	1/200	

## Dehorning Saw TECNALL with saw blade

- for dehorning adult cattle consisting of angle sander, blade attachment and blade
- saw blade also perfect for woodas it has interlocking teeth

Technical dat	a	178	2	
Voltage		230	V	
Mains freque	ncy	50 H	Ηz	
Power		2.40	00 W	
		<i>—</i>		
Ref. no.	Colour	Ħ	€	
1782	yellow	1		FOR EXPORT ONLY!
Ref. no.		Desc	ription	
	-			

Ref. no.	Description	Ð	€
1781	Saw Blade for dehorner saw	1/10	
1772	Saw Attachment without saw blade	1/6	

## Cooling Spray IceCool

 cooling spray for cold shock treatment
 frozen locations are less sensitive to pain
 for de-horning preparation
 easy to use
 Please note the use and safety instructions.

i icase note the	use and survey instructions.		
Ref. no.	Contents	Ð	€
15879	400 ml / Spray Can	1/12	









## **Weaning Supplies**

#### Cow weaning system Müller THE ORIGINAL




**Top Quality** 

13152

for mature cattle

Top Quality





#### Cattle Weaner Müller

blue

blue

• elastic material plus a screw ensure easy adjustment and thus proper fitting to the animal's nasal cartilage


Livestock

Livestock

· this weaner is impossible to lose

13152

13152/2



6 pieces

6 / pack

1 blister pack 2 / blister pack

1/6/210

1/105

## Cattle Weaner SuckStop Müller

The new and innovative Cattle Weaner SuckStop Müller will win you over with its extremely easy handling, its realised learning effect with the animal as well as the improvement of the animal's well-being.

#### **Especially easy handling**

The cattle weaner is really easy to use and can also be removed. The ring has a certain amount of elasticity which enables it to be applied without any aid. The cattle weaner is hooked onto the side of the nose and inserted into the other side by stretching the ring. The extensions here point upward.

#### Long-term learning effect

Regular weaning rings have spines that point outwards, which can irritate other animals and lead to a defence reaction. The animal with a strong suckling need will not learn from this situation. However, it's a different story with the new and innovative Cattle Weaner SuckStop Müller. It corrects the suckling animal. The rounded extensions turned inward press into the nose of the animal when suckling from another animal. This impulse disrupts the act and inhibits misbehaviour. This ensures a long-term learning effect, even after just a few weeks.

#### Improving animals' well-being

The innovative cattle weaner can be attached and secured without any aid. The ring cannot be attached too closely and injure the nasal septum.

Animals with newly attached rings start retaking food and water after a brief time because they feel no pain. Even nipple and tongue drinkers are used by the animals without problem with the Cattle Weaner SuckStop Müller. Calves can still drink from the feeding bucket. Thus there are no output losses in the herd.





Ref. no.	Material	Colour	Suitable for	MOQ	Pieces / unit	Ø	€
13140	Plastic	transparent	Calves, Young cattle	6 pieces	6 / pack	1/6/210	
13140/2	Plastic	transparent	Calves, Young cattle	1 blister pack	2 / blister pack	1/105	
13141	Plastic	yellow	Young cattle, Livestock	6 pieces	6 / pack	1/6/210	
13141/2	Plastic	yellow	Young cattle, Livestock	1 blister pack	2 / blister pack	1/105	
13142	Plastic	white	Livestock	6 pieces	6 / pack	1/6/210	
13142/2	Plastic	white	Livestock	1 blister pack	2 / blister pack	1/105	

## Weaning Supplies

Ŧ

## **Taming Aids**

## Cow Immobiliser FlexCow

This cow immobiliser developed together with farmers adjust itself automatically and continuously to nearly all cattle sizes thanks to the spring mechanism, thus applying constant light pressure on the flank. It prevents a setting that is too loose or too tight, preventing the animal from either escaping or putting too must pressure on it. The cow immobiliser increases the animal's comfort level as well as the work safety at the milking station.

• Patent pending • robust design • material: Stainless steel



#### Fast and safe insertion and removal:

- 1. The cow immobiliser can be set with the lock to the widest position, so that even milkers standing lower down can apply it to the cow quickly and easily.
- 2. When the lock is released with the cable pull, the cow immobiliser automatically adjusts to the size of the cow.
- 3. To remove the cow immobiliser, pull the bracket up again all the way to the lock, then remove it from the flank and back.

packaged

unpackaged

in individual box

Ref. no.	Ø		€
110	1/10	150	

#### **Cow Immobiliser**

• when positioned correctly, this restraint prevents animals from thrashing around • adjustable for different animal sizes • the 45° offset of the hole series and the ø 9 mm thick locking bolts ensure ergonomic length adjustment and prevent inadvertent opening • marking of the long side (= bottom) with the black cap



112 in single box

Ref. no.

111

112





#### Spare Parts for Cow Immobiliser

Description

Galvanised Metal

stainless steel



240

160

€

1147 (only with 9 mm pin)

Ref. no.	Description	Material	can be used for	MOQ	Pieces / unit	Ø	€
115	Individual Replacement Cap	Plastic	all models	10 pieces	10 / pack 💙	1/10/1.000	
1147	Individual Replacement Spring (9 mm pin)	stainless steel	111, 112	10 pieces	10 / pack 🛛 🕯	1/10/1.000	
1148	Replacement Parts Kit with Spring and Cap		111, 112	1 blister pack	2 / blister pack	1	
1149	Replacement Spring Set		111, 112	1 blister pack	4 / blister pack	1	
116	Individual Replacement Spring (7 mm pin)	metal galvanised	Previous models 114, 1143	10 pieces	10 / pack 🛛 🕯	1/10/1.000	
1142	Replacement Parts Kit with Spring and Cap		Previous models 114, 1143	1 blister pack	2 / blister pack	1	
1144	Replacement Spring Set		Previous models 114, 1143	1 blister pack	4 / blister pack	1	


1/10

1/10

## **Taming Aids**

## Kick Stop Amerika for cows

• prevents kicking, even on particularly stubborn animals • indispensable during examinations, medical treatments and artificial insemination




## **Supporting Breeding Equipment**

#### Ruminal magnets - for effective prevention of disease from foreign bodies.

Foreign bodies hidden in feed, such as nails, wires and metal splinters, represent a major risk to cattle because they are non-selective when eating: they get into the reticulum where they can bore through the stomach wall due to the reticulum contractions required for mixing and further transport of the food. This usually results in an infection of the abdominal cavity followed by an inflammatory response. The organs surrounding the reticulum can also be traumatised by this.

The early administration of a magnet to a cow suspected of having a foreign body can lead to recovery of the animal within two to three days. If the animal is not treated, the foreign body can migrate and cause peritonitis, which can lead to a total loss of the animal. Even the preventative administration of a magnet has proven successful.



Ref. no.	Colour	Material	Length	Ð	€
2129	green	stainless steel	53 cm	1/30	
2139	green	stainless steel	70 cm	1/30	

## **Cattle Halter**

## Cattle halter in top quality

#### Halter

• extraordinary quality for the toughest demands • made from skin-friendly material • with adjustable head and nose band • leather-reinforced • with oval link and D-ring • with crenellated pattern • with simple round buckle





12501

Ref. no.	Colour	Suitable for	Ø		€
12515	olive green / black	Calves	1/10	500	
12501	olive green / black	Cattle, Young bulls	1/10	750	

Made in Germany

Made in Germany

Made in Germany



GE7



Ŧ





Ш

## Cow Halter with curb chain

• extraordinary quality for the toughest demands • made from skin-friendly material • with adjustable headband and curb chain that can be tightened for controlled guiding of the animal • leather-reinforced • with sturdy fittings

• with crenellated pattern • with simple round buckle

Ref. no.	Colour	Ē		€
125010	olive green / black	1/10	500	

## **Bull Halter**


• made from heavy, very resistant leather • double layer • stable fittings

• with simple round buckle • Material: Leather

Ref. no.	Colour	Ø		€
12510	light green	1/20	80	


## **Bridle**

• doubly adjustable • with simple round buckle





## **Top quality connection**



Ref. no.	Collar	Tether Part		Lii	nk thickness	Ð	€	1
125303	100 x 4 cm	Chain Component	Single with swivel and toggle		5 mm	1/10/50		_
Ref. no.	1	Description	Colour	Length	Width	Ø	€	
12508	Collar with	n oval link and D-ring	black / olive green	100 cm	4 cm	1/10		

## Chain Component for tethering calves and young animals

• all chain components galvanic zinc-plated



Ref. no.	Tether Part	Length	Link thickness	Ē	€
12462	Chain Component Single with swivel and toggle	60 cm	5 mm	1/10/50	
1238	Chain Component Single with carabiner and toggle	63 cm	5 mm	1/10/50	

## Top quality connection

		<b>Tethering</b> Tomponents galvani	Top Quality with collar c zinc-plated			1. 2		A.	GEA
k	and the	200030	and a state of the		1250		1		T
		12414	12504		1250	0	1	New York	
		L	Contraction of the		12503				
	P		12502				Anter		A
Wit	th solid	round buckles for		125251				Quality	*
stro	ong ten	sile loads		0		Made in	n Germany		-
Re	f. no.	Collar	Tether Pa	rt		Link thickne	ess 🗐	€	
12	2504	130 x 4 cm	Chain Component Double with	n carabiner and toggle		6 mm	1/10		
	2414	130 x 4 cm	Chain Component Double with sn			6 mm	1/10		
12	2500	130 x 4 cm	Floor Belt Double with ca	rabiner and rings			1/10		Ŧ
Re	f. no.		Description	Colour	Length	Width	Ø	€	
12	2502		Collar with oval link and D-ring	black / olive green	130 cm	4 cm	1/10		
	2503		or Belt double with carabiner hook		60 cm		1/10/60		
12	5251	Floo	r Belt double with small safety lock		60 cm		1/10/50		

# Chain Component for tethering cattle • all chain components galvanic zinc-plated



Ref. no.	Tether Part	Length	Link thickness	Ø	€
12509	Chain Component Single with carabiner and toggle	66 cm	6 mm	1/10/40	
12505	Chain Component Double with carabiner and toggle	70 cm	6 mm	1/10/20	
12528	Chain Component Double with small safety lock and toggle	82 cm	6 mm	1/10	

## **Top quality connection**



With double roller buckle for heavy tensile loads

Top Quality

Ref. no.	Collar	Teth	Lin	k thickness	Ð	€	
12520	150 x 5 cm	Chain Component Double		7 mm	1/5		
Ref. no.		Description	Colour	Length	Width	Ħ	€
12521	C	ollar with oval link and D-ring	black / olive green	150 cm	5 cm	1/10	



Made in the EU

16366

GE/

Ŧ

#### **Hoof Cutting Disc ProTrim**

Our new Cutting Disc ProTrim offers you an innovative tool for professional hoof care. This cutting disc specially developed for hoof care will win you over with its excellent cutting ability, its clean cut surfaces and its excellent handling properties.

• excellent handling of the sole of the hoof and the interdigital space • the very clean cutting are does not require any additional treatment • its light weight and systematic arrangement of the blade ensure even lower operating noise • its closed edge limits shavings being thrown out and reduces the risk of injury to the animal and the user • incl. 6 replaceable hard metal reversible blades • 4-sided, usable reversible blades ensure an optimal price-performance ratio • easy handling due to quick release screw connection, among other things • Material: Aluminium

					1	6367
Ref. no.	Ø	Cutting height	€ €	I		
16366	114 mm	2 mm	1/30			3
Ref. no.	Descriptio	n MO	Q Pieces /	unit	€	
16367	Blade Set	: 1 pa	ck 10/pa	nck 1/10	)	-

#### **Hoof Cutting Disc**

the base body of the blade is made from aluminium, providing for easy handling • low weight ensures even greater smoothness
the diagonal angle of the cutting elements means the horn is removed faster and more gently • the very clean cutting are does not require any additional treatment • The cutting elements can be used on both sides (blades can be turned round) • can be replaced individually • easy handling due to quick release screw connection, among other things • Cutting height: 1.2 mm (1.8 mm with guard)
Material: Aluminium

			2/05 b	SIGNUM TEST restanden		00	16316
Ref. no.	Description	Ø	MOQ	Pieces / unit	Ð	€	
16318	6 Cut	120 mm	1 blister pack	1 / blister pack	1/50		
16316	3 Cut	120 mm	1 blister pack	1 / blister pack	1/50		Top Seller
Ref. no.		Descriptio	on		Ð	€	Made in Germany
16320	Blade	Set Profi (3 blad	les and screws)		1/25		Made in Gennally

16318

## **Hoof Cutting Disc P6**

the optimised geometry and arrangement of the blade set enable excellent handling of the soles of the hoof and the interdigital space the P6 thus has the significant advantage that no other hoof care tool is necessary

complete base Disc: quieter operating noise and reduced vibrations increased the Disc's service life • inclined contact surface: perfect handling and high ergonomic efficiency • Carbide blade made from the finest grain alloy with improved durability allows the processing of up to 600 pairs of hooves (prerequisite: no stone inclusions!)
 cutting geometry: optimised position of the blade for the cleanest cut and 40 % faster cutting than with regular discs • Material: metal

Developed with professional hoof trimmers!								
Ref. no. Colour Ø Cutting height 🛱 €								
16358	red	~ 105 mm	1,5 mm	1/50	-			
16360	1/50							



## Hoof Cutting Disc SuperProfi

#### Developed with hoof trimmers for hoof trimmers and experienced farmers!

Directly soldered carbide blades on a compact 90 mm metal disc with optimised radii provide excellent abrasion, very good handling characteristics and low vibration! The cut material is removed gently and quickly by the disc using specially shaped recesses without accumulation.

• the radial extension of the carbide tips allows experienced users to work on defective points in the claw wall, permitting hollow grooves to be made • conical design of the body back, permitting good entry into the ga the pro

Ref. no.     Colour     Ø     Cutting height     €       16309     blue     90 mm     3 mm     1/50	
Made in Germany	
the processing of up to 1,500 pairs of hooves (prerequisite: no stone inclusions!)	

16359

 hoof p value for money • incl. instructions

Ref. no.	Ø	Grain on the front	Grain on the back	Design	MOQ	Pieces / unit	Ø	€
16348	115 mm	30		one-sided	1 blister pack	1 / blister pack	1/50	
16349	125 mm	30		one-sided	1 blister pack	1 / blister pack	1/50	
16359	115 mm	30	30	both sides	1 blister pack	1 / blister pack	1/50	

lop

#### **Hoof Abrasive Disc wide**

• hoof plate made of twisted steel dish with carbide assembly • excellent value for money

• incl. instructions

Ref. no.	Ø	Placement	Grain on the front	Design	Ø	;
16377	115 mm	wide	40	one-sided	1/50	
16353	125 mm	wide	40	one-sided	1/50	
16354	150 mm	wide	40	one-sided	1/50	



16359

Reverse

#### **Hoof Abrasive Disc**

• for one-handed angle grinders • wavy surface structure • for grinding and cleaning hooves and claws . Long service life

#### Beim Arbeiten unbedingt einen Stützteller verwenden!

Ref. no.	Ø	MOQ	Pieces / unit	Ð	€
1627	115 mm	5 pieces	5 / pack	1/5/200	
1627/2	115 mm	1 blister pack	2 / blister pack	1	
1631	127 mm	5 pieces	5 / pack	1/5/200	
1631/2	127 mm	1 blister pack	2 / blister pack	1	
1633	178 mm	5 pieces	5 / pack	1/5/100	



GE/

Ŧ

## Hoof and claw knife SuperProfi

The knife for the professional hoof trimmer and farrier as well as for anyone who needs a perfect tool for hoof and claw care!

• high alloy special steel for long life and grindability • 0° scalpel cut for exceptional sharpness and cutting performance • ergonomic handle made from heat-treated beech wood



#### Hoof and claw knife Profi

• made from high-quality special steel developed for cutting tools • improved cutting performance • optimised grinding properties • revised blade radius for more precise working · ergonomically shaped noble wood handle for fatigue-free working



Made in the EU

Top Seller

Ref. no.	Length	Cutting side	Blade length	Blade width	Cutting edge length	MOQ	Pieces / unit	Ø	€
16801	20 cm	single-edge right	82 mm	11 mm	71 mm			1/10/200	
16801/1	20 cm	single-edge right	82 mm	11 mm	71 mm	1 blister pack	1 / blister pack	1	
16802	20 cm	single-edge right	80 mm	17 mm	70 mm			1/10/200	
16803	20 cm	single-edge left	82 mm	11 mm	71 mm			1/10/200	
16803/1	20 cm	single-edge left	82 mm	11 mm	71 mm	1 blister pack	1 / blister pack	1	
16804	20 cm	single-edge left	80 mm	17 mm	70 mm			1/10/200	
16805	20 cm	double-edged	80 mm	17 mm	70 mm			1/10/200	
16805/1	20 cm	double-edged	80 mm	17 mm	70 mm	1 blister pack	1 / blister pack	1	

16803

16801


16805

#### Hoof and claw knife

- inexpensive tool with excellent cutting and sanding properties
- blade made from rust-free steel with moulded wooden handle



Ref. no.	Length	Cutting side	Blade length	Blade width	Cutting edge length	Ø	€
16163	21 cm	single-edge right	83 mm	11 mm	69 mm	1/10/200	
16164	21 cm	single-edge left	83 mm	11 mm	69 mm	1/10/200	
16160	21 cm	double-edged	85 mm	12 mm	48 mm / 68 mm	1/10/200	



Made in Germany

GE/

#### **DICK Chopping Blade**

- Hatchet-Shaped Chopping Blade specially sharpened cutting edge
- high-quality, rust-free carbon steel with "softgrip" PVC handle

Ref. no.	Length	Blade width	Ø	€
1657	36 cm	3,1 cm	1/10	

## **Chopping Blade with handle**

• whetted • Material: stainless steel

Ref. no.	Length	Blade width	Ð	€
1615	30 cm	3 cm	1/10/60	

## **DICK Shoeing Mallet**

• robust design

Ref. no.	Material	Length	Ø	€
32670	Beechwood	30 cm	1/25	

#### **KNIPEX Hoof Pliers**

 $\bullet$  with rivet joint  $\bullet$  can also be used as farrier's tongs  $\bullet$  Cutting edge hardness approximately 56 HRc  $\bullet$  Special tool steel, oil-hardened

Ref. no.	Length	Ø	€
1618	30 cm	1/6	

## **Hoof pliers**

• robust design

Ref. no.	Length	Ð	€
16182	36 cm	1/5/25	

#### **Hoof-Checking Pliers**

• forged steel • with straight legs

Ref. no.	Length	Ð	€
1619	30 cm	1/6/30	

#### **Shoeing Hammer**


• forged design • with steel-reinforced wooden handle

Ref. no.	Length	Ē		€
1650	33 cm	1/12/48	240	

#### Hoof Nail Clinch

• for pulling hoof nails

Ref. no.	Length	Ē	€
1666	35 cm	1/6/36	







#### Hoof Shoe Tubbease™

Tubbease<sup>TM</sup> was developed in New Zealand with the aim to create a breathable treatment shoe for problem horse hooves (e.g. sole ulcers). The supplied hook and loop tapes mean Tubbease<sup>TM</sup> is easy to attach to the horse's leg.

can escape upwards meaning no heat or humidity is trapped within the shoe • the rubber-coated base reliably prevents moisture from entering and simultaneously ensures that the treatment fluid remains on the hoof • the optimum climate within the shoe means the hoof retains its natural strength
the thick EVA insole reduces pressure pain for the horse (e.g. with sole ulcers) and extends the life of Tubbease™ • various remedies to treat abscesses, thrush, hoof injuries, hoof outbreaks etc. can be used with Tubbease™ • tubbease™ design is protected (NZ 417646) • Important: only use during stall rest • EVA insert not included

Ref. no.	Colour	Size	Ø	Ð	€
3211765	purple	XS	7,5 cm	1/8/48	
3210559	pink	S	11 cm	1/8/48	
3210560	red	М	14 cm	1/8/48	
3210561	blue	L	15,5 cm	1/8/48	
3210562	orange	XL	16,5 cm	1/8/48	
3210596	yellow	XXL	17,5 cm	1/8/48	

Ref. no.	Description	Colour	Size	Ð	€
3211766	EVA Insert Tubbease™	purple	XS	1/2/80	
3211767	Hook and Loop Fastener in pairs	purple		1/40	
3210595	EVA Insert Tubbease™	pink	S	1/2/40	
3222300	Hook and Loop Fastener in pairs	pink		1/40	
3210564	EVA Insert Tubbease™	red	М	1/2/24	
3222301	Hook and Loop Fastener in pairs	red		1/40	
3210565	EVA Insert Tubbease™	blue	L	1/2/24	
3222302	Hook and Loop Fastener in pairs	blue		1/40	
3210566	EVA Insert Tubbease™	orange	XL	1/2/20	
3222303	Hook and Loop Fastener in pairs	orange		1/40	
3210597	EVA Insert Tubbease™	yellow	XXL	1/2/20	
3222304	Hook and Loop Fastener in pairs	yellow		1/40	



#### **SHOOF Hoof Shoe**

• made from sturdy, durable polyurethane • this hoof shoe was developed as an aid for the worldwide problem of repairing damage (injuries) to cattle hooves • ideal for high stress on hooves on hard surfaces such as concrete floors, hoof rot, twisted toes, damage caused by natural malformation, cuts to the sole due to sharp stones etc. • reduces the penetration of dirt and bacteria • prevents infectious diseases • polyurethane

Ref. no.	Colour	Size	Design	Ø	€
16501	yellow	Μ	both sides	1/25/100	
16505	yellow	М	right	1/10/100	
16509	yellow	М	left	1/25/100	
16502	blue	L	both sides	1/80	
16506	blue	L	right	1/20/80	
16510	blue	L	left	1/20/80	
Ref. no.		Descriptio	n	Ø	€
16520		Spare Set for	1/20/400		

#### Treatment Shoe for hooves and claws

Durable and robust treatment shoe made of canvas with two bands. Ideal for treating horse or cattle hooves with ointments or solutions.

strong plastic sheet on the inside to allow the treatment solution to work effectively
Standard size (15 x 30 cm)

Ref. no.	Length	Width	Ē	€
16143	30 cm	15 cm	1/50	



## **Hoof Bandage Vetlastic**

Specially for claw care and for self-adhesive bandages developed for veterinary use! VetLastic is characterised by a thick fabric with an enhanced latex coating, thus providing extra adhesive power! Despite the compact material thickness, Vetlastic can be easily torn laterally!

medium-elastic, self-adhesive bandage
 very hard to tear lengthwise, but easy to tear laterally
 does not stick to hair or to itself
 modern latex-reinforced high-tech synthetic material
 easy to put on, even on the most difficult places

Ref. no.	Colour	Length	Width	Ð	€
1663	light green	450 cm	7,5 cm	1/24/144	
1664	light green	450 cm	10 cm	1/18/108	
1667	blue	450 cm	7,5 cm	1/24/144	
1668	blue	450 cm	10 cm	1/18/108	
1672	black	450 cm	7,5 cm	1/24/144	
1673	black	450 cm	10 cm	1/18/108	
1675	red	450 cm	7,5 cm	1/24/144	
1676	red	450 cm	10 cm	1/18/108	



Especially recommend for winter due to enhanced latex coating! Recommended by hoof care professionals!

This product was specially developed to treat large animals and is only for use in veterinary medicine/hoof and claw care.

#### Self-adhesive Bandage EquiLastic

• highly-elastic, self-adhesive bandage • very hard to tear lengthwise, but easy to tear laterally • does not stick to hair or to itself • easy to put on, even on the most difficult places • Year-round bandage for support and other dressings.

Ref. no.	Colour	Length	Width	Ø	€
1685	red	450 cm	5 cm	1/12/288	
1687	red	450 cm	7,5 cm	1/12/192	
1694	red	450 cm	10 cm	1/12/144	
1683	blue	450 cm	5 cm	1/12/288	
1688	blue	450 cm	7,5 cm	1/12/192	
1695	blue	450 cm	10 cm	1/12/144	
1686	black	450 cm	5 cm	1/12/288	
1689	black	450 cm	7,5 cm	1/12/192	
1697	black	450 cm	10 cm	1/12/144	
16551	violet	450 cm	5 cm	1/12/288	
16553	violet	450 cm	7,5 cm	1/12/192	
16555	violet	450 cm	10 cm	1/12/144	
16550	green	450 cm	5 cm	1/12/288	
16552	green	450 cm	7,5 cm	1/12/192	
16554	green	450 cm	10 cm	1/12/144	
1684	white	450 cm	5 cm	1/12/288	
1690	white	450 cm	7,5 cm	1/12/192	
1692	white	450 cm	10 cm	1/12/144	



The optimal summer bandage for claw care!

This product was specially developed to treat large animals and is only for use in veterinary medicine/hoof and claw care.

#### Bandage Knife



Ŧ

# Technovit 6091



The special properties of fast-curing plastic Technovit 6091 make it an indispensable, universal resin used in veterinary medicine for claw care and treatment. In some areas of treatment, Technovit 6091 aids the vet's therapeutic measures and shortens otherwise quite long healing periods. In claw and hoof treatment, Technovit 6091 is especially suitable for the following: for immobilizing claws in the event of inflammatory diseases, fixing claw tips, concealing hoof defects, horn cracks, shaping hooves and orthopaedic hoof treatment, especially in foals (e.g. clubfoot, prosthesis).

#### Technovit<sup>®</sup> 6091

#### The indispensable universal tool for claw treatment

• the classic claw treatment system! • the market-leading system for claw immobilisation through wood blocks used and approved for more than 15 years!

16220: Powder has already been packaged in 12 bags of 70 g each!

#### Technovit® 6091 with catalyst

• low outside temperatures generally lengthen the curing time of glue in claw treatment systems with wood blocks or shoes • The unique advantage of the Technovit catalyst is its ability to shorten this polymerisation time by up to 50 % • A problem-solver for colder months

Temperature	Recommended Mixture ratio Catalyst: Liquid	Curing time with catalyst Curi		Curing	time without catalyst	
+ 5 °C	1:7	Approx. 13 min.			Approx	x. 24 min.
+ 10 °C	1 : 10	Approx. 9 min.			Approx	x. 15 min.
+ 20 °C		Approx. 5 min.			Approx	x. 8 min.
Ref. no.	Description	Applications		Ē	€	
1621	without accelerator	2-pce mix		1/100		
1622	without accelerator	10-pce mix		1/6		
16220	without accelerator	12-pce mix		1/6		
16121	incl. accelerator	2-pce mix		1/100		
16122	incl. accelerator	10-pce mix		1/6		
Ref. no.	Description	Co	ontents	Ø	€	
16232	Accelerator Technovit <sup>®</sup> 6091			1/120		
1623	Powder Technovit <sup>®</sup> 6091	1	1000 g	1/70		Please note the use and safety
1624	Liquid Technovit <sup>®</sup> 6091	5	500 ml	1/144		instructions.

mended by hoof ofessionals!

Contents

500 ml

1000 g

Æ

1

1/70

1/100

ŧ

#### Technobase 8000

#### Universal plastic for veterinary medicine

• rapid processing: can be modelled immediately after mixing • Technobase 8000 cures fully in less than 4 minutes at 20 °C product temperature • highly adhesive so you can be sure that the diseased claw will be perfectly spared until the wood block has worn off • models without becoming sticky: the dough remains flexible and can be shaped and processed until polymerisation • low temperature at the end of polymerisation, therefore extra-cutaneous splinting can be performed safely and without affecting the tissue

Ref. no.	Applications	Ð	€	recomm
16251	14-pce mix	1/6		care pr
16259	4-pce mix	1		

Description

Liquid for Technobase 8000

Powder for Technobase 8000

Wooden Spatula for Technobase 8000



	NUM St
12/04 besta	nden

Please note the use and safety instructions.

Ref. no.

16257

16258

16231

## Hoof Block HoloBlock

• made from wood fibres • biodegradable material • patented shape • nubs on the surface ensure optimal spacing between the claw and the block • glue forms a stable structure via integrated holes on the surface and honeycomb hollow spaces • very strong adhesion and no unnecessary use of glue • hollow spaces enable easy and effective heating of the glue • ideal for treatments with a quick healing process



GE#

1

Ŧ

Ref. no.	Length	MOQ	Pieces / unit	Ø	€
16136	114 mm			1/250	
16137	114 mm	1 pack	10 / pack	1/30	

#### Wooden Block Wedge shape

- · recommended for low heel height to increase the ball area
- also suitable for "normal" hooves on highly abrasion-resistant floors (such as concrete)



recommended by hoof care professionals!

Ref. no.	Description	Length	Ð	€
16132	Standard	112 mm	1/50	
16133	XL	130 mm	1/50	

## Wooden Block flat design

• extra flat design (50% lower in height than a standard block) for uses requiring early loading of the injured hoof • prevention of any tendon problems that may occur if the block is worn for an extended period • mainly used for low-wear rubber flooring instead of standard blocks • developed in line with the latest hoof care theory with hoof care specialists

Ref. no.	Length	Ð	€
16134	112 mm	1/50	
16135	130 mm	1/80	

## Wooden Block Standard





€
-

#### Technovit®-2-Bond

#### The fast, 2-part PU adhesive for hoof treatment!

• The benefits at a glance: • dries within 30 seconds • can be used at a 45° and a 90° angle • the hoof can bear full weight again after approx. 3 minutes (if stored correctly over 15° C) • bonds powerfully and permanently to wood and rubber blocks • easy to use - no mixing, no waste







Set includes:	16239	16240
1 x 160 ml cartridge with 2-part adhesive	Х	х
10 x mixing tips	Х	Х
10 x wooden blocks XL	Х	Х
1 x dispensing gun	Х	-



Please note the use and safety instructions.

Ref. no.	Description	Applications	5	Ø	€		
16239	Starter Set with Dispensing Gun	10-pce mix		1			
16240	Set without dosing gun	10-pce mix		1			
Ref. no.	Description	Contents	MOO	Pieces / unit	Æ	€	
16241	Cartridge Technovit®-2-Bond	160 ml / Cartridge	MOQ	rieces / unit	1/10	t	
16292	Dispensing gun for Technovit-2-Bond for 160 ml cartridge	100 mil / Cartiluge			1/10		_ N
16243	Mixer Cannula for Technovit-2-Bond		1 pack	10 / pack	1/10/240		_

New product

GE#

Ŧ

NEW

## Block Bond Eco®

#### 2-component latest generation claw adhesive

The two-component polyurethane adhesive Block Bond Eco® has been specially developed for hoof care and the safe and rapid gluing of wooden blocks with bovine hooves. Block Bond Eco® guarantees that the block adheres firmly to the hoof, giving the hoof enough time to completely heal. The main advantage is the high strength and the speed of application. The patented Block Bond Eco® formula has no carcinogenic ingredients at all. This makes Bond Eco® one of the most user and cow-friendly hoof adhesives on the market. The increased efficiency in hoof care, easy and fast application and the optimal cow healing support is of particular note in this new adhesive technology.

#### Experience the advantages of the latest generation of hoof glue Especially fast

- · Makes your work really efficient.
- Processing time: 10 s / fixture time: 20 s / time to full load: 1:30 3:30 min. depending on outside temperature.

#### **Especially strong**

- Exceptionally strong, permanent bonds.
- Highly reliable bond while healing takes place.

#### Especially safe

- No carcinogenic hazardous substances in the formula.
- High health protection for users and cows.

#### Fresh, premium quality

- German manufacturer. The latest scientific research.
- High quality. Fresh product. Highly durable.

#### Summer & winter

- Suitable for all seasons, from 0 °C to +30 °C.
- No crystallisation at subzero temperatures.



16297

BLOCK BOND



#### **Thermal Container HeatBox**

The solution to problems using two-component adhesives for hoof care in winter! HeatBox is the perfect way to keep two cartridges at the correct temperature during use in stables, thanks to the temperature-critical property of its chemistry.

 one heat chamber each for cartridges in the pistol and for spare cartridges • fits all common 200 ml cartridges such as Technobase 2CB
 constant temperature in the chamber of 20 °C thanks to integrated thermostat • Control light to check the power supply • incl. metal bracket for attaching to the hoof stand or bar/tube • with vehicle plug and power pack for connection to a 230 V power supply • suitable dispensing guns: item no. 16299, 16284, 16242, 16292

	20 1710	roffer <sup>®</sup> normal farming
New p	oroduct	NEW

#### **Hoof Care Walkease**

Colour

grey

Technical data

**Connecting Cable** 

Protection class

Ref. no.

16279

Voltage Mains frequency

#### For rapid intervention in case of hoof problems

The novel combination of EVA hoof block and secondary adhesive makes hoof care very easy

12 V DC

IPX4

Heating output

30 W

50 - 60 Hz

Length

17 cm

• extremely quick - the hoof can take weight again after 10 seconds • extremely economical - small amounts of gluten are enough for a secure grip

Width

12 cm

Ħ

1/12

€

INSTRUCTIONS FOR USE

walkease

QA

Height

17,5 cm

WALKEASE GLUF

• extremely comfortable - no mixing of liquids and powders • extremely easy - work the cleaned hoof with a special hoof rasp - glue to block - press for about 10 seconds, and you're done!

The hoof block is available in 4 sizes; special material absorbs the hoof impact and enables uniform wear.

The special angled 'Wedgy' block (16488) is modelled on the latest findings on hoof rest positions to protect tendons and ligaments and to allow correct wear, especially on rough ground.

Included in delivery: 10 x hoof blocks, 1 x adhesive (10 x 2 ml), 1 x rasp, 1 x disposable gloves, 1 x instruction manual and DVD

Important: The cleaned hoof must be properly prepared with the Shoof hoof rasp to produce perfect adhesion! The hoof and hoof block must be clean and dry!

Ref. no.	Colour	Size	Applications	Ð	€
16481	yellow	Μ	10-pce mix	1/12	
16482	blue	L	10-pce mix	1/12	
16489	mixed	S/M/L	10-pce mix	1/12	

Ref. no.	Description	Size	Contents	MOQ	Pieces / unit	Ø	€
16483	Hoof Block Walkease	S		1 pack	10 / pack	1/10	
16484	Hoof Block Walkease	М		1 pack	10 / pack	1/10	
16485	Hoof Block Walkease	L		1 pack	10 / pack	1/10	
16488	Hoof Block Walkease "Wedgy", angled large			1 pack	10 / pack	1/10	
16486	Adhesive Walkease		2 ml	1 pack	10 / pack	1/10/120	
16487	Rasp Walkease					1/50	

## Kromberg Hoof Bandage

• for bandaging and application of protective bandages

Ref no	Colour	Length	Width	MOO	Pieces / unit	Æ	£
					5 / pack		L.

#### **Certoplast Hoof Bandage**

• for bandaging and application of protective bandages • Type Certoplast/Vorwerk

Ref. no.	Length	Width	MOQ	Pieces / unit	Ð	€
16381	25 m	45 mm	5 pieces	5 / pack	1/5/60	

#### Hoof Bandage ClawTape

• Textile Strip for Hoof Care • for bandaging and application of protective bandages

• with high-quality natural rubber adhesive • high adhesion • adhesive on both sides

· simple to use and easy to tear by hand

Ref. no.	Colour	Length	Width	Ð	€	
16378	black	25 m	45 mm	1/5/60		Available from: April 202

#### Tesa Hoof Bandage

 $\bullet$  Woven Cotton Tape  $\bullet$  air permeable and adhesive on one side (meaning no straw etc. sticks)

Ref. no.	Colour	Length	Width	Material thickness	MOQ	Pieces / unit	Ð	€
16382	black	50 m	50 mm	0,3 mm	3 pieces	3 / pack	1/3/18	

#### Hoof Bandage VetTape

• with strong rubber adhesive • adheres securely • tried and tested for hoof bandages • air permeable

Ref. no.	Colour	Length	Width	Ð	€
16388	white	50 m	50 mm	1/12	
16390	black	50 m	50 mm	1/12	

#### Hoof Bandage Silbertape

• watertight design (suitable for pens) • excellent tear resistance • very good adhesive properties • easy to use

Ref. no.	Colour	Length	Width	Ð	€
16385	silver	50 m	50 mm	1/24	

#### Adhesive Tape

high-quality, PE-coated industrial adhesive tape coated with natural rubber glue
 has an excellent initial bonding force - even at low temperatures
 excellent bonding to different surfaces
 excellent unrolling behaviour
 Areas of application:
 Hoof Care
 repairs, water-proof packaging
 Protection, Covering, Fixing
 labelling, packaging, bundling
 Tear resistance:
 180 N/25 mm
 Bonding force on steel:
 15 N/25 mm

Ref. no.	Colour	Length	Width	Ð	€
291335	black	50 m	19 mm	1/60	
291336	black	50 m	50 mm	1/24	

# Hoof and Claw Care



## Footbath Container SuperKombi

The Footbath SuperKombi can be connected both lengthways and sideways. Depending on the space available in the stable, this means you can create ideal situations for the cows. The consecutive baths ensure better hygiene: The first bath serves as a rinse to get rid of dirt and faecal residues from the hooves. The second bath, the hoof hardening bath, thus remains free of dirt for longer, the disinfection solution remains usable for longer. The newly developed base profile ensures optimal traction. The animals go through the hoof bath more calmly, which promotes longer contact, achieving a better result. The shape and height of the profile ensure that the cow's hoof is slightly spread, allowing the hoof bath to reach areas between claws where it will be most effective more easily.

expandable length or width-ways
high impact polyethylene for abrasion and chemical resistance
suitable for use with all types of hoof bath solutions
With gauge display
Material: polyethylene



Footbaths can be lined up one after another TV using the teeth Base with special nub provided With gauge display profile 16601 specially designed anchor points make it easy to line up additional containers Ref. no. Colour Width Capacity Length Height Ħ € F 200 L 16603 black 203 cm 83 cm 18,5 cm 25 A 1 Ħ Ref. no. Description € Outlet for footbath / water trough 16601 1/100

#### **Hoof Mat Standard**

• for claws • without sleeve

Ref. no.	Colour	Length	Width	Height	Ø		€
16416	blue	180 cm	90 cm	4 cm	1	25	
					_		
Ref. no.		Description	<u> </u>	€			
16414		Cover	1				

## **Disinfection Mat**

 for use at entrances to stables vulnerable to disease
 the sturdy, permeable upper material allows liquid to penetrate to the core
 impermeable material on the bottom and on the side prevents fluid loss



Ref. no.	Colour	Length	Width	Height	Capacity	Ē		€
16418	blue	45 cm	45 cm	3 cm	6 L	1/20	100	
16413	blue	85 cm	60 cm	3 cm	8 L	1	100	

# **Disinfection Care Products**


GE#


## **Powder Disperser**

specially developed for hygienic litter powder like Seche-etable stable drying agent or lime • suitable for all common screwdrivers (min. 600 rpm, 13 mm chuck)
the bedding material is evenly distributed in the stalls, saving you a lot of bedding products • adjustable dispenser opening for precise dosage of lime/powder • highly productive: 120 boxes of 100 g powder each with one filling • Filled weight: 8 - 10 kg
Material container: LDPE • with carrying strap

y distributed in the stalls, saving you a lot of bedding r opening for precise dosage of lime/powder • highly powder each with one filling • Filled weight: 8 - 10 kg ith carrying strap	1
	<b>1</b>
Vink SPREADES	×
	+
	¥

Ref. no.	Colour	Max. fill level	Weight	Ø	€
291910	blue	12 l	3 kg	1	





#### Top-quality cattle brushes

Cows have a need to rub and scratch themselves. This is how they clean themselves and rid themselves of parasites, lichens and mites. Brushing stimulates and encourages blood circulation. The use of a cow cleaning machine or cattle brush helps considerably to improve the cow's welfare and is therefore essential for a high milk yield. The animals are calmer and their well-being is increased.

Our electric cattle brushes are easy to assemble. A sensor prevents tail hair from getting pulled in. All frame parts are zinc-plated and have been tested in pens under the toughest conditions. In addition, the Duo and Swing Brushes have intelligent control and a display. The extensive

user guide included with every machine contains all the key information on how to put together, maintain and troubleshoot the equipment.

Electric cattle brushes are virtually maintenance-free. The lubrication of pressure points and the prompt replacement of brush rollers extend service life and attractiveness to animals.



#### **Cattle Brush HAPPYCOW Duo**

With the fully automatic Cow Cleaning Machine HAPPYCOW Duo, the cow is happy, willing and fully independently able to wash itself. The animals feel very happy with the 2-brush machine, and it is interesting to see how extensively they brush and massage themselves. The large brushes and massaging action encourages the circulation in the skin and stimulates the metabolism. Milk output is improved and increases the frequency of ,in heat' periods.

• high-quality polyamide brushes ensure a long service life • newly developed electronics for fault-free and low-maintenance operation

flexibly installable control unit in spray and dust-proof casing (IP 56)
informative display for status information • variable setting options for brush running time (7.5 - 120 s) • alternating direction of brush movement after each activation (60 s) ensures even wear on the bristles

optimised brushes ensure that animals are happy to use them

permanent lubrication over the gears' entire service life • safety

switch-off (torque dependent) • plug ready for connection to 230 V socket

Technical data	18820
Voltage	230 V
Mains frequency	50 Hz
Power	370 W
Speed	60 rpm
Weight	140 kg
Protection class	IP56
Bristle material	Polyamide

The cow is cleaned on the head, neck, back, torso and side



Ref. no.	Colour	Width	Depth	Height	Ø brush		€		ти	
18820	red / blue	40 cm	105 cm	115 cm	31,5 - 42 cm	1		<b>•</b> •		
Ref. no.	Descri	ation	Material		suitable for			Æ		£
18821	Spare Bru		Polyamide	НарруСоу	v Duo, Kerbl; Schur	r; Krazzma	хх	1	24	Ľ
18822	Spare Brus	h below	Polyamide	117	/Cow Duo, Kerbl; Ki			1	36	
18824	Spare Brus	sh below	Polyamide		Schurr (> 2008)			1	36	

GE/

潦

Ŧ

(---7



#### **Cattle Brush HAPPYCOW Swing**

The special arrangement of the CowCleaner Swing brushes in a vertical, swinging direction makes cleaning the coat easier from head to tail. The brush rotates in every direction and nearly every angle, so each part of the animal's body (head, torso) can be reached. It can be fastened on both sides ensuring even use of the brushes. • furthermore, there is no risk of jumping up as with horizontal brushes!

• the HAPPYCOW Swing is automatically activated for approx. 60 seconds by the animals slightly lifting the brush • the changing direction of the brush after ever activation ensures even wear of the brushes • the torque safety shutdown stops the brush when it encounters too much resistance, ensuring safety in the stable • sturdy motor/powertrain for maximum loads • transparent cover to the control box for quick identification of the operational status on the display • Material: metal galvanised

Technical data	18880
Voltage	230 V
Mains frequency	50 - 60 Hz
Power	550 W
Speed	50 rpm
Weight	93 kg
Protection class	IP55
Bristle material	Polypropylene

Ref. no.	Width	Depth	Height	Ø	Ħ	€	
18880	50 cm	135 cm	198 cm	1	6		<b>. .</b>
Ref. no.		Description				€	
18881	Bru	sh for HAPPYCOW Sv	ving	1	6		<b>. .</b>

ΤV

cleaned due to the vertical, oscillating shape



## Scratch Brush HAPPYCOW MiniSwing

#### for calves, goats and pigs

The HAPPYCOW MiniSwing automatic scratch brush rotates in any direction and almost every angle. The vertical pendulum brush reaches almost any body part, head and rump especially are thoroughly cleaned. The HAPPYCOW MiniSwing scratch brush is suitable for calves from 3 months of age, adult goats and breeding sows. One brush is designed for max. 40 calves or max. 60 goats and breeding sows.


the HAPPYCOW MiniSwing is automatically activated for approx.
 seconds by the animals slightly lifting the brush • the changing direction of the brush after ever activation ensures even wear of the brushes • the torque safety shutdown stops the brush when it encounters too much resistance, ensuring safety in the stable
 Material: metal galvanised

Technical data	18890
Voltage	230 V
Mains frequency	50 - 60 Hz
Power	250 W
Speed	27 rpm
Weight	48 kg
Protection class	IP54
Bristle material	Polypropylene

Ref. no.	Colour	Width	Depth	Height	Ø		€	
18890	red / blue	30 cm	80 cm	125 cm	1	8		<b>P</b>
Ref. no.	Description						Ø	€
18891		Brush for	HAPPYCOW Minis	wing			1	

#### Scratch Brush

• ensures ideal fur cleaning and care • head and throat in particular can be cleaned • suitable for cattle and calves, horses, goats etc. • various mounting options (walls, corners, stables, posts) • Bristle material: Polyamide • Bristle length: 5 cm





32678

32689

a like the ball down

ANNA TEAMA

GE/

6

Ŧ

#### Scratch Mat

• made from natural rubber material • mobile and soft nubs provide optimum coat care without risk of skin irritation • rectangular shape with many mounting holes for stable mounting • multi-functional applications such as flat on the wall or around pillars, posts or corners



Ref. no.	Colour	Length	Width	Ø	€
32678	black	40 cm	30 cm	1/12	
32689	black	60 cm	40 cm	1/6	

#### **Cattle Brush Texas**

• stable design with built-in spring • Horizontal brush movable in all directions

Ref. no.	Brush length	Brush width	Ø	Ħ	€		
29310	50 cm	10 cm	1	24			
Ref. no.	Description	n	Length	Width	Ø		€
29305	Spare Brus	h	50 cm	10 cm	1/2	200	
6033	Spring for Texas ca	ttle brush			1	180	

## **Cattle Brush**

• complete with spring • the especially robust design of this brush ensures a high level of user comfort • animals of various sizes can properly scrub themselves • the enormous flexibility even stands up to extraordinary loads (e.g. jumping animals) • special Nylon bristles for fur cleaning and care • stable spring suspension

Ref. no.	Colour	Brush length	Brus	sh width	Ø		€
29325	blue / red	50 cm	1	10 cm	1	24	
Ref. no.	Des	cription	Length	Width	Ø		€
29302	Spare Brush		50 cm	10 cm	1/2	200	
29326	Top with spri	ng without brush			1/2	24	



# **Aesculap Clippers**

#### Aesculap Precision Adjusting Aid Torqui for cattle / horse clippers

 $\overline{}$ 

Every Econom clipping head is child's play to adjust with this torque key. • precise basic adjustment of the blade pressure • increased clipping head life thanks to longer intervals between regrinding • consistent edge-retention • easy to handle • no prior knowledge needed • small, easy to handle, maintenance-free • precision instrument engineered in Germany • suitable for all Econom cattle and horse clippers • all Econom shaving heads can be retrofitted with the knurled screw GT147





If required, the thumbscrew can be
adjusted by up to half a turn.
For the perfect shearing blade pressure!

Ref. no.	Ħ	€				
GT146	1/20/200					
Ref. no.			Description	Ø	€	
GT147		Aesculap	Knurled screw for Torqui	1/500		



# **Aesculap Clippers**

Made in Germany

GEA

A

統

+

#### Aesculap Shearing blades Econom

• very long service life thanks to wear-resistant carbon steel • cutting surfaces can be reground very often • resistant surface coating • ideal hardness thanks to vacuum hardening process • made on CNC machines, producing consistently high level of quality

Upper blade	Lower blade	Teeth	Suitable for	
GT501	GT502	15 / 31	Cattle and horses standard cut 3 mm	
GT501	GT511	15/31	Industrial cut (e.g. fur shearing)	
GT505	GT502	23 / 31	Cattle and horses – for smooth standard cut 3 mm	
GT505	GT508	23 / 51	Cattle (udder shear), horses and industrial cut (e.g. fur shearing)	
GT505	GT511	23 / 31	Cattle and horses – for very fine, smooth cut 1 mm	
GT505	GT506	23 / 23	Cattle, dogs and goats 3 mm	
GT505	GT507	23 / 21	Cattle, 3 mm	
GT505	GT510	23 / 24	Dogs and goats 5 mm	
GT503	GT504	17 / 18	Cattle, fine-wool sheep and noble sheep 3 mm	
	GT501 GT501 GT505 GT505 GT505 GT505 GT505 GT505 GT505	GT501         GT502           GT501         GT511           GT505         GT502           GT505         GT508           GT505         GT511           GT505         GT511           GT505         GT506           GT505         GT506           GT505         GT507           GT505         GT510	GT501         GT502         15 / 31           GT501         GT511         15 / 31           GT505         GT502         23 / 31           GT505         GT508         23 / 51           GT505         GT511         23 / 31           GT505         GT511         23 / 31           GT505         GT506         23 / 23           GT505         GT507         23 / 21           GT505         GT510         23 / 24	GT501GT50215 / 31Cattle and horses standard cut 3 mmGT501GT51115 / 31Industrial cut (e.g. fur shearing)GT505GT50223 / 31Cattle and horses – for smooth standard cut 3 mmGT505GT50823 / 51Cattle (udder shear), horses and industrial cut (e.g. fur shearing)GT505GT51123 / 31Cattle and horses – for very fine, smooth cut 1 mmGT505GT50623 / 23Cattle, dogs and goats 3 mmGT505GT50723 / 21Cattle, 3 mmGT505GT51023 / 24Dogs and goats 5 mm

#### Upper blade

Upper blade	● BARDCARP KK ● INT SHI	······································	AAESOLLAP & O Gr 500
	Wase in Germany	Mate in Germany	GT 503 Nati a Comay
	GT501 15 teeth	GT505 23 teeth	GT503 17 teeth
Lower blade		เสนาสนาสนาสนาสนาสนาสนา	
/www.www.www.www.	Anteria disease etc. 2 Anteria disease GT502 3,0 mm 31 teeth	Mate & Bonney etc. **#2620489 GT504 3,0 mm 18 teeth	GT507 3,0 mm 21 teeth
GT506 3,0 mm 23 teeth	GT508 0,1 mm 51 teeth	GT511 1,0 mm 31 teeth	GT510 5,0 mm 24 teeth
Ref. no. Description Shearing height U	pper blade teeth Lower blade te	eeth Shearing type	€

Ref. no.	Description	Shearing height	Upper blade teeth	Lower blade teeth	Shearing type	Ħ	€
GT501	Upper blade		15		Cattle Shearing, Horse Shearing, Standard cut	1/10/100	
GT502	Bottom blade	3 mm		31	Cattle Shearing, Horse Shearing, Standard cut	1/10/100	
GT503	Upper blade		17		Cattle Shearing, Sheep Shearing, fine-wool sheep shearing	1/10/100	
GT504	Bottom blade	3 mm		18	Cattle Shearing, Sheep Shearing, fine-wool sheep shearing	1/10/100	
GT505	Upper blade		23		Horse Shearing, Cattle Shearing	1/10/100	
GT507	Bottom blade	3 mm		21	All-round cut, Cattle Shearing	1/10/100	
GT506	Bottom blade	3 mm		23	Cattle Shearing, Dog Shearing, Goat Shearing	1/10/100	
GT508	Bottom blade	0,1 mm		51	Horse Shearing, Cattle (udder clipping), industrial shearing	1/10/100	
GT511	Bottom blade	1 mm		31	Fine Horse Shearing, Fine Cattle Shearing	1/10/100	
GT510	Bottom blade	5 mm		24	Dog Shearing, Goat Shearing	1/10/100	

# constanta Clippers

**Constanta4 clippers** Constanta clippers – developed with the aim of building the perfect clipper:

- Their weight, centre of gravity and shape have been selected to ensure that working with them is as fatigue-free as possible
- Optimised ventilation technology provides perfect cooling of the cutter head and shearing blades
- Service-friendly shell housing
- · Air filter can be replaced without tools

#### **Animal Clipper constanta4**

• the tried-and-tested motor technology gives the constanta4 tremendous tractive power • even on matted and dirt-encrusted animals the constanta4 does not "yield" • the blades glide through the most difficult of coats without loss of power





Included in delivery: 1 x animal clippers constanta4, 1 x clipper blade set, 1 x oil, 1 x screwdriver, 1 x instruction manual, 1 x Durable plastic case

Technical data	
Voltage	230 V AC
Mains frequency	50 - 60 Hz
Power	400 W
Clipper head system	Shearing Blade Set
Stroke rate	approx. 2.400 strokes/min
Sound pressure level	87 dB (A)
Cable length	3 m
Dimensions	33 x 7,8 x 9,7 cm
Weight	1.490 g without cable
Protection class	I





Ref. no.	Colour	Teeth lower/upper blade	Shearing type	Ø		€
18990	green	21 / 23	Cattle Shearing, Horse Shearing	1/8	48	
18991	green	31 / 15	Cattle Shearing, Horse Shearing	1/8	48	

# constanta Clippers


GE/

Ŧ

#### **Shearing Blade Set Premium**

- optimised blade geometry with hollowed grinding Improved grinding capacity and increased material service life for long periods of use
- Selected steel tool with special hardening suitable for constanta, FarmClipper and other common brands, such as Heiniger, Aesculap and Liscop

#### made by Aesculap



#### **Animal Clipper constanta4**

• Special clippers for cattle with difficult coat conditions • ideally suited for shearing lamas and alpacas • technology based on the Constanta4 sheep clippers

Technical data	18989
Voltage	230 V
Mains frequency	50 - 60 Hz
Power	400 W
Clipper head system	Shearing Blade Set
Stroke rate	approx. 2.400 strokes/min
Sound pressure level	87 dB
Cable length	3 m
Dimensions	34 x 10 x 6 cm
Weight	1.510 g without cable
Protection class	11

Con a

Included in delivery: 1 x animal clippers constanta4, 1 x clipper blade set, 1 x small oil bottle, 1 x screwdriver, 1 x instruction manual, 1 x Durable plastic case

Ref. no.	Colour	Teeth lower/upper blade	Shearing type	Ē	Ħ	€
18989	green	20 / 4	Lama Shearing, Alpaca Fleece, Cattle Shearing	1/8	48	
					Æ	
Ref. no.		Description	Lower blade teeth	Upper blade teeth	$\blacksquare$	€
18978		Shearing blades Upper blade		4	1/50	
18534		Shearing blades Bottom blad	e 20		1/50	



18978 Upper blade



# **Clipster Clippers**

# **CLIPST** R

#### Cordless Clipper FarmClipper Akku2

The new battery-powered clipper designed for horses or cattle boasts exceptional value for money! The supplied package includes two 14.4 Volt Lithium ion block batteries, which allow uninterrupted shearing thanks to their optimised operating and charging times. The ergonomic characteristics of the FarmClipper Akku2 are also plain to see: the special surface properties of the housing shells and the balanced centre of gravity prevent the user from tiring too quickly. The size of the plastic shells also means that even small hands can be sure of a firm grip on the clipper. The FarmClipper Akku2 is a clipper with fantastic all-round properties boasting excellent handling.

• available in horse and cattle versions • special, non-slip housing shell for low-fatigue work

• balanced centre of gravity ensures effortless shearing

Technical data	
Voltage	14,4 V
Stroke rate	approx. 2.300 strokes/min
Battery technology	Li-Ion
Battery voltage	14,4 V
Battery run time	90 min
Battery charge time	90 min
Dimensions	28,5 x 8 x 8 cm
Weight	1.090 g incl. battery

## 360°

incl. replacement battery

Included in delivery: 1 x clipper FarmClipper Akku2, 1 x clipper blade set, 2 x batteries 14.4 Volt, 1 x small oil bottle, 1 x screwdriver, 1 x charging station, 1 x instruction manual, 1 x Durable plastic case

	•	blour	blade	Shearing type	₽₽	<b>≓</b> €
181881 incl. 2	batteries b	olue 3	31/15 H	orse Shearing 1	1/3 7	72
181891 incl. 2	incl. 2 batteries		21 / 23 Ca	attle Shearing 1	1/3 7	72

Ref. no.	Description	Lower blade teeth	Upper blade teeth	MOQ	Pieces / unit	Ø	€
181911	Spare Battery for Clippers FarmClipper Akku2					1	
18955	Shearing Blade Set Premium Cow	21	23	1 blister pack	1 / blister pack	1/100	
18956	Shearing Blade Set Premium Cattle / Horse	31	15	1 blister pack	1 / blister pack	1/100	

# CLIPST R

#### **Clipper FarmClipper4**

even very dirty animals or matted fur are no obstacle to the new FarmClipper4
 universal shearing machine for cattle and horses
 optimised weight distribution for low-fatigue working
 attractive, ergonomic design
 powerful motor delivering 200 Watt DC

Technical da Voltage	ta	18192 220 - 240 V AC		9	-1)		<b>В</b> тор	p Seller
Mains freque	ency	50 - 60 Hz						
Clipper head	system	Shearing Blade Set						
Drive		DC motor		and and		manent Magn		200 Watt
Stroke rate		approx. 3.000 strokes/min	с. С	and the second s	DC	= 400 Watt A0	-	
Sound pressu	ure level	85 dB		and the second s				
Dimensions		29,5 x 8 x 6,2 cm	Included in delivery 1.	, clippor Form Cl	inner/			
Weight		1.190 g without cable	Included in delivery: 1 > 1 x clipper blade set, 1					
Protection cla	ass		instruction manual, 1 x					
Ref. no.	Colour	Teeth lower/upper blade	Shearing type	Ð	Ħ	€		
18192	blue	31 / 15	All-round cut	1/3	108			
Ref. no.		Description	Lower blade teeth	Upper blade teeth	MOQ	Pieces / unit	Ø	€
18956	Sh	earing Blade Set Premium Cattle / Horse	31	15	1 blister pack	1 / blister pack	1/100	

# **Clipper Accessories**

BladeCoo

AESCUL

GE7

In the

6

Ŧ

#### Aesculap BladeCool

• highly effective, technical spray that immediately cools and cleans the blade set • easy to use: simply spray on before, during and after using the blade set • improves the cutting result and keeps the shearing blades and cutter head sharp longer • removes hair and fur residue as well as dirt

#### Please note the use and safety instructions.

After the spray is used, the cutter head should be oiled.

#### Please note the use and safety instructions.

Ref. no.	Contents	Ø		€
GTA100	500 ml / Spray Can	1/12	1.008	

## Aesculap Clipper Oil

Specialist oil for all Aesculap clippers and for all moving parts on and in the clipping head.

Ref. no.	Contents	Ð	€
GT604	90 ml / Bottle	1/100	




# **Clipster Wireless Clippers**



#### **Cordless Clipper DeloX**

• 3 cutting speeds • excellent clipping properties thanks to stainless steel clipping head • high-quality, long-lasting motor • digital display of the charging status, oiling, cleaning and remaining battery capacity • can also be operated with power pack connected • with powerful li-ion 2200 mAh battery • Clipping height adjustment: 5-tier adjustable with setting wheel

Included in delivery: 1 x cordless clippers DeloX, 4 x clip-on combs (3,6, 9, 12 mm), 1 x cleaning brush, 1 x power pack, 1 x charging station, 1 x oil, 1 x instruction manual





Technical dat	a	18463			
Voltage		5 V DC			
Clipper head s	system	SnapOn			
Stroke rate		approx. 4.000 strokes/min / approx	. 5.000 strokes/min /	approx. 6.000 s	strokes/min
Battery techno	ology	Li-Ion			
Battery capac	ity	2.200 mAh			
Battery run tir	ne	300 min			
Battery charge time 300 min					
Shear width	hear width 38 mm				
Shearing heig	ht	0,8 mm / 1,1 mm / 1,4 mm /	1,7 mm / 2 mm		
Weight		242 g without cable			
Protection clas	SS	III			
				Æ	
Ref. no.	Colour	Shearing type	Shear width	Ħ	€
18463	black	Detailed shearing	38 mm	1/6/24	
Ref. no.		Description		Ē	€
18477	Sta	inless Steel Clipping Head for	DeloX	1/500	

mm



# Marking

#### Marking Spray TopMarker

• for marking cattle or pigs and goats • colourful and fast-drying marking, highest quality • we recommend our special sheep marking spray for sheep

#### Quick-drying and colour-intensive!

Ref. no.	Colour	Contents	Ð		€
20122	green	200 ml / Spray Can	1/12	2.880	
20123	blue	200 ml / Spray Can	1/12	2.880	
20124	red	200 ml / Spray Can	1/12	2.880	
20148	green	400 ml / Spray Can	1/12	1.512	
20149	blue	400 ml / Spray Can	1/12	1.512	
20150	red	400 ml / Spray Can	1/12	1.512	
20157	green	500 ml / Spray Can	1/12	1.344	
20158	blue	500 ml / Spray Can	1/12	1.344	
20156	red	500 ml / Spray Can	1/12	1.344	
20173	orange	500 ml / Spray Can	1/12	1.344	
20174	violet	500 ml / Spray Can	1/12	1.344	
20177	black	500 ml / Spray Can	1/12	1.344	



#### Cattle Marking Pen TopMarker

• for the short-term marking of pigs, sheep and cattle • Paints with high coverage • extremely economical • easy to use thanks to tommy bar

Available in customer-specific composition. Note the instructions at the end of the catalogue.

Ref.	no.	Colour	Contents	MOQ	Pieces / unit	Ø		€
206	20	blue	60 ml / Tommy Bar	10 pieces	10 / pack	1/10/100	4.200	
2062	20/2	blue	60 ml / Tommy Bar	1 blister pack2	2 / blister pack	< 1		
206	21	red	60 ml / Tommy Bar	10 pieces	10 / pack	1/10/100	4.200	
2062	1/2	red	60 ml / Tommy Bar	1 blister pack2	2 / blister pack	<b>(</b> 1		
206	22	green	60 ml / Tommy Bar	10 pieces	10 / pack	1/10/100	4.200	
2062	2/2	green	60 ml / Tommy Bar	1 blister pack	2 / blister pack	( 1		
206	23	yellow	60 ml / Tommy Bar	10 pieces	10 / pack	1/10/100	4.200	
206	24	orange	60 ml / Tommy Bar	10 pieces	10 / pack	1/10/100	4.200	
206	25	violet	60 ml / Tommy Bar	10 pieces	10 / pack	1/10/100	4.200	
206	26	black	60 ml / Tommy Bar	10 pieces	10 / pack	1/10/100	4.200	



## Aerosol grip SprayMaster

for marking spray

• the spraying aid for comfortable application of colour and marking sprays • for clean and efficient work with all common spray can types • the spraying aid permits professional handling similar to using a gun and helps you to work effortlessly on larger areas • protects the worker's hands

Ref. no.	Ð	€
20170	1/135	

## **Cattle Marking Scissors**

• upturned tip • Material: stainless steel

Ref. no.	Length	Ð	€
208	19 cm	1/10/300	





6

Ŧ

# Marking

#### **Fetlock strap**

The ORIGINAL

- for long-term marking unlabelled for marking cows in pens Material: Plastic
- steplessly adjustable



Easy to open by hand!

## **Fetlock Marking Tape**

Colour

yellow

red

blue

green

orange

Ref. no.

20110

20111

20112

20113

20114

• for marking cows e.g. dry areas, mastitis, hoof treatment etc. • with hook and loop fastener

37 cm

10 pieces

10 / pack

1/10/200

20895: mixed colours (3 x yellow, 3 x red, 2 x blue, 2 x green)

Ref. no.	Colour	Length	MOQ Pieces / unit	
2089	yellow	36 cm	1 blister pack 10 / blister pack 1/100	
20892	red	36 cm	1 blister pack 10 / blister pack 1/100	
20893	blue	36 cm	1 blister pack 10 / blister pack 1/100	
20894	green	36 cm	1 blister pack 10 / blister pack 1/100	
20895	mixed	36 cm	1 blister pack 10 / blister pack 1/100	


#### Fetlock strap for pedometer

• compatible with all common pedometers (including GEA/Nedap, Lemmer-Fullwood)

• with ring fastener

Ref. no.	Colour	Length	Width	Ø	€
20102	blue	40 cm	4 cm	1/10/400	





## Leg band numbers

#### 1-digit

for looping in • optimal recognisability thanks to practical colour code • makes animal identification easier during milking • made from a flexible material to prevent pressure points • suitable for fetlock straps up to 30 mm wide • suitable fetlock strap item no. 20103
 Dimensions: 36 x 36 mm

Ref. no.	Number	Colour	MOQ	Pieces / unit	Ø	€
208420	0	black	1 pack	10 / pack	1/45	
208421	1	yellow	1 pack	10 / pack	1/45	
208422	2	orange	1 pack	10 / pack	1/45	
208423	3	red	1 pack	10 / pack	1/45	
208424	4	violet	1 pack	10 / pack	1/45	
208425	5	blue	1 pack	10 / pack	1/45	
208426	6	green	1 pack	10 / pack	1/45	
208427	7	grey	1 pack	10 / pack	1/45	
208428	8	brown	1 pack	10 / pack	1/45	
208429	9	white	1 pack	10 / pack	1/45	

## Fetlock strap for leg band numbers

• with ring fastener

Ref. no.	Colour	Length	Width	Ē	€
20103	blue	30 cm	3 cm	1/10/500	

#### Weight for ear marking tape

• keeps the neck marking strap in the correct position • with metal core surrounded by impact-resistant plastic • suitable for neck marking straps up to 40 mm wide • incl. oval link

Ref. no.	Colour	Weight	Ø	€
20810	green	500 g	1/10	

#### Numbering block Standard

#### 1-digit

• for looping in • suitable for neck marking straps up to 40 mm wide • Set of 10 • Dimensions: 44 x 46 mm

MOQ	Pieces / unit	Ø	€		
10 pieces	10 / pack	1/10/1.000			
Number	r 0	1	2	3	

Number	0	1	2	3	4	5	6/9	7	8
yellow	208480	208481	208482	208483	208484	208485	208486	208487	208488
orange	208460	208461	208462	208463	208464	208465	208466	208467	208468
red	208470	208471	208472	208473	208474	208475	208476	208477	208478

# Marking

GE/

**3**6

Ŧ

15

#### **Collar Number Duo**

#### 1-digit

• effortless attachment and removal thanks to two-part design • optimised recognisability thanks to handy colour code, double-sided labelling and large format (54 x 59 mm) • suitable for neck marking straps up to 40 mm wide • patented

#### Hugely reduced workload

Collar numbers Duo are a huge help, especially if there are livestock changes. Conventional collar numbers must be pushed from the collar which, due to dirt and soiling, is extremely difficult or even impossible after just a short period of use. Sometimes, the collar including equipment such as transponders, sensors or weights – must be completely dismantled, simply for changing just one number. By contrast, collar numbers Duo can be opened, removed and inserted in the required position easily. With tethered animals, they can be even be fitted without removing the collar.

#### **Optimum recognisability**

The special colour coding (one colour for each number) and large format make animal recognition much easier, especially at long distances, with partially concealed digits or in poor lighting conditions. Thanks to the double-sided labelling and colour coding, even twisted collars are no longer a problem.

Ref. no.	Number	Colour	MOQ	Pieces / unit	Ð	€
209420	0	black	1 pack	6 / pack	1/45	
209421	1	yellow	1 pack	6 / pack	1/45	
209422	2	orange	1 pack	6 / pack	1/45	
209423	3	red	1 pack	6 / pack	1/45	
209424	4	violet	1 pack	6 / pack	1/45	
209425	5	blue	1 pack	6 / pack	1/45	
209426	6	green	1 pack	6 / pack	1/45	
209427	7	grey	1 pack	6 / pack	1/45	
209428	8	brown	1 pack	6 / pack	1/45	
209429	9	white	1 pack	6 / pack	1/45	

#### Accessories Collar Number Duo

2	20944: for easier insertion and removal of the pin				3				
	Ref. no.	Description	Material	MOQ	Pieces / unit	Ø	€	•	209
	20943/12	Spare Pins	Plastic	1 pack	12 / pack	1			
	20944	Installation tools				1/100			



#### for neck marking


The numbering block is positioned upright on the animal's neck, making it very easy to recognise. Side-mounted collar numbers are often hidden in the stable and cannot be seen by the farmer. The numbering block is positioned upright on the animal's neck, making it very easy to recognise the animals, especially in cubicles or at the feeding fence, where a side-attached number can often not be seen.

• especially stable • for looping in • suitable for neck marking straps up to 40 mm wide

Ref. no.	Labelling	Colour	Series of numbers	MOQ	Pieces / unit	Ø	€	New
208430	plain	yellow		1 pack	25 / pack	1/100		
208431	printed	yellow	1 - 25	1 pack	25 / pack	1/100		
208432	printed	yellow	26 - 50	1 pack	25 / pack	1/100		
208433	printed	yellow	51 - 75	1 pack	25 / pack	1/100		
208434	printed	yellow	76 - 100	1 pack	25 / pack	1/100		
208435	printed	yellow	101 - 125	1 pack	25 / pack	1/100		
208436	printed	yellow	126 - 150	1 pack	25 / pack	1/100		
208437	printed	yellow	151 - 175	1 pack	25 / pack	1/100		
208438	printed	yellow	176 - 200	1 pack	25 / pack	1/100		
208439	printed	yellow	201 - 225	1 pack	25 / pack	1/100		
208440	printed	yellow	226 - 250	1 pack	25 / pack	1/100		
208441	printed	yellow	251 - 275	1 pack	25 / pack	1/100		
208442	printed	yellow	276 - 300	1 pack	25 / pack	1/100		




# Marking



Made in Germany

# Marking



#### Marking collar

• with ring fastener

			Y				Made in Germany	
Ref. no.	Colour	Length	Width	Ħ	€			
2088	white / black	130 cm	40 mm	1/10				
Marking • with clip fast			20923 20925 20921				Made in Germany	
Ref. no.	Colour	Length	Width	Ħ	€			
20923	green / white	130 cm	40 mm	1/10				
20925	blue	130 cm	40 mm	1/10				
20921	white / black	130 cm	40 mm	1/10				
20924	green / white	90 cm	40 mm	1/10				
20926	blue	90 cm	40 mm	1/10				

1-1-

# Lick Holders and Licks

NEW

New product

## Delizia<sup>®</sup> Mineral Lick Equisal NoFly

Mineral lick based on sea salt for natural insect deterrence with natural ingredients. The animal is also provided with minerals, trace elements and vitamins as required individually. • consists of highly digestible and high quality food-grade Mediterranean salt • can deter annoying insects such as flies, mosquitoes and fleas • can promote blood circulation and support the immune system • promotes the maintenance of a neutral stomach pH • antioxidant effect through the minerals iron, selenium, zinc, manganese and vitamin E • can improve digestion and metabolism • can reduce the stress factor that is triggered by annoying insects

Ref. no.	Single weight	MOQ	Pieces / unit	Ð	€
325670	3 kg	4 pieces	4 / box	1/4	

#### Delizia<sup>®</sup> Salt Lick

- pressed rock crystal salt lick contains minerals and trace elements
- dimensions approx. 20 x 10 x 5 cm (L x W x H) per lick

Ref. no.	Single weight	MOQ	Pieces / unit	Ø	€
324804	2 kg	1 box	4 / box	1	

#### Lick holder

• practical, virtually indestructible lick holder for angular licks • incl. reinforced mounting holes • suitable for 2 kg salt lick (324804) and angular salt or mineral licks of max. 10 x 5 cm • made of robust plastic • screw in or nail on

Ref. no.	Colour	Ø		€
324803	black	1/60	800	

#### Lick holder

• innovative lick holder made from shock-resistant plastic • for various lick types in round or square shape • screw-on fastening

32480: with removable insert for round licks up to 3 kg e.g. Equisal

Ref. no.	Colour	Length	Width	Lick Insert	Ð		€
32479	dark green	18,5 cm	19 cm	without insert	1	150	
32480	dark green	18,5 cm	19 cm	with round insert	1	150	

patented

Made in the EU

Made in the EU

£

## Lick holder

• no sharp edges • also suitable for 15 kg salt stones • Internal dimensions: 191 x 194 mm • Material: Plastic • screw in or nail on

Ref. no.	Colour	Length	Width	Lick Insert	Ø	
324793	black	20,2 cm	20,6 cm	without insert	1	275
324794	aquamarine	20,2 cm	20,6 cm	without insert	1	275
324795	rosé	20,2 cm	20,6 cm	without insert	1	275

## Lick holder

• Material: metal galvanised

Ref. no.	Length	Width	Height	Ð		€
32472	20,5 cm	20,5 cm	23,5 cm	1	150	



#### **Feeding Troughs Calf and Sheep Trough** Made in the EU • ideal for feeding during the drinking period GE/ Ħ Ref. no. Width Depth Height Capacity Ħ € 3257 23 cm 22 cm 21 cm 6 L 200 1 Trough for concentrated feed • shatter-proof plastic • with drain plug Top Seller Ref. no. Colour Width Depth Height Capacity 邰 Ħ € 32460 9 L dark green 33 cm 28 cm 33,5 cm 150 1 Feed trough • shatter-proof plastic • square **Top Selle** Ŧ Æ Ref. no. Width Depth Capacity Description Colour Height € 3258 without protective edge green 42 cm 30 cm 32 cm 15 L 1 100 32582 with protective edge (unmounted!) green 42 cm 30 cm 32 cm 15 L 1 100 Ref. no. Description Ħ € 32581 **Protective Edge** 1/25 (mr Feed trough Corner Model • complete with feed saver and bite protecting edge (not mounted) • Material: Plastic • for corner mounting Ħ Ref. no. Colour Width Depth Height Capacity € 32592 45 cm 31 L 50 green 60 cm 30 cm 1 Ø Ref. no. Description € Protective Edge for feeding trough corner model 32591 1/25 Feed trough with metal pins • shatter-proof plastic • the metal rods can be removed with a few simple steps • with drain plug Ħ Ref. no. Colour Width Depth Height Capacity €

32465

green

33 cm

28 cm

33,5 cm

9 L

1

30

# **Feeding Troughs**

#### **Rectangular Trough**

• extremely durable and keeps its shape • additional protection against injuries due to continuous round tubes • Material: metal hot-dip galvanised • with drain plug 15 mm



Ref. no.	Length	Width	Height	Capacity		€
32483	45 cm	34 cm	24 cm	35 L	1 16	

#### **Triangular Trough**

 $\cdot$  extremely durable and keeps its shape  $\cdot$  additional protection against injuries due to continuous round tubes  $\cdot$  Material: metal hot-dip galvanised  $\cdot$  for corner mounting  $\cdot$  with drain plug 15 mm



Ref. no.	Length	Width	Height	Capacity	Ð		€
32482	44 cm	44 cm	24 cm	35 L	1	16	

## **Round Trough**

Ref. no.

32484

• extremely durable and keeps its shape • additional protection against injuries due to continuous round tubes • Material: metal hot-dip galvanised • with drain plug 15 mm

Height

24 cm



Plug for feeding	a trouahs
ing for recam	g trougils

Width

35 cm

• easy and secure to screw in thanks to M12 x 18 thread • suitable for Troughs 32460, 32465, 32482, 32483, 32484, 32490, 32495, 32496



倒

1

16

€

Capacity

28 L

Ref. no.	Ø	€
32498	1/100/300	

Length

55 cm

# Hay Racks

GE7

# Square hay rack Standard

suitable for round and rectangular bales up to 1.8 m in length or diameter
 1 x square tubular support
 2 sides can easily be opened for filling
 three-point attachment
 very little food loss
 supplied as a construction kit including circumferential roof edge protection, three-point safety clip
 Internal trough dimensions: approx. 1.9 x 1.9 m
 Material: metal hot-dip galvanised



Please note separate freight costs.

Ref. no.	Description	Length	Width	Height	Feed areas	Ø		€	
291289	with palisade feeding grate for horses and cattle	230 cm	230 cm	250 cm	12	1	6		<b>. .</b>
291294	with self-closing feeding grate for hornless cattle	230 cm	230 cm	250 cm	12	1	6		<b>~</b> •
Ref. no.	Description		Material		Ø	Ē	3	€	
291299	Self-Closing Feeding Grate single	metal	hot-dip galv	vanised	1		6		<b>. .</b>


# **Hay Racks**

<ul> <li>shatter-proof, frost-proof, frost-proof, sturdy construction</li> <li>openings</li> <li>water-remo</li> <li>with integrated carryi</li> <li>with integrated fixing</li> </ul>	max. ø 160 x H 125 cm or ø 130 x roof plastic material with built-in l with animal-friendly and non-dar ving rain channels over the food o ing handle, suitable for front load y eyelets for fixing the base to the ately) for dry storage of the bales;	JV protection naging food openings er forks hay bell			
Technical data	14557 14558		Jan		Carlos Za
Height	164 cm 164 cm			Sale of Alexander	A REAL AND
Exterior diameter	185 cm 185 cm				
Interior diameter	160 cm 160 cm	_			200
Feed areas	5 10	<ul> <li>Please note separate freig</li> </ul>	ht costs.		n an ri
Ref. no. Colou	ır Suitable	for 🗍	€		
14557 olive gr	een Cattle / Ho	orses 1	6		
14558 olive gr	een Sheep / Goats / Ca	lves / Ponies 1	6	the second second way	- Barris
Ref. no.	Description	Colour	Material	suitable for	€
14559	Ground for hay bell	olive green	Plastic UV-stabilised	14557, 14558 1	
14556 Gr	ound anchor for hay bell and ba	se		14557, 14558, 14559 1/1	

# Square hay rack Hobby

. 11 . 6 .

• suitable for round and rectangular bales up to 1.4 m in length or diameter • 1 x square tubular support • 2 sides can easily be opened for filling • three-point attachment • very little food loss • supplied as a construction kit including circumferential roof edge protection, three-point safety clip • Internal trough dimensions: approx. 1.50 x 1.50 m • height-adjustable runners (adjustable to the animal's size) • Material: metal hot-dip galvanised





# Round hay rack with 8 feeding places

for loose feed or small high-pressure bales

• palisade feeding grid • supplied as a kit • 4-part, can be transported in an estate car • outdoors or in play pens, the segments can also be used to set up wall or corner mangers • no three-point hitch • Material: metal hot-dip galvanised

Technical data	291257
Material	metal hot-dip galvanised
Height	116 cm
Exterior diameter	150 cm
Interior diameter	132,5 cm
Feed areas	8

Please note separate freight costs. Ref. no. ∰ झ € 291257 1 5



# **Fence Panels**



# **Pasture Panel**

• perfect for erecting mobile and flexible fencing as well as temporary horse boxes • also commonly used to fence off riding and training areas • also suitable for constructing trap systems and gangways • height of upper tube 1.6 m • safety mounting bracket prevents animals from being injured. When landing on the panel, the animal does not fall between two panels if it slips • made from flat oval pipe 50 x 30 mm • clear distance between tubes 20 cm • rapid chain fastening makes it quicker and easier to connect several panels • very stable at light loads • curved feet ensure excellent stability



hot-dip galvanised

curved feet ensure excellent stability



潦

Ŧ

(---7


Safety mounting bracket





#### Flat Oval Pipe

Please note separate freight costs.

Ref. no.	Description	Material	Length	Height	Ð		€	
442591	Pasture Panel without gate	metal hot-dip galvanised	240 cm	170 cm	1	48		- P
442592	Pasture Panel without gate	metal hot-dip galvanised	300 cm	170 cm	1	36		<b>•</b> •
442593	Pasture Panel without gate	metal hot-dip galvanised	360 cm	170 cm	1	18		<b>•</b> •







# **Fence Panels**


Locking bolt

# **Pasture Panel with Gate**

• allows an opening to be created in the fencing • gate width

1 m • lock for opening and closing the fenced area








Example for mounting

Please note separate freight costs.

Ref. no.	Description	Material	Length	Height	Ø	Ħ	€	
442594	Pasture Panel with Gate	metal hot-dip galvanised	240 cm	220 cm	1	18		<b>•</b> ••
442595	Pasture Panel with Gate	metal hot-dip galvanised	300 cm	220 cm	1	18		<b>. .</b>
442596	Pasture Panel with Gate	metal hot-dip galvanised	360 cm	220 cm	1	18		<b>P</b>







# **Extension element**

for constructing gangways and mobile treatment facilities

• potential uses, such as immunisations, ear tag control or loading and sorting the herd





Example for mounting

Ref. no.	Description	Material	Width	Height	Ð	€	
442620	Extension element Sliding door, single	metal hot-dip galvanised	85 cm	200 cm	1		<b>B</b>
442621	Extension element Connector frame for panels	metal hot-dip galvanised	85 cm	186 cm	1		

GE/

Ŧ

### Water Bowl E21 with pipe valve

• with drinking bowl made of stainless steel, pipe valve and robust cast iron body • ideal for dairy cows, as results in a large water flow • extra-large and wide bowl (Ø 27 cm, height 12 cm) • Stainless steel ensures optimum water hygiene • 4-point fastening on wall or pipe • Fastening material not included



Top Quality

# Technical data2218602218605Connection optionfrom above or belowfrom above or belowFlow rate14 L/min at 3 bar, 20 L/min at 5 bar14 L/min at 3 bar, 20 L/min at 5 bar

Ref. no.	Water connection	Capacity	€ 🗐
221860	G 1/2"	5 L	1 60
2218605	G 3/4"	5 L	1 60

Ref. no.	Description	Material	Ø	€
22365	Mounting Bracket in pairs	metal	1/25	
221861	Valve		1/20	
221971	Guard Size 2	metal hot-dip galvanised	1/4	

### Water Bowl G51 with pipe valve

• large drinking bowl made of grey cast iron • high-quality enamelled surface • easy to clean bowl shape • for wall and pipe mounting

					allor			
Technical da	ata	221851			ener			47
Connection	option	from above or below				G1/2	94	75 Ø13.5
Flow rate	•	8 L/min at 3 bar	enamelled			l mľ		
						19		
Ref. no.	Colour	Water connection	Capacity		€	₩	2"	
221851	black	G 1/2"	1,7 L	1 84			260	215
Ref. no.		Description		Material	Ð	€		
221885		Pipe Valve Set			1/20			
22365		Mounting Bracket in pairs		metal	1/25			
221970		Guard Size 1	metal	hot-dip galvanised	1/4			

### Water Bowl K75

controllable water flow rate (up to max. 11 litres/minute)
with outlet plug for easy cleaning • for wall and pipe mounting • with drain plug • Material: Polypropylene

Technical da	ata								<b>1</b>
Connection	option	from above or below							
Flow rate		11 L/min at 3 bar					G1/2*		
Ref. no.	Colour	Water connection	Capacity	A		€		<del>~</del>	
221875	green	G 1/2"	2,8 L	1	60				
221876	green	G 3/4"	2,8 L	1	60			316	252
Ref. no.		Description		Mate	rial		Ø	€	
222019		Pipe Mounting Bracket in pairs		metal powd	er-coate	d	1		
221971		Guard Size 2		metal hot-dip	galvani	sed	1/4		


€

€

**Top Seller** 


# Water Bowl Mod. 221500

• large drinking bowl made of grey powder-coated cast iron • for wall and pipe mounting



Technical data	
Dimensions (W x D x H)	20,5 x
Connection ontion	from a


Dimensions (W X D X H)	20,5 X 25,5 X 17 CM
Connection option	from above or below
Flow rate	5 L/min at 3 bar
Weight	3,7 kg




enamelled

# Water Bowl G16 with stainless steel guide

• Drinking bowl made of grey cast iron, enamelled • individually packed • for wall and pipe mounting





Technical data	221600
Dimensions (W x D x H)	20,5 x 25,5 x 17 cm
Connection option	from above or below
Flow rate	5 L/min at 3 bar
Weight	3,7 kg







1

Ref. no.	Colour	Water connection	Capacity	Ħ	Ħ	€		
221600	black	G 1/2"	1,45 L	1	120			
Ref. no.	De	escription	Material		MOQ	Pieces / unit	Ø	€
22202		Valve	brass				1/10/400	
22202/1		Valve	brass	1 k	lister pacl	c 1 / blister pack	: 1	
22210	mou	nting plate	metal				1/100	
221970	Gu	ard Size 1	metal hot-dip galvanised				1/4	

GE/

1

ĥ

+

1-1-1


### Water Bowl Mod. 222000

- large drinking bowl made of grey powder-coated cast iron
  lockable paddle
  for wall and pipe mounting

	lockable paddle	
Technical data222000Dimensions (W x D x H)20,5 x 26 x 18,5 cmConnection optionfrom above or belowFlow rate5 L/min at 3 barWeight4,5 kg	22202 22210	
Ref. no. Colour Water connection Capacit	ty MOQ Pieces / unit 🛱 🚍	€
222000 black G 1/2" 1,5 L		
Ref. no.Description22202Valve	Material MOQ brass	1/10/400
22202/1 Valve		pack 1 / blister pack 1
22210mounting plate221970Guard Size 1	metal metal hot-dip galvanised	<u> </u>
	metai not-uip gaivaniseu	1/4

### Float Bowl S522

 $\mbox{ \bullet }$  low-priced float bowl made of polypropylene  $\mbox{ \bullet }$  with outlet plug for easy cleaning



Technical dat Dimensions ( Connection o	W x D x H)	22522 25,5 x 29 x 14,5 cm from left or right		22523		1	
Ref. no.	Colour	Water connection	Capacity	É	Ŧ		€
22522	green	G 1/2"	3 L	•	1/9	189	
Ref. no.		Description	Ð	€			
22523		Floating valve	1/100				
22524		Drain Plug	1/100				

### Float Bowl S190

• 1/2" connection for high pressure float valve (22192) • float cover made of stainless steel • Supplies with float valve • Material: Grey Cast Iron powder-coated


40	/2"		in powder couled				
Technical data		22190					
Dimensions (V	V x D x H)	22 x 26 x 15,5 cm					
Flow rate		5 L/min at 3 bar					
Weight		6 kg					
Ref. no.	Colour	Water connection	Capacity			€	
22190	green	G 1/2"	2 L		1 72		22192
			-				
Ref. no.		Description	Ð	€			
22192		Floating valve High pressure	1/50		_		

### Float Bowl S195

• drinking bowl made of gray cast iron, black enamelled

• Supplied with float valve







8

GE/

Ŧ

### Float Bowl S1090

 $\bullet$  sturdy hot-dip galvanised float bowl  $\bullet$  with efficient float valve  $\bullet$  folding, self-locking valve cover


- F*-	
s O TT	
254	

Technical data	221090
Dimensions (W x D x H)	28 x 26 x 13 cm
Connection option	from left or right
Flow rate	6,5 L/min at 3 bar
Flow rate	6,5 L/min at 3 bar

Ref. no.	Water connection	Capacity	Ø		€
221090	G 1/2"	2,5 L	1	120	
Ref. no.	Dese	cription		Ø	€
22192	Floating valv	e High pressure		1/50	




17.5 cm deep trough made from high-strength polyethylene with inner edge to limit waste when slurping • with constant water level • Drain at the base • the float valve is not accessible to the animals and maintains a pressure of 9 bar • galvanised mounting plate • Connection with hose made from woven stainless steel, above or below, right or left, 1/2" inner thread • suitable for 15 large cattle
 • for wall and pipe mounting • Material: polyethylene



Technical da	ta	22349			-
Connection of	option	from left, right, above or be	low		
Flow rate		34 L/min at 4 bar			
Ref. no.	Colour	Water connection	Capacity		€
22349	green	1/2" IG	25 L	1 16	

# Feed Trough Long with float valve



# Water trough

• sturdy special material, extremely break-resistant and keeps its shape • UV and frost resistant • carefully thought-out design • stable internal wall curving inwards • oval shape allows easy loading into a small transporter • large outlet for rapid drainage (outlet item no. 16601 included) • water connection and float valve protected from animals • easy cleaning thanks to smooth surfaces and rounded edges - no inaccessible areas • stackable • Floor anchoring optionally available (accessories not included in the scope of delivery) • suitable for float valve 220P (41 l/min at 3 bar) and XtraFlo (250 l/min at 3 bar) • Float valve not included!



Extra-reinforced inner rim and optimised float position for better water level regulation

Ref. no.	Colour	Capacity	Length	Width	Height	Ø		€	
223623	green	550 L	150 cm	115 cm	58 cm	1	6		<b>. .</b>
223624	green	1000 L	235 cm	125 cm	58 cm	1	6		<b>. .</b>
Ref. no.	Description						Ē	J	€
223440	Floating valve XtraFlo Top Entry						1/10	/20	
223///1	Elasting valve 220P						1		

223441	Floating valve 220P	1
16601	Outlet for footbath / water trough	1/100
223629	Ground anchor	1/10

### Water trough

 stackable • stable and inexpensive water troughs for outdoor use • with edge for optimal stability • a Suspended Float Valve 222905 can be retrofitted • lightweight and simple to set up
 Material: Plastic UV-stabilised



1/100

Ref. no.	Description	Colour	Length	Width	Height	Capacity	Ø		€	
223518	without drain plug	dark green	102 cm	72 cm	38 cm	150 L	1	45		<b>- -</b>
223517	with drain plug	dark green	130 cm	81 cm	63 cm	380 L	1	35		<b>P</b>
Ref. no.		Des	cription				Materia	I	Ð	€
222905		Immersio	on Float Valv	e			stainless st	eel	1/50	

Outlet for footbath / water trough

16601

152

# Drinking bowl for low pressure

# Float Bowl SN190

#### for low pressure

• powder-coated grey cast iron bowl • Bowl volume: 2 litres • float cover made of stainless steel • G 1/2" connection to low pressure float valve (22182) • Supplied with float valve • for wall mounting

Technical data		22215			
Dimensions (W x D x H	)	24 x 26	x 15,5 cm		
Connection option		from let	ft or right		
Flow rate		4 L/min	at 0,5 bar,	6 L/min at 3 b	ar
Weight		6 kg			
Ref. no.	Colour		Ø		€
22215	green		1	72	
Ref. no.	Descri	ption		Ð	€
22182	Floating valve	Low pressu	ıre	1/100	

# Water Bowl KN50

#### for low pressure

• water bowl made from high-quality plastic • with low-pressure valve • lockable tongue (separate accessory) • fastening clip and stabilisation plate are not included in the scope of delivery • for wall and pipe mounting

Technical da	ta	225035				2004
Dimensions (	W x D x H)	21 x 30,2 x 17 cm				
Connection o	ption	from above or below				
Flow rate		7,2 L/min at 0,5 bar, 1	0,8 L/min at 0,75 bar			~
Weight		0,95 kg			223	437
Ref. no.	Colour	Water connection	Capacity	Ø		€
225035	green	G 1/2" / G 3/4"	2,2 L	1	120	

Ref. no.	Description Material	⊞∮	€
22501	Mounting Bracket with stabilising plates in pairs metal	1/25	
221970	Guard Size 1 metal hot-dip galvanise	ed 1/4	
225034	Nose Paddle Plastic	1/20	
223437	Valve Low pressure Plastic	1/100/400	

22501

### Water Bowl for pasture attachments

• drinking trough made of corrosion-free cast aluminium • suitable for all water containers • complete with gasket (221753) • complete with low pressure valve

Technical dat	ta	2	2175				
Dimensions (	W x D x H)	2	3,5 x 28,7 d	cm			
Flow rate		1	0 L/min at 0	),2 bar			0
							2
Ref. no.	Ħ		€			C.	
22175	1	90					2217
				-			
Ref. no.		Dese	cription		Ø	€	
22176		Valve Lo	w pressure		1/50/500		
221753		Box Sea	al 8-edged		1/300		



GE/


Ŧ

1-1

110








Æ

Material	H 1	€
metal	1/25	
hot-dip galvanised	1/4	
Plastic	1/20	
Plastic	1/100/400	




# Drinking bowl for low pressure

### Water Bowl N20

 $\bullet$  solid, enamelled grey cast body with particularly large, deep bowl  $\bullet$  with low-pressure valve  $\bullet$  complete with flange seal  $\bullet$  Adapter plate for direct connection to pasture barrels

- Adapter plate not included; please order separately for wall and pipe mounting
- Material: Grey Cast Iron enamelled

Technical dat	ta	222030				<b>MARS</b>
Dimensions (	W x D x H)	23,5 x 29 x 15,8 cm				A Lee / S. III
Connection o	ption	from above or below				
Flow rate		10 L/min at 0,2 bar		22176		·
Ref. no.	Colour	Water connection	Capacity		₹ €	
222030	black	G 1/2"	2 L	1 55	;	
Ref. no.		Description			€	G1/2"
221757		Adapter plate for pasture attac	hments	1/5		
221758		Box Seal for adapter plat	e	1/100		
22176		Valve Low pressure		1/50/50	0	G1/2" 290



• water bowl made from high-quality plastic • incl. adapter plate for direct connection to pasture barrels • complete with low pressure valve • complete with flange seal • for attaching to barrels

Technical data	a 2217	'55				
Dimensions (W	/ x D x H) 21 x	30,2 x 17 cm				
Ref. no.	Description	Colour	Capacity	Æ	€	
221755	incl. adapter plate	green	2,2 L	1		
Ref. no.	Description	ı	Material	Ð	€	
221757	Adapter plate for pastur	e attachments		1/5		

Ref. no.	Description	Material	Ħ	€
221757	Adapter plate for pasture attachments		1/5	
221758	Box Seal for adapter plate		1/100	
225034	Nose Paddle	Plastic	1/20	
223437	Valve Low pressure	Plastic	1/100/400	

Ø13.5

# Double Float Drinking Bowl S60 for pasture attachments

 water bowl made from high-quality plastic • for up to 40 large cows • complete assembly for easy mounting to pasture barrel • with inner lip to avoid water waste • with 2 outlet plugs for easy cleaning • larger outlet (16601) can be retrofitted • valve on the top for rapid access to the valve
 with drain plug


Outlet for footbath / water trough

complete assembly for easy mounting to pasture barrel

Technical data	223619
Dimensions (W x D x H)	90 x 45 x 35 cm
Connection option	from above, below or behind
Flow rate	24 L/min at 1 bar
Weight	15 kg



1/100



Ref. no.	Description	Colour	Water connection	Capacity		Ø		€	TV
223619	for pasture attachments	green	G 3/4"	58 L		1	8		
Ref. no.	I	Description		Ø	€				
223441	Float	ting valve 220P		1					

16601

# Drinking bowl for low pressure

GE/

Ŧ

# **Connection Set for IBC containers**

• for connecting a drinking bowl to an IBC container • flexible reinforced hose 70 cm • incl. connecting accessories (see scope of delivery)

Included in delivery: 1 x reinforced hose 70 cm (2 x 3/4" IT connection), 1 x adapter for IBC container incl. gasket (S60 x 6 on 3/4" OT), 1 x straight reducer 3/4" OT to 1/2" IT, 1 x double nipple 1/2"OT to 1/2"OT, 1 x double nipple 3/4"OT x 3/4" OT

Ref. no.	Description	€ 🗐
221980	Connection Set for IBC containers	1/20 240

# Installation plate for IBC containers

 ${\mbox{ \bullet}}$  installation plate for securing drinking bowls to IBC container  ${\mbox{ \bullet }}$  suitable for drinking bowls with low-pressure valve



Si

Which drin	kers will fit?					
Item no. 222	215	F	loat drinki	ng bowl SI		
Item no. 225	5035	C	rinking bo	wl KN50		
Item no. 222	2030	C	Drinking bowl N20			
Ref. no.	Length	Width	Ð	€		
221981	275 mm	175 mm	1/10			




# Water Troughs

# Valve trough drinker

drinkers made from rust-resistant stainless steel
straightforward cleaning of the trough drinkers by lifting the pressure flap
suitable for connection to the circulation pipe, single-sided connection also possible
additional heater optionally available
attachment is externally on the underside of the drinking trough
for wall and pipe mounting

2 heaters are necessary for item no. 221131





Technical data		221130	221131			
Dimensions (W	x D x H)	300 x 375 x 400 mm	300 x 760 x 400 mm			
Connection opt	ion	from left or right	from left or right			
Ref. no.	Description	Water connection	Capacity	Ø		€
221130	simply	G 3/4"	5 L	1	12	
221131	double	G 3/4"	10 L	1	9	
Ref. no.		Description	Ē	€		
221132		Additional heater	1			
221133	١	/alve for valve trough drinker	1			

# Water Troughs

GE7

## **Stainless Steel Water Trough**

• Drinking trough made from rust-resistant stainless steel • Galvanised wall bracket and floor stand • large drain and inclined trough base ensure rapid draining of the water and self-cleaning of the trough • expansion sealing plugs for quick opening and closing of the drain • drain connection so suit KG pipe DN 100 • with 3/4" high performance float valve • easy to open valve cover • Frost-free down to -15 °C: integrated electric heating 200 W (item no. 221142, 221143, 221152, 221153) or can be retrofitted (item no. 221094), operation with transformer (not included) • valve XtraFlo with 250 l/min at 3 bar optionally available



Technical data:	Water trough 100 cm (inside)	Water trou	gh 190 cm (inside)					
Outer dimensions with wall panel (L x W x H)	117 x 60 x 64 cm	207 x 60 x 6	207 x 60 x 64 cm					
Outer dimensions with floor stand (L x W x H)	122 x 58 x 102 cm	212 x 58 x	102 cm					
Water connection	From left or right	From left or	right					
Water flow rate	54 l/min at 5 bar, 41 l/min at 3 bar	54 l/min at	5 bar, 41 l/min at 3 bar					
Ref. no. Description	Interior le	ngth Capao	city 🛱	€				
221140 with floor stand	100 cn	n 50	L 1	<b>-</b>				
221141 with wall bracket	t 100 cn	n 50	L 1	P.				
221150 with floor stand	190 cn	n 95	L 1	<b>•</b> ••				
221151 with wall bracket	t 190 cn	n 95	L 1	P.				
221142 heatable, with base f	rame 100 cm	n 50	L 1	P P				
221143 heatable, with wall br	acket 100 cm	n 50	L 1	<b>.</b> P				
heatable, with base f	rame 190 cm	n 95	L 1	<b>- -</b>				
221153 heatable, with wall br	acket 190 cm	n 95	L 1	- B				
Ref. no.	Description	SU	uitable for	€				
221145 Floor Stand	for stainless steel water trough	221	140, 221150 1					
221146 Wall Bracke	Wall Bracket for stainless steel water trough							
223441	Floating valve 220P							
223440 Floati	Floating valve XtraFlo Top Entry			/20				
221094 Additiona	Additional / replacement heating 200 W							
221144 Sealing Plug	for stainless steel water trough		1/20	/80				

# Water Troughs

Made in Germany

# Tip trough

#### with tipping mechanism

• flat drinking trough made from rust-resistant stainless steel • Galvanised wall bracket and floor stand • fast cleaning thanks to tilting mechanism • float valve with 1/2 " connection • can be used at up to 6 bar max. without pressure reducer

Versions with heating:

- · Heating under the float valve cover
- to be operated with transformer (not included)

#### with heating frost-protected down to about -15°



Tip: An additional 100 W or 200 W heater can be retrofitted. For all tilting drinkers (including those made after 2010), only items 221048 and 221047 are suitable.

Technical data:	Tip trough 30 l	Tip trough 50 l	Tip trough 70 l
Inner dimensions of tip trough (L x W x H)	89 x 40 x 17 cm	139 x 40 x 17 cm	188 x 40 x 17 cm
Outer dimensions with wall panel (L x W x H)	103 x 50 x 43 cm	153 x 50 x 43 cm	203 x 50 x 43 cm
Outer dimensions with floor stand (L x W x H)	103 x 45 x 87.5 cm	153 x 45 x 87.5 cm	203 x 45 x 87.5 cm
Water connection	from left or right	from left or right	from left or right
Water flow rate	30 l/min at 3 bar	30 l/min at 3 bar	30 l/min at 3 bar

Ref. no.	Description	Capacity	Ø		€	
221033	with wall bracket	30 L	1	8		~ <b>P</b>
221032	with floor stand	30 L	1	8		<b>•</b> ••
221020	with wall bracket	50 L	1	8		<b>P</b>
221021	with floor stand	50 L	1	8		<b>-</b> P
221022	with wall bracket	70 L	1	8		<b>-</b> B
221023	with floor stand	70 L	1	8		<b>-</b> B
221019	heatable, with wall bracket	30 L	1	8		- B
221018	heatable, with base frame	30 L	1	8		~ P
221024	heatable, with wall bracket	50 L	1	8		P P
221025	heatable, with base frame	50 L	1	8		<b>P</b> B
221026	heatable, with wall bracket	70 L	1	8		P. P.
221027	heatable, with base frame	70 L	1	8		

Ref. no.	Description	€
221056	Heating 100 W, 24 V - for Tip Troughs from 2010	1
221057	Heating 200 W, 24 V - for Tip Troughs from 2010	1
221048	Heating 100 W, 24 V - for Tip Troughs up to 2009	1
221047	Heating 200 W, 24 V - for Tip Troughs up to 2009	1
221038	Floating valve	1/100

# Universal and boiler brush

• Polypropylene bristles, medium hardness • Bristle thickness: 0,3 mm

	φ.				2	9182		
	14	1	291	173				
up to 80 °C h	neat-resistant							
Ref. no.	Customer no.	Connection	Colour		Length	MOQ	Pieces / unit	
29172					200 mm			
Ref. no.	Description		Length	Ħ	€			29172
29173	Fibreglass Hand	lle	100 cm	1/20				
29182	Fibreglass Hand	lle	145 cm	1/20		_		1 Page

GE#

Ŧ

230 V

24 V

Bite area 24 V

10

11

# Heated 24 V drinking bowls – how do they work?

Heating drinking water using drinking bowls is so easy! You only need at least one heated drinking bowl, a thermostat and a transformer (as 24 V operation). Which transformer for how many bowls? Simple! If you only want to use one drinking bowl with 80 W of power, a 100 VA transformer will suffice.

If you also want to connect a 24 V heating cable, simply add the power consumption (= wattage) of the cable and this gives you the minimum power required for the transformer. Do not measure the transformer's power too precisely, so you will have a buffer for extensions.

When choosing a transformer, ensure that you factor in the power loss caused by the supply cables. You will find a sample calculation and a table containing power loss values in this catalogue.

# **Connection diagram**

- 1. Mains connection 230 V, separately fused
- 2. Water connection, spur line or circulation system possible
- 3. Frost-protection thermostat 230 V (222794)
- 4. Junction box, protection class at least IP54
- Transformer 230 V AC => 24 V AC, 100 W (222796), 200 W (222797), 300 W (222626), 400 W (222798)
- 6. Junction box, protection class at least IP54
- 24 V supply cable for further heated drinking bowls or heating cables
- 8. 24 V supply cable for connecting to the drinking bowl
- 9. 24 V frost-protection heating line (22358, 223581) (if not connected to a circulating heat system)
- 10. Protective plate for the bite area (221975)
- 11. Pipe insulation
- 12. Heated drinking bowl (e.g. 222010)

### Water Bowl H10 heatable

 drinking bowl made of gray cast iron, black enamelled • Grey cast iron bottom tray, black power-coated finish • water flow rate can be regulated on the pipe valve • new heating concept with valve heating to keep clear of frost • easy to install bowl, no need to remove the valve for installation • power supply via transformer at least 100 W (not supplied) • suitable for circulating heating systems • simple electrical connection through the terminal box on the outside
 for wall and pipe mounting

frost-protected down to approx. -20  $^{\circ}\mathrm{C}$ 




#### Upper shell Heating element Lower shell



24 V pin can be connected to the 24 V conduit without disassembling the drinking bowl



#### 80 W or 50 W $\,$



G1/2"

#### Technical data

Dimensions (W x D x H)	25,8 x 28,2 x 17,8 cm	
Connection option	from above or below	
Flow rate	8 L/min at 3 bar	
Weight	11,5 kg	

Ref. no.	Colour	Heating output	Voltage	Water connection		Capacity	Ē		€
222010	black	80 W	24 V	24 V G 1/2"		1,6 L	1	48	
222005	black	50 W	24 V	24 V G 1/2"		1,6 L	1	48	
Ref. no.	Description			Material		Width	Height	Ø	€
222019	Pipe M	ounting Bracket in pairs		metal powder-coated				1	
221971		Guard Size 2		metal hot-dip galvanised				1/4	
221975	Gna	w protection for pipes	Sheet metal galvanic zinc-plated		100 cm	13,2 cm	8 cm	1	

# Float Bowl SH30 heatable

• drinking bowl made from high-quality plastic with integrated heating cable • integrated frost protection thermostat (switch-on temperature approx. +5 °C, switch-off temperature approx. +13 °C) • heating cable easy to replace • suitable for circulating heating systems • valve cover with snap hook for rapid access • with valve type 22182 also suitable for connection to low pressure • with outlet plug for easy cleaning • for wall and pipe mounting




GE/

Ŧ

- 222062 + 222063: with heating cable (approx. 31 W) for heating the drinking bowl and valve
- 222064 + 222065: with heating cable (approx. 73 W) for heating the drinking bowl, valve and up to 2 metres of pipeline (auxiliary pipe heating).
- a transformer is required for the 24 V version (not included)

frost-protected down to approx. -15 °C



4 versions	with auxiliary pipe heating, 73 W	without auxiliary pipe heating, 31 W
24 V	222065	222063
230 V	222064	222062

#### Technical data

Connection option	from left or right
Flow rate	6 L/min at 3 bar
Weight	2,7 kg

Ref. no.	Colour	Pipe Heating	Heating output	Voltage	Water connection	Capacity	Ø		€
222062	green	without pipe heating	31 W	230 V	G 1/2"	5 L	1	42	
222063	green	without pipe heating	31 W	24 V	G 1/2"	5 L	1	42	
222064	green	with auxiliary pipe heating	73 W	230 V	G 1/2"	5 L	1	42	
222065	green	with auxiliary pipe heating	73 W	24 V	G 1/2"	5 L	1	42	

Ref. no.	Description	Material	Ð	€
222019	Pipe Mounting Bracket in pairs	metal powder-coated	1	
22192	Floating valve High pressure		1/50	
22182	Floating valve Low pressure		1/100	
221970	Guard Size 1	metal hot-dip galvanised	1/4	

# Frost Protection Heating 24 V

• for heating the spur line of waterers • a 24 V transformer is required for operation • IPX7

Ref. no.	Heating output	Length	Ē		€
22358	15 W	1,5 m	1/60	720	
223581	30 W	3 m	1/60	720	

# Transformer for pool heating

• transforms the voltage from 230 volts to 24 volts • can be used for all frost-free waterers • Short circuit and overload protection through easily replaceable automotive fuse in the output circuit • the transformers are also secured against overheating thanks to an integrated temperature limiter (automatic reset after cool-down) • IP 65 (transformer) / IP 20 (connection) • Produced using vacuum casting: the best possible protection against moisture, mechanical and electronic loads



Ref. no.	Thickness	Ø	€
222796	100 VA	1	
222797	200 VA	1	
222626	300 VA	1	
222798	400 VA	1	

#### Which transformer should be used?

If you want to operate a water bowl with 80 watts of power (supplied), then a 100-watt transformer will suffice (item no. 222796). If you also want to connect a 24 V heating cable, simply add the current consumption (= wattage) of the cable. When selecting the transformer, plan for a power reserve of 15 % (factor 1.15).

Conventional car microfuses for safe operation of the installation

#### Calculation example for transformer:

,	
2 x drinking bowls with 100 W power consumption	= 200 W
1 x frost-protection heating line 24 V each with 30 W	= 30 W
1 x frost-protection heating line 24 V each with 15 W	= 15 W
Total consumer power	= 245 W
Buffer (flat rate of 15 %) 245 W x 1.15	= 282 W
The transformer of choice has	

an output of 300 W.

#### Which cable should I use?

If the 24 V supply has to cover a larger distance between the transformer and the heater, please pay attention to the cable cross-section, to prevent the risk of drops in voltages along the cable's route.

Calculation to ascertain the minimum cable cross-section: **Power x cable length: 3200 W/m** In the above example, the result for a distance of 25 metres from the transformer to the heater is as follows: **(282 W x 25 m: 3200 W/m) mm<sup>2</sup> = 2.2 mm<sup>2</sup>** 

In this case, a cable with a cross-section of 2.5 mm<sup>2</sup> must be used.

### **Frost Protection Heating with thermostat**

keeps your water line frost-free to -45 ° C • integrated frost protection thermostat (switch-on temperature approx. +5 °C, switch-off temperature approx. +13 °C) • not suitable for heating pipes • do not insulate the thermostat when adding insulation • Protect the area animals could chew on with a bite protector
 VDE tested heating cable • 230 V • IPX7

GE/

Ŧ



Do not mount in animal feed area unprotected - use only 24-volt heating cable. Do not shorten the heating cable!





Ref. no.	Heating output	Length	Plug type	MOQ	Pieces / unit	Ø		€
223582	16 W	1 m	with safety plug	1 blister pack	1 / blister pack	1/16	192	
223585	32 W	2 m	with safety plug	1 blister pack	1 / blister pack	1/16	192	
223586	64 W	4 m	with safety plug	1 blister pack	1 / blister pack	1/16	192	
223587	128 W	8 m	with safety plug	1 blister pack	1 / blister pack	1/16	192	
223588	192 W	12 m	with safety plug	1 blister pack	1 / blister pack	1/16	192	
223590	224 W	14 m	with safety plug	1 blister pack	1 / blister pack	1/16	192	
223589	288 W	18 m	with safety plug	1 blister pack	1 / blister pack	1/10	100	
223591	384 W	24 m	with safety plug	1 blister pack	1 / blister pack	1/10	100	
223592	592 W	37 m	with safety plug	1 blister pack	1 / blister pack	1/5	75	
223593	784 W	49 m	with safety plug	1 blister pack	1 / blister pack	1/5	60	

# **Frost-protection heating lines**

- · prevent water pipes from freezing
- Thermostat in the heating cable switches the cable on automatically

#### What to remember about 230 V heating cables:

- · Always attach the heating cable to the underside of the pipe
- the water pipe must be earthed
- 230 V heating cables are ready to connect and should be connected to a power supply with a 30 mA residual current circuit breaker
- heating cables must not be shortened and should therefore be ordered in the correct length
- Excess length can be wound around the pipe (note that a winding distance of at least 15 mm must be maintained between coils)
- Do not bend heating cables and note the maximum bending radius of approx. 35 mm
- heating cables can be secured to the pipe with insulating tape or aluminium tape (222809)
- if using plastic pipes, wrap aluminium tape (222809) around the pipe

before routing the heating cable

- if using plastic pipes, please pay attention to the separate, specific assembly instructions
- insulate the pipe and heating cable with insulation of max. 13 mm
- attach the heating cable thermostat to the coldest part of the pipe
- · insulate the thermostat only moderately
- do not use 230 V heating cables in the bite area of animals
- installation must be carried out by a qualified professional in accordance with VDE0100

Pipe	Ø 15 mm	Ø 22 mm ½″	Ø 28 mm ¾″	Ø 35 mm 1″	Ø 42 mm 1 ¼″	Ø 48 mm 1 ½″	Ø 60 mm 2″	Ø 76 mm 2 ½″
With insulation (max. 13 mm) frost-resistant to	- 45 °C	- 45 °C	- 40 °C	- 40 °C	- 35 °C	- 30 °C	- 25 °C	- 20 °C

# **Circulation Pump AquaLine**

#### Circulation pump with integrated heater

AquaLine is the ideal solution for watering systems with a loop length of max. 250 m (with 3/4'' pipeline) for providing animals with tempered water. The constant movement of the water and the switchable heating provide double anti-freezing protection.

- AquaLine Classic and AquaLine Digital:
- winter and summer operation (with/without heating)
- automatic control of the set water temperature
- automatic safety shut-off in case of overheating
- separate display of the operating status of the pump and heater via indicator lights on the control unit
- venting valve on the heating body
- high-quality insulated electronics housing made from polyamide to avoid the build-up of condensation
- easy installation for a heating or plumbing specialist
- low space requirement due to compact design
- · low-maintenance thanks to high-quality materials
- mounting kit included for wall mounting
- 2-year warranty
- Water connection: 3/4" from below
- Voltage: 230 V

#### AquaLine Digital:

- PTC probe with digital control thermostat
- precise setting of the target temperature via the display or control box (10 °C to 25 °C)
- indication of the measured temperature on the display
- acoustic and visual signal when the temperature falls below or exceeds the limit temperatures (5 °C / 30 °C)
- flow monitoring with an acoustic and visual signal as well as an automatic heater interrupter when the flow rate falls below the min. value of 6 l/min


Adjusts Sozial Ideam Juliage 230 VAC - 90 Ho Faver 2000W - 115 A




Ref. no.	Description	Length	Width	Height	Power	Ø	€
22331	Classic	410 mm	110 mm	160 mm	3.000 W	1	
223073	Digital	410 mm	110 mm	160 mm	3.000 W	1	

# **Connection diagram**

The entire ring line must be adequately insulated in the frost-risk area. In the bite area, the insulation and additional electrical cables must be protected against biting.



- 1. Aqualine (22331, 223073)
- 2. Non-return ball valve
- 3. Safety overpressure valve
- 4. Automatic bleed valve
- 5. Overpressure manometer
- 6. Flow rate display
- 7. Ball valve
- 8. Outlet valve
- 9. Water filter
- 10. Junction box with residual current circuit breaker for Aqualine 30 mA
- 11. On/Off switch for Aqualine
- 12. Supply cable to 16 A socket for Aqualine
- 13. Drinking bowl, suitable for circulation systems (e.g. 221851)
- 14. Insulation material
- 15. Bite protection for insulation material and cables
- 16. Spur line



Installation with the BYPASS system – the ball cocks allow the pump to be separated quickly and easily from the ring circuit. The two supplied self-sealing screws allow the pump to be quickly and easily removed once it has been disconnected.

With a 3/4' pipe diameter, up to 250 m of ring cable are possible. Max. pumping height: 6 m.

The following accessories for producing the pipework are included: 1 x safety overpressure valve, 3 automatic bleed valves and 1 x non-return valve. The pipework must be built and dismantled by a suitably qualified professional. GE#

223600

# **Thermal Trough**

high insulation through double wall with a thermal foam filling • stays frost-free thanks to flowing water • constant water temperature (approx. 3 to 5 °C in winter, approx. 10 to 12 °C in summer), pleasant for animals all year round • fast emptying and rinsing thanks to large drain with ø 100 mm • enclosed housing prevents soiling and ensures optimum water hygiene • no mains supply needed
incl. base seals, spare gaskets for float valve and drain plug, flexible stainless steel hose, pipe insulation, floor anchor • for floor mounting • with drain plug 100 mm • Material: Plastic

#### Duo:

- 20 animals recommended minimum stocking
- for feeding water to up to 30 animals
- Uno:
- 10 animals recommended minimum stocking
- for feeding water to up to 15 animals

#### frost-protected down to approx. -30 °C

Size of outlet openings

Float valve with water flow up to 35 L/min







223610

Technical data Dimensions (W x D x H) Connection option 223600 108,5 x 70 x 52,5 cm


from below

223610 60 x 70 x 52,5 cm from below

Ref. no.	Description	Water connection	Capacity		Ø		€	
223600	Duo	G 1/2"	100 L		1	4		<b>. .</b>
223610	Uno	G 1/2"	40 L		1	8		• •
Ref. no.	Description		€	€				
223601	Floating valve		1/10		_			

#### **Connection diagram**

- 1. Pipe insulation
- 2. Ground insulating seal
- 3. braided stainless steel hose
- 4. double sealing strips
- 5. Float valve
- 6. Ball
- 7. PU hard foam insulation
- 8. large fast-acting drain
- 9. Concrete step plinth (at least 15 cm thick)
- 10. frost-resistant depth (0.8 2.0 m, depending on region)
- 11. Water inlet, 1/2"
- 12. Open to the ground, so that ground heat can rise
- 13. Pipe: Minimum diameter 30 cm



# **Scales and Measuring Devices**

GE/

浙

Ŧ

# **Animal Scales**

The PS animal scale represents simple, easy and precise weighing. It boasts extremely easy installation and operation and is also virtually maintenance-free.Battery and power pack included • includes operating instructions

#### Platform PS 1000/PS 2000:

• capacity: 500 kg (PS 1000) or 1,000 kg (PS 2000) • robust, powder-coated steel construction with profiled non-slip surface, access ramps on both sides and height-adjustable feet to compensate uneven surfaces • portable thanks to low weight and integrated carry handles

#### Platform PS 3000:

• capacity: 1,500 kg • extremely robust, powder-coated steel construction with large surface, designed for large animals • the integrated anti-slip rubber mat offers exceptionally good grip

#### Display unit:

• LCD (PS 1000/2000) or LED (PS 3000) with digital display • 5 m connecting cable to platform • 230 V mains or battery operation (power pack and batteries included) • RS232 interface (full duplex) for the connection of printers, external displays, etc. (RS232 cable included) • automatic shut-off • housing of stainless steel (PS 1000/2000) or high-quality ABS plastic (PS 3000) • wall bracket included • stand (height 1 m) optionally available

#### Functions:

• Hold (animal weighing function): The average weight measured in the first seconds after the animal walks onto the scale remains on the display until the next animal walks onto the platform. ideal for weight fluctuations when restless animals are being weighed • Print: Send data via RS232 interface • Units: Toggle display between kg and lb • Tare: Tare function (display of net weight)



Technical data	291310	291311	291312
Display	LCD	LCD	LED
tare weight function	100 % of the weighing range	100 % of the weighing range	100 % of the weighing range
Overload capacity	150 %	150 %	150 %
Weighing platform	141,6 x 51,4 x 6,4 cm	149,8 x 76,2 x 6,4 cm	200 x 100 x 10 cm
Weight of weighing platform	34 kg	55 kg	135 kg
Weighing precision	+/- 0,5 kg	+/- 1 kg	+/- 1,5 kg
Weighing unit can be switched	kg / lb	kg / lb	kg / lb
Battery Operation	4 x 1.5 V - AAA (Micro) Alkaline	4 x 1.5 V - AAA (Micro) Alkaline	4 x 1.5 V - AAA (Micro) Alkaline

Ref. no.	Description	Scales readability (d)	Weighing range	Ø		€	
291310	PS 1000	200 g	500 kg	1	8		• •
291311	PS 2000	500 g	1.000 kg	1	6		<b>•</b> •
291312	PS 3000	500 g	1.500 kg	1	7		<b>•</b> ••
Ref. no.	Description			Ħ	€		
291314	Stand for display unit				1/5		<b>. .</b>

# **Scales and Measuring Devices**

# Animal Scales AniScale

This animal scale with cradle stand is ideal for weighing large animals. The animals can easily be put into the cage and held for the weighing procedure. The animal scale can be integrated into trap systems or races.

• The complete set consists of stand and scale set. • To combine the animal scale with a trap system, please use the connector frame so as not to distort the weighing result.

#### The scale stand

weighing platform with rubber mat • animals can stand safely, noise-dampening • extremely robust design • hot-dip galvanised
with 2 sliding doors at the front and rear • 2 panels of 240 cm included • easy to integrate in palisade trap systems or races

#### The weighing set

robust scale beams are mounted below the cage • handles on the scale beams for easy carrying and positioning • display with handy carry handle
with LED display • with battery, operating time per charge approx. 30 hours • charger included • optional stand for display

#### Functions

- stabilisation function, determines the weight of moving animals
- tare function totalling possible

Technical data	291320
Display	LED
tare weight function	100 % of the weighing range
Overload capacity	110 %
Weight	380 kg
Weight of weighing platform	167 kg
Weighing precision	+/- 1,5 kg

Ref. no.	Description	Length	Width	Height	Scales reada	bility (d)	Weighing	g range	5	€	
291320	Complete Set	265,7 cm	88 cm	200 cm	500 g	9	1.500	) kg			
Ref. no.	Descri	ption		Material	Length	Width	Height	Ø		€	
291324	Weighing platform with weighing set (no panels or sliding door)							1			<b>-</b>
291325	Scale Stand (with v 2 panels and 2	5 5 .	l,	metal hot-dip galvanised	265,7 cm	88 cm	200 cm	1	2		<b>.</b>
291321	Weighing pla	tform single		metal hot-dip galvanised				1			<b>.</b>
291322	Weighi (2 x scale beam							1	2		
442620	Extension element :	Sliding door, singl	e	metal hot-dip galvanised		85 cm	200 cm	1			
442591	Pasture Panel	without gate		metal hot-dip galvanised	240 cm		170 cm	1	48		
442621	Extension element Conr	nector frame for p	anels	metal hot-dip galvanised		85 cm	186 cm	1			~ 8
291323	Stand for weig	gh set display		metal				1			





291322

# Weigh and Feed Scoops

29738

29797

29692

29760

29694

29761

GE7

7

#### Rain Gauge with counter

• easy installation on a round pile up to ø 27 mm • Precipitation is easy to read: 1 scale bar = 1 mm = 1 L/m<sup>2</sup> • monthly rainfall is easy to total up using the adjustable counter. Simply turn the rotary ring by the respective additional rainfall amount • with printed measurement scale

291199 green Plastic 1/16	Ref. no.	Colour	Material	Ē	€
	291199	green	Plastic	1/16	

### Feed Scoop

• Material: Plastic • with embossed measuring scale

Ref. no.	Colour	Capacity	Ø		€
29725	transparent	2 L	1/24	288	

# Feed scoop with inverted handle

• ergonomic inverted handle • made of durable plastic with UV protection

Ref. no.	Colour	Capacity	Ø		€
29693	green	2000 g	1	320	

# **Feed Scoop**

• break-proof plastic

Available in customer-specific composition. Note the instructions at the end of the catalogue.

Colour	Capacity	Ø		€
dark green	500 g	1	800	
green	2000 g	1	600	
light green	2000 g	1/60	720	
	dark green green	dark green 500 g green 2000 g	dark green         500 g         1           green         2000 g         1	dark green         500 g         1         800           green         2000 g         1         600

# Weigh Scoop

• for weighing concentrated feed

Ref. no.	Description	Material	Capacity	Ð		€
29758	angular	Aluminium	900 g	1/75	600	
29796	round	Aluminium	900 g	1/80	800	
29760	angular	Aluminium	1600 g	1/75	600	
29797	round	Aluminium	1600 g	1/50	400	
29761	angular	Aluminium	2500 g	1/50	400	
29798	round	Aluminium	2500 g	1/40	320	

# Weigh Scoop Inverted Handle

• Handy • versatile application

Ref. no.	Material	Capacity	Ð		€
29762	Aluminium	1250 g	1/50	300	
29763	Aluminium	2000 g	1/40	240	

# Lubricant

### **Multipurpose Grease Viscano**

• can be used for plain bearings and roller bearings under normal loads • can be used at low to high speeds, low and high temperatures, as a universal grease both for general machine lubrication and for demanding lubrication points • guaranteed a good seal and durability in wet or dusty environments • easy to move, even through long lubrication lines



# **Broom**

Ŧ

### Large broom

• wooden back • suitable handle for handle holder Ø 24 mm: 2962 • suitable handle for handle holder Ø 27 mm: 2961 • with elastane bristles • with bolted handle holder



Ref. no.	Handle	Colour	Width	Ø handle holder	Ð		€
2943	without handle	red	40 cm	24 mm	1	250	
2944	without handle	red	50 cm	24 mm	1	200	
2945	without handle	red	60 cm	27 mm	1	150	
2946	without handle	red	80 cm	27 mm	1	100	
29461	without handle	red	100 cm	27 mm	1	80	

# Large broom Kompakt

- wooden back with elastane bristles with handle halter
- matching handle: 2962



Ref. no.	Handle	Colour	Width	Ø handle holder	Ø	Ħ	€
29473	without handle	red	40 cm	24 mm	1	250	
29441	without handle	red	50 cm	24 mm	1	200	
29477	without handle	red	60 cm	24 mm	1	150	
					1 1		

# Large broom

• wooden back • Arenga Elaston bristles • with handle halter

29478: matching handle 2962 29481: matching handle 2961



Ref. no.	Handle	Colour	Width	Ø handle holder		€
29478	without handle	black / red	50 cm	24 mm	1/10 200	
29481	without handle	black / red	60 cm	28 mm	1/10 120	

# **Broom**

### Large broom with horsehair

- wooden back for fine dust extra fully stocked with horsehair bristles
- with handle halter matching handle: 2962

Ref. no.	Handle	Colour	Material	Width	Ø handle holder		₹ €	
29463	without handle	black	Wood	40 cm	24 mm	1/10 16	0	
29471	without handle	black	Wood	50 cm	24 mm	1/10 12	0	_
29474	without handle	black	Wood	60 cm	24 mm	1/10 12	0	_

# Large broom with scraper edge

ideal for removing ice, compacted snow, chewing gum, cigarettes, etc.
fully assembled with bolted handle holder
wooden back
galvanised steel sheet 1.2 mm
Width: 26.5 cm
with elastane bristles
matching handle: 2961





Ref. no.	Handle	Colour	Width	Ø handle holder	Ø		€
29433	without handle	red	40 cm	27 mm	1	150	
29434	without handle	red	60 cm	27 mm	1	120	

### Scrubber

- Wood back with metal handle holder with polypropylene bristles
- with handle halter matching handle: 2962

								0	
Ref. no.	Handle	Width	Ø handle holder	Ø		€	- m		1111111
29528	without handle	30 cm	24 mm	1/10	480				
Ref. no.	Description			Μ	laterial	Length	Ð	€	
2962	Device and Broom Handle without cone			Asp	en Wood	130 cm	1/25		-

# **Bucket and Scoop**

GE#

Ŧ



# **Universal Bucket**

29882

• very sturdy design • Material: Plastic

green

• with metal carry handle • food safe

Ref. no.	Colour	Capacity	Ð		€
298840	red	10 L	1	600	

20 L

180

1

Available in customer-specific composition. Note the instructions at the end of the catalogue.

Available in customer-specific composition. Note the instructions at the end of the catalogue.



Milling

29300

### Box rake

very light and robust
can be used on both sides
versatile use, e.g. for cleaning cubicles
Rake and scraper at the same time

										• /	////
Ref. no.	Handle	Colour	Mate	erial	Width	ØI	nandle	holder	Ħ		€
29244	without handle	black	Nylon fibre-gla	ass reinforced	40 cm	2	8 - 28,5	5 mm	1/4/24	288	
	re Scraper Ile halter • matching	g handle: 2961.	3	29	227				2926	-	
Ref. no.	Handle	Ма	terial	Width	Ø handle ho	lder	Æ		€		
2926	without handle	Shee	t metal	35 cm	33 mm		1	500			
2927	without handle	Iron	forged	35 cm	33 mm		1	500	-	_	
Ref. no.	Descrip	otion	Material	Length	F	€					
29613	Manure Scrap	per Handle	ash	150 cm	1/25						
-	Pusher	halter			E		-				

29242

29242: matching handle 2961, 29603, 29604 or 29611 29300: matching handle 29604

Ref. no.HandleColourMaterialWidthØ handle holderImage: Colour€29300without handlegreenPlastic40 cm27 mm1/2072029242without handlebluePlastic36 cm25 mm1/20600									
	Ref. no.	Handle	Colour	Material	Width	Ø handle holder	Ð		€
29242 without handle blue Plastic 36 cm 25 mm 1/20 600	29300	without handle	green	Plastic	40 cm	27 mm	1/20	720	
	29242	without handle	blue	Plastic	36 cm	25 mm	1/20	600	

# Muck and Slurry Pusher

• very versatile • with handle halter Ħ Ref. no. Handle Colour Material Width Ø handle holder Ħ € 29243 without handle green Polypropylene 35 cm 28 mm 1/40 800



# Muck and Slurry Pusher

• very robust thanks to metal reinforcement • can be used on both sides • very clean removal of liquids thanks to the integrated lip made from foam rubber • very versatile, e.g. can also be usedas a feed pusher, squeegee or snow shovel • with handle halter





Ref. no.	Handle	Colour	Material	Width	Ø handle holder			€
29287	without handle	green	Polypropylene	46 cm	27 mm	1/15	300	
Ref. no.	Description				Colour	Width	Ð	€
29288	Rubber for muck and slurry pusher				black	46 cm	1/15	

### **Muck and Slurry Pusher**

• with interchangeable, ammonia-resistant rubber scraper • bolted • high-quality rubber blend with mesh insert guarantees maximum flexibility while preventing the occurrence of fractures and cracks • very long life thanks to low abrasion • with handle halter • matching handle: 29612

High-quali	ty rubber blend with m	esh insert					•		
Ref. no.	Handle	Material	Width	Ø handle holder	Ø		€		
291285	without handle	Steel powder-coated	30 cm	30 mm	1	400			
291266	without handle	Steel powder-coated	35 cm	30 mm	1	350			
291267	without handle	Steel powder-coated	40 cm	30 mm	1	300			
291268	without handle	Steel powder-coated	55 cm	30 mm	1	275			
Ref. no.		Description	Colour	Material	Length	n	Width	Ð	€
291286	Rubber for r	muck and slurry pusher	black	Rubber			30 cm	1/100	
291271	Rubber for r	muck and slurry pusher	black	Rubber			35 cm	1/100	
291272	Rubber for r	muck and slurry pusher	black	Rubber			40 cm	1/100	
291273	Rubber for r	muck and slurry pusher	black	Rubber			55 cm	1/100	
29612	Handle for r	muck and slurry pusher		ash	165 cn	m		1/25	

# Muck and Slurry Pusher half round

• with interchangeable, ammonia-resistant rubber scraper • bolted • high-quality rubber blend with mesh insert guarantees maximum flexibility while preventing the occurrence of fractures and cracks  ${\mbox{\cdot}}$  very long life thanks to low abrasion • shaft holder with wing-nut, infinitely variable • with handle halter • matching handle: 29612

#### High-quality rubber blend with mesh insert

								100 million	/
Ref. no.	Handle	Material	Width	Ø handle holder	Ø		€		
291269	without handle	Steel powder-coated	66 cm	32 mm	1	120			/
291270	without handle	Steel powder-coated	50 cm	32 mm	1	180			
Ref. no.		Description	Colour	Material	Length	I	Width	Ð	€
291274	Rubber for muck	and slurry pusher, half round	black	Rubber			66 cm	1/100	
291275	Rubber for muck	and slurry pusher, half round	black	Rubber			50 cm	1/100	
29612	Handle for	muck and slurry pusher		ash	165 cm	1		1/25	

# Muck and Slurry Pusher half round

• galvanised shaft • bolted • with interchangeable, ammonia-resistant rubber scraper · high-quality rubber blend with mesh insert guarantees maximum flexibility while preventing the occurrence of fractures and cracks • very long life thanks to low abrasion • extremely sturdy design with reinforced back • shaft holder with wing-nut, infinitely variable • with handle halter • matching handle: 29612

Ref. no.	Handle	Material	Width	Ø handle holder	Ø		€
29232	without handle	Steel galvanised	58 cm	32 mm	1	150	
29233	without handle	Steel galvanised	66 cm	32 mm	1	120	
29234	without handle	Steel galvanised	73 cm	32 mm	1	80	

Ref. no.	Description	Material	Length	Width	Ø	€
29235	Rubber for muck and slurry pusher, half round	Rubber		58 cm	1/10/50	
29236	Rubber for muck and slurry pusher, half round	Rubber		66 cm	1/10/50	
29237	Rubber for muck and slurry pusher, half round	Rubber		73 cm	1/10/50	
29612	Handle for muck and slurry pusher	ash	165 cm		1/25	





GE/

1000

Ŧ

# Squeegee


Ref. no.

29284

29285

29286

universal handle fitting with clamp screw cap: rapid and tool-free fastening of all types of handels with diameters from 18 to 26 mm
 very sturdy construction • with splash guard • high-quality rubber lip made from natural rubber: does not absorb water, long-lasting, wear-resistant, elastic and maintains its shape - for the best results even on rough and uneven ground • firmly riveted rubber lip • Handle holder with clamping screw



### **Squeegee Premium**

Handle

without handle

without handle

without handle

• zinc-plated design • very sturdy construction • perfect for professional use and large areas • with removable, screwed-on rubber • with pre-mounted handle holder • with handle halter • matching handle: 2961

Material

metal galvanised

metal galvanised

metal galvanised

29272without handlemetal galvanised40 cm24 mm1/1030029273without handlemetal galvanised50 cm24 mm1/1030029274without handlemetal galvanised60 cm24 mm1/1025029275without handlemetal galvanised80 cm28 mm1/10200	Ref. no.	Handle	Material	Width	Ø handle holder	Ø		€	
29274 without handle metal galvanised 60 cm 24 mm 1/10 250	29272	without handle	metal galvanised	40 cm	24 mm	1/10	300		<b>Top Quality</b>
	29273	without handle	metal galvanised	50 cm	24 mm	1/10	300		
29275 without handle metal galvanised 80 cm 28 mm 1/10 200	29274	without handle	metal galvanised	60 cm	24 mm	1/10	250		
	29275	without handle	metal galvanised	80 cm	28 mm	1/10	200		

Ref. no.	Description	Colour	Material	Width	Ð	€
29276	Rubber for Premium squeegee	black	Rubber	40 cm	1/50	
29277	Rubber for Premium squeegee	black	Rubber	50 cm	1/50	
29278	Rubber for Premium squeegee	black	Rubber	60 cm	1/50	
29279	Rubber for Premium squeegee	black	Rubber	80 cm	1/50	

# Squeegee

- zinc-plated design with splash guard Natural rubber
- with handle halter matching handle: 2962



Ref. no.	Handle	Material	Width	Ø handle holder	Ø		€
29281	without handle	metal galvanised	45 cm	23 mm	1/10	350	
29282	without handle	metal galvanised	55 cm	23 mm	1/10	250	
29283	without handle	metal galvanised	75 cm	23 mm	1/10	360	

# **Rubber wiper**

 $\bullet$  zinc-plated design  $\bullet$  without handle  $\bullet$  firmly riveted rubber blade to prevent blade from loosening  $\bullet$  with handle halter  $\bullet$  matching handle: 2962



Ref. no.	Material	Width	Ø handle holder	Ð		€
29466	metal galvanised	45 cm	24 mm	1/10	770	
29467	metal galvanised	60 cm	24 mm	1/10	560	

# **Feed Pusher**

• with handle, unmounted • replaceable plastic blade with an anti-stick coating • very versatile, e.g. can also be usedas a feed pusher or snow shovel • Plastic blade dimensions: 20 x 61 cm



Ref. no.	Handle	Colour	Length	Ð		€
29250	with fibreglass handle and D-grip	red / black	140 cm	1/6	42	

### **Feed Pusher**

• extremely stable and durable • very versatile • suitable for silage, grain, manure or snow • with sharp corners for better accessibility of edges and corners • matching handle: 29246



# **Aluminium Shovel**

- abutment edge, galvanized
- Material thickness: 2 mm
- with handle halter
- matching handle: 29589, 29674, 29585, 29581







GE/

統

Ref. no.	Handle	Size	Material	Width	Ø handle holder	Ø		€
2967	without handle	9	Aluminium	36 cm	36 mm	1/10	220	
2970	without handle	7	Aluminium	32 cm	36 mm	1/10	280	
2973	without handle	5	Aluminium	28 cm	36 mm	1/10	350	

								Shovels
• extra-thi galvanized	nium Shove ck material approx. 2 • with handle halter 589, 29674, 29585	.5 mm • abutm	andle:	p Quality	9675			2977
2.5 mm	material thickness							
Ref. no.	Handle	Size	Material	Ø handle hol	der 🗍	] =	€	
29675	without handle	9	Aluminium	38 mm	1/*	0 200		
2977	without handle	7	Aluminium	38 mm	1/*	0 280		- // //
halter • m	e • Material thicknes atching handle: 2958	33					296	91
Ref. no. 29691	Hanc with beech ha		Size 9	Material Aluminium	1/5	70	€	
Specia • with edg 2,5 mm • v								9679
29679	with beech ha	ndle 135 cm	9	Aluminium	1/5	70		

# **Accessories for Aluminium Shovel** and Aluminium Shovel Profi



Ref. no.	Description	Size	Material	Length	Width	Ø	€
2969	Edge for aluminium shovel incl. 5 rivets	9			36 cm	1/10/50	
2972	Edge for aluminium shovel incl. 5 rivets	7			32 cm	1/10/50	
29732	Edge for aluminium shovel incl. 4 rivets	5			28 cm	1/10/50	
29721	Rivets for edges					1/5/5.000	
29581	Handle for Shovel 1a quality		ash	130 cm		1/25	

### Snow and grain shovel

Ref. no.

29665

various grip options
working positions that are gentle on the body
light and stable
with handle halter
matching handle: 29589, 29581

29671

GE7

Ŧ

29666 29665 Ħ Description Handle Width Height Ø handle holder Colour Material Length € without without handle green Plastic 42 cm 40 cm 10 cm 39 mm 1/5 150 protective edge

29666	with protective edge	without handle	green	Plastic	42 cm	40 cm	10 cm	39 mm	1/5	150
296710	with protective edge	with aluminium handle and D-grip	green	Plastic	42 cm	40 cm	10 cm	39 mm	1/5	50

### Snow and grain shovel

• various grip options • working positions that are gentle on the body • with handle halter • matching handle: 29589, 29674, 29585, 29581

29667

Ref. no.	Description	Hand	lle	Material	Length	Width	Ø handle holder	Ø		€
29670	without protective edge	with beech	n handle	Aluminium	41 cm	33 cm	39 mm	1/5	50	
29671	with protective edge	without I	handle	Aluminium	41 cm	33 cm	39 mm	1/5	160	
29667	with protective edge	with alun handle and		Aluminium	41 cm	33 cm	39 mm	1/5	50	
								-		
Ref. no.	Description	Ð	€					$\bigtriangledown$		
29673	Edge with rivets	1/10/150								

### All-purpose Shovel

• versatile, e.g. as a snow or grain shovel • reinforced blade edge

• 4-piece glass fibre reinforced handle • Handle is robustly inserted

and screwed together • comes disassembled in cardboard box

• matching handle: 29699



Plug-in	system	tor	two	lengths!

29699

					-			
Ref. no.	Description	Handle	Colour	Width	Height	Ø		€
29697	without protective edge	with glass fibre reinforced handle and D-grip	red	44 cm	40 cm	1	100	
29698	with protective edge	with glass fibre reinforced handle and D-grip	red	29 cm	36 cm	1	112	

## **Quality Forks**

50102

### European high-quality forks made of premium steel!

### Litter fork

- hand-forged and hardened with spring sleeve
- matching handle: 29581, 2959

					/ /	/ / /	//	//	
Ref. no.	Handle	Material	Length	Width	Tines	Ø handle holder	Ø		€
50100	without handle	Steel	31 cm	23 cm	4	38 mm	1/5	500	
50102	without handle	Steel	31 cm	24 cm	5	38 mm	1/5	400	

50100

#### **Bedding Fork**

hand-forged and hardened
with spring sleeve
matching handle: 29581, 2959

Ref. no.	Handle	Material	Length	Width	Tines	Ø handle holder	Ħ		€
50104	without handle	Steel	30 cm	30 cm	3	38 mm	1/5	500	

### **Bedding and Bale Fork**

• hand-forged and hardened • with grommet

• matching handle: 29581, 2959

Ref. no.	Handle	Material	Length	Width	Tines	Ø handle holder	Ð		€
502720	without handle	Steel	26 cm	13 cm	2	38 mm	1/5	600	
50105	without handle	Steel	28 cm	21 cm	3	38 mm	1/5	600	
50106	without handle	Steel	26 cm	20 cm	3	38 mm	1/5	600	

### **Dung Rake**

• hand-forged and hardened • with grommet

• matching handle: 29581, 2959



All forks are forged from a single piece!

Ref. no.	Handle	Material	Length	Width	Tines	Ø handle holder	Ø	Ħ	€
29115	without handle	Steel	21 cm	20 cm	4	38 mm	1/5	500	
294430	without handle	Steel	21 cm	17 cm	3	38 mm	1/5	500	

## Stable and yard essentials

### Moisture Meter for hay and straw

• Portable digital device for the determination of moisture and temperature in pressed hay and straw • incl. 68 cm long sensor that registers changes in the electrical conductivity of hay and straw and turns them into moisture percentages • can store up to 50 measurement results • operated with: 1 x 9 V - Block PP3 • Battery included

Technical da	ta			29356
Battery Oper	ation			1 x 9 V - Block PP3
Display				LCD 1 x 3-digit
Temperature	measuring rang	je		1 - 100 °C
Moisture me	asurement accu	racy		10 - 80 %
Sensor cable	length			100 cm
Ref. no.	Colour	Ð	€	
29356	yellow	1/20		

### Hay Cutter Hay Cutter TF 2000 M

suitable for vertical as well as horizontal cutting of hay bales, allows for dust free working • its perfect cutting, handling and ease of use without maintenance requirements reduce labour costs
the TF 2000 M hay cutter is perfect for cutting hay bales, pressed fodder and silage (e.g. hay, corn, millet, beet leaves or grass silage in a clamp silo) • with closed blade • cuts round hay bales without raker • Sound pressure level: 103.5 LWA • Vibration level ISO 5349: 5.9 m/sec2

Technical data		29190					
Voltage		230 V					
Mains frequency		50 Hz					
Power		1.400 W					
Weight		13,4 kg					
Cutting width		25 cm					
Cutting height		60 cm					
Sound pressure lev	rel	89,9 LpAm					
Ref. no.	Colour	Ð	€				
29190	black / blue	1					



GE/

## Stable and yard essentials

### **Outlet Raimo BigBag**

• for easy and controlled emptying of BigBags with the help of a resealable slider • suitable for all kinds of free-flowing materials such as seeds, fertilisers, feed etc. • unused materials stays in the BigBag, meaning no waste • can be applied to the empty or already filled sacks in seconds – the integrated blades cut the hole when rotated, even in the BigBag • extremely robust and reusable







Ref. no.	Description	Ð		€
29389	with extension	1	76	
29425	without extension	1	126	

### **Strip Curtain Set**

Set consisting of: 5 x PVC strips 30 x 225 cm, 3 mm thick, 5 x hanging panels 30 cm, 2 x hook strips (total length 130 cm)



Ref. no.	Description	Length	Width	MOQ	Pieces / unit	Ø	€
291163	PVC Strips punched and assembled	225 cm	30 cm			1	
291154-1	Screw and Nut Set for hanging panels			1 pouch	8 / pouch	1	

Ŧ



Made for long-lasting use in harsh environments!

#### Put your trust in Kerbl's experience: Our lights were specially developed for lasting use in stables and similarly demanding environments.

As well as high stress due to humidity and dust, lights in stables are exposed to a lot of chemicals in the ambient air and due to cleaning processes. In particular, lights have to be able to withstand high concentrations of ammonia.

Therefore, to ensure a long service life, we focus our efforts on the technical design, the use of suitable electronic components and materials, and high-quality workmanship of our LED lights. And we don't just rely on our own expertise – we also put our products through special safety and load tests by independent and recognised testing institutes such as TÜV Süd and the DLG Test Lab.

Our LED indoor spotlights and MultiLED Pro and FarmPRO lights have passed ammonia resistance tests at the DLG Test Lab.



#### LED technology in the stable pays off

LEDs operate at a high level of effectiveness and are extremely efficient. Their luminous efficacy is therefore especially high.

As a rule, the investment costs for new equipment or a conversion are currently still higher than for conventional lighting; however these costs will pay for themselves over a short time due to the considerable savings in running costs.

#### More light means more milk

Lighting duration, lighting intensity and light colour all have a major impact on lactation, fertility and the well-being of animals. In dairy cattle farming, lighting management is therefore extremely important. Scientific studies have shown that daily milk production can be increased by 5 - 15 % on average during long daylight phases with 16 hours of light and 8 hours of darkness. However, this requires a uniform lighting strength of 150 - 200 lux.



#### **LED Indoor Spotlight**

#### LED light for lighting stables, riding halls, industrial buildings and warehouses

• resistant to ammonia (DLG-tested) • ideal for high-ceiling structures • with energy efficient SMD chips from Philips • excellent light yield • high colour temperature for fatigue-free visibility • with D marking according to DIN EN 60598-2-24, therefore suitable for areas at risk of fires due to combustible dusts or fibres (hay storage, feed, litter, etc.) • direct or suspended ceiling installation • special heat sink shape for optimised heat dissipation • protected against powerful water jets and dust-proof (IP 65 protection class) • Light angle: 110 ° • Voltage: 100 - 240 V • suitable for outdoor use • 5-year warranty • TÜV-GS approved

In combination with the lighting control system (item no. 345000), it is ideally suited to help minimise energy costs, optimise the milk and growth output of the animals and increase comfort for both people and the animal

Technical data Voltage 100 - 240 V Mains frequency 50 - 60 Hz Luminous efficacy 132 lm/W 110° Light angle (half intensity angle) Chip service life (L70) > 100.000 h 1...10 V, 10 V PWM, 0 - 100 kΩ resistance Dimming function (only with dimmable lamps) Die-cast aluminium with anti-corrosion coating Material Operating ambient temperature -40 - 60 °C Ra > 80 Colour rendering (CRI) Protection class IP65

Ref. no.	Power	Ø	Dimming function	Luminous flux	Colour temperature	Ð		€
345805	100 W	280 mm	cannot be dimmed	13.200 lm	5.700 K	1	24	
345815	150 W	320 mm	cannot be dimmed	19.800 lm	5.700 K	1	21	
345825	200 W	365 mm	cannot be dimmed	26.400 lm	5.700 K	1	28	
345835	240 W	400 mm	cannot be dimmed	31.680 lm	5.700 K	1	28	
345810	150 W	320 mm	dimmable	19.800 lm	5.700 K	1	24	
345830	240 W	400 mm	dimmable	31.680 lm	5.700 K	1	24	
Ref. no.			Desc	ription			Æ1	€

Rei. no.	Description		£
345802	Metal Bracket for Ceiling/Wall Mounting	1/20	

The lights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.



KERBL HALLENSTRAHLER

DLG-Prüfbericht 7019

/ Ammoniakbeständigkeit





GE/

**Å** 

Ŧ

#### **MultiLED** pro

## LED light for lighting stables, riding halls, industrial buildings and warehouses

optimal light distribution via individually adjustable modules

 excellent heat dissipation due to a solid heat sink • high-quality materials for use in tough environments • very high ammonia-resistant
 protected against powerful water jets and dust-proof (IP 65 protection class) • with D marking according to DIN EN 60598-2-24, therefore suitable for areas at risk of fires due to combustible dusts or fibres (hay storage, feed, litter, etc.) • direct or hanging ceiling installation with adjustable mounting brackets or eyelets • incl. dimming function (can be controlled via a 1 - 10 V, PWM or resistance signal) • with energy efficient SMD chips from Philips • Light angle: 110 ° • Voltage: 100 - 277 V • suitable for outdoor use • 5-year warranty

In combination with the lighting control system (item no. 345000), it is ideally suited to help minimise energy costs, optimise the milk and growth output of the animals and increase comfort for both people and the animal

Technical data	
Voltage	100 - 277 V
Mains frequency	50 - 60 Hz
Luminous efficacy	120 - 130 lm/W
Light angle (half intensity angle)	110 °
Chip service life (L70)	> 100.000 h
Dimming function (only with dimmable lamps)	110 V, 10 V PWM, 0 - 100 kΩ resistance
Operating ambient temperature	-40 - 50 °C
Colour rendering (CRI)	Ra > 80
Protection class	IP65

Ref. no.	Power	Length	Width	Height	Dimming function	Luminous flux	Colour temperature	Ø		€
345985	150 W	430 mm	298 mm	350 mm	dimmable	19.500 lm	5.700 K	1	20	
345990	300 W	580 mm	298 mm	430 mm	dimmable	36.000 lm	5.700 K	1	12	

The lights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.





5





#### control unit for LED lighting

This lighting control allows you to switch the artificial stable lighting on or off, on a timer and regardless of existing daylight, or even achieve a constant light level (e.g. min. 200 lux) through automatic dimming. This means it ensures ideal lighting conditions throughout the day and year while minimising electricity consumption. Comfort for animals and humans! • controls lighting dependent on time and/or daylight • four different lighting circuits (groups) can be independently controlled, two of which with a dimming function • suitable for LED lights with 1...10V interface • standard surface-mount housing for mounting in the equipment room • Dust and moisture protection (IP54) • suitable e.g. for up to 50 150 watt lights (up to 15 lights on the dimmable circuits 1 and 2, and up to 10 lights on circuits 3 and 4) • supplied with a light sensor (can request up to four light sensors) • input for up to four button signals • easy to use with display and three buttons • with extensive documentation and terminal description • IP65

Technical data	345000
Supply voltage	230 V / 400 V
Fuse	B16 A
Pole Connectors	3-pin
Max. current value per output	16 A
Max. total power circuit 3 and 4	16 A
Number of circuits	4
Number of dimmable circuits	2
Max. switching capacity	11 kVA
Dimming function circuit 1 and 2	110 V
Number of max. light sensors	4
Number of max. button signals	4
Protection class	IP65

Ref. no.	Material	Width	Height	Ø	€
345000	Plastic	300 mm	450 mm	1	
Ref. no.		Description		Ø	€
345001	Se	nsor for control		1	



easy to install by your electric company



## LED Tubes and Moisture-proof Lights

The LED tubes EcoTUBE and EcoTUBE Plus come with the latest LED technology and their high light output, high efficiency and extremely attractive price-performance ratio cannot fail to impress.

Compared with conventional fluorescent tubes, you can save a great deal on energy costs and enjoy many other benefits as well:

- very long service life and high switching durability
- full light output even at low temperatures
- full, immediate luminosity, no flickering, no humming
- uniform and glare-free illumination
- high colour reproduction (Ra > 80), suitable for nearly all operating sites according to workplace guidelines
- sturdy housing
- mercury-free



GE#

Ŧ

### LED Tube EcoTUBE

• Lamp tube made out of glass with special plastic coating to prevent sagging while also ensuring optimal splinter protection • very high light angle ensures particularly uniform illumination • flicker-free, thus also for poultry with high visual acuity • very efficient through high lumen output • only suitable for lights with conventional electro-magnetic ballasts (conventional ballasts/low-loss ballasts). • Light angle: 210 ° • Lamp Base: G13 • Voltage: 220 - 240 V • 5-year warranty • TÜV tested

Technical da	ta			flicke	er-free					
Voltage			220 - 240 V							
Mains freque	ency		50 - 60 Hz							
Light angle (	half intensit	y angle)	210 °							الاستعل
Chip service	life (L70)		> 50.000 h	. (			5-year	warrant	ty	🦉 5 🎉
Colour rende	ring (CRI)		Ra > 80							محلى واللا
Lamp Base			G13	ſ	A Type Appiped Safety Rouse Production					
Bulb shape			T8	T	VAhelistand		New	produ	ct	NEW
Energy efficie	ency class		A++		GERTIFIED.			produ		
Ref. no.	Power	Length	Dimming function	Luminous flux	Colour temperature	MOQ	Pieces / unit	Ø	€	
345610	21 W	150 cm	cannot be dimmed	2.750 lm	6.500 K	10 pieces	10 / box	1/10		
345611 17 W 120 cm cannot be dimmed 2.200		2.200 lm	6.500 K	10 pieces	10 / box	1/10				

### LED Tube EcoTUBE Plus

• Lamp tube made out of glass with special plastic coating to prevent sagging while also ensuring optimal splinter protection • very high light angle ensures particularly uniform illumination • flicker-free, thus also for poultry with high visual acuity • very high light output • extremely efficient through high lumen output • only suitable for lights with conventional electro-magnetic ballasts (conventional ballasts/low-loss ballasts). • Light angle: 210 ° • Lamp Base: G13 • Voltage: 220 - 240 V • 5-year warranty • TÜV tested

Technical data		flicker-free	
Voltage	220 - 240 V		
Mains frequency	50 - 60 Hz		
Light angle (half intensity angle)	210 °		
Chip service life (L70)	> 50.000 h		E-year warranty
Colour rendering (CRI)	Ra > 80		5-year warranty
Lamp Base	G13		
Bulb shape	T8		Name and Associated
Energy efficiency class	A++	SUD	New product NEW

Ref. no.	Power	Length	Dimming function	Luminous flux	Colour temperature	MOQ	Pieces / unit	Ø	€
345614	24 W	150 cm	cannot be dimmed	3.600 lm	4.000 K	10 pieces	10 / box	1/10	
345612	24 W	150 cm	cannot be dimmed	3.600 lm	6.500 K	10 pieces	10 / box	1/10	
345615	18 W	120 cm	cannot be dimmed	2.700 lm	4.000 K	10 pieces	10 / box	1/10	
345613	18 W	120 cm	cannot be dimmed	2.700 lm	6.500 K	10 pieces	10 / box	1/10	

### **LED Tubes and Moisture-proof Lights**

Made in Germany

### Moisture-proof diffuser light for LED tubes

• housing made from glass fibre reinforced polyester, low inflammability • cover made from acrylic glass (PMMA), transparent, pearled interior, with clip locks • protected against powerful water jets and dustproof (IP 65 protection class) • with D marking according to DIN EN 60598-2-24, therefore suitable for areas at risk of fires due to combustible dusts or fibres (hay storage, feed, litter, etc.) • incl. microfuse • no bridging starter required • only suitable for T8 LED Tubes (Ø 26 mm) • suitable for LED tubes EcoSTAR and EcoSTAR Plus • 2-year warranty

Technical da	ata					
Protection cl	ass	IP65				
Protection cl	ass	I				
- (			Æ			
Ref. no.	Colour	Length	H1		€	
34561	white	120 cm	1	120		Light course not
34562	white	150 cm	1	120		<ul> <li>Light source not included!</li> </ul>

### Moisture-proof diffuser light for LED tubes

• only suitable for T8 LED tubes • no bridging starter required • protected against powerful water jets and dust-proof (IP 65 protection class) • unbreakable housing with a high resistance to ammonia • with D marking according to DIN EN 60598-2-24, therefore suitable for areas at risk of fires due to combustible dusts or fibres (hay storage, feed, litter, etc.) • incl. installation clips made of stainless steel • Lamp Base: G13

Technical da	ata				
Protection cl	ass	IP65			
Protection cl	ass	I		_	New product (NEW)
Ref. no.	Length	Ħ	€		New product
345670	120 cm	1/12	Ľ		
34567	150 cm	1/9		<ul> <li>Light source not</li> <li>included!</li> </ul>	$\cup$
					V

cannot be dimmed

### LED moisture-proof lamp FarmSTAR

Perfect for rough conditions in wet, moist or dusty environments!

• for lighting stables, riding halls, industrial buildings and warehouses, barns, workshops, etc. • with integrated high-performance LED chips (no fluorescent tubes required) • protected against powerful water jets and dust-proof (IP 65 protection class) • with D marking according to DIN EN 60598-2-24, therefore suitable for areas at risk of fires due to combustible dusts or fibres (hay storage, feed, litter, etc.) • stable, shock-resistant housing made from ABS plastic • uniform and glare-free illumination due to a frosted cover • incl. installation clips made of stainless steel • Light angle: 140 ° • Voltage: 220 - 240 V • 2-year warranty • D-label

Technical da	ata					
Voltage				220 - 24	40 V	
Mains frequ	ency			50 - 60	Hz	
Luminous ef	ficacy			2.000 lr	m/W	
Light angle	(half intensit	y angle)	140 °			
Chip service	life (L70)		> 30.000 h			
Material			ABS plastic			
Colour rend	ering (CRI)		Ra > 80			
Protection c	lass			IP65		
Protection c	lass					
Ref. no.	Power	Length	Width	Height	Dimming function	

7,5 cm

7,8 cm



The lights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.

120 cm

25 W

## LED Tubes and Moisture-proof Lights

### LED moisture-proof lamp FarmPRO

#### Perfect for animal stalls!

• suitable for low to medium-high ceiling heights • extremely tough aluminium housing with safety glass – no plastic content • resistant to ammonia (DLG-tested) • flicker-free, thus also for poultry with high visual acuity • protected against powerful water jets and dust-proof (IP 65 protection class) • with D marking according to DIN EN 60598-2-24, therefore suitable for areas at risk of fires due to combustible dusts or fibres (hay storage, feed, litter, etc.) • with integrated high-power LED chips from Philips • very high efficiency and energy cost savings • extremely high service life and switching capacity • high colour reproduction (Ra > 80), suitable for nearly all operating site according to workplace guidelines • incl. installation clips made of stainless steel • incl. 1 m connection cable with stainless steel screw connections • Light angle: 112 ° • Voltage: 100 - 277 V • 5-year warranty • DLG tested

Technical da	ta			the second	2222		
Voltage			100 - 277 V	New pr	oduct	NEW	5-year warranty
Mains freque	ency		50 - 60 Hz		ouuce		المع والح
Luminous eff	icacy		130 lm/W				
Light angle (	half intensity angle)		112 °				KERBL
Chip service	life (L70)		> 100.000 h			N.C.	
Colour rende	ring (CRI)		Ra > 80			V.	
Protection cl	ass		IP65			4	WW.DLG. OF DLG-Prüfbericht 7018
Protection cl	ass						
Ref. no.	Power	Length	Dimming function	Luminous flux	Ø	€	$\overline{D}$
345616	40 W	90 cm	cannot be dimmed	5.200 lm	1/6		V
345617	60 W	120 cm	cannot be dimmed	7.800 lm	1/4		-

The lights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.

### LED moisture-proof lamp

#### Perfect for rough conditions in wet, moist or dusty environments!

• for lighting stables, riding halls, industrial buildings and warehouses, barns, workshops, etc. • with integrated high-performance LED chips (no fluorescent tubes required) • high energy cost savings compared to regular T8 fluorescent lamps • water-proof and dust-proof (IP 67 protection class), corrosion-protected • with D marking according to DIN EN 60598-2-24, therefore suitable for areas at risk of fires due to combustible dusts or fibres (hay storage, feed, litter, etc.) • stable, shock-resistant housing made from polycarbonate • uniform and glare-free illumination due to a frosted cover • incl. installation clips made of stainless steel • Light angle: 130 ° • Voltage: 100 - 277 V • 5-year warranty

				6		-
echnical da	ta					
Voltage			100 - 277 V			
Mains freque	ency		50 - 60 Hz			
Luminous eff	icacy		120 - 125 lm/W			
Light angle (	half intensity ang	le)	130 °			
Chip service	life (L70)		> 50.000 h			
LED type			SMD 2835			
Operating an	nbient temperatu	re	-40 - 50 °C			
Colour rende	ring (CRI)		Ra > 80			
Protection cla	ass		IP67			
Energy efficie	ency class		A++			
Ref. no.	Power	Length	Width	Height	Luminous flux	Colour temperat

Ref. no.	Power	Length	Width	Height	Luminous flux	Colour temperature	Ħ		€
34546	40 W	1.192 mm	72 mm	82 mm	5.000 lm	6.000 K	1/6	48	
34547	55 W	1.492 mm	72 mm	82 mm	6.500 lm	6.000 K	1/6	48	

The lights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.

GE#

Ŧ

### **LED Outdoor Spotlight**

The LED outdoor lamps reflect the latest LED technology and boast efficiency, compact design and an extremely attractive price-performance ratio! Compared to conventional spotlights, you can achieve a high level of cost savings and enjoy the many other benefits of LED lighting.



Intertel

NEW

• compact design • for lighting stalls, barns, sheds etc. • with energy-efficient, SMD LED chips • up to 80 % less power consumption • uniform and glare-free illumination due to a frosted cover • robust housing made from cast aluminium with safety glass • with adjustable clamping bracket • incl. 1 m connection cable • Light angle: 100 ° • Voltage: 220 - 240 V • suitable for outdoor use • 2-year warranty • GS-tested

Technical data	
Voltage	220 - 240 V
Mains frequency	50 Hz
Luminous efficacy	80 lm/W
Light angle (half intensity angle)	100 °
Chip service life (L70)	> 30.000 h
LED type	SMD
Material	Die-cast aluminium
Colour rendering (CRI)	Ra > 65
Switch cycles	> 15.000
Cable length	100 cm
Protection class (without motion sensor)	IP65
Protection class (with motion sensor)	IP44



Ref. no.	Description	Power	Width	Height	Depth	Dimming function	Luminous flux	Colour temperature	Ø		€
345680	without motion sensor	10 W	106 mm	114 mm	38 mm	cannot be dimmed	800 lm	6.000 K	1/24	864	
345681	without motion sensor	20 W	136 mm	121 mm	47 mm	cannot be dimmed	1.600 lm	6.000 K	1/16	512	
345682	without motion sensor	30 W	180 mm	156 mm	62 mm	cannot be dimmed	2.400 lm	6.000 K	1/12	360	
345683	without motion sensor	50 W	230 mm	220 mm	67 mm	cannot be dimmed	4.000 lm	6.000 K	1/8	192	
345684	without motion sensor	100 W	285 mm	250 mm	64 mm	cannot be dimmed	8.000 lm	6.000 K	1/4	128	
345685	with motion detector	10 W	106 mm	150 mm	70 mm	cannot be dimmed	800 lm	6.000 K	1/24	576	
345686	with motion detector	20 W	136 mm	158 mm	70 mm	cannot be dimmed	1.600 lm	6.000 K	1/16	288	
345687	with motion detector	30 W	180 mm	191 mm	71 mm	cannot be dimmed	2.400 lm	6.000 K	1/12	324	
345688	with motion detector	50 W	230 mm	238 mm	71 mm	cannot be dimmed	4.000 lm	6.000 K	1/8	128	
345689	with motion detector	100 W	335 mm	330 mm	64 mm	cannot be dimmed	8.000 lm	6.000 K	1/4	96	

The spotlights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.



## **Mobile Spotlights and Lamps**

360°

GE/

獗

Ŧ


NEW

New product

#### **LED Oval Light**

ideal for passage areas, garage, basement, etc.
 sturdy plastic housing with glazed cover
 Splash-proof
 ceiling or wall mounting
 with energy-efficient, SMD LED chips
 up to 80 %
 less power consumption
 Light angle: 100 °
 Voltage: 220 - 240 V
 suitable for outdoor use
 2-year warranty
 TÜV-GS approved

Technical data	345606
Voltage	220 - 240 V
Mains frequency	50 Hz
Luminous efficacy	80 lm/W
Light angle (half intensity angle)	100 °
Chip service life (L70)	> 30.000 h
Colour rendering (CRI)	Ra > 80
Protection class	IP54



1

The lights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.

### Mobile LED Battery Spotlight WorkFire Pro 30

 sturdy plastic housing • steplessly adjustable stand • with additional carry handle / mounting bracket • incl. power bank function • Li-ion battery with a charge status display and integrated overcharging and deep discharging protection • LED source: 30 W COB
 incl. USB cable and USB power pack • Dual operation (battery/cable) • with On/Off switch • dust-proof jet-proof • suitable for outdoor use

Technical data	345608
Luminous efficacy	83 lm/W
Chip service life (L70)	> 50.000 h
Light levels	3 light levels
Light level modes	100 % / 50 % / Warning light flashing red
Material	Plastic
Voltage	5 V
Battery technology	Li-Ion
Battery capacity	8.000 mAh
Battery charge time	8 h
Hours of light	~ 1,5 h 100 %, ~ 3 h 50 %, ~ 6 h Flashing
Colour rendering (CRI)	Ra > 70
Protection class	IP65



Ref. no.	Colour	Power	Length	Width	Height	Luminous flux	Colour temperature	Ø		€
345608	black / yellow	30 W	20,5 cm	18 cm	6,5 cm	2.500 lm	6.500 K	1/4/8	192	

### **Mobile Spotlights and Lamps**

### Mobile LED Battery Spotlight WorkFire Pro

• sturdy plastic housing with silicon edge protection • adjustable stand, can also be usedas a carrying handle or mounting bracket • Li-ion battery with a charge status display and integrated overcharging and deep discharging protection • confusion-proof low-heat device charging cable with earthed plug • with energy-efficient, SMD LED chips • up to 80 % less power consumption • with On/Off switch • Splash-proof impact and shock-resistant • suitable for outdoor use • 2-year warranty • Battery built-in

1	SPL	
1		0
	4	
-6	1	

Technical da	ata
--------------	-----

80 lm/W
> 35.000 h
3 light levels
100 % / 50 % / 20 %
7,4 V
Li-Ion
4.400 mAh
5 hours
approx. 2,5 h, approx. 5 h, approx. 8 h
Ra > 80
IP54
A++

Intertek



Ref. no.	Colour	Power	Length	Width	Height	Luminous flux	Colour temperature	Ø		€
345605	black / yellow	20 W	23 cm	16 cm	6 cm	1.600 lm	6.000 K	1/6	360	

The lights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.

### **LED Floodlight**

• robust housing made from cast aluminium with safety glass • robust tubular frame with cable bracket • with adjustable clamping bracket • with plastic carrying handle • 230 volt connecting cable with earthed plug, length 3 m • with energy-efficient, SMD LED chips • up to 80 % less power consumption • Light angle: 100 ° • Voltage: 220 - 240 V • suitable for outdoor use • 2-year warranty • GS-tested

Technical data	
Voltage	220 - 240 V
Mains frequency	50 Hz
Luminous efficacy	75 lm/W
Light angle (half intensity angle)	100 °
Chip service life (L70)	> 35.000 h
LED type	SMD
Material	Die-cast aluminium
Colour rendering (CRI)	Ra > 80
Cable length	3 m
Protection class	IP65



Ref. no.	Colour	Power	Length	Width	Height	Dimming function	Luminous flux	Colour temperature	Ø	Ħ	€
345604	yellow / black	50 W	32 cm	22 cm	40 cm	cannot be dimmed	3.750 lm	6.000 K	1/2	32	

DEKRA

The lights comprise built-in LED bulbs. The bulbs in the light cannot be replaced.

## **Electric Insect Control**

#### Electric fly killers orig. Halley

- Cost-efficient and economical: Low energy consumption
- Effective and practical: Works both in daylight and artificial light.
- Suitable for hanging (holding eyelet) or standing.
- since 1985



GE/

36

Ŧ

<u>جم</u> 360°

299806

### Halley Insect Killers 2138


• Splash protection (IP 44) for the special conditions in agriculture

Technical data			299804			-
Voltage			230 V			Ho
Mains frequenc	у		50 Hz		-	
Effective area			150 m <sup>2</sup>			
High voltage			5.000 V			
Protection class			IP44			
Housing materia	al		Aluminium			
Dimensions (W	x D x H)		51 x 12 x 39	cm		
Ref. no.	Lamps	Ø		€		1
299804	2 x 15 W	1	40			
Ref. no.	Description		Power	Colour	Ø	€
299811	Spare Pipe		15 W	blue	1/25	



### Halley Insect Killers Green Line

• the proven fly trap now also with green fluorescent tubes • Testimonials have shown that flies and insects are more attracted to green light tubes than blue ones under certain circumstances. This can greatly increase the catch numbers of the "green line" fly killer as opposed to the standard blue model. • Splash protection (IP 44) for the special conditions in agriculture




Technical dat	а	299806		299807	
Voltage		230 V		230 V	
Mains frequer	псу	50 Hz		50 Hz	
Effective area		300 m <sup>2</sup>		300 m²	
High voltage		5.000 V		5.000 V	
Protection clas	SS	IP44		IP44	
Housing mate	rial	Aluminium		Aluminium	
Dimensions (V	V x D x H)	66 x 12 x 3	1 cm	66 x 12 x 52	2 cm
Ref. no.	Description	Lamps	Ø	Ħ	€
299806	Mod. 2214/B	2 x 20 W	1	36	
299807	Mod. 2214	2 x 20 W	1	22	
Ref. no.	Description	Power	Colour	Ð	€
299819	Spare Pipe	20 W	green	1/25	

### **Electric Insect Control**

### **Insect Killers EcoKill Inox**

The electric fly killer with a high-quality stainless steel housing. All EcoKill Inox models are TÜV-GS tested and fitted with long-life UV lamps. The high-quality stainless steel matte-look housing is easy to clean and retains its attractive surface for years. The slim design with the exposed mesh facilitates optimum capture properties. • extremely robust thanks to stainless steel housing • Including suspension chain and collecting tray • outstanding value for money • corrosion-resistant and scratchproof • special UVA lamp which is very attractive to insects



Technical data		299930	29993	1	299932	
Voltage		230 V	230 V		230 V	
Mains frequency		50 Hz	50 Hz		50 Hz	
Effective area		80 m <sup>2</sup>	150 m	2	200 m <sup>2</sup>	
High voltage		2.200 V	2.200	V	2.200 V	
Housing material		stainless steel	stainle	ss steel	stainless s	steel
Dimensions (W x D	x H)	34 x 11,5 x 32,5 cm	56 x 11	,5 x 32,5 cm	72 x 12 x 3	32,5 cm
Ref. no.	Description	Lan	ıps	Ø		€
299930	Model 2012	2 x	6 W	1/3	108	
299931	Model 2030	2 x 1	5 W	1/3	60	
299932	Model 2040	2 x 2	0 W	1/2	48	
					Æ	
Ref. no.	Description	Power		Colour	Ð	€
299812	Spare Pipe	6 W		blue	1/25	
299986	Spare Pipe	15 W		blue	1/25	
299987	Spare Pipe	20 W		blue	1/25	



## **Electric Insect Control**

GE7

**Å** 

Ŧ

IIN

Top Seller

360°

299935

### **Insect Killers EcoKill**

• extremely lightweight aluminium construction • Including suspension chain and collecting tray • outstanding value for money • corrosion-resistant and scratchproof • special UVA lamp which is very attractive to insects

Technical data	1	:	299950	
Voltage			230 V	
Mains frequen	су		50 Hz	
Effective area			150 m²	
High voltage			2.200 V	
Housing mater	rial		Aluminium	
Dimensions (W	/ x D x H)	4	49 x 11 x 34	l cm
Ref. no.	Lamps	Ø		€
299950	2 x 15 W	1/3	48	
Ref. no.	Description		Power	Colour
299811	Spare Pipe		15 W	blue

### **Insect Killers EcoKill Inox IPX4**

The fly killer with splash-proof electronics! IPX4 ensures adequate safety in areas such as stalls, outdoors or simply anywhere that a certain level of moisture cannot be ruled out! Identical in terms of shape, performance data and design to the EcoKill Inox without splash protection!

299936

EcoKill Inox IPX4



Ħ

1/25

€

\_\_\_\_\_

Technical data	299935	299936
Voltage	230 V	230 V
Mains frequency	50 Hz	50 Hz
Effective area	150 m <sup>2</sup>	200 m <sup>2</sup>
Protection class	IPX4	IPX4
Housing material	stainless steel	stainless steel
Dimensions (W x D x H)	56 x 11,5 x 32,5 cm	72 x 12 x 32,5 cm

299935 2 x 15 W 1/3 60	C		Ð	Lamps	Ref. no.
233333 2 X 13 W 1/3 00		60	1/3	2 x 15 W	299935
299936 2 x 20 W 1/2 48		48	1/2	2 x 20 W	299936

Ref. no.	Description	Power	Colour	Ð	€
299986	Spare Pipe	15 W	blue	1/25	
299987	Spare Pipe	20 W	blue	1/25	





## **Insect Traps**

### cit Fly roll 3D

Adhesive catcher with special 3D print to combat flies and flying insects

- the 3D printing simulates edges and stripes and thus potential landing sites
- for flies this increases the attractiveness to flieswith new improved adhesive coating
- Mill new improved a
  100 % non-toxic



Ref. no.	Roll length	Roll width	Ø		€
299904	9 m	30 cm	1/15	540	
299905	7 m	10 cm	1/70		
233303	7 111	To chi	1//0		

### Stable Fly Roll ECO

• glue trap for controlling flies and flying insects • 100 % non-toxic







### Fly roll

• glue trap for controlling flies and flying insects • with yellow paper for even greater attraction of flies and insects • with new improved adhesive coating • 100 % non-toxic



Ref. no.   Roll length   Roll width   Fastening   Image: Provide the second s							
20078 7 m 30 cm with banger 1/15 540	Ref. no.	Roll length	Roll width	Fastening	Ð		€
	29978	7 m	30 cm	with hanger	1/15	540	

Flyroll Rotolo contro le mosche

#### **Insect Traps** Fly roll • flies are attracted by the paper and remain stuck on the trap • the new form of printing on yellow paper improves the attractant's appeal, since it simulates apparent GE/ landing spots • simple - clean - non-toxic - 100 % effective • 100 % non-toxic Top Sellei with yellow paper attractant Made in the EU approved for use on Ħ Ref. no. **Roll length** Roll width Fastening Bio € organic farms 1/15 299847 9 m 30 cm with hanger 540 **Fly roll JumboXL** • the new form of printing on yellow paper improves the attractant's appeal, since it simulates apparent landing spots • simple - clean - non-toxic - 100 % effective • Stable fly reel with large capture surface at an absolute bargain price Ŧ Made in the EU Fly roll with XL catching surface of 4 m<sup>2</sup> approved for use on Bia organic farms Ref. no. Roll length Roll width Fastening Ħ € 299789 10 m 40 cm with hanger 1/15 450

### Stable Flypaper Sheet FlyMaster

• 6 sheets each 595 x 300 mm • flyMaster Flypaper reliably catches flies due in stables, milking parlours and inside houses • You can catch up to 5,000 flies and/ or cover around 200 m<sup>2</sup> with one sheet • Usage: Hang the whole or cut fly sheet - remove protective film - finished! • 100 % non-toxic

with yellow	paper attractan	t			
Ref. no.	Length	Width	Ħ		€
299842	59,5 cm	30 cm	1/50	1.400	



## **Insect Traps**

Made in the EU

### Stable Fly Catcher FlyMaster Complete Set

 $\bullet$  environmentally-friendly alternative for stable fly control  $\bullet$  spent material is rolled onto the empty reel (included)  $\bullet$  easy self assembly  $\bullet$  Spare rolls can be easily replaced







	29976
	1
WILL?	0
?? ФФ 💭 💭 💭	

100	%	non-toxic
-----	---	-----------

Ref. no.	Description	Roll length	Ð	Ħ	€			
29976	Adhesive tape	400 m	1	96				29977
299776	Adhesive Cord	440 m	1	96				
Ref. no.		Description			Roll length		€	
299777	Roll FlyMaster Stable Fly Catcher Adhesive Cord				440 m	1		
29977	Roll FlyMast	er Stable Fly Catche	er Adhesive	tape	400 m	1		

### **Roll Stable Fly Catcher**

• Spare Fly Trap Roll, suitable for e.g. systems from Flyson, Fly-End, Silva

Ref. no.	Roll length	Ø		€
299779	440 m	1	240	

### Fly Trap FlyCage2

• the number of flying insects caught can provide an indication of an infestation or high numbers, allowing control measures to be instigated • easy to use, very effective • effective for 4 to 6 weeks depending on the weather • Material: Plastic

Ref. no.	Ø		€	100 % non-toxic
299851	1/20	600		





### Fly Catcher Twister

• the glued paper strip is made from natural ingredients such as resins, oils and fats • the free-hanging fly trap provides the perfect landing pad for flying insects • use the red strap to carefully pull the rolled-up twister out of the lukewarm case and use the tacks provided to fasten to the ceiling • Supplied with a display when purchasing 24 pieces. • 4 piece / box

The classic one – 100 % non-toxic!							
Ref. no.	MOQ	Pieces / unit	Ø		€		
299839	1 pack	4 / pack	1/24/144	3.456			

### **Rat and Mouse Traps**

### **Ultrasound Device Felix**

• Modern and efficient system for keeping mice and rats away • Environmentally friendly and not harmful to either persons or pets • only mice and rats can hear the ultrasound, making them flee • Applications: closed stables, storehouses, offices, houses, wine cellars, restaurants, hotels, cafés etc. • suitable for indoor use



GE/

j,

**(**)


Ŧ

			°	POWER	0
Technical data	29986			N A	
Voltage	220 - 230 V		+0		
Mains frequency	50 - 60 Hz				0
Power	10 - 30 W				
Sound pressure level	96 - 110 dB				
High frequency	22.000 - 28.000 Hz				
Effective area	100 - 200 m <sup>2</sup>				
Effective area with 10 speakers	600 - 1.200 m <sup>2</sup>	Ref. no.	Ð	€	
Housing material	metal	29986	1/6		Up to
Ref. no.	Description		Ø	€	single
29987	Additional Speaker for Felix		1/18		

Up to 10 external speakers can be connected to the device, with a single range of 80-100 m<sup>2</sup>.

### **Mousetrap Luna**

• with wooden shutter • 2 pieces on a tab card



### Rat trap Luna

• with wooden shutter

Ref. no.	MOQ	Pieces / unit	Ø		€
299613	1 blister pack	1 / blister pack	1/30	2.160	

#### **Mousetrap Snapper**

made of robust plastic

Ref. no.	Length	Width	MOQ Pieces / unit	Ð		€
299826	11 cm	5 cm	1 blister pack 2 / blister pack	1/100	1.000	

### Rat trap Snapper

• made of robust plastic

Ref. no.	Length	Width	MOQ Pi	eces / unit	Ē		€
299834	14 cm	7,5 cm	1 blister pack 1 /	blister pack	1/40	560	

### **Rat and Mouse Traps**

#### Mousetrap mouseStop

- effective and ready-to-use mousetrap incl. special trigger
- used trigger can be replaced quick as a flash
- · effective immediately after activation of the bait simply remove the protective cap
- guaranteed trapping efficiency due to the calibrated punch of the trigger mechanism
- Material: Plastic
- 100 % non-toxic



Top Seller

299822: For orders of 16 pieces, the delivery takes place in a representative counter display



•	simple	•	safe	•	non-toxic
---	--------	---	------	---	-----------

Ref. no.	Description	MOQ	Pieces / unit	Ø		€
299822	in pairs	1 pack	2 / pack	1/16	1.440	
299823	in a stand display	44 pack	44 / display	1/44	880	
Ref. no.	Description	Material	MOQ P	ieces / unit	Ø	€
299824	Bait mouseStop	Plastic	1 blister pack 6	/ blister pack	1/20/680	



### Rat trap ratStop

- effective and ready-to-use rat trap incl. special trigger
- used trigger can be replaced quick as a flash
- · effective immediately after activation of the bait simply remove the protective cap
- guaranteed trapping efficiency through calibrated trigger mechanism
- Material: Plastic
- 100 % non-toxic





299825: For orders of 12 pieces, the delivery takes place in a representative counter display



### 360°

#### • simple • safe • non-toxic

Ref. no.	Description	MOQ	Pieces / unit	Ð		€
299825	single	1 blister pack	1 / blister pack	1/12	696	
2998250	in a stand display	25 pieces	25 / display	1/25	500	
Ref. no.	Description	Material	MOQ	Pieces / unit	Ð	€
2998251	Bait ratStop	Plastic	1 blister pack	3 / blister pack	1/10/360	

### **Cage Mousetrap Alive**

- with plastic base
- 2 entrances
- made from galvanised wire
- with opening flap
- no residues from previous catches, therefore higher catch rate



Ref. no.	Length	Width	Height	Ø		€
299617	15 cm	15 cm	7,5 cm	1/12/72	288	

### **Infrared Heater**

• Aluminium Screen ø 21 cm • with 6 air vents for better air circulation, extending the life of the infrared lamp • Fastening chain (max. 20 kg load capacity) • max. 175 W lighting source for equipment with economy switches! • E27

- 22318: in individual cardboard packaging
- 225280: in individual cardboard packaging

22291-S

2229-Е









€

Ref. no.	Cable length	Switch type	Plug type	MOQ	Pieces / unit	Ħ		
2228	2,5 m		with Euro flat plug	2 pieces	2 / box	1/2	192	
22281	2,5 m	with economy switch	with Euro flat plug	2 pieces	2 / box	1/2	192	
2229	5 m		with Euro flat plug	2 pieces	2 / box	1/2	192	
22318	5 m		with Euro flat plug			1	96	
22291	5 m	with economy switch	with Euro flat plug	2 pieces	2 / box	1/2	192	
225280	5 m	with economy switch	with Euro flat plug			1	96	
2229-E	5 m		with British plug	2 pieces	2 / box	1/2	192	
22291-S	5 m	with economy switch	with Swiss plug	2 pieces	2 / box	1/2	192	
Ref. no.		Description		Ø	€			
22296	Po	rcelain Socket for prote	ective cage	1/15/300				

### **Philips Infrared Energy-Saving Lamp**

 sturdy design thanks to moulded glass • Save up to 30 % on your energy costs now (compared to conventional infrared lamps) • This lamp stands out from the crowd thanks to its cost-effectiveness (average service life approx 5,000 hours), excellent heat transmission directed straight toward the animal, directly warming the surface of its skin. This ensures an optimum heat balance and boosts circulation in the tissues and muscle layers • universally usable e.g. poultry, piglets, veterinary therapy, drying processes for feed and food in agriculture
 fits infra-red heater • splash-proof • Lamp Base: E27 • PAR 38 • Voltage: 230 V

Ref. no.	Colour	Power	Ø		€
22302	red	100 W	1/12	396	
22303	red	175 W	1/12	396	
22304	Clear	100 W	1/12	396	
22309	Clear	175 W	1/12	396	

Save up to 30 % on your energy costs!

## PHILIPS

## **Pig Breeding**

GE/

Ŧ

Made in Germany

### Digital thermometer for large animals

• with 14 cm-long probe • high precision • storage of the last value • Automatic shut-off

- waterproof - battery change display - operated with: 1 x 3 V - CR2032 Lithium-ion

Technical data	2138
Temperature measuring range	32 - 43,9 °C
Measuring time	8 sec
Temperature can be selected	Celsius °C / Fahrenheit °F
Temperature measurement accuracy	+/- 0,1 °C
. 77	

Ref. no.	Ð	€	Ref. no.	Description	Ē
2138	1/6/24		29918	Button Battery 3 Volt	1/20

### Digital thermometer topTEMP

 ${\mbox{ \bullet}}$  Digital thermometer for rectal use for animals  ${\mbox{ \bullet}}$  ergonomically tailored to the animal

• operated with: 1 x 1.5 V - AAA (Micro) • Battery included

Technical data	21124			
Temperature measuring range	32 - 42 °C			
Measuring time	10 - 15 sec	-		
Temperature can be selected	Celsius °C / Fahrenheit °F			
Temperature measurement accuracy	+/- 0,1 °C	Ref. no.	Ĥ	€
Weight	69 g	21124	1/32	



• high precision • rapid measurement in 10 seconds (rectal) or 17 seconds (oral) • automatic audible signal at the end of measurement • storage of the last value • Automatic shut-off • each with transparent protective cover • waterproof • battery change display • operated with: 1 x 1.5 V - R41 Alkaline-manganese • Battery included

Technical data	3			
Temperature m	neasuring range	32 - 42 °C		
Temperature m	neasurement accuracy	+/- 0,1 °C		
Ref. no.	Description	Colour	Ē	€
2136	with rigid probe	purple	1/10/200	
2137	with flexible probe	orange	1/10/200	

### Digital thermometer BigScreen

with flexible probe • high precision • with indicator backlight: green - no fever, red - fever region • automatic audible signal at the end of measurement • storage of the last value
Automatic shut-off • waterproof • battery change display • operated with: 1 x 3 V - CR2032 Lithium • Battery included

Technical data	2130
Temperature measuring range	32 - 43,9 °C
Measuring time	10 sec
Temperature can be selected	Celsius °C / Fahrenheit °F
Temperature measurement accuracy	+/- 0,1 °C
,	

e		[301	19
Ref. no.	€		
2130	1/6/24		
Ref. no.	Description	Ē	€
29918	Button Battery 3 Volt	1/20	



TAF F





**Veterinary Equipment** 

NEW

GE#

Ŧ

New product

### Lamb Feeder Tray Multi Feeder

#### with portioning

with 5 portion compartments for the simultaneous provision of drinks to up to 5 lambs • with 5 Little Softy Teats (item no. 27120)
makes animal surveillance easier during milk feeding • Volume per portion compartment: 3 litres • with rounded corners, thus very easy to clean • for hanging on barn walls, feed barriers, fences, etc.
easy mounting and securing of the trough thanks to elastic straps
stackable • easy to transport • food safe • acid-proof

stackable	easy to transport • food safe	• acid-proof						l		
Ref. no.	Capacity	Length	Width	Height	Ø	€				
27700	30 L	81 cm	43 cm	38 cm	1				27120	
Ref. no.	Description	Colour	Longth	Width	Unight	Capacity	MOO	Pieces / unit	Ħ	£
Rel. no.	Description	Colour	Length	Width	Height	Capacity	MOQ	Pieces / unit		€
14205	Drinking Trough Multi Feeder without teat	green	81 cm	43 cm	38 cm	30 L			1	
14142	Corner for Big Softy and Little Softy teats with valve	orange					1 pack	10 / pack	1	
14144	Corner for Big Softy and Little Softy teats without valve	white					1 pack	10 / pack	1	
14214	Cover for Multi Feeder	black							1/100	
27120	Teat Little Softy	white						25 / pack		
27120/5	Teat Little Softy	white					1 pouch	5 / pouch	1	

### Lamb Bucket

Ref. no.

27500

• for feeding up to 6 lambs • with metal bracket for hanging on barn walls, feed barriers, fences, etc. • stackable • Material: Plastic • food safe • with metal carry handle

Included in delivery: 1 x lamb feeding bucket, 6 x teat (item 274), 6 x teat (item 275)

Colour

green



Capacity

12 L



Ref. no.	Description	Colour	MOQ	Pieces / unit	Ø	€
274	Teat	yellow	6 pieces	6 / pack	1/6/600	
274/6	Teat	yellow	1 blister pack	6 / blister pack	1	
275	Valve		6 pieces	6 / pouch	1/6/1.200	
275/6	Valve		1 blister pack	6 / blister pack	1	
324482	Cover for buckets and feeding bowls	black	1 pack	2 / pack	1/100	

### Lamb Bucket

 for feeding up to 6 lambs
 residue-free drainage thanks to angled base
 for hanging on barn walls, feed barriers, fences, etc.
 stable plastic
 with metal carry handle

274

Capacity

2 x 5 L

Included in delivery: 1 x lamb feeding bucket, 6 x teat (item 274), 6 x teat (item 275)



Ref. no.	Description	Colour	MOQ	Pieces / unit	Ø	€
274	Teat	yellow	6 pieces	6 / pack	1/6/600	
274/6	Teat	yellow	1 blister pack	6 / blister pack	1	
275	Valve		6 pieces	6 / pouch	1/6/1.200	
275/6	Valve		1 blister pack	6 / blister pack	1	
324482	Cover for buckets and feeding bowls	black	1 pack	2 / pack	1/100	

### Lamb Bucket

Ref. no.

27510

• for feeding up to 6 lambs • complete with retaining plate, teats and valves • flattened on both sides • reinforced design • Supplies without cover • Material: Plastic • food safe • with metal carry handle

Colour

dark green





Ref. no.	Colour	Capacity	Watering places	Ø		€
271	green	8 L	6	1	240	

Ref. no.	Description	Colour	Material	MOQ	Pieces / unit	Ø	€
274	Teat	yellow		6 pieces	6 / pack	1/6/600	
274/6	Teat	yellow		1 blister pack	6 / blister pack	1	
275	Valve			6 pieces	6 / pouch	1/6/1.200	
275/6	Valve			1 blister pack	6 / blister pack	1	
14211	Cover for Feeding Bucket simply	green				1/50	
1410	Mounting Bracket simply		metal galvanised	10 pieces	10 / pack	1/10/150	

**Top Seller** 

1410

...

### Lamb Bucket

· complete with retaining plate, short, red teats and valves • Material: Plastic • food safe • with metal carry handle

É.

派

Ŧ



Ref. no.	Description Colour		Capacity		Watering places			€
276	with 5 red teats (item no. 277)	grey		8 L	5	1	240	
2769	with 3 red teats (item no. 277)	grey		8 L	3	1	240	
Ref. no.	Description		Colour	Material	MOQ	Pieces / unit	Ø	€
149	Screw Valve complete		grey	Plastic	10 pieces	10 / pack	1/10	
277	Teat		red		20 pieces	20 / pack	1/20/1.000	
2784	Teat		white		20 pieces	20 / pack	1/20/1.000	
27111	Teat		beige		20 pieces	20 / pack	1/20/800	
277/5	Teat		red		1 blister pack	5 / blister pack	1	
1410	Mounting Bracket simply			metal galvanised	10 pieces	10 / pack	1/10/150	

### Lamb Bucket transparent

• fill level easy to see from a distance • complete with retaining plate, teats and valves

• flattened on both sides • food safe • with metal carry handle • with printed measurement

scale, with additional embossed scale on the inside

New product NEW





Ref. no.	Description	Colour		Capacity	Watering place	s 🗐		€
27512	with 6 teats	white transparent	t	8 L	6	1	240	
27513	with 5 short, red teats	white transparent	t	8 L	5	1	240	
27514	with 5 Little Softy Teats	white transparent	t	8 L	5	1		
D (			<b>C</b> 1			<b>D</b> <sup>1</sup> ( );	Æ	6
Ref. no.	Description		Colour	Material	MOQ	Pieces / unit	Ø	ŧ
149	Screw Valve compl	ete	grey	Plastic	10 pieces	10 / pack	1/10	

149	Sciew valve complete	grey	Flastic	To pieces	107 pack	1/10	
274	Teat	yellow		6 pieces	6 / pack	1/6/600	
274/6	Teat	yellow		1 blister pack	6 / blister pack	1	
277	Teat	red		20 pieces	20 / pack	1/20/1.000	
277/5	Teat	red		1 blister pack	5 / blister pack	1	
1410	Mounting Bracket simply		metal galvanised	10 pieces	10 / pack	1/10/150	
27120	Teat Little Softy	white		25 pieces	25 / pack	1/25/250	
27120/5	Teat Little Softy	white		1 pouch	5 / pouch	1	

### Lamb Bottle Anti-Vac

 $\bullet$  complete with teat  $\bullet$  special regulation of the flow rate  $\bullet$  wide spout for easy filling  $\bullet$  Material: Plastic  $\bullet$  with printed measurement scale

Ref. no.	Colour	Capacity	Ø		€
278	transparent	450 ml	1/24/144	1.728	
Ref. no.	Description	MOQ	Pieces / unit	Ø	€
279	Teat for 278			1/50/1.000	
279/2	Teat for 278	1 blister pack	2 / blister pack	1/60	



### Holder for lamb bottle

• for hanging on fences, pens, etc. • for 5 lamb bottles • suitable for Lamb Bottles Anti-Vac (item no. 278) • with plastic coating, making them very long-lasting • for hanging

Ref. no.	Colour	Ø		€
27110	dark green	1	36	

### Lamb Bottle

• complete with teat • with hanging tab on the bottle base

Material: Plastic • with embossed measuring scale

Ref. no.	Colour	Capacity	Ð		€	
2780	white	1000 ml	1/20	320		
Ref. no.	Description	Colour	MOQ	Pieces / unit	Ĥ	€
277	Teat	red	20 pieces	20 / pack	1/20/1.000	
277/5	Teat	red	1 hlister nack	5 / blister pack	1	-
27775	Teat	ieu	i blister pack	57 blister puck	•	

### Teat for lamb bottles

• Material: Natural rubber

Ref. no.	MOQ	Pieces / unit	Ð	€
2710	6 pieces	6 / pack	1/6/600	
2710/6	1 blister pack	6 / blister pack	1	

### **Bolt-On Bottle Nipple for lambs**

• fits conventional bottle threads with an exterior diameter of 25 mm • mimics the natural shape of the mother's teat • special flutter vale ensures air flow when sucking • Material: Latex

New, impro	New, improved quality with stronger rubber!						
Ref. no.	Colour	MOQ	Pieces / unit	Æ	€		
2783/5	red / yellow	1 pack	5 / pack	1/20/200		_	





277

### **Hoof and Claw Care**

GE#

### Footbath Container SuperKombi Mini

#### for sheep

The SuperKombi Mini foot bath can be linked together successively and is ideal for hoof baths. Depending on the space available in the stable or field, this means you can create ideal situations for the animals. Consecutive baths are more hygienic: the first bath serves as a rinse to get rid of dirt and faecal residues from the hooves. The second bath, the treatment bath, thus remains free of dirt for longer, the disinfection solution remains usable for longer. The newly developed base profile ensures optimal traction. The animals go through the hoof bath more calmly, which promotes longer contact, achieving a better result. The shape and height of the profile ensure that the animal's hooves are slightly spread, allowing the hoof bath to reach areas between claws where it will be most effective more easily.

- can be flexibly expanded lengthwise high impact polyethylene for abrasion and chemical resistance
- suitable for use with all types of hoof bath solutions With gauge display











Footbaths can be lined up one after another using the teeth provided

With gauge display

Ref. no.	Colour	Length	Width	Height	Capacity	Ø		€
16610	black	120 cm	40 cm	18 cm	50 L	1	40	
Ref. no.	Description			Ð	€			
16601	Outlet for footbath / water trough			ter trough	1/100			

## **Clippers**

### Sheep Shearing Machine constanta4

• the tried-and-tested motor technology gives the constanta4 tremendous tractive power • even on matted and dirt-encrusted animals the constanta4 does not "yield" • the blades glide through thickest wool without loss of performance • special ventilation system with newly developed fan and new air duct produces substantially improved ventilation dynamics • air filter can be replaced without tools • Easy-to-service housing with ergonomic grip area for fatigue-free working • Clipper blades made from tool steel with a special HRC hardening process have excellent durability with improved grinding properties and first-class cutting capacity

Included in delivery: 1 x sheep clippers constanta4, 1 x clipper blade set, 1 x small oil bottle, 1 x screwdriver, 1 x Durable plastic case



Technical data	18993
Voltage	230 V AC
Mains frequency	50 - 60 Hz
Power	400 W
Stroke rate	approx. 2.400 strokes/min
Sound pressure level	87 dB
Cable length	3 m
Dimensions	35,5 x 8 x 10,8 cm
Weight	1.468 g without cable
Protection class	II

Ref. no.	Colour	Teeth lower/upper blade		Shearing type			Ø	€
18993	green	13 / 4	1	Sheep Shearing,	als	1/8		
Ref. no.	D	escription	Lower blade teeth	Upper blade teeth	MOQ	Pieces / unit	Ø	€
18931	Cutter head	without clipper blade					1	
18978	Shearing b	olades Upper blade		4			1/50	
18988	Во	ttom blade	13				1/50	
18913	Shear	ring Blade Set	13	4	1 blister pack	1 / blister pack	1/50	

### **Shearing blades**

• for cattle, llama and alpaca shearing with the sheep clipper



18978 Upper blade

18534 Lower blade

Ref. no.	Description	Upper blade teeth	Lower blade teeth	Shearing type	Ø	€
18534	Bottom blade		20	Cattle Shearing, very dirty animals	1/50	
18978	Upper blade	4		Alpaca Fleece, Lama Shearing, Cattle Shearing	1/50	

### Sheep Shearing Machine FarmClipper Profi

Powerful shearing machine with steplessly adjustable speed. At maximum power, the FarmClipper reaches 350 Watt and 2400 rpm. The customisable setting options for each animal and its coat conditions mean a perfect shear every time. Thanks to the fitting of premium blades, the FarmClipper produces an extremely clean and even shearing pattern. The blades glide precisely through the coat, and even heavily soiled animals are shorn professionally, leaving behind no residual hair. The FarmClipper is also an ergonomic dream. The balanced centre of gravity ensures the continuous shearing of multiple animals without the shearer getting tired. The rubberised insert in the upper part of the housing ensures a safe and non-slip grip. As a result, the FarmClipper lies perfectly in the hand and its powerful motor means it can be used for long periods of time to produce professional shearing results.

Included in delivery: 1 x sheep clippers FarmClipper Profi, 1 x clipper blade set, 1 x small oil bottle, 1 x screwdriver, 1 x Durable plastic case

#### 6-speed

Technical data	
Voltage	220 - 240 V
Mains frequency	50 Hz
Power	350 W
Stroke rate	approx. 2.400 strokes/min
Sound pressure level	87 dB
Cable length	5,5 m
Dimensions	33 x 7,8 x 9,7 cm
Weight	1.490 g without cable
Protection class	II



Ref. no.	Colour	Teeth lower/upper blade	Shearing type	Ø	€
18261	red / black	13 / 4	very dirty animals, Sheep Shearing	1/3	

Ref. no.	Description	Lower blade teeth	Upper blade teeth	MOQ	Pieces / unit	Ø	€
18140	Shearing blades Wellington Upper blade		4	1 blister pack	1 / blister pack	1/100	
18141	Shearing blades Wellington Bottom blade	13		1 blister pack	1 / blister pack	1/100	
18142	Shearing blades Wellington Clipper Blade Set (18140 + 18141)	13	4	1 blister pack	1 / blister pack	1/100	

## Clippers

GE#

1

201

Ŧ

### **Protective Clothing**

### Plant Protection Overall Typ 4

• spray tight chemical protection coverall CAT III, type 4B, 5B and 6B, suitable for use with pesticides • infection protection against blood and viruses • white with red, self-sealing zip fastener covers • the inner spun-bonded fabric provides wearing comfort, the exterior is spray-tight polyethylene • breathable but still on the arms, leqs and waist • corresponds to EN 13034:2005+A1:2009, EN ISO 13982-1:2004+A1:2010, EN 14605:2005+A1:2009, EN 1073-2:2002, EN 1149-5:2008, EN 14126:2003+AC:2004, EN 369, ISO 14644 classes ISO-7, ISO-8, ISO-9 • Areas of use: handling of agricultural chemicals, disease control, pest control, food industry, waste disposal, asbestos disposal, clean room use, etc. • III



### **Protective Clothing**

GE#

Ŧ



#### **Disposable Coverall**

• with long sleeves • non-sterile • Material: polyethylene

Ref. no.	Colour	Length	MOQ	Pieces / unit	Ð	€
3427	green	135 cm	1 pack	20 / pack	1/5	

### **Disposable Coverall Basic**

• protects against dust, dirt and splashes • with hood and zip fastener • elasticated arms, legs and waist • lightweight, soft and tear-resistant • with a zip fastener • Material: Polypropylene

Ref. no.	Colour	Size	Weight	Ð	€
3408	white	М	45 g/m²	1/50	
3409	white	L	45 g/m²	1/50	
3430	white	XL	45 g/m²	1/50	
3431	white	XXL	45 g/m²	1/50	
3479	white	XXXL	45 g/m²	1/50	

#### **Disposable Coverall**

• with long sleeves • ideal for veterinaries • with press stud

Ref. no.	Colour	Length	Ø	€
3428	white	120 cm	1/50	

### **Disposable Coverall**

protects against dust, dirt and splashes
with hood and zip fastener
elasticated arms, legs and waist
extra tear-resistant
with a zip fastener
Material: Polypropylene

Ref. no.	Colour	Size	Weight	Ø	€
3432	blue	L	55 g/m²	1/50	
3433	blue	XL	55 g/m²	1/50	
3434	blue	XXL	55 g/m²	1/50	
3482	blue	XXXL	55 g/m²	1/50	

### Washing and Cleaning Overalls with hood

the durable fabric is waterproof, breathable and is ideal for harsh, continuous work in agriculture • with watertight taped seams • zip covering with extra button facing • with sealed elasticated band at the back
tightly-closing cuffs and double leg cuffs offer optimum protection from dirt and moisture • the overalls are meant to be worn in or over boots • hood with elastic in face area and hook and loop fastening behind the head for individual fitting according to body size • a protective strip sealed into the neck piece stops water from finding its way in • with suspension loop on the neck • with 2-way zip • washable at 30 °C

Composition				
Textile		100 % Polyest	er	
Ref. no.	Colour	Size	Ø	€
291243	dark blue	М	1/5	
291244	dark blue	L	1/5	
291245	dark blue	XL	1/5	
291246	dark blue	XXL	1/5	
291247	dark blue	XXXL	1/5	



## **Protective Clothing**

### Disposable overshoe

• with elastic • 0,07 mm • Material: polyethylene

								15375
Ref. no.	Description	Colour	Length	Height	MOQ	Pieces / unit	Ð	€
15375	tall design	white transparent	40 cm	50 cm	1 pack	100 / pack	1/5	
15360	half-height version	blue transparent	40 cm	29 cm	1 pack	100 / pack	1/5	
								11

### **Disposable overshoe**

- ankle high - with elastic - 0,035 mm - Material: polyethylene

	C.	
€		dal 1/2 3

15360



Ref. no.	Colour	Length	Width	MOQ	Pieces / unit	Ē	€
15377	blue	41 cm	15 cm	1 pack	100 / pack	1/10	

### **Disposable Cap**

- prevents the spread of germs - round shape (Ø 53 cm) - with elastic rubber strap - Material: Polypropylene fleece fabric

Ref. no.	Colour	MOQ	Pieces / unit	Ø	€
15378	light blue	1 pack	100 / pack	1/10	

### Anti-Odour Cap

Protects your hair against odours!

odour-inhibiting for stable odours, fatty odours, fire and smoke odours, sweat etc.
wind and weather-resistant
breathable and heat-regulating
maximum comfort
durable seams and improved fit through even more elastic

cuffs. • also has sufficient space for long and voluminous hair • Material: Softshell and built-in anti-odour protection • breathable • washable at 30 °C

Composition				
Textile		80 % Polyester, 20 %	% polyuretha	ne
Ref. no.	Colour	Size	Ø	€
15345	black	XXS / XS	1/20	
15346	black	S / M	1/20	
15347	black	L / XL	1/20	



### Anti-Odour Headscarf

#### Protects your hair against odours!

• odour-inhibiting for stable odours, fatty odours, fire and smoke odours, sweat etc. • wind and weather-resistant

- breathable and heat-regulating maximum comfort durable seams and improved fit through even more elastic
- cuffs. also has sufficient space for long and voluminous hair Material: Softshell and built-in anti-odour protection

• breathable • washable at 30 °C

Composition				
Textile	8	0 % Polyester, 20 %	polyuretha	ne
			Æ	
Ref. no.	Colour	Size	Ħ	€
15348	black	XS / S	1/20	
15349	black	M / L	1/20	
15350	black	XL	1/20	





## **Respiratory Protection**

CE 204

GE/

Ŧ

# Respirator FFP2 without valve effective against coarse dust, liquid droplets and droplet-borne infection no personal protective equipment (PPE)

Ref. no.	MOQ	Pieces / unit	Ð	€
34510/10	1 pouch	10 / pouch	1/20	

#### Fine dust mask FFP1 NR D

• protects up to 4 x the MAK value\* • protects against dust, pollen, rust, tile dust, aqueous aerosols • EN149

Exhalation valve reduces the exhalation resistance, allowing moisture and heat to disperse more easily

\* MAK value = maximum workplace concentration (limit)

						34512/3
Ref. no.	Description	Colour	MOQ Pieces / unit	Ø	€	
34511/3	without exhalation valve	white	1 blister pack 3 / blister pack	1/5/70		
34511/10	without exhalation valve	white	1 pouch 10 / pouch	1/50		
34512/3	with exhalation valve	white	1 blister pack 3 / blister pack	1/5/70		

### Fine dust mask FFP2 NR D

• protects up to 10 x the MAK value\* • protects against quartz, cement, flour and wood dust, metal smoke, fungal spores, aqueous solutions of herbicides • EN149

Exhalation valve reduces the exhalation resistance, allowing moisture and heat to disperse more easily



KERBI

\* MAK value = maximum workplace concentration (limit)

Ref. no.	Description	Colour	MOQ	Pieces / unit	Ē	€
34513	without exhalation valve	white	1 blister pack	1 / blister pack	1/5/70	
34695/3	with exhalation valve	white	1 blister pack	3 / blister pack	1/5/70	
34695/10	with exhalation valve	white	1 display	10 / display	1/12	

### **Protective Clothing and Equipment**

### Goggles

• with direct ventilation • Frame made from PVC, lenses made from polycarbonate • can be worn over regular spectacles • quick-fastening strap • Protects against drips and flying particles • EN166 Klasse B

MOQ

a frail	
K CAL	



Ref. no.

34520

Colour

Clear

• sterile eye wash bottle with phosphate buffered rinse solution (4.9 %) • for chemical burns to the eye • high buffering capacity, especially gentle thanks to the exclusion of extraneous ingredients and preservatives • for mobile use or refilling stations and emergency kits with ergonomic eye bath and dust cap • Wash time: approx. 2.5 minutes • Shelf life: > 3 years • complies with DIN EN 15154-4

Pieces / unit

Ref. no.	Capacity	Ø	€
34534	250 ml	1/10/80	

### **Pesticide Set**

#### complies with the Federal Office of Consumer Protection and Food Safety (BVL) 2017 guidelines

Personal protective equipment for dealing with pesticides, also suitable for transportation of dangerous goods (complies with the ADR guidelines).

set includes: 1 x tightly fitting pair of goggles as per EN 166 (item no. 34520), 1 pair of nitrile gloves size 10 / XL as per EN 374 (item no. 29825), 1 x 250 ml eye wash bottle with 4.9 % phosphate buffer solution as per EN 15154-4 (item no. 34534), 1 x half mask respirator ETNA, as per EN 149 (item no. 34535) with 1 pair of multigrade combination filters ABEK1P3, as per EN 14387 (item no. 34537), 1 x spray-proof disposable coverall size XXL type 4B, 5, 6 (CAT III), as per EN 14605 (item no. 34356), in a practical, dust-proof case 39 x 29 x 10.5 cm



Ref. no.	Description	∰ 🚍 €
34507	Pesticide Set	1/10 160

# 000

#### NORAMAX Safety S5

#### NORA PU safety boots with steel toe and steel midsole

• extremely lightweight, only 970 g • excellent comfort thanks to anatomic footbed and ergonomically shaped shaft • flexible at low temperatures and cold-insulating down to -20 °C • extremely durable due to new PU system by BASF – "ELASTOPAN" • extremely anti-slip profile sole (SRC) through optimised profile geometry • self-cleaning profile outsole • NORA PU Insole Standard: extremely shock-absorbent, extremely moisture-absorbent • very good resistance to: animal fats, manure, blood, organic acids, alkalis, hydrocarbonate, alcohol • dirt-resistant, easy-clean surface • large, asymmetric comfort steel cap on 11 width base • Pull-out Aid • EN ISO 20345:2011 S5 CI HI SRC

			Æ		
Ref. no.	Colour	Size	Ð		€
347580	olive green	36	1/6	84	
347581	olive green	37	1/6	84	
347582	olive green	38	1/6	84	
347583	olive green	39	1/6	84	
347584	olive green	40	1/6	84	
347585	olive green	41	1/6	84	
347586	olive green	42	1/6	84	
347587	olive green	43	1/6	84	
347588	olive green	44	1/6	84	
347589	olive green	45	1/6	84	
347590	olive green	46	1/6	84	
347591	olive green	47	1/6	84	
347592	olive green	48	1/6	84	
347593	olive green	49	1/6	84	
	-				



#### **NORAMAX Non Safety**

#### NORA PU work boots without steel toe and steel midsole

• extremely lightweight, only 850 g • excellent comfort thanks to anatomic footbed and ergonomically shaped shaft

• flexible at low temperatures and cold-insulating down to -20 °C • extremely durable due to new PU system by BASF – "ELASTOPAN" • extremely anti-slip profile sole (SRC) through optimised profile geometry • self-cleaning profile outsole

Nora PU Insole Standard, extremely shock-absorbent, extremely moisture-absorbent • very good resistance to: animal fats, manure, blood, organic acids, alkalis, hydrocarbonate, alcohol • dirt-resistant, easy-clean surface • Pull-out Aid
 tested according to: EN ISO 20345:2011 CI SRC

Ref. no.	Colour	Size	Ð		€
347670	olive green	36	1/6	84	
347671	olive green	37	1/6	84	
347672	olive green	38	1/6	84	
347673	olive green	39	1/6	84	
347674	olive green	40	1/6	84	
347675	olive green	41	1/6	84	
347676	olive green	42	1/6	84	
347677	olive green	43	1/6	84	
347678	olive green	44	1/6	84	
347679	olive green	45	1/6	84	
347680	olive green	46	1/6	84	
347681	olive green	47	1/6	84	
347682	olive green	48	1/6	84	
347683	olive green	49	1/6	84	



Ŧ

GE#

## 

#### **NORATHERM S5**

#### NORA PU thermal safety boots with steel toe and steel midsole

extremely lightweight, only 1300 g • flexible at low temperatures and cold-insulating down to -50 °C • excellent comfort thanks to anatomic footbed and ergonomically shaped shaft • very good rolling movement thanks to the flexible shaft in the instep • extremely durable due to new PU system by BASF – "ELASTOPAN" • extremely anti-slip profile sole (SRC) through optimised profile geometry • self-cleaning profile outsole • NORA PU Insole Standard: extremely shock-absorbent, extremely moisture-absorbent • very good resistance to: animal fats, manure, blood, organic acids, alkalis, hydrocarbonate, alcohol
 • dirt-resistant, easy-clean surface • Pull-out Aid • tested according to: EN ISO 20345:2011.S5.CI.HI.SRC

Ref. no.	Colour	Size	Ĥ		€
347594	olive green	39	1/6	84	
347595	olive green	40	1/6	84	
347596	olive green	41	1/6	84	
347597	olive green	42	1/5	70	
347598	olive green	43	1/5	70	
347599	olive green	44	1/5	70	
347600	olive green	45	1/5	70	
347601	olive green	46	1/5	70	
347602	olive green	47	1/5	70	
347603	olive green	48	1/5	70	



#### **UNIK LOW S5**

#### NORA Safety Canadian Boot

PU galoshes, rubber sole: extremely durable thanks to new PU system by BASF – "ELASTOPAN" • Galoshes completely waterproof – water-resistant shaft – the ideal combination of the features of both shoes and boots
 extremely lightweight • 100 % metal-free – composite cap and Kevlar midsole • excellent comfort thanks to anatomic footbed and ergonomically shaped shaft • flexible at low temperatures and cold-insulating down to -20 °C • extremely anti-slip profile sole (SRC) through optimised profile geometry • self-cleaning profile outsole
 Insole: extremely shock-absorbent, extremely moisture-absorbent • very good resistance to: animal fats, manure, blood, organic acids, alkalis, hydrocarbonate, alcohol • dirt-resistant, easy-clean surface
 Pull-out Aid • tested according to: EN ISO 20345:2011 SH CI HI SRC

Ref. no.	Colour	Size	Ø	€
347658	black / grey	39	1/6	
347659	black / grey	40	1/6	
347660	black / grey	41	1/6	
347661	black / grey	42	1/6	
347662	black / grey	43	1/6	
347663	black / grey	44	1/6	
347664	black / grey	45	1/6	
347665	black / grey	46	1/6	
347666	black / grey	47	1/6	



New product

GE/

Ŧ

NEW

### 

#### **NORA PU Clogs COMFY**


#### A PU CLOG that does everything ... ideal for gardening and leisure, but also for work.

• flexible at low temperatures • extremely durable due to new PU system by BASF – "ELASTOPAN" • removable PU footbed with microfibre insole: shock-absorbent and antibacterial • washable • comfortable to wear • extremely lightweight • waterproof • very good resistance to: animal fats, manure, blood, organic acids, alkalis, hydrocarbonate, alcohol • profiled, self-cleaning outsole – very slip resistant

Ref. no.	Colour	Size	Ø	Ħ	€
347632	olive green	36	1/5	280	
347633	olive green	37	1/5	280	
347634	olive green	38	1/5	280	
347635	olive green	39	1/5	280	
347636	olive green	40	1/5	280	
347637	olive green	41	1/5	230	
347638	olive green	42	1/5	230	
347639	olive green	43	1/5	230	
347640	olive green	44	1/5	230	
347641	olive green	45	1/5	180	
347642	olive green	46	1/5	180	
347643	olive green	47	1/5	180	
347644	olive green	48	1/5	180	
			-		

#### **NORA PU Insole Clog**

- $\bullet$  removable PU footbed  $\bullet$  with antibacterial microfibre lining  $\bullet$  shock-absorbing
- resistant to pressure-related deformation washable



#### **NORA PU Insole Safety Boots**

#### Long-lasting cushioning

- very low compression rate of less than 5 %
- · constant cushioning and fit inside the shoe

#### **High-level breathability**

- open cell PU foam has up to 100 % breathability
- · Air can circulate into and around the insert, keeping the foot cooler inside the shoe
- Upper of antibacterial polyester

#### Moisture management

the open cell structure creates a moisture management system: Moisture is conveyed away from the foot, ensuring a cooler, drier and healthier shoe environment

#### Easy

NORA insoles are light and increase shoe effectiveness with airy comfort

1/10	€											New pro	duct	NEW
Size	36	37	38	39	40	41	42	43	44	45	46	47	48	49
black	347604	347605	347606	347607	347608	347609	347610	347611	347612	347613	347614	347615	347616	347617









More safety – higher steel cap



More skid resistance – optimised sole profile

#### Bekina Safety boot S5 Steplite® Easygrip


• made from ultra-lightweight polyurethane: 40 % lighter than rubber or PVC • with steel cap and steel midsole • supplied with anti-slip 3-layer inlay sole • durable: lasts 3-4 x longer than PVC boots • anti-slip and dirt-repellent sole • resistant to manure, oil, petrol, grease, alkali and acid • good heat and cold insulation down to - 20°C • tested according to: EN ISO20345:2011.S5.SRC



You can find more information on NEO-TANE Technology at www.kerbl.de.

recommended by professional associations in Germany!

Ref. no.	Colour	Size	Ø	Ħ	€
34140	olive green	36	1/5	80	
34141	olive green	37	1/5	80	
34142	olive green	38	1/5	80	
34143	olive green	39	1/5	80	
34144	olive green	40	1/5	80	
34145	olive green	41	1/5	80	
34146	olive green	42	1/5	80	
34147	olive green	43	1/5	80	
34148	olive green	44	1/5	80	
34149	olive green	45	1/5	80	
34150	olive green	46	1/5	80	
34151	olive green	47	1/5	80	
34152	olive green	48	1/5	80	



• made from ultra-lightweight polyurethane: 40 % lighter than rubber or PVC • durable: lasts 3-4 x longer than PVC boots • more comfort: extra-wide and high fit • more safety: higher steel bar and proven steel sole • anti-slip and dirt-repellent sole • resistant to manure, oil, petrol, grease, alkali and acid • good heat and cold insulation down to - 30 °C • supplied with shock-absorbing 2-layer footbed • tested according to: EN ISO 20345:2011.S5.SRC



You can find more information on NEO-TANE Technology at www.kerbl.de.

#### according to S5 EN 345 and EN ISO 20345:2011.S5.SRC

Ref. no.	Colour	Size	Ð		€
3485	olive green	36	1/5	80	
3486	olive green	37	1/5	80	
3487	olive green	38	1/5	80	
3488	olive green	39	1/5	80	
3489	olive green	40	1/5	80	
3490	olive green	41	1/5	80	
3491	olive green	42	1/5	80	
3492	olive green	43	1/5	80	
3493	olive green	44	1/5	80	
3494	olive green	45	1/5	80	
3495	olive green	46	1/5	80	
3496	olive green	47	1/5	80	
3497	olive green	48	1/5	80	
3498	olive green	49	1/5	80	







More comfort – wider fit



More safety – higher steel cap



More skid resistance – optimised sole profile

GEA

Ŧ

#### Bekina Safety boot S5 StepliteX® Thermoprotec

• ultra-lightweight, but no less secure, thanks to metal-free toe protection and sole • upper material made from foamed polyurethane • dirt-repellent and anti-slip sole profile • excellent insulation performance - cool in summer, warm in winter (down to -40 °C) • Supplied with shock-absorbing 2-layer footbed • oil resistant, Petrol-resistant, acid-proof • tested according to: EN ISO 20345:2011.S5.SRC

NEOTANE<sup>®</sup> TECHNOLOGY

You can find more information on NEO-TANE Technology at www.kerbl.de.

Steplite<sup>®</sup> XCI is the ideal combination for a summer and winter boot. Experience the wearing comfort of a summer boot enhanced with the thermal properties of a winter boot.

Ref. no.	Colour	Size	Ø		€
34341	olive green	37	1/4	64	
34342	olive green	38	1/4	64	
34343	olive green	39	1/4	64	
34344	olive green	40	1/4	64	
34345	olive green	41	1/4	64	
34346	olive green	42	1/4	64	
34347	olive green	43	1/4	64	
34348	olive green	44	1/4	64	
34349	olive green	45	1/4	64	
34350	olive green	46	1/4	64	
34351	olive green	47	1/4	64	
34352	olive green	48	1/4	64	

#### Bekina Safety boot S5 Thermolite® Iceshield

with insulation to - 50 °C, the Thermolite shows its strengths wherever the wearer is exposed to adverse weather conditions
 excellent service life thanks to silky PU material
 maximum wearing comfort and resilience thanks to thick shaft and extra-thick sole
 dirt-repellent and anti-slip sole profile
 supplied with shock-absorbing 2-layer footbed
 integrated steel cap
 made from polyurethane
 tested according to: EN ISO 20345:2011.S4.SRC



You can find more information on NEO-TANE Technology at www.kerbl.de.

insulated to -50 °C 10 % lighter than comparable polyurethane boots Conversion to S5 during the year 2020

R	ef. no.	Colour	Size	Ø	Ħ	€
	3470	olive green	39	1/4	64	
	3471	olive green	40	1/4	64	
	3472	olive green	41	1/4	64	
	3473	olive green	42	1/4	64	
	3474	olive green	43	1/4	64	
	3475	olive green	44	1/4	64	
	3476	olive green	45	1/4	64	
	3477	olive green	46	1/4	32	
	3478	olive green	47	1/4	64	





More comfort – wider fit



More safety — higher steel cap



More skid resistance – optimised sole profile

#### 2-layer Footbed

- ergonomically shaped footbed for even greater comfort inside the boot and better ventilation
- anti-bacterial treatment shock-absorbing reinforcement of the heel improved breathability
- suitable for all BEKINA® boots washable at 30  $^\circ\text{C}$

1/40	€													
Size	36	37	38	39	40	41	42	43	44	45	46	47	48	49
green	34106	34107	34108	34109	34110	34111	34112	34113	34114	34115	34116	34117	34118	34119

#### 3-layer Inlay Sole

excellent insulation thanks to additional felt upper layer
 felt layer is odour-absorbing
 padding effect across the whole of the base of the foot
 excellent slip resistance thanks to rubberised sole
 suitable for all BEKINA® boots
 washable at 30 °C

1/40	€												
Size	36	37	38	39	40	41	42	43	44	45	46	47	48
green	34174	34175	34176	34177	34178	34179	34180	34181	34182	34183	34184	34185	34186


#### **Boot Cleaner**

• for standing • non-slip • complete with 5 brushes and grate • sturdy stainless steel design • easy cleaning with water • the application of cleaning agents prevents the introduction of pathogens into the stables

Ref. no.	Connection	Ø		€
29320	1/2"	1	25	

Ref. no.	Description	Ē	€
29321	Floor Brush	1/10	
29322	Side Brush top	1	
29323	Side Brush below	1/10	





• Toe protection: Steel cap • Perforation protection: Steel midsole • upper material made from foamed polyurethane • reflectors for increased safety • Dunlop red inner

ECTIVE FOOTWEAR

Inner lining made from anti-bacterial material

lining made from antibacterial material • anti-slip, dirt-repellent PU profile sole • midsole with improved comfort and durability • wide profile for all surface types • Purofort® material technology ensures temperature insulation to -20 °C • limited resistance to oil, petrol and acid • anti-static • ideal for use in agriculture • tested according to: EN ISO 20345:2011.S5.CI.SRA

Ref. no.	Colour	Size	Ø		€
34750	olive green	37	1/6	108	
34751	olive green	38	1/6	108	
34752	olive green	39	1/6	108	
34753	olive green	40	1/6	108	
34754	olive green	41	1/6	108	
34755	olive green	42	1/6	108	
34756	olive green	43	1/6	72	
34757	olive green	44	1/6	72	
34758	olive green	45	1/6	72	
34759	olive green	46	1/6	72	
34760	olive green	47	1/6	72	
34761	olive green	48	1/6	72	

#### Dunlop<sup>®</sup> Safety boot Purofort<sup>®</sup>+ S5

• extra room in the toe area • anatomically shaped footbed • upper material made from foamed polyurethane • Dunlop red inner lining made from antibacterial material • anatomically shaped Premium inner sole • anti-slip, dirt-repellent, easy-to-clean PU profile sole with ladder rung protection • anti-static • limited resistance to oil, petrol and acid • Purofort® material technology ensures temperature insulation to -20 °C • easy-to-clean profile - ideal for use in agriculture • Toe protection: Steel cap • Perforation protection: Steel midsole • tested according to: EN ISO 20345:2011.S5.CI.SRC

#### Inner lining made from anti-bacterial material

Ref. no.	Colour	Size	Ð		€
34770	olive green	36	1/6	72	
34771	olive green	37	1/6	108	
34772	olive green	38	1/6	108	
34773	olive green	39	1/6	108	
34774	olive green	40	1/6	108	
34775	olive green	41	1/6	108	
34776	olive green	42	1/6	108	
34777	olive green	43	1/6	72	
34778	olive green	44	1/6	72	
34779	olive green	45	1/6	72	
34780	olive green	46	1/6	72	
34781	olive green	47	1/6	72	
34782	olive green	48	1/6	72	
34783	olive green	49 / 50	1/6	72	







GE/

Ŧ



#### Dunlop® Safety boot Purofort® Thermo+ S5

• Toe protection: Steel cap • Perforation protection: Steel midsole • upper material made from foamed polyurethane • Dunlop red inner lining made from antibacterial material • anatomically shaped Premium inner sole • anti-slip, dirt-repellent PU profile sole • anti-static • limited resistance to oil, petrol and acid • ideal for use on dairy farms • with insulation to - 50 °C, the Thermo+ shows its strengths wherever the wearer is exposed to adverse weather conditions • ideal for work in cold weather conditions, including for livestock farmers. The thick sole prevents the foot from cooling down, while the particularly low profile is especially suitable for wet areas • shock-absorbent and extremely hard-wearing • tested according to: EN ISO 20345:2011.S5.CI.SRC

#### Inner lining made from anti-bacterial material

Ref. no.	Colour	Size	Ð		€
34880	olive green	37 / 38	1/6	60	
34881	olive green	39 / 40	1/6	60	
34882	olive green	41	1/6	60	
34883	olive green	42	1/5	60	
34884	olive green	43	1/5	60	
34885	olive green	44 / 45	1/5	60	
34886	olive green	46	1/5	60	
34887	olive green	47	1/5	60	
34888	olive green	48	1/5	60	



#### **Dunlop® Work Boots Pricemastor**

• classic, highly waterproof PVC boots for work, garden and leisure • inner lining made from easy-care polyester • black shaft, black sole • conditionally resistant to oils, acids, fertilisers, disinfectants and various chemicals • CE approved

Ref. no.	Colour	Size	Ø		€
34785	black	37	1/8	240	
34786	black	38	1/8	192	
34787	black	39	1/8	192	
34788	black	40	1/8	192	
34789	black	41	1/8	192	
34790	black	42	1/8	192	
34791	black	43	1/8	192	
34792	black	44	1/8	192	
34793	black	45	1/8	144	
34794	black	46	1/8	144	
34795	black	47	1/8	144	



GE7

lp-1

÷.

Ŧ

1-1-1

₩.



#### Dunlop<sup>®</sup> Work Boots Dee

• half-height waterproof PVC boots for work, garden and leisure • shaft height approx. 26 cm • dark green shaft, black sole • conditionally resistant to oils, acids, fertilisers, disinfectants and various chemicals • with Dunlop<sup>®</sup> profile sole • inner lining made from easy-care polyester



extra low shaft height approx. 26 cm

Ref. no.	Colour	Size	Ð	Ħ	€
34951	olive green	37	1/10	240	
34952	olive green	38	1/10	240	
34953	olive green	39	1/10	240	
34954	olive green	40	1/10	240	
34955	olive green	41	1/10	240	
34956	olive green	42	1/10	240	
34957	olive green	43	1/10	240	
34958	olive green	44	1/10	240	
34959	olive green	45	1/10	180	
34960	olive green	46	1/10	180	
34961	olive green	47	1/10	180	



#### **Dunlop® Winter Boots Blizzard**

• attractive design and comfortable feel when wearing • thick, comfortable inner lining made from synthetic fleece • PVC upper and sole • excellent insulation against cold • colour-accentuated, shock-absorbing midsole • waterproof laced cuff • outer sole with particularly good grip

Ref. no.	Colour	Size	Ø		€
34850	olive green / black	36	1/6	72	
34851	olive green / black	37	1/6	72	
34852	olive green / black	38	1/6	72	
34853	olive green / black	39	1/6	54	
34854	olive green / black	40	1/6	54	
34855	olive green / black	41	1/6	54	
34856	olive green / black	42	1/6	54	
34857	olive green / black	43	1/6	54	
34858	olive green / black	44	1/6	54	
34859	olive green / black	45	1/6	54	
34860	olive green / black	46	1/6	54	
34861	olive green / black	47	1/6	54	
34862	olive green / black	48	1/6	54	



#### Snugboots

#### Dunlop<sup>®</sup> Inlay sole Basic

#### suitable for Purofort® S5

• absorption: the new inlay soles can absorb up to 3 times more moisture than their own sole weight • double improvement in energy-absorbing properties • 30 % better odour control • maintain their shape better while being put on and taken off, and remain in the boot • made from Poliyou<sup>®</sup>, a PU component, which makes them the perfect match for Dunlop Purofort boots

										6-182	and the second second	_		
Ø	€	Size	37	38	39	40	41	42	43	44	45	46	47	48
1/10		black	34910	34911	34912	34913	34914	34915	34916	34917	34918	34919	34920	34921

#### **Dunlop® Inlay sole Premium**

#### suitable for Purofort®+ S5 and Purofort® Thermo+ S5

absorption: the new inlay soles can absorb up to 3 times more moisture than their own sole weight
 double improvement in energy-absorbing properties • 30 % better odour control • maintain their shape better while being put on and taken off, and remain in the boot • made from Poliyou<sup>®</sup>, a PU component, which makes them the perfect match for Dunlop Purofort boots • ergonomically shaped footbed with 3-zone cushioning for even greater comfort inside the boot • improved breathability thanks to "ventilation channels" in the toe area



Ð	€	Size	37	38	39	40	41	42	43	44	45	46	47	48	49 / 50
1/10		black	34891	34892	34893	34894	34895	34896	34897	34898	34899	34900	34901	34902	34903

#### **Dunlop® Snugboot Pioneer**

Developed for more comfort for people who go their own way.

• the PUROTEX material creates the first breathable and waterproof boot shaft • pUROFORT Flexzone makes it easy to put on and take off • lightweight, wear-resistant upper for comfort from dawn to dusk • SRC-certified, anti-slip outer sole so you can truly master any terrain • abrasion-resistant and easy-clean outer sole • the stable fit envelops your foot and ensures biomechanical support at every step • precision-developed snug fit • lightweight Purofort<sup>®</sup> material for long-lasting comfort • purotex's breathability and absorption capacity means no sweaty feet

Ret. no.	Colour	Size	H1	Ħ	€
347550	black	37	1/6	60	
347551	black	38	1/6	96	
347552	black	39 / 40	1/6	60	
347553	black	41	1/6	60	
347554	black	42	1/6	60	
347555	black	43	1/5	50	
347556	black	44 / 45	1/5	50	
347557	black	46	1/5	50	
347558	black	47	1/5	50	
347559	black	48	1/5	50	



#### Boots

GE#

Ŧ

#### Dunlop® Snugboot WorkPro Full Safety

Designed for more comfort for those who know how to do things. • the PUROTEX material creates the first breathable and waterproof boot shaft • lightweight, wear-resistant upper for comfort from dawn to dusk • high-quality Purofort® material for maximum safety • SRC-certified, anti-slip outer sole so you can truly master any terrain • abrasion-resistant and easy-clean outer sole • the stable fit envelops your foot and ensures biomechanical support at every step • lightweight metal-free toe cap and midsole • lightweight Purofort® material for long-lasting comfort • certified in accordance with all the world's major safety standards • tested according to: EN ISO 20345:2011 S5 CI CR SRC | CSA Z195-14 PR SD | ASTM F2413-17 M I/75 C/75 PR SD 100

Ref. no.	Colour	Size	Ø		€
347560	black	37	1/6	60	
347561	black	38	1/6	60	
347562	black	39 / 40	1/6	60	
347563	black	41	1/6	60	
347564	black	42	1/6	60	
347565	black	43	1/5	50	
347566	black	44 / 45	1/5	50	
347567	black	46	1/5	50	
347568	black	47	1/5	50	
347569	black	48	1/5	50	

#### **Dunlop<sup>®</sup> Snugboot Wildlander**

Designed for more comfort for those who are at home outside.

• the PUROTEX material creates the first breathable and waterproof boot shaft • (odourless) anti-microbial lining with Mossy Oak Break-Up-Country pattern • wear-resistant for all outdoor activities • SRC-certified, anti-slip outer sole so you can truly master any terrain • abrasion-resistant and easy-clean outer sole • the stable fit envelops your foot and ensures biomechanical support at every step • precision-developed snug fit • lightweight Purofort<sup>®</sup> material for long-lasting comfort • purotex's breathability and absorption capacity means no sweaty feet

Ref. no.	Colour	Size	Ð		€
347570	brown	37	1/6	60	
347571	brown	38	1/6	60	
347572	brown	39 / 40	1/6	60	
347573	brown	41	1/6	60	
347574	brown	42	1/6	60	
347575	brown	43	1/5	50	
347576	brown	44 / 45	1/5	50	
347577	brown	46	1/5	50	
347578	brown	47	1/5	50	
347579	brown	48	1/5	50	



₩.

#### **Boots**

#### **Boots NeoLite**

• ideal for working in stalls or pastures • 100 % watertight • sole with self-cleaning profile for a high level of slip resistance • the heat insulating properties of synthetic rubber also keep feet pleasantly warm in winter • the low weight and flexible shaft made from synthetic rubber provide an extremely high level of wearing comfort

360

#### New sizes available from: April 2020

Composition	
Shaft	100 % synthetic rubber
Insole	100 % PVC
Base	100 % PVC

Ref. no.	Colour	Size	Ø	€	
322071	black	36	1/10		
322072	black	37	1/10		
322073	black	38	1/10		
322074	black	39	1/10		
322075	black	40	1/10		
322076	black	41	1/10		
3222071	black	42	1/10		
3222072	black	43	1/10		NEW
3222073	black	44	1/10		NEW
3222074	black	45	1/10		NEW

#### **Boots NeoLite**

#### mid high

• ideal for working in stalls or pastures • 100 % watertight • sole with self-cleaning profile for a high level of slip resistance • the heat insulating properties of synthetic rubber also keep feet pleasantly warm in winter • the low weight and flexible shaft made from synthetic rubber provide an extremely high level of wearing comfort

#### New sizes available from: April 2020

Composition	
Shaft	100 % synthetic rubber
Insole	100 % PVC
Base	100 % PVC

Ref. no.	Colour	Size	Ð	€	
3210190	black	36	1/10		
3210191	black	37	1/10		
3210192	black	38	1/10		
3210193	black	39	1/10		
3210194	black	40	1/10		
3210195	black	41	1/10		
3222098	black	42	1/10		NEW
3222099	black	43	1/10		NEW
3222100	black	44	1/10		NEW
3222101	black	45	1/10		NEW






#### **Keron Works Assembly Glove Premium Plus** Evaluation • elastic, seamless Nylon fabric (15 gauge) for a perfect fit Durability . . . . with any hand shape, good mobility • thin, breathable nitrile GE/ Dexterity . . . . foam coating for excellent protection against mechanical Moisture protection • • hazards, oil and water-repellent • secure grip especially in Resistant to oil/grease . . . dry conditions because of dotted palm • band in various Slip-resistance . . . . colours according to size • solvent free (DMF) Breathability • • • • EN 388:2016 **Top Seller** with presentation tag 4121 X Ħ Ref. no. Colour **Glove Size** € 297971 7 / S 1/6/144 bordeaux 297972 8 / M 1/6/144 bordeaux **OEKO-TEX**® 297973 9/L 1/6/144 bordeaux STANDARD 100 CONFIDENCE IN TEXTILES 297974 bordeaux 10 / XL 1/6/144 19.HCN.89583 HOHENSTEIN HTTI 297975 bordeaux 11 / XXL 1/6/144 Tested for harmful substances. www.oeko-tex.com/standard100 297976 bordeaux 12 / XXXL 1/6/144

#### Finely knitted glove SmoothGrip

• fine-knit glove made from polyester (13 gauge) • with soft latex foam coating with good grip properties • back of hands and fingers free • perfect fit for high sensitivity • breathable, with good grip • Usage: assembly, repairs, universal uses • EN 388, CAT II





Ŧ



with barcode tag

	5					
Ref. no.	Colour	Glove Size	MOQ	Pair / VE	Ø	€
297572	red	8 / M	6 pair	6 / pack	1/6/60	
297573	red	9 / L	6 pair	6 / pack	1/6/60	
297574	red	10 / XL	6 pair	6 / pack	1/6/60	
297575	red	11 / XXL	6 pair	6 / pack	1/6/60	





GEA

#### Finely knitted glove ActivGrip XA325

• fine-knit glove made from polyester / cotton (13 gauge) • double-dipped in latex, making them more abrasion-resistant than regular latex gloves • Open back, thumb fully covered • Palm with "MicroFinish" (the surface structure is similar to suction cups making it especially anti-slip) • excellent fingertip sensitivity and perfect fit • washed, thus protection against latex allergies



#### with presentation tag

Ref. no.	Colour	Glove Size	Ð	€	
297671	orange / grey	7 / S	1/6/144		diadate.
297672	orange / grey	8 / M	1/6/144		
297673	orange / grey	9 / L	1/6/144		-000-
297674	orange / grey	10 / XL	1/6/144		
297675	orange / grey	11 / XXL	1/6/144		<b>Micro</b> Finish

#### Finely knitted glove ActivGrip Advance

• seamless fine-knit nylon glove (13 gauge) • high quality nitrile coating, very good mechanical properties (abrasion), oil-resistant • "MicroFinish" (surface structure is similar to suction cups), especially good grip, even in dry, damp or oily conditions • elastic Nylon fabric ensures a perfect fit and pleasant climate, glove is like a second skin • universal use



with presentation tag

Ref. no.	Colour	Glove Size	MOQ	Pair / VE	Ē	€
297290	purple	6 / XS	6 pair	6 / pack	1/6/144	
297291	purple	7 / S	6 pair	6 / pack	1/6/144	
297292	purple	8 / M	6 pair	6 / pack	1/6/144	
297293	purple	9 / L	6 pair	6 / pack	1/6/144	
297294	purple	10 / XL	6 pair	6 / pack	1/6/144	
297295	purple	11 / XXL	6 pair	6 / pack	1/6/144	

#### **Keron Works Assembly**



Evaluation	
Durability	• • •
Dexterity	• • • •
Moisture protection	• • • •
Resistant to oil/grease	•
Slip-resistance	• • • • •
Breathability	• • •











Evaluation	
Durability	•••••
Dexterity	• • • •
Moisture protection	• • •
Resistant to oil/grease	••••
Slip-resistance	• • • • •
Breathability	• • • •











#### **Keron Works Working**

#### Full Cowhide Glove YELLTOR Yelltor

- leather thickness approx 1.1 mm - large cut - semi-lined - professional quality

# EvaluationDurability• • •Dexterity•Moisture protection• •Resistant to oil/grease• •Slip-resistance• •Breathability• • •



GE/

A


淤


Ŧ



with barcode tag

Ref. no.	Colour	Glove Size	Ð	€
29748	yellow	10 / XL	1/6/60	
29749	yellow	11 / XXL	1/6/60	





#### Winter Glove IceGrip

seamless fine-knit glove made from polyester/cotton • fluorescent
with warm acrylic lining • elastic latex foam coating • Areas of use:

construction, industrial freezers and outdoor work



Evaluation	
Durability	• • •
Dexterity	• • •
Moisture protection	• • •
Resistant to oil/grease	•
Slip-resistance	• • • •
Breathability	• • •
Winter	• • • •



3
2

with barcode tag

Ref. no.	Colour	Glove Size	Ð	€
297481	orange	7 / S	1/6/60	
297482	orange	8 / M	1/6/60	
297483	orange	9 / L	1/6/60	
297484	orange	10 / XL	1/6/60	
297485	orange	11 / XXL	1/6/60	

#### Α

Accessories Collar Number Duo133Accessories for foam lance74ActivGrip Advance Finely knitted glove223ActivGrip XA325 Finely knitted glove224Adhesive Tape114Aerosol grip SprayMaster133Alive Cage Mousetrap200All-Purpose Bucket177All-Purpose Bucket Jumbo177All-Purpose Shovel177Aluminium calf feeder valve33Aluminium Shovel177Aluminium Shovel177Anbic Pre-milk Cup66Amerika Kick Stop10Angular Dip Sprayer7Animal Scales16Animal Scales16Ania Scales16Anka Rinser7
AniScale Animal Scales 168
AquaLine Circulation Pump 164

#### R

6	
Bandage Knife 11	3
Barrel Pump 7	6
Barrel Pump Profi 7	6
Basic Disposable Coverall	1
Basic Inlay sole 22	
Basin	
Battery-operated Horn Remover buddex 9	4
Bedding and Bale Fork 18	0
Bedding Fork 18	0
Big Softy Teat 3	3
Biglac 25 Float Bowl 15	1
BigScreen Digital thermometer 20	2
BladeCool 13	3
Blizzard Winter Boots	3
Block Bond Eco® 11	
Bolt-On Bottle Nipple	6
Bolus Bufferlyt 6	
Bolus Calzogol 6	2
Bolus Fertilgol 6 Bolus Ket-o-Vital® 6	3
Bolus Ket-o-Vital <sup>®</sup>	2
Bolus Phosphogol 6	
Bolus Vitagol 6	3
Boot Cleaner 22	0
Boots NeoLite 22	
Bottle Teat 3	4
Box rake 17	4
Bridle	
Bucket Guard Catch 3	1
Bucket Mount 5	7
buddex Battery-operated Horn Remover 9	4
Bufferlyt Bolus 6	3
Bull Halter 10	3

#### С

C
Cage Mousetrap Alive 200
Calf and Sheep Trough 141
Calf blanket 16
Calf blanket EasyWear 60
Calf blanket Ripstopp 61
Calf blanket ThermoPlus 61
Calf Bottle MilkyFeeder 35
Calf Bottle Speedy Feeder
Calf box
Calf Bucket
Calf Drencher MilkyDrencher 36
Calf Drencher Profi 36
Calf Feeder Tray Multi Feeder 32
Calf Feeding Bucket 29
Calf Paste
Calf Teat
Calf Teat MilkyTeat 33
Calf tethering 104
CalfHouse Master Plus 49
CalfHouse PE UV+ 45
CalfHouse Premium Plus 47
CalfHouse Premium XL 51

CalfHouse Premium XXL . . . . . . . . . . . 53 

 CalfHouse Premium XXL
 53

 Calving Alarm.
 20

 Calving Cord.
 23

 Calzogol Bolus
 62

 Camera.
 18

 Can Brush.
 84

 Carister Drain Valve
 76

 CareMINT Udder Care Products.
 72

 Case for Dangerous Goods
 13

 Carth Bucket Guard
 31

 Cattle Brush HAPPYCOW Duo . . . . . 124 Cattle Brush HAPPYCOW Swing . . . . . 125 Cattle Brush Texas ..... 127 Cattle Connector. . . . . . . . . . . . . . . . . . 106 Cattle Marking Pen TopMarker . . . . . . . 135 Cattle Tethering Top Quality ..... 105 Chain Component. . . . . . . . . . . . . 104, 105 Chemex Chemicals Glove ..... 230 Chemical protection overall CoverBase . . 210 Chemicals Glove Chemex ..... 230 Chopping Blade ..... 111 Circulation Pump AquaLine. . . . . . . . 164 constanta4 Sheep Shearing Machine .... 208 

 control unit.
 186

 Cooling Spray IceCool.
 97

 Cordless Clipper
 15

 Cordless Clipper DeloX.
 134

 Cordless Clipper FarmClipper Akku2.
 132

 Cover for Feeding Bucket ..... 31 CoverBase Chemical protection overall . . 210 Cow Blanket..... 26 Cow Immobiliser FlexCow..... 100 Cow Lifting Frame Standard ..... 27

#### D

#### Ε

E21 Water Bowl
EasyHeat Milk heater for calf feeding 41
EasyWear Calf blanket 60
ECO Stable Fly Roll
EcoKill Inox Insect Killers
EcoKill Inox IPX4 Insect Killers 195
EcoKill Insect Killers
Econom Shearing blades 129
Economy Supplies Set 4
EcoTUBE LED Tube
EcoTUBE Plus LED Tube
Edelweiß Soft Soap
EquiLastic Self-adhesive Bandage 113
Equisal NoFly Mineral Lick 140
Estrus Detection
Extension element 146
Eyewash

#### F

FarmClipper Akku2 Cordless Clipper	132
FarmClipper Sheep Shearing Machine	209
FarmClipper4 Clipper	
FarmPRO LED moisture-proof lamp	189
FarmSTAR LED moisture-proof lamp	188
FastHeat Digital Milk heater for	
calf feeding	. 40
FastHeat Milk heater for calf feeding	. 41
Feed Ball Toy HeuBoy	. 58
Feed Pusher	177
Feed Scoop	169
Feed scoop with inverted handle	169
Feed trough	141
Feed Trough Long 56, 57,	151
Feeding Bowl	
Felix Ultrasound Device	
Fertilgol Bolus	
Fetlock Marking Tape	136
Fetlock strap 136,	137
FFP1 NR D Fine dust mask	213
FFP2 NR D Fine dust mask	
FFP2 Respirator	
Filter Disc	7
Fine dust mask FFP1 NR D	213
Fine dust mask FFP2 NR D	213
Finely knitted glove ActivGrip Advance	228
Finely knitted glove ActivGrip XA325	
Finely knitted glove SmoothGrip	
FixClip New Generation Valve	
FlexCow Cow Immobiliser	
Flexo Brush	
Float Bowl Biglac 25	151
Float Bowl S1090	151
Float Bowl S190	150
Float Bowl S195	150
Float Bowl S522	
Float Bowl SH30	
Float Bowl SN190	
Floating Suction Cup	
Fly Catcher Twister	198

GE#

Ŧ

#### G

#### Н

п	
H10 Water Bowl	
Halter	103
Hand Cleaner with Cleansing Beads	74
Hand Wash Brush	
Hand-wash Paste	
Handle Brush	
HAPPYCOW Duo Cattle Brush	12/
HAPPYCOW MiniSwing Scratch Brush	
	120
HAPPYCOW Swing Cattle Brush	125
Hay Bell	144
Hay Cutter Hay Cutter TF 2000 M	181
Hay Cutter TF 2000 M Hay Cutter	181
Hay Rack	57
HayBag	59
Head Support for Cattle	64
HeatBox Thermal Container	118
HeuBoy Feed Ball Toy	58
HK Calf Pullers	22
HK Calf Resuscitator	24
HK Flexi Frames	
HK Lubricating Gel	25
HK Plastic Attachment Support	21
Hobby Square hay rack	144
Holder	206
HoloBlock Hoof Block	
Hoof Abrasive Disc	108
	108
Hoof and Claw Cutter	110
Hoof and claw knife	109
Hoof and claw knife Profi	109
	109
	119
	119
	119
	113
	119
	115
	118
	107
Hoof Cutting Disc P6	107
Hool Cutting Disc Po	
	107
	108
	120
	111
	111
	110
Hoof Shoe	112
Hoof Shoe Tubbease <sup>™</sup>	
Hoof Side Cutter	110
Hoof-Checking Pliers.	111
Hornstick	
Hose Wiper.	
Hygiene Apron	
Hygiene Sleeve Protector	81
	01

1
IceCool Cooling Spray
IceGrip Winter Glove
Indicator Paper 69
Infrared Energy-Saving Lamp 201
Infrared Heater
Inlay sole Basic 224
Inlay sole Premium
Insect Killers 2138 193
Insect Killers EcoKill 195
Insect Killers EcoKill Inox 194
Insect Killers EcoKill Inox IPX4 195
Insect Killers Green Line
Installation plate
Introducer
IPCam 2.0 HD
IPCam 360 FHD 18
IPCam 360 FHD mini 19

Jumbo All-Purpose Bucket ..... 173 

#### Κ

K75 Water Bowl 14
Ket-o-Vital <sup>®</sup> Bolus
Kick Stop Amerika 10
KN50 Water Bowl 153, 15
Komfort Spray Rinser 7
Kompakt Large broom 17

#### L

Lamb Bottle 200	6
Lamb Bottle Anti-Vac 200	
Lamb Bucket 203, 204, 205	5
Lamb Feeder Tray Multi Feeder 202	
Large broom	2
Large broom Kompakt 17	1
Large scrubber	
LED Floodlight 192	
LED Indoor Spotlight	4
LED Lighting Control	
LED moisture-proof lamp 189	
LED moisture-proof lamp FarmPRO 189	
LED moisture-proof lamp FarmSTAR 18	
LED Outdoor Spotlight 190	
LED Oval Light 19	
LED Tube EcoTUBE	
LED Tube EcoTUBE Plus	
Leg band numbers 13	
Leimer Teat	
Lick holder	
Litter fork	
Lubricating Gel VetGel 2	
Luna Mousetrap	
Luna Rat trap	9

#### Μ

Manure Scraper       174         Marking collar       139         Marking Spray TopMarker       135         Master Plus CalfHouse       49
Master Plus Calinouse
MaxiMove Milking and washing apron 80
Measuring cup
Metal Curry Comb
Milk and Cheese Thermometer 92
Milk Bottle
Milk dummy cap 89
Milk Filter Sock 6, 7
Milk Filters Premium
Milk heater for calf feeding 42
Milk heater for calf feeding EasyHeat 41
Milk heater for calf feeding FastHeat 41
Milk heater for calf feeding
FastHeat Digital 40
Milk measuring device 93
Milk Sieve
Milk Tube Cleaning Sponge 8
Milk warmer MilkPot 50

Milker Apron 13
Milking and washing apron 79, 80
Milking and washing apron MaxiMove 80
Milking Fat 72
Milking Machine Oil Viscano 91
Milking Pail 14, 90
Milking Pail Lid
Milking Pail Stainless Steel 90
Milking Sealing Plug
Milking Stool 89
MilkPot 50 Milk warmer
MilkyDrencher Calf Drencher 36
MilkyFeeder Calf Bottle
MilkyTeat Calf Teat 33
Mineral Lick Equisal NoFly 140
Mobile LED Battery Spotlight
WorkFire Pro
Mobile LED Battery Spotlight
WorkFire Pro 30
Mod. 221500 Water Bowl 148
Mod. 222000 Water Bowl 149
Modell A 800 Bayern SECURPART
Calf Puller 23
Modular fence stabling 54
Moisture Meter
Moisture-proof diffuser light 188
Mounting Bracket
Mounting Set
mouseStop Mousetrap 200
Mousetrap Luna
Mousetrap mouseStop 200
Mousetrap Snapper 199
Muck and Slurry Pusher 174, 175
Müller 2010 Cattle Weaner 98
Müller Cattle Weaner
Multi Feeder Calf Feeder Tray 32
Multi Feeder Drinking Trough 32
Multi Feeder Lamb Feeder Tray 203
MultiLED pro 185
Multipurpose Grease Viscano 170

#### Ν

ſ	V20 Water Bowl 154
ſ	NeoLite Boots 226
ſ	Nirosta Snow Broom
ſ	Nitril Disposable glove 12
	Nitrile Basic Disposable glove
ſ	Nitrile Classic Disposable glove 83
	Nitrile Long Black Disposable glove 82
	Nitrile Premium Disposable glove 82
	Nitrile Profi Disposable glove
	Non-Return Dip Cup
	NonReturn Cross Dip Cup
	NonReturn Dip Cup
	NonReturn Twin Dip Cup
	NORAMAX Non Safety
	NORAMAX Safety S5 215
ſ	NORATHERM 55
	Numbering block 138
	Numbering block Standard
	5

#### 0

orig. Gilmour Spray Shower	78
Outlet Raimo BigBag	182
Oxford Protective Sleeve	81

#### D

P
P6 Hoof Cutting Disc 107
Paper Towel Roll
Pasture Panel 145, 146
Pesticide Set
Phosphogol Bolus
Pipe Brush
Plant Protection Overall Typ 4 210
Play Rope 59
Plug 142
Portasol 3 Gas Dehorner
PortaSpray Dip Sprayer
Powder Disperser
Power Tail Trimmer II
Pre-milk Cup
Pre-milk Cup Ambic 69

Milker Apron	Precision Adjusting Aid Torqui 128
Milking and washing apron 79, 80	Pregnancy Tester
Milking and washing apron MaxiMove 80	Premium Inlay sole
Milking Fat	Premium Milk Filters
Milking Machine Oil Viscano	Premium Plus CalfHouse
Milking Pail 14, 90	Premium Plus Glove 227
Milking Pail Lid	Premium Shearing Blade Set 131
Milking Pail Stainless Steel	Premium Squeegee 176
Milking Sealing Plug	Premium Supplies Set 4
Milking Stool 89	PREVENTA Udder Hair Remover
MilkPot 50 Milk warmer	Pricemastor Work Boots
MilkyDrencher Calf Drencher	Profi Aluminium Shovel 178
MilkyFeeder Calf Bottle	Profi Barrel Pump
MilkyTeat Calf Teat 33	Profi Calf Drencher
Mineral Lick Equisal NoFly 140	Profi Cow Lifting Frame
Mobile LED Battery Spotlight	Profi Dispensing Pump
Mobile LED Battery Spotlight WorkFire Pro	Profi Hoof and claw knife 109
Mobile LED Battery Spotlight	Profi Special Aluminium Shovel 178
Mobile LED Battery Spotlight WorkFire Pro 30	ProfilacDermacel Udder Paper
Mod. 221500 Water Bowl	ProfilacDermatex Udder Cloth
Mod. 222000 Water Bowl 149	Prolapse Bandage
Modell A 800 Bayern SECURPART	ProStream Teat Spraying System 11
Calf Puller	Protective Sleeve
Modular fence stabling	Protective Sleeve Oxford
Moisture Meter	Protective Sleeve Softshell
Moisture-proof diffuser light 188	ProTrim Hoof Cutting Disc 107
Mounting Bracket	PU Clogs COMFY
Mounting Set	PU Insole Clog
mouseStop Mousetrap 200	PU Insole Safety Boots
Mousetrap Luna	Purofort <sup>®</sup> S5 Safety boot
Mousetrap mouseStop	Purofort <sup>®</sup> Thermo+ S5 Safety boot 222
Mousetrap Snapper 199	Purofort®+ S5 Safety boot
moused up simpler	. a.

#### Q

C

2
S1090 Float Bowl
S190 Float Bowl 150
S195 Float Bowl 150
S5 StepliteX <sup>®</sup> Solidgrip Safety boot 218
S5 StepliteX® Thermoprotec Safety boot . 219
S5 Steplite <sup>®</sup> Easygrip Safety boot 218
S5 Thermolite® Iceshield Safety boot 219
S522 Float Bowl 149
S60 Double Float Drinking Bowl 154
Safety boot Purofort® S5 221
Safety boot Purofort® Thermo+ S5 222
Safety boot Purofort®+ S5 221
Safety boot S5 StepliteX <sup>®</sup> Solidgrip 218
Safety boot S5 StepliteX® Thermoprotec . 219
Safety boot S5 Steplite® Easygrip 218
Safety boot S5 Thermolite® Iceshield 219
Salt Lick 140
SalvoCare Mint Udder Care Products 14
schalm test disk 69
Scratch Brush
Scratch Brush HAPPYCOW MiniSwing 126

#### Scratch Mat ..... 58, 127 Screw Valve ..... 31 Scrubber. 172 sealing ring. 31 SECURPART Calf Puller 23 SECURPART Calf Puller Modell A Sheep Shearing Machine constanta4 . . . 208 Sheep Shearing Machine FarmClipper. . . 209 Shoeing Hammer 111 Shoeing Mallet 111 Silbertape Hoof Bandage 119 Slurry Pusher 174 SmoothGrip Finely knitted glove 227 Sluop Loat Bowd 153 SN190 Float Bowl. 153 Snapper Mousetrap 199 Snapper Rat trap199Snow and grain shovel179Snow Broom Nirosta34 Snugboot Pioneer224Snugboot Wildlander225Snugboot WorkPro Full Safety225 Spare Parts for Cow Immobiliser. 100 Special Aluminium Shovel Profi. 178 Speedy Drencher. 37 Speedy Feeder Calf Bottle 36 Spiral Curry Comb. 122 Spray Guns. 78 Spray Guns. 78 Spray Oil WL-75 5 Spray Rinser Komfort 78 Spray Shower orig. Gilmour 78 Spray Master Aerosol grip 135 Square hay rack Hobby 144 Square hay rack Standard 143 Squeegee 176 ST-73 Foam Lance. 79 Stable Fly Coll ECO 196 Stable Fly Roll ECO 196 Stable Fly Roll ECO 196 Stable Flypaper Sheet FlyMaster 197 Stainless Steel Bucket 173 Stainless Steel Lid. 91 Cheinless Cheve Merker Travel 191 Standard Hoof Abrasive Disc. . . . . . . . 108 Standard Hoof Mat.120Standard Numbering block137Standard Square hay rack143 SuperKombi Footbath Container . . . . . . 120 SuperKombi Mini Footbath Container . . . 207 SuperProfi Hoof and claw knife. . . . . . . 109 SuperProfi Hoof Auting Disc. 108 Supplies Set Economy. 4 Supplies Set Premium 4 Syringe Drencher 38

#### Т

Teat	30, 33, 206
Teat Activity Set	59
Teat Bandage UdderoSoft	73
Teat Big Softy	33
Teat cannula	70
Teat Cup Brush	
Teat Leimer	34
Teat Pens	
Teat Protector	73

Teat Spraying System ProStream11Teat tips70Technobase 8000114Technovit® 6091114Technovit®-2-Bond116ECNALL Dehorning Saw97Teething Ring59Texas Cattle Brush127Thermal Container HeatBox118Thermal Trough66Tip trough158Top Quality Cattle Tethering105Top-Qualität Cattle Marking Pen135TopMarker Cattle Marking Spray135TopMarker Marking Spray135Torqui Precision Adjusting Aid128Traansformer162Triangular Trough142Trough for concentrated feed141Tubbease™ Hoof Shoe112Torianter Marking Fen112
Trough for concentrated feed 141
Tubbease™ Hoof Shoe
Twister Fly Catcher
Typ 4 Plant Protection Overall

# Water Bowl K75 147 Water Bowl KN50 153, 154 Water Bowl Mod. 221500 148 Water Bowl Mod. 222000 149 Water Bowl N20 154 Water Bucket 173 Water Bucket 173 Water Bookl N20 154 Water Bucket 173 Water Goop 169 Weigh Scoop 169 Weigh Scoop Inverted Handle. 169 Weigh Scoop Inverted Handle. 169 Weight 137 Winter Boots Blizzard 223 Winter Glove IceGrip. 230 Wire Saw 97 WL-75 Spray Oil 5 Wooden Block 115 Wool Teat Plug 70 Wool Teat Plug Uddero Dil 70 Work Boots Pricemastor 222 Work Boots Pricemastor 222 WorkFire Pro 30 Mobile 120 LED Battery Spotlight 191 WorkFire Pro Mobile 192 LED Battery Spotlight 192 Wound care spray 73

#### U

#### ۷


Vacuum Pump Oil5
Vacuum Pump Oil VCL 22
Valve FixClip New Generation
Valve trough drinker
VCL 22 Vacuum Pump Oil
VETbasic Veterinary disposable gloves 25
Veterinary disposable gloves VETbasic 25
Veterinary disposable gloves VETtop 25
VetGel Lubricating Gel 25
Vetlastic Hoof Bandage
VetTape Hoof Bandage
VETtop Veterinary disposable gloves 25
Viscano Milking Machine Oil 91
Viscano Multipurpose Grease 170
Vitagol Bolus

#### W

Walkease Hoof Care	118
Wall bracket	2, 83
Wall Roll Holder 68	8, 75
Washing and Cleaning Overalls	211
Washing brush 84	, 85
Water Bowl	
Water Bowl E21	147
Water Bowl G16	148
Water Bowl G51	147
Water Bowl H10	160

Y

Yelltor Full Cowhide Glove YELLTOR	229
Young bull tethering	106
Young cattle tethering	104





#### We live our values.

Excellence · Passion · Integrity · Responsibility · GEA-versity

GEA Group is a global engineering company with multi-billion euro sales and operations in more than 50 countries. Founded in 1881, the company is one of the largest providers of innovative equipment and process technology. GEA Group is listed in the STOXX ® Europe 600 index.

#### GEA Germany

GEA Farm Technologies GmbH Siemensstraße 25 - 27 D-59199 Bönen

Tel +49 (0) 23 83 93 7-0 Fax +49 (0) 23 83 93 8-0



#### gea.com/contact

We do our best to constantly improve our range of products and keep it up-to-date. Thus we reserve the right to change the design of our products. With the publication of this catalogue all previous catalogues and price lists for the respective products are void. All prices provided are the manufacturer's recommended retail prices and are inclusive of VAT. All information is subject to typing and printing errors. All prices are subject to change. Changes in colour and design may occur due to printing technology reasons. Reprinting in whole or in part is due to prior authorisation.

© 10/2020